## TencorFlow

TensorFlow API r1.4

tf.nn.batch\_norm\_with\_global\_normalization

```
batch_norm_with_global_normalization(
    t,
    m,
    v,
    beta,
    gamma,
    variance_epsilon,
    scale_after_normalization,
    name=None
)
```

Defined in tensorflow/python/ops/nn\_impl.py.

See the guide: Neural Network > Normalization

Batch normalization.

This op is deprecated. See tf.nn.batch\_normalization.

## Args:

- t: A 4D input Tensor.
- m: A 1D mean Tensor with size matching the last dimension of t. This is the first output from tf.nn.moments, or a saved moving average thereof.
- v: A 1D variance Tensor with size matching the last dimension of t. This is the second output from tf.nn.moments, or a saved moving average thereof.
- beta: A 1D beta Tensor with size matching the last dimension of t. An offset to be added to the normalized tensor.
- gamma: A 1D gamma Tensor with size matching the last dimension of t. If "scale\_after\_normalization" is true, this tensor will be multiplied with the normalized tensor.
- variance\_epsilon: A small float number to avoid dividing by 0.
- scale\_after\_normalization: A bool indicating whether the resulted tensor needs to be multiplied with gamma.
- name: A name for this operation (optional).

## Returns:

A batch-normalized t.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

GitHub	
Twitter	
Support	
Issue Tracker	
Release Notes	
Stack Overflow	
English	
Terms   Privacy	