## TancarFlow

TensorFlow API r1.4

tf.sparse\_split

```
sparse_split(
    keyword_required=KeywordRequired(),
    sp_input=None,
    num_split=None,
    axis=None,
    name=None,
    split_dim=None
)
```

Defined in tensorflow/python/ops/sparse\_ops.py.

See the guide: Sparse Tensors > Manipulation

Split a SparseTensor into num\_split tensors along axis.

If the sp\_input.dense\_shape[axis] is not an integer multiple of num\_split each slice starting from 0: shape[axis] % num\_split gets extra one dimension. For example, if axis = 1 and num\_split = 2 and the input is:

Graphically the output tensors are:

## Args:

- keyword\_required: Python 2 standin for \* (temporary for argument reorder)
- sp\_input: The SparseTensor to split.
- num\_split: A Python integer. The number of ways to split.
- axis: A 0-D int32 Tensor. The dimension along which to split.
- name: A name for the operation (optional).
- split\_dim: Deprecated old name for axis.

## Returns:

num\_split SparseTensor objects resulting from splitting value .

Raises:

- TypeError: If sp\_input is not a SparseTensor.
- ValueError: If the deprecated split\_dim and axis are both non None.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

