TencorFlow

TensorFlow API r1.4

tf.contrib.bayesflow.csiszar_divergence.symmetrized_csiszar_function

```
symmetrized_csiszar_function(
    logu,
    csiszar_function,
    name=None
)
```

Defined in tensorflow/contrib/bayesflow/python/ops/csiszar_divergence_impl.py.

Symmetrizes a Csiszar-function in log-space.

A Csiszar-function is a member of,

```
F = \{ f:R_+ \text{ to } R : f \text{ convex } \}.
```

The symmetrized Csiszar-function is defined as:

```
f_g(u) = 0.5 g(u) + 0.5 u g (1 / u)
```

where g is some other Csiszar-function.

We say the function is "symmetrized" because:

```
D_{f_g}[p, q] = D_{f_g}[q, p]
```

for all p << >> q (i.e., support(p) = support(q)).

There exists alternatives for symmetrizing a Csiszar-function. For example,

```
f_g(u) = \max(f(u), f^*(u)),
```

where f^* is the dual Csiszar-function, also implies a symmetric f-Divergence.

Example:

When either of the following functions are symmetrized, we obtain the Jensen-Shannon Csiszar-function, i.e.,

```
g(u) = -log(u) - (1 + u) log((1 + u) / 2) + u - 1

h(u) = log(4) + 2 u log(u / (1 + u))
```

implies,

```
f_g(u) = f_h(u) = u \log(u) - (1 + u) \log((1 + u) / 2)
= jensen_shannon(log(u)).
```

A

Warning: this function makes non-log-space calculations and may therefore be numerically unstable for $|\log u| >> 0$.

Args:

• logu: float -like Tensor representing log(u) from above.

- csiszar_function: Python callable representing a Csiszar-function over log-domain.
- name: Python str name prefixed to Ops created by this function.

Returns:

• symmetrized_g_of_u: float-like Tensor of the result of applying the symmetrization of g evaluated at u = exp(logu).

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

