TancarFlow

TensorFlow API r1.4

tf.keras.datasets.imdb.load_data

```
load_data(
    path='imdb.npz',
    num_words=None,
    skip_top=0,
    maxlen=None,
    seed=113,
    start_char=1,
    oov_char=2,
    index_from=3
)
```

Defined in tensorflow/python/keras/_impl/keras/datasets/imdb.py.

Loads the IMDB dataset.

Arguments:

- path: where to cache the data (relative to ~/.keras/dataset).
- num_words: max number of words to include. Words are ranked by how often they occur (in the training set) and only the most frequent words are kept
- skip_top: skip the top N most frequently occurring words (which may not be informative).
- maxlen: truncate sequences after this length.
- seed: random seed for sample shuffling.
- start_char: The start of a sequence will be marked with this character. Set to 1 because 0 is usually the padding character.
- oov_char: words that were cut out because of the num_words or skip_top limit will be replaced with this character.
- index_from: index actual words with this index and higher.

Returns:

Tuple of Numpy arrays: (x_train, y_train), (x_test, y_test).

Raises:

ValueError: in case maxlen is so low that no input sequence could be kept.

Note that the 'out of vocabulary' character is only used for words that were present in the training set but are not included because they're not making the num_words cut here. Words that were not seen in the training set but are in the test set have simply been skipped.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Stay Connected	
Blog	
GitHub	
Twitter	
Support	
Issue Tracker	
Release Notes	
Stack Overflow	
English	
Terms Privacy	