TancarFlow

TensorFlow API r1.4

tf.contrib.gan.losses.wargs.wasserstein_generator_loss

```
wasserstein_generator_loss(
    discriminator_gen_outputs,
    weights=1.0,
    scope=None,
    loss_collection=tf.GraphKeys.LOSSES,
    reduction=losses.Reduction.SUM_BY_NONZERO_WEIGHTS,
    add_summaries=False
)
```

Defined in tensorflow/contrib/gan/python/losses/python/losses_impl.py.

Wasserstein generator loss for GANs.

See Wasserstein GAN (https://arxiv.org/abs/1701.07875) for more details.

Args:

- discriminator_gen_outputs: Discriminator output on generated data. Expected to be in the range of (-inf, inf).
- weights: Optional Tensor whose rank is either 0, or the same rank as discriminator_gen_outputs, and must be broadcastable to discriminator_gen_outputs (i.e., all dimensions must be either 1, or the same as the corresponding dimension).
- scope: The scope for the operations performed in computing the loss.
- loss_collection: collection to which this loss will be added.
- reduction: A tf.losses.Reduction to apply to loss.
- add_summaries: Whether or not to add detailed summaries for the loss.

Returns:

Issue Tracker

A loss Tensor. The shape depends on reduction.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected Blog GitHub Twitter Support

Release Notes
Stack Overflow

English
Terms | Privacy