

tf.global_norm

```
global_norm(  
    t_list,  
    name=None  
)
```

Defined in [tensorflow/python/ops/clip_ops.py](#).

See the guide: [Training > Gradient Clipping](#)

Computes the global norm of multiple tensors.

Given a tuple or list of tensors `t_list`, this operation returns the global norm of the elements in all tensors in `t_list`. The global norm is computed as:

```
global_norm = sqrt(sum([l2norm(t)**2 for t in t_list]))
```

Any entries in `t_list` that are of type `None` are ignored.

Args:

- `t_list`: A tuple or list of mixed `Tensors`, `IndexedSlices`, or `None`.
- `name`: A name for the operation (optional).

Returns:

A 0-D (scalar) `Tensor` of type `float`.

Raises:

- `TypeError`: If `t_list` is not a sequence.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)