

## tf.contrib.seq2seq.basic\_rnn\_seq2seq

```
basic_rnn_seq2seq(  
    encoder_inputs,  
    decoder_inputs,  
    cell,  
    dtype=tf.float32,  
    scope=None  
)
```

Defined in [tensorflow/contrib/legacy\\_seq2seq/python/ops/seq2seq.py](#).

Basic RNN sequence-to-sequence model.

This model first runs an RNN to encode `encoder_inputs` into a state vector, then runs decoder, initialized with the last encoder state, on `decoder_inputs`. Encoder and decoder use the same RNN cell type, but don't share parameters.

### Args:

- `encoder_inputs`: A list of 2D Tensors [batch\_size x input\_size].
- `decoder_inputs`: A list of 2D Tensors [batch\_size x input\_size].
- `cell`: `tf.nn.rnn_cell.RNNCell` defining the cell function and size.
- `dtype`: The dtype of the initial state of the RNN cell (default: `tf.float32`).
- `scope`: `VariableScope` for the created subgraph; default: "basic\_rnn\_seq2seq".

### Returns:

A tuple of the form (outputs, state), where: `outputs`: A list of the same length as `decoder_inputs` of 2D Tensors with shape [batch\_size x output\_size] containing the generated outputs. `state`: The state of each decoder cell in the final time-step. It is a 2D Tensor of shape [batch\_size x cell.state\_size].

---

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

### Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

### Support

[Issue Tracker](#)

[Release Notes](#)

English

[Terms](#) | [Privacy](#)