TancarFlow

TensorFlow API r1.4

tf.sparse_reshape

```
sparse_reshape(
    sp_input,
    shape,
    name=None
)
```

Defined in tensorflow/python/ops/sparse_ops.py.

See the guide: Sparse Tensors > Manipulation

Reshapes a SparseTensor to represent values in a new dense shape.

This operation has the same semantics as **reshape** on the represented dense tensor. The indices of non-empty values in **sp_input** are recomputed based on the new dense shape, and a new **SparseTensor** is returned containing the new indices and new shape. The order of non-empty values in **sp_input** is unchanged.

If one component of **shape** is the special value -1, the size of that dimension is computed so that the total dense size remains constant. At most one component of **shape** can be -1. The number of dense elements implied by **shape** must be the same as the number of dense elements originally represented by **sp_input**.

For example, if sp_input has shape [2, 3, 6] and indices / values:

```
[0, 0, 0]: a

[0, 0, 1]: b

[0, 1, 0]: c

[1, 0, 0]: d

[1, 2, 3]: e
```

and shape is [9, -1], then the output will be a SparseTensor of shape [9, 4] and indices / values:

```
[0, 0]: a
[0, 1]: b
[1, 2]: c
[4, 2]: d
[8, 1]: e
```

Args:

- sp_input: The input SparseTensor.
- shape: A 1-D (vector) int64 Tensor specifying the new dense shape of the represented SparseTensor.
- name : A name prefix for the returned tensors (optional)

Returns:

A SparseTensor with the same non-empty values but with indices calculated by the new dense shape.

Raises:

- TypeError: If sp_input is not a SparseTensor.
- ValueError: If argument shape requests a SparseTensor with a different number of elements than sp_input.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

