

tf.contrib.timeseries.NumpyReader

Contents

Class NumpyReader

Methods

`__init__`

`check_dataset_size`

`read`

`read_full`

Class NumpyReader

Defined in [tensorflow/contrib/timeseries/python/timeseries/input_pipeline.py](#).

A time series parser for feeding Numpy arrays to a `TimeSeriesInputFn`.

Avoids embedding data in the graph as constants.

Methods

`__init__`

```
__init__(
    data,
    read_num_records_hint=4096
)
```

Numpy array input for a `TimeSeriesInputFn`.

Args:

- `data`: A dictionary mapping feature names to Numpy arrays, with two possible shapes (requires keys `TrainEvalFeatures.TIMES` and `TrainEvalFeatures.VALUES`): Univariate; `TIMES` and `VALUES` are both vectors of shape [series length] Multivariate; `TIMES` is a vector of shape [series length], `VALUES` has shape [series length x number of features]. In any case, `VALUES` and any exogenous features must have their shapes prefixed by the shape of the value corresponding to the `TIMES` key.
- `read_num_records_hint`: The maximum number of samples to read at one time, for efficiency.

`check_dataset_size`

```
check_dataset_size(minimum_dataset_size)
```

Raise an error if the dataset is too small.

`read`

```
read()
```

Returns a large chunk of the Numpy arrays for later re-chunking.

read_full

```
read_full()
```

Returns **Tensor** versions of the full Numpy arrays.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)