TancarFlow

TensorFlow API r1.4

tf.image.resize_bicubic

```
resize_bicubic(
  images,
  size,
  align_corners=False,
  name=None
)
```

Defined in tensorflow/python/ops/gen_image_ops.py.

See the guide: Images > Resizing

Resize images to size using bicubic interpolation.

Input images can be of different types but output images are always float.

Args:

- images: A Tensor. Must be one of the following types: uint8, int8, int16, int32, int64, half, float32, float64. 4-D with shape [batch, height, width, channels].
- size: A 1-D int32 Tensor of 2 elements: new_height, new_width. The new size for the images.
- align_corners: An optional bool. Defaults to False. If true, rescale input by (new_height 1) / (height 1), which
 exactly aligns the 4 corners of images and resized images. If false, rescale by new_height / height. Treat similarly the
 width dimension.
- name: A name for the operation (optional).

Returns:

A Tensor of type float32.4-D with shape [batch, new_height, new_width, channels].

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support

Issue Tracker

Release Notes

Stack Overflow

English

Terms | Privacy