## TanaarElaw

TensorFlow API r1.4

tf.metrics.mean\_iou

```
mean_iou(
    labels,
    predictions,
    num_classes,
    weights=None,
    metrics_collections=None,
    updates_collections=None,
    name=None
)
```

Defined in tensorflow/python/ops/metrics\_impl.py.

Calculate per-step mean Intersection-Over-Union (mIOU).

Mean Intersection-Over-Union is a common evaluation metric for semantic image segmentation, which first computes the IOU for each semantic class and then computes the average over classes. IOU is defined as follows: IOU = true\_positive / (true\_positive + false\_positive + false\_negative). The predictions are accumulated in a confusion matrix, weighted by weights, and mIOU is then calculated from it.

For estimation of the metric over a stream of data, the function creates an **update\_op** operation that updates these variables and returns the **mean\_iou**.

If weights is None, weights default to 1. Use weights of 0 to mask values.

## Args:

- labels: A **Tensor** of ground truth labels with shape [batch size] and of type **int32** or **int64**. The tensor will be flattened if its rank > 1.
- predictions: A Tensor of prediction results for semantic labels, whose shape is [batch size] and type int32 or int64. The tensor will be flattened if its rank > 1.
- num\_classes: The possible number of labels the prediction task can have. This value must be provided, since a confusion matrix of dimension = [num\_classes, num\_classes] will be allocated.
- weights: Optional **Tensor** whose rank is either 0, or the same rank as **labels**, and must be broadcastable to **labels** (i.e., all dimensions must be either **1**, or the same as the corresponding **labels** dimension).
- metrics\_collections: An optional list of collections that mean\_iou should be added to.
- updates\_collections : An optional list of collections update\_op should be added to.
- name: An optional variable\_scope name.

## Returns:

- mean\_iou: A Tensor representing the mean intersection-over-union.
- update\_op: An operation that increments the confusion matrix.

## Raises:

· ValueError: If predictions and labels have mismatched shapes, or if weights is not None and its shape

doesn't match predictions, or if either metrics\_collections or updates\_collections are not a list or tuple.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

