

tf.contrib.bayesflow.stochastic_tensor.value_type

```
value_type(  
    *args,  
    **kwds  
)
```

See the guide: [BayesFlow Stochastic Tensors \(contrib\) > Stochastic Tensor Value Types](#)

Creates a value type context for any StochasticTensor created within.

Typical usage:

```
with sg.value_type(sg.MeanValue(stop_gradients=True)):  
    st = sg.StochasticTensor(tf.contrib.distributions.Normal, mu=mu,  
                             sigma=sigma)
```

In the example above, `st.value()` (or equivalently, `tf.identity(st)`) will be the mean value of the Normal distribution, i.e., `mu` (possibly broadcasted to the shape of `sigma`). Furthermore, because the `MeanValue` was marked with `stop_gradients=True`, this value will have been wrapped in a `stop_gradients` call to disable any possible backpropagation.

Args:

- `dist_value_type`: An instance of `MeanValue`, `SampleValue`, or any other stochastic value type.

Yields:

A context for `StochasticTensor` objects that controls the value created when they are initialized.

Raises:

- `TypeError`: if `dist_value_type` is not an instance of a stochastic value type.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)