

tf.contrib.learn.run_n

```
run_n(  
    output_dict,  
    feed_dict=None,  
    restore_checkpoint_path=None,  
    n=1  
)
```

Defined in [tensorflow/contrib/learn/python/learn/graph_actions.py](#).

See the guide: [Learn \(contrib\) > Graph actions](#)

Run `output_dict` tensors `n` times, with the same `feed_dict` each run. (deprecated)

THIS FUNCTION IS DEPRECATED. It will be removed after 2017-02-15. Instructions for updating: `graph_actions.py` will be deleted. Use `tf.train.*` utilities instead. You can use `learn/estimators/estimator.py` as an example.

Args:

- `output_dict`: A `dict` mapping string names to tensors to run. Must all be from the same graph.
- `feed_dict`: `dict` of input values to feed each run.
- `restore_checkpoint_path`: A string containing the path to a checkpoint to restore.
- `n`: Number of times to repeat.

Returns:

A list of `n dict` objects, each containing values read from `output_dict` tensors.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

