

tf.contrib.crf.crf_log_likelihood

```
crf_log_likelihood(  
    inputs,  
    tag_indices,  
    sequence_lengths,  
    transition_params=None  
)
```

Defined in [tensorflow/contrib/crf/python/ops/crf.py](#).

See the guide: [CRF \(contrib\)](#)

Computes the log-likelihood of tag sequences in a CRF.

Args:

- `inputs`: A [batch_size, max_seq_len, num_tags] tensor of unary potentials to use as input to the CRF layer.
- `tag_indices`: A [batch_size, max_seq_len] matrix of tag indices for which we compute the log-likelihood.
- `sequence_lengths`: A [batch_size] vector of true sequence lengths.
- `transition_params`: A [num_tags, num_tags] transition matrix, if available.

Returns:

- `log_likelihood`: A scalar containing the log-likelihood of the given sequence of tag indices.
- `transition_params`: A [num_tags, num_tags] transition matrix. This is either provided by the caller or created in this function.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

