

tf.contrib.layers.maxout

```
maxout(  
    inputs,  
    num_units,  
    axis=-1,  
    name=None  
)
```

Defined in [tensorflow/python/layers/maxout.py](#).

Adds a maxout op from <https://arxiv.org/abs/1302.4389>

"Maxout Networks" Ian J. Goodfellow, David Warde-Farley, Mehdi Mirza, Aaron Courville, Yoshua Bengio

Usually the operation is performed in the filter/channel dimension. This can also be used after fully-connected layers to reduce number of features.

Arguments: inputs: Tensor input num_units: Specifies how many features will remain after maxout in the **axis** dimension (usually channel). This must be multiple of number of **axis**. axis: The dimension where max pooling will be performed. Default is the last dimension. name: Optional scope for name_scope.

Returns: A **Tensor** representing the results of the pooling operation.

Raises: ValueError: if num_units is not multiple of number of features.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)