

tf.nn.max_pool3d

```
max_pool3d(  
    input,  
    ksize,  
    strides,  
    padding,  
    data_format='NDHWC',  
    name=None  
)
```

Defined in `tensorflow/python/ops/gen_nn_ops.py`.

See the guide: [Neural Network > Pooling](#)

Performs 3D max pooling on the input.

Args:

- `input`: A `Tensor`. Must be one of the following types: `float32`. Shape `[batch, depth, rows, cols, channels]` tensor to pool over.
- `ksize`: A list of `ints` that has length `>= 5`. 1-D tensor of length 5. The size of the window for each dimension of the input tensor. Must have `ksize[0] = ksize[4] = 1`.
- `strides`: A list of `ints` that has length `>= 5`. 1-D tensor of length 5. The stride of the sliding window for each dimension of `input`. Must have `strides[0] = strides[4] = 1`.
- `padding`: A `string` from: `"SAME"`, `"VALID"`. The type of padding algorithm to use.
- `data_format`: An optional `string` from: `"NDHWC"`, `"NCDHW"`. Defaults to `"NDHWC"`. The data format of the input and output data. With the default format "NDHWC", the data is stored in the order of: `[batch, in_depth, in_height, in_width, in_channels]`. Alternatively, the format could be "NCDHW", the data storage order is: `[batch, in_channels, in_depth, in_height, in_width]`.
- `name`: A name for the operation (optional).

Returns:

A `Tensor`. Has the same type as `input`. The max pooled output tensor.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)