TopogrElow

TensorFlow API r1.4

tf.contrib.gan.losses.wargs.wasserstein_gradient_penalty

```
wasserstein_gradient_penalty(
    real_data,
    generated_data,
    generator_inputs,
    discriminator_fn,
    discriminator_scope,
    epsilon=1e-10,
    weights=1.0,
    scope=None,
    loss_collection=tf.GraphKeys.LOSSES,
    reduction=losses.Reduction.SUM_BY_NONZERO_WEIGHTS,
    add_summaries=False
)
```

Defined in tensorflow/contrib/gan/python/losses/python/losses_impl.py.

The gradient penalty for the Wasserstein discriminator loss.

See Improved Training of Wasserstein GANs (https://arxiv.org/abs/1704.00028) for more details.

Args:

- real_data: Real data.
- generated_data: Output of the generator.
- generator_inputs: Exact argument to pass to the generator, which is used as optional conditioning to the discriminator.
- discriminator_fn: A discriminator function that conforms to TFGAN API.
- discriminator_scope: If not None, reuse discriminators from this scope.
- epsilon: A small positive number added for numerical stability when computing the gradient norm.
- weights: Optional **Tensor** whose rank is either 0, or the same rank as **real_data** and **generated_data**, and must be broadcastable to them (i.e., all dimensions must be either 1, or the same as the corresponding dimension).
- scope: The scope for the operations performed in computing the loss.
- loss_collection: collection to which this loss will be added.
- reduction: A tf.losses.Reduction to apply to loss.
- add_summaries: Whether or not to add summaries for the loss.

Returns:

A loss Tensor. The shape depends on reduction.

Raises:

ValueError: If the rank of data Tensors is unknown.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

