tf.contrib.kfac.fisher_factors.ConvInputKroneckerFactor

Contents

Class **ConvInputKroneckerFactor**

Inherits From: **InverseProvidingFactor**

Defined in **tensorflow/contrib/kfac/python/ops/fisher_factors.py** .

Kronecker factor for the input side of a convolutional layer.

Methods

__init__

```
__init__(
    inputs,
    filter_shape,
    strides,
    padding,
    has_bias=False
)
```

get_cov

```
get_cov()
```

get_eigendecomp

```
get_eigendecomp()
```

get_inverse

```
get_inverse(damping)
```

get_matpower

```
get_matpower(
    exp,
    damping
)
```

instantiate_covariance

```
instantiate_covariance()
```

Instantiates the covariance Variable as the instance member _cov.

make_covariance_update_op

```
make_covariance_update_op(ema_decay)
```

Constructs and returns the covariance update Op.

Args:

- `ema_decay` : The exponential moving average decay (float or Tensor).

Returns:

An Op for updating the covariance Variable referenced by _cov.

make_inverse_update_ops

```
make_inverse_update_ops()
```

Create and return update ops corresponding to registered computations.

register_damped_inverse

```
register_damped_inverse(damping)
```

Registers a damped inverse needed by a FisherBlock.

Args:

- `damping` : The damping value (float or Tensor) for this factor.

register_eigendecomp

```
register_eigendecomp()
```

Registers that an eigendecomposition is needed by a FisherBlock.

register_matpower

```
register_matpower(
    exp,
    damping
)
```

Registers a matrix power needed by a FisherBlock.

Args:

- `exp` : The exponent (float or Tensor) to raise the matrix to.
- `damping` : The damping value (float or Tensor).

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support

Issue Tracker

Release Notes

Stack Overflow

English

Terms | **Privacy**