

## tfdbg.LocalCLIDebugWrapperSession

## Contents

Class LocalCLIDebugWrapperSession

## Properties

graph

graph\_def

Class **LocalCLIDebugWrapperSession**Defined in [tensorflow/python/debug/wrappers/local\\_cli\\_wrapper.py](#).See the guide: [TensorFlow Debugger > Session wrapper class and SessionRunHook implementations](#)

Concrete subclass of BaseDebugWrapperSession implementing a local CLI.

This class has all the methods that a `session.Session` object has, in order to support debugging with minimal code changes. Invoking its `run()` method will launch the command-line interface (CLI) of tfdbg.

## Properties

**graph****graph\_def****run\_call\_count****sess\_str****session**

## Methods

**\_\_init\_\_**

```
__init__(  
    sess,  
    dump_root=None,  
    log_usage=True,  
    ui_type='curses',  
    thread_name_filter=None  
)
```

Constructor of LocalCLIDebugWrapperSession.

Args:

- `sess` : The TensorFlow `Session` object being wrapped.
- `dump_root` : ( `str` ) optional path to the dump root directory. Must be a directory that does not exist or an empty directory. If the directory does not exist, it will be created by the debugger core during debug `run()` calls and removed afterwards. If `None`, the debug dumps will be at `tfdbg_` under the system temp directory.
- `log_usage` : ( `bool` ) whether the usage of this class is to be logged.
- `ui_type` : ( `str` ) requested UI type. Currently supported: (curses | readline)
- `thread_name_filter` : Regular-expression white list for thread name. See the doc of `BaseDebugWrapperSession` for details.

Raises:

- `ValueError` : If `dump_root` is an existing and non-empty directory or if `dump_root` is a file.

## `__enter__`

```
__enter__()
```

## `__exit__`

```
__exit__(
    exec_type,
    exec_value,
    exec_tb
)
```

## `add_tensor_filter`

```
add_tensor_filter(
    filter_name,
    tensor_filter
)
```

Add a tensor filter.

Args:

- `filter_name` : ( `str` ) name of the filter.
- `tensor_filter` : ( `callable` ) the filter callable. See the doc string of `DebugDumpDir.find()` for more details about its signature.

## `as_default`

```
as_default()
```

## `close`

```
close()
```

## `increment_run_call_count`

```
increment_run_call_count()
```

## invoke\_node\_stepper

```
invoke_node_stepper(  
    node_stepper,  
    restore_variable_values_on_exit=True  
)
```

Overrides method in base class to implement interactive node stepper.

Args:

- `node_stepper : ( stepper.NodeStepper )` The underlying NodeStepper API object.
- `restore_variable_values_on_exit : ( bool )` Whether any variables whose values have been altered during this node-stepper invocation should be restored to their old values when this invocation ends.

Returns:

The same return values as the `Session.run()` call on the same fetches as the NodeStepper.

## list\_devices

```
list_devices(  
    *args,  
    **kwargs  
)
```

## make\_callable

```
make_callable(  
    fetches,  
    feed_list=None,  
    accept_options=False  
)
```

## on\_run\_end

```
on_run_end(request)
```

Overrides on-run-end callback.

Actions taken: 1) Load the debug dump. 2) Bring up the Analyzer CLI.

Args:

- `request` : An instance of OnSessionInitRequest.

Returns:

An instance of `OnSessionInitResponse`.

## **on\_run\_start**

```
on_run_start(request)
```

Overrides on-run-start callback.

Invoke the CLI to let user choose what action to take: `run` / `invoke_stepper` .

Args:

- `request` : An instance of `OnRunStartRequest` .

Returns:

An instance of `OnRunStartResponse` .

## **on\_session\_init**

```
on_session_init(request)
```

Overrides on-session-init callback.

Args:

- `request` : An instance of `OnSessionInitRequest` .

Returns:

An instance of `OnSessionInitResponse` .

## **partial\_run**

```
partial_run(  
    handle,  
    fetches,  
    feed_dict=None  
)
```

## **partial\_run\_setup**

```
partial_run_setup(  
    fetches,  
    feeds=None  
)
```

Sets up the feeds and fetches for partial runs in the session.

## **reset**

```
reset(
    *args,
    **kwargs
)
```

## run

```
run(
    fetches,
    feed_dict=None,
    options=None,
    run_metadata=None,
    callable_runner=None,
    callable_runner_args=None
)
```

Wrapper around `Session.run()` that inserts tensor watch options.

### Args:

- `fetches`: Same as the `fetches` arg to regular `Session.run()`.
- `feed_dict`: Same as the `feed_dict` arg to regular `Session.run()`.
- `options`: Same as the `options` arg to regular `Session.run()`.
- `run_metadata`: Same as the `run_metadata` arg to regular `Session.run()`.
- `callable_runner`: A `callable` returned by `Session.make_callable()`. If not `None`, `fetches` and `feed_dict` must both be `None`.
- `callable_runner_args`: An optional list of arguments to `callable_runner`.

### Returns:

Simply forwards the output of the wrapped `Session.run()` call.

### Raises:

- `ValueError`: On invalid `OnRunStartAction` value. Or if `callable_runner` is not `None` and either or both of `fetches` and `feed_dict` is `None`.

## should\_stop

```
should_stop()
```

---

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

### Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

**Support**

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

**English**

[Terms](#) | [Privacy](#)