

tf.contrib.kfac.fisher_factors.NaiveDiagonalFactor

Contents

Class `NaiveDiagonalFactor`

Methods

`__init__`

`get_cov`

`instantiate_covariance`

`make_covariance_update_op`

`make_inverse_update_ops`

Class `NaiveDiagonalFactor`

Inherits From: [DiagonalFactor](#)

Defined in [tensorflow/contrib/kfac/python/ops/fisher_factors.py](#).

FisherFactor for a diagonal approximation of any type of param's Fisher.

Note that this uses the naive "square the sum estimator", and so is applicable to any type of parameter in principle, but has very high variance.

Methods

`__init__`

```
__init__(
    params_grads,
    batch_size
)
```

`get_cov`

```
get_cov()
```

`instantiate_covariance`

```
instantiate_covariance()
```

Instantiates the covariance Variable as the instance member `_cov`.

`make_covariance_update_op`

```
make_covariance_update_op(ema_decay)
```

Constructs and returns the covariance update Op.

Args:

- `ema_decay` : The exponential moving average decay (float or Tensor).

Returns:

An Op for updating the covariance Variable referenced by `_cov`.

make_inverse_update_ops

```
make_inverse_update_ops()
```

Create and return update ops corresponding to registered computations.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support

Issue Tracker

Release Notes

Stack Overflow

English

[Terms](#) | [Privacy](#)