TancarFlow

TensorFlow API r1.4

tf.nn.with_space_to_batch

```
with_space_to_batch(
    input,
    dilation_rate,
    padding,
    op,
    filter_shape=None,
    spatial_dims=None,
    data_format=None
)
```

Defined in tensorflow/python/ops/nn_ops.py.

See the guide: Neural Network > Morphological filtering

Performs op on the space-to-batch representation of input.

This has the effect of transforming sliding window operations into the corresponding "atrous" operation in which the input is sampled at the specified **dilation_rate**.

In the special case that **dilation_rate** is uniformly 1, this simply returns:

op(input, num_spatial_dims, padding)

Otherwise, it returns:

batch_to_space_nd(op(space_to_batch_nd(input, adjusted_dilation_rate, adjusted_paddings), num_spatial_dims, "VALID") adjusted_dilation_rate, adjusted_crops),

where:

adjusted_dilation_rate is an int64 tensor of shape [max(spatial_dims)], adjusted_{paddings,crops} are int64 tensors of shape [max(spatial_dims), 2]

defined as follows:

We first define two int64 tensors **paddings** and **crops** of shape **[num_spatial_dims, 2]** based on the value of **padding** and the spatial dimensions of the **input**:

```
If padding = "VALID", then:
```

paddings, crops = required_space_to_batch_paddings(input_shape[spatial_dims], dilation_rate)

```
If padding = "SAME", then:
```

```
dilated_filter_shape = filter_shape + (filter_shape - 1) * (dilation_rate - 1)
```

paddings, crops = required_space_to_batch_paddings(input_shape[spatial_dims], dilation_rate, [(dilated_filter_shape - 1) // 2, dilated_filter_shape - 1 - (dilated_filter_shape - 1) // 2])

Because <code>space_to_batch_nd</code> and <code>batch_to_space_nd</code> assume that the spatial dimensions are contiguous starting at the second dimension, but the specified <code>spatial_dims</code> may not be, we must adjust <code>dilation_rate</code>, <code>paddings</code> and <code>crops</code> in order to be usable with these operations. For a given dimension, if the block size is 1, and both the starting and ending padding and crop amounts are 0, then <code>space_to_batch_nd</code> effectively leaves that dimension alone, which is what is needed

for dimensions not part of **spatial_dims**. Furthermore, **space_to_batch_nd** and **batch_to_space_nd** handle this case efficiently for any number of leading and trailing dimensions.

For $0 \le i \le len(spatial_dims)$, we assign:

adjusted_dilation_rate[spatial_dims[i] - 1] = dilation_rate[i] adjusted_paddings[spatial_dims[i] - 1, :] = paddings[i, :] adjusted_crops[spatial_dims[i] - 1, :] = crops[i, :]

All unassigned values of **adjusted_dilation_rate** default to 1, while all unassigned values of **adjusted_paddings** and **adjusted_crops** default to 0.

Note in the case that **dilation_rate** is not uniformly 1, specifying "VALID" padding is equivalent to specifying **padding** = "SAME" with a filter_shape of [1]*N.

Advanced usage. Note the following optimization: A sequence of with_space_to_batch operations with identical (not uniformly 1) dilation_rate parameters and "VALID" padding

net = with_space_to_batch(net, dilation_rate, "VALID", op_1) ... net = with_space_to_batch(net, dilation_rate, "VALID", op_k)

can be combined into a single with_space_to_batch operation as follows:

def combined_op(converted_input, num_spatial_dims, _): result = op_1(converted_input, num_spatial_dims, "VALID") ... result = op_k(result, num_spatial_dims, "VALID")

net = with_space_to_batch(net, dilation_rate, "VALID", combined_op)

This eliminates the overhead of k-1 calls to space_to_batch_nd and batch_to_space_nd.

Similarly, a sequence of with_space_to_batch operations with identical (not uniformly 1) dilation_rate parameters, "SAME" padding, and odd filter dimensions

net = with_space_to_batch(net, dilation_rate, "SAME", op_1, filter_shape_1) ... net = with_space_to_batch(net, dilation_rate,
"SAME", op_k, filter_shape_k)

can be combined into a single with_space_to_batch operation as follows:

def combined_op(converted_input, num_spatial_dims, _): result = op_1(converted_input, num_spatial_dims, "SAME") ... result = op_k(result, num_spatial_dims, "SAME")

net = with_space_to_batch(net, dilation_rate, "VALID", combined_op)

Args:

- input: Tensor of rank > max(spatial_dims).
- dilation_rate: int32 Tensor of known shape [num_spatial_dims].
- padding: str constant equal to "VALID" or "SAME"
- op: Function that maps (input, num_spatial_dims, padding) -> output
- filter_shape: If padding = "SAME", specifies the shape of the convolution kernel/pooling window as an integer Tensor of shape [>=num_spatial_dims]. If padding = "VALID", filter_shape is ignored and need not be specified.
- spatial_dims: Monotonically increasing sequence of num_spatial_dims integers (which are >= 1) specifying the spatial dimensions of input and output. Defaults to: range(1, num_spatial_dims+1).
- data_format: A string or None. Specifies whether the channel dimension of the input and output is the last dimension (default, or if data_format does not start with "NC"), or the second dimension (if data_format starts with "NC"). For N=1, the valid values are "NWC" (default) and "NCW". For N=2, the valid values are "NHWC" (default) and "NCHW".
 For N=3, the valid values are "NDHWC" (default) and "NCDHW".

Returns:

The output Tensor as described above, dimensions will vary based on the op provided.

Raises:

- ValueError: if padding is invalid or the arguments are incompatible.
- ValueError: if spatial_dims are invalid.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

