

tf.contrib.gan.gan_train_ops

```
gan_train_ops(  
    model,  
    loss,  
    generator_optimizer,  
    discriminator_optimizer,  
    check_for_unused_update_ops=True,  
    **kwargs  
)
```

Defined in [tensorflow/contrib/gan/python/train.py](#).

Returns GAN train ops.

The highest-level call in TFGAN. It is composed of functions that can also be called, should a user require more control over some part of the GAN training process.

Args:

- `model`: A GANModel.
- `loss`: A GANLoss.
- `generator_optimizer`: The optimizer for generator updates.
- `discriminator_optimizer`: The optimizer for the discriminator updates.
- `check_for_unused_update_ops`: If `True`, throws an exception if there are update ops outside of the generator or discriminator scopes.
- `**kwargs`: Keyword args to pass directly to `training.create_train_op` for both the generator and discriminator train op.

Returns:

A GANTrainOps tuple of (generator_train_op, discriminator_train_op) that can be used to train a generator/discriminator pair.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)