## TancarFlow

TensorFlow API r1.4

tf.metrics.false\_positives\_at\_thresholds

```
false_positives_at_thresholds(
    labels,
    predictions,
    thresholds,
    weights=None,
    metrics_collections=None,
    updates_collections=None,
    name=None
)
```

Defined in tensorflow/python/ops/metrics\_impl.py.

Computes false positives at provided threshold values.

If weights is None, weights default to 1. Use weights of 0 to mask values.

## Args:

- labels: A Tensor whose shape matches predictions. Will be cast to bool.
- predictions: A floating point Tensor of arbitrary shape and whose values are in the range [0, 1].
- thresholds: A python list or tuple of float thresholds in [0, 1].
- weights: Optional Tensor whose rank is either 0, or the same rank as labels, and must be broadcastable to labels (i.e., all dimensions must be either 1, or the same as the corresponding labels dimension).
- metrics\_collections: An optional list of collections that false\_positives should be added to.
- updates\_collections: An optional list of collections that update\_op should be added to.
- name: An optional variable\_scope name.

## Returns:

- false\_positives: A float Tensor of shape [len(thresholds)].
- update\_op: An operation that updates the false\_positives variable and returns its current value.

## Raises:

ValueError: If predictions and labels have mismatched shapes, or if weights is not None and its shape
doesn't match predictions, or if either metrics\_collections or updates\_collections are not a list or tuple.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Blog			
GitHub			
Twitter			
Support			
oupport			
Issue Tracker			
Release Notes			
Stack Overflow			
English			
Terms   Privacy			