```
wir::intrusive::list
                                     node_base< T >
                                   # m next
                                   # m prev
                                   + list node base()
                                   + list_node_base()
                                   + list node base()
                                   + list_node_base()
                                   + operator=()
                                   + operator=()
                                   + ~list_node_base()
                                   + init self()
                                   + empty()
                                   + push back()
                                      9 8 8 8 ...
 wjr::btree_node< Traits >
                                 wjr::intrusive::list
+ m node
                                  node< btree_leaf_node
+ m root size
                                    < Traits, Inline > >
+ @1
+ m parent
                                      pop_front()
+ as inner()
                                      pop back()
+ as_inner()
                                   + next()
+ as leaf()
                                   + next()
+ as leaf()
                                   + prev()
+ WJR ENABLE DEFAULT
                                      prev()
  _SPECIAL_MEMBERS()
                                      front()
+ btree node()
                                      front()
+ size()
                                      back()
+ size()
                                      back()
+ pos()
                                      0 0 12 0 0 0 0 0 ...
+ pos()
                   wjr::btree_leaf_node
                     < Traits, Inline >
               + m values
               + WJR ENABLE DEFAULT
                 _SPECIAL_MEMBERS()
               + btree leaf node()
```

+ from_ivalue() + from_ivalue()