

Worth: 100 points (10% of course grade)
Assigned: Friday, Jan 24, 2014
Due: 1:25 pm, Monday, Feb 24, 2014

This project is intended to help you understand the instructions of a very simple assembly language and how to assemble programs into machine language.

This project has three parts. In the first part, you will write a program to take an assembly-language program and produce the corresponding machine language. In the second part, you will write a behavioral simulator for the resulting machine code. In the third part, you will write a short assembly-language program to multiply two numbers.

3. LC3101 Instruction-Set Architecture BT 0 0 1 75.024 699.1 Tm0>> BDC BT 0 0 1 75.

Take pr365.03D 01>>7(de)] 7(a0) 7(o)] 7(eb) 7(n[u0 7Qnba +Ag> k n[u 7](eTJ7(epr) h eT8h(idgrs)(eTJl(v

Symbolic addresses refer to labels. For lw or sw instructions, the assembler should compute offsetField to be equal to the address of the label. This could be used with a zero base register to refer to the label, or could be used

a non-zero base register to index into an array starting at the label.

For beq instructions, the assembler should translate the label into the number of offsetField needed to branch to that label.

After the last used field comes more white space, then any comments. The comment field ends at the end of a line. Comments are vital to creating understandable assembly-language programs, because the instructions themselves are rather cryptic.

In addition to LC3101 instructions, an assembly language program may contain directions for the assembler. The only assembler directive we will use is .fill

As with the assembler, you will write a suite of test cases to validate the LC3101 simulator.

The test cases for the simulator part of this project will be short assembly-language programs that, after being assembled into machine code, serve


```

    /* after doing a readAndParse, you may want to do the following to
test the
        opcode */
    if (!strcmp(opcode, "add")) {
        /* do whatever you need to do for opcode "add" */
    }

    return(0);
}

/*
 * Read and parse a line of the assembly-language file. Fields are
returned
 * in label, opcode, arg0, arg1, arg2 (these strings must have memory
already
 * allocated to them).
 *
 * Return values:
 *     0 if reached end of file
 *     1 if all went well
 *
 * exit(1) if line is too long.
 */
int
readAndParse(FILE *inFilePtr, char *label, char *opcode, char *arg0,
             char *arg1, char *arg2)
{
    char line[MAXLINELENGTH];
    char *ptr = line;

    /* delete prior values */
    label[0] = opcode[0] = arg0[0] = arg1[0] = arg2[0] = '\0';

    /* read the line from the assembly-language file */
    if (fgets(line, MAXLINELENGTH, inFilePtr) == NULL) {
        /* reached end of file */
        return(0);
    }

    /* check for line too long (by looking for a \n) */
    if (strchr(line, '\n') == NULL) {
        /* line too long */
        printf("error: line too long\n");
        exit(1);
    }

    /* is there a label? */
    ptr = line;
    if (sscanf(ptr, "%[^\\t\\n ]", label)) {
        /* successfully read label; advance pointer over the label */
        ptr += strlen(label);
    }

    /*

```

```

        * Parse the rest of the line.  Would be nice to have real regular
        * expressions, but scanf will suffice.
        */
        sscanf(ptr, "%*[\t\n ]%[^\\t\\n ]%*[\t\n ]%[^\\t\\n ]%*[\t\n ]%[^\\t\\n
]%^*[\t\n ]%[^\\t\\n ]",
               opcode, arg0, arg1, arg2);
        return(1);
    }

int
isNumber(char *string)
{
    /* return 1 if string is a number */
    int i;
    return( (sscanf(string, "%d", &i)) == 1);
}

```

10. Code Fragment for Simulator

Here is some C code that may help you write the simulator. Again, you should take this merely as a hint. You may have to re-code this to make it do exactly what you want, but this should help you get started. Remember not to change stateStruct or printState.

```

/* instruction-level simulator for LC3101 */

#include <stdio.h>
#include <string.h>

#define NUMMEMORY 65536 /* maximum number of words in memory */
#define NUMREGS 8 /* number of machine registers */
#define MAXLINELENGTH 1000

typedef struct stateStruct {
    int pc;
    int mem[NUMMEMORY];
    int reg[NUMREGS];
    int numMemory;
} stateType;

void printState(stateType *);

int
main(int argc, char *argv[])
{
    char line[MAXLINELENGTH];
    stateType state;
    FILE *filePtr;

    if (argc != 2) {

```


bits. Neither a nor b are changed. E.g. $(25 \gg 2)$ is 6. Note that 25 is 11001 in binary, and 6 is 110 in binary.

3) The value of the expression $(a \ll b)$ is the number "a" shifted left by "b" bits. Neither a nor b are changed. E.g. $(25 \ll 2)$ is 100. Note that 25 is 11001 in binary, and 100 is 1100100 in binary.

4) To find the value of the expression $(a \& b)$, perform a logical AND on each bit of a and b (i.e. bit 31 of a ANDED with bit 31 of b, bit 30 of a ANDED with bit 30 of b, etc.). E.g. $(25 \& 11)$ is 9, since:

```
      11001 (binary)
      & 01011 (binary)
      -----
      = 01001 (binary), which is 9 decimal.
```

5) To find the value of the expression $(a | b)$, perform a logical OR on each bit of a and b (i.e. bit 31 of a ORED with bit 31 of b, bit 30 of a ORED with bit 30 of b, etc.). E.g. $(25 | 11)$ is 27, since:

```
      11001 (binary)
      & 01011 (binary)
      -----
      = 11011 (binary), which is 27 decimal.
```

6) $\sim a$ is the bit-wise complement of a (a is not changed).

Use these operations to create and manipulate machine-code. E.g. to look at bit 3 of the variable a, you might do: $(a \gg 3) \& 0x1$. To look at bits (bits 15-12) of a 16-bit word, you could do: $(a \gg 12) \& 0xF$. To put a 6 into bits 5-3 and a 3 into bits 2-1, you could do: $(6 \ll 3) | (3 \ll 1)$. If you're not sure what an operation is doing, print some intermediate results to help you debug.

12. Example Run of Simulator

```
memory[0]=8454151
memory[1]=9043971
memory[2]=655361
memory[3]=16842754
memory[4]=16842749
memory[5]=29360128
memory[6]=25165824
```

```
memory[7]=5
memory[8]=-1
memory[9]=2
```

```
@@@
```

```
state:
```

```
    pc 0
```

```
    memory:
```

```
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
```

```
    registers:
```

```
        reg[ 0 ] 0
        reg[ 1 ] 0
        reg[ 2 ] 0
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
```

```
end state
```

```
@@@
```

```
state:
```

```
    pc 1
```

```
    memory:
```

```
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
```

```
    registers:
```

```
        reg[ 0 ] 0
        reg[ 1 ] 5
        reg[ 2 ] 0
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
```

```
end state
```



```

@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 5
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 4
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 4

```

```

memory:
    mem[ 0 ] 8454151
    mem[ 1 ] 9043971
    mem[ 2 ] 655361
    mem[ 3 ] 16842754
    mem[ 4 ] 16842749
    mem[ 5 ] 29360128
    mem[ 6 ] 25165824
    mem[ 7 ] 5
    mem[ 8 ] -1
    mem[ 9 ] 2
registers:
    reg[ 0 ] 0
    reg[ 1 ] 4
    reg[ 2 ] -1
    reg[ 3 ] 0
    reg[ 4 ] 0
    reg[ 5 ] 0
    reg[ 6 ] 0
    reg[ 7 ] 0
end state

```

@@@

```

state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 4
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

@@@

```

state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361

```

```

        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 4
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824

```

```

        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

@@@

state:

pc 3

memory:

```

        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2

```

registers:

```

        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0

```

end state

@@@

state:

pc 4

memory:

```

        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2

```

registers:

```
        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state
```

@@@

state:

pc 2

memory:

```
    mem[ 0 ] 8454151
    mem[ 1 ] 9043971
    mem[ 2 ] 655361
    mem[ 3 ] 16842754
    mem[ 4 ] 16842749
    mem[ 5 ] 29360128
    mem[ 6 ] 25165824
    mem[ 7 ] 5
    mem[ 8 ] -1
    mem[ 9 ] 2
```

registers:

```
    reg[ 0 ] 0
    reg[ 1 ] 2
    reg[ 2 ] -1
    reg[ 3 ] 0
    reg[ 4 ] 0
    reg[ 5 ] 0
    reg[ 6 ] 0
    reg[ 7 ] 0
```

end state

@@@

state:

pc 3

memory:

```
    mem[ 0 ] 8454151
    mem[ 1 ] 9043971
    mem[ 2 ] 655361
    mem[ 3 ] 16842754
    mem[ 4 ] 16842749
    mem[ 5 ] 29360128
    mem[ 6 ] 25165824
    mem[ 7 ] 5
    mem[ 8 ] -1
    mem[ 9 ] 2
```

registers:

```
    reg[ 0 ] 0
    reg[ 1 ] 1
    reg[ 2 ] -1
    reg[ 3 ] 0
```

```
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state
```

@@@

state:

pc 4

memory:

```
mem[ 0 ] 8454151
mem[ 1 ] 9043971
mem[ 2 ] 655361
mem[ 3 ] 16842754
mem[ 4 ] 16842749
mem[ 5 ] 29360128
mem[ 6 ] 25165824
mem[ 7 ] 5
mem[ 8 ] -1
mem[ 9 ] 2
```

registers:

```
reg[ 0 ] 0
reg[ 1 ] 1
reg[ 2 ] -1
reg[ 3 ] 0
reg[ 4 ] 0
reg[ 5 ] 0
reg[ 6 ] 0
reg[ 7 ] 0
```

end state

@@@

state:

pc 2

memory:

```
mem[ 0 ] 8454151
mem[ 1 ] 9043971
mem[ 2 ] 655361
mem[ 3 ] 16842754
mem[ 4 ] 16842749
mem[ 5 ] 29360128
mem[ 6 ] 25165824
mem[ 7 ] 5
mem[ 8 ] -1
mem[ 9 ] 2
```

registers:

```
reg[ 0 ] 0
reg[ 1 ] 1
reg[ 2 ] -1
reg[ 3 ] 0
reg[ 4 ] 0
reg[ 5 ] 0
reg[ 6 ] 0
reg[ 7 ] 0
```

end state

@@@

state:

pc 3

memory:

mem[0]	8454151
mem[1]	9043971
mem[2]	655361
mem[3]	16842754
mem[4]	16842749
mem[5]	29360128
mem[6]	25165824
mem[7]	5
mem[8]	-1
mem[9]	2

registers:

reg[0]	0
reg[1]	0
reg[2]	-1
reg[3]	0
reg[4]	0
reg[5]	0
reg[6]	0
reg[7]	0

end state

@@@

state:

pc 6

memory:

mem[0]	8454151
mem[1]	9043971
mem[2]	655361
mem[3]	16842754
mem[4]	16842749
mem[5]	29360128
mem[6]	25165824
mem[7]	5
mem[8]	-1
mem[9]	2

registers:

reg[0]	0
reg[1]	0
reg[2]	-1
reg[3]	0
reg[4]	0
reg[5]	0
reg[6]	0
reg[7]	0

end state

machine halted

total of 17 instructions executed

final state of machine:

```
@@@
state:
  pc 7
  memory:
    mem[ 0 ] 8454151
    mem[ 1 ] 9043971
    mem[ 2 ] 655361
    mem[ 3 ] 16842754
    mem[ 4 ] 16842749
    mem[ 5 ] 29360128
    mem[ 6 ] 25165824
    mem[ 7 ] 5
    mem[ 8 ] -1
    mem[ 9 ] 2
  registers:
    reg[ 0 ] 0
    reg[ 1 ] 0
    reg[ 2 ] -1
    reg[ 3 ] 0
    reg[ 4 ] 0
    reg[ 5 ] 0
    reg[ 6 ] 0
    reg[ 7 ] 0
end state
```