

Project 1--CDA 3101 (Spring 2014)

Worth: 100 points (10% of course grade)

Assigned: Friday, Jan 24, 2014 1:25 pm

Due: 1:25 pm, Monday, Feb 24, 2014

1. Purpose

This project is intended to help you understand the instructions of a very simple assembly language and how to assemble programs into machine language.

2. Problem

This project has three parts. In the first part, you will write a program to take an assembly-language program and produce the corresponding machine language. In the second part, you will write a behavioral simulator for the

resulting machine code. In the third part, you will write a short

assD 17>> BDC BT 0 0 1 75.024 461.11 Tm BT 0 0 1 75.024 663.46 >> BDC BT 0 8 508.7

bits 24-22: opcode
bits 21-19: reg A
bits 18-16: reg B
bits 15-0: offsetField (16-bit, range of -32768 to 32767)

O-

file, one instruction per line. Any deviation from this format (e.g. extra spaces or empty lines) will render your machine-code file ungradable. Any other output that you want the program to generate (e.g. debugging output) can be printed to standard output.

4.2. Error Checking

Your assembler should catch the following errors in the assembly-language program: use of undefined labels, duplicate labels, offsetFields that don't fit

Hints: the example assembly-language program above is a good case to include in your test suite, though you'll need to write more test cases to get full credit. Remember to create some test cases that test the ability of an assembler to check for the errors in Section 4.2.

4.4. Assembler Hints

Since offsetField is a 2's complement number, it can only store numbers ranging from -32768 to 32767. For symbolic addresses, your assembler will compute offsetField so that the instruction refers to the correct label.

Remember that offsetField is only an 16-bit 2's complement number. It can only store numbers ranging from -32768 to 32767. For symbolic addresses, your assembler will compute offsetField so that the instruction refers to the correct label.

As with the assembler, you will write a suite of test cases to validate the LC3101 simulator.

The test cases for the simulator part of this project will be short assembly-language programs that, after being assembled into machine code, serve as input to a simulator. You will submit your suite of test cases together with your simulator, and we will grade your test suite according to how thoroughly it exercises an LC3101 simulator. Each test case may execute at most 200 instructions on a correct simulator, and your test suite may contain up to 20 test cases. These limits are much larger than needed for full credit (the solution test suite is composed of a couple test cases, each executing less than 40 instructions). See Section 7 for how your test suite will be graded.

5.2. Simulator Hints

Be careful how you handle `offsetField` for `lw`, `sw`, and `beq`. Remember that it's a 2's complement 16-bit number, so you need to convert a negative `offsetField` to a negative 32-bit integer on the Sun workstations (by sign extending it). To do this, use the following function.

```
int
convertNum(int num)
{
    /* convert a 16-bit number into a 32-bit Sun integer */
    if (num & (1<<15) ) {
        num -= (1<<16);
    }
    return(num);
}
```

An example run of the simulator (not for the specified task of multiplication) is included at the end of this posting.

6. Assembly-Language Multiplication (20%)

The third part of this assignment is to write an assembly-language program to multiply two numbers. Input the numbers by reading memory locations called "mcand" and "mplier". The result should be stored in register 1 when the

program halts. You may assume that the two input numbers are at most 15 bits and are positive; this ensures that the (positive) result fits in an LC3101 word. See the algorithm on page 252 of the textbook for how to multiply. Remember that shifting left by one bit is the same as adding the number to itself. Given the LC3101 instruction set, it's easiest to modify the algorithm so that you avoid the right shift. Submit a version of the program that computes $(32766 * 10383)$.

Your multiplication program must be reasonably efficient--it must be at most 50 lines long and execute at most 1000 instructions for any valid numbers (this is several times longer and slower than the solution). To achieve this, you must use a loop and shift algorithm to perform the multiplication; algorithms such as successive addition (e.g. multiplying $5 * 6$ by adding 5 six times) will take too long.

7. Grading and Formatting

We will grade primarily on functionality, including error handling, correctly assembling and simulating all instructions, input and output format, method of executing your program, correctly multiplying, and comprehensiveness of the test suites.

The best way to debug your program is to generate your own test cases, figure out the correct answers, and compare your program's output to the correct answers. This is also one of the best ways to learn the concepts in the project.

The student suite of test cases for the assembler and simulator parts of this project will be graded according to how thoroughly they test an LC3101 assembler or simulator. We will judge thoroughness of the test suite by how well it exposes potentially bugs in an assembler or simulator.

For the assembler test suite, we will use each test case as input to a set of buggy assemblers. A test case exposes a buggy assembler by causing it to generate a different answer from a correct assembler. The test suite is graded based on how many of the buggy assemblers were exposed by at least one test case. This is known as "mutation testing" in the research literature on automated testing.

You may also choose to not use this fragment.

```
/* Assembler code fragment for LC3101 */
```

```
#include <stdlib.h>
```

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#define MAXLINELENGTH 1000
```

```
int readAndParse(FILE *, char *,
```

```

    /* after doing a readAndParse, you may want to do the following to
test the
    opcode */
    if (!strcmp(opcode, "add")) {
        /* do whatever you need to do for opcode "add" */
    }

    return(0);
}

/*
 * Read and parse a line of the assembly-language file. Fields are
returned
 * in label, opcode, arg0, arg1, arg2 (these strings must have memory
already
 * allocated to them).
 *
 * Return values:
 *     0 if reached end of file
 *     1 if all went well
 *
 * exit(1) if line is too long.
 */
int
readAndParse(FILE *inFilePtr, char *label, char *opcode, char *arg0,
             char *arg1, char *arg2)
{
    char line[MAXLINELENGTH];
    char *ptr = line;

    /* delete prior values */
    label[0] = opcode[0] = arg0[0] = arg1[0] = arg2[0] = '\0';

    /* read the line from the assembly-language file */
    if (fgets(line, MAXLINELENGTH, inFilePtr) == NULL) {
        /* reached end of file */
        return(0);
    }

    /* check for line too long (by looking for a \n) */
    if (strchr(line, '\n') == NULL) {
        /* line too long */
        printf("error: line too long\n");
        exit(1);
    }

    /* is there a label? */
    ptr = line;
    if (sscanf(ptr, "%[^\\t\\n ]", label)) {
        /* successfully read label; advance pointer over the label */
        ptr += strlen(label);
    }

    /*

```

```

        * Parse the rest of the line.  Would be nice to have real regular
        * expressions, but scanf will suffice.
        */
        sscanf(ptr, "%*[\t\n ]%[^\\t\\n ]%*[\t\n ]%[^\\t\\n ]%*[\t\n ]%[^\\t\\n
]%^*[\t\n ]%[^\\t\\n ]",
               opcode, arg0, arg1, arg2);
        return(1);
    }

int
isNumber(char *string)
{
    /* return 1 if string is a number */
    int i;
    return( (sscanf(string, "%d", &i)) == 1);
}

```

10. Code Fragment for Simulator

Here is some C code that may help you write the simulator. Again, you should take this merely as a hint. You may have to re-code this to make it do exactly what you want, but this should help you get started. Remember not to change stateStruct or printState.

```

/* instruction-level simulator for LC3101 */

#include <stdio.h>
#include <string.h>

#define NUMMEMORY 65536 /* maximum number of words in memory */
#define NUMREGS 8 /* number of machine registers */
#define MAXLINELENGTH 1000

typedef struct stateStruct {
    int pc;
    int mem[NUMMEMORY];
    int reg[NUMREGS];
    int numMemory;
} stateType;

void printState(stateType *);

int
main(int argc, char *argv[])
{
    char line[MAXLINELENGTH];
    stateType state;
    FILE *filePtr;

    if (argc != 2) {

```


bits. Neither a nor b are changed. E.g. (25 >> 2) is 6. Note that 25 is 11001 in binary, and 6 is 110 in binary.

3) The value of the expression (a << b) is the number "a" shifted left by "b" bits. Neither a nor b are changed. E.g. (25 << 2) is 100. Note that 25 is 11001 in binary, and 100 is 1100100 in binary.

4) To find the value of the expression (a & b), perform a logical AND on each bit of a and b (i.e. bit 31 of a ANDED with bit 31 of b, bit 30 of a ANDED with bit 30 of b, etc.). E.g. (25 & 11) is 9, since:

```
      11001 (binary)
      & 01011 (binary)
      -----
= 01001 (binary), which is 9 decimal.
```

5) To find the value of the expression (a | b), perform a logical OR on each bit of a and b (i.e. bit 31 of a ORED with bit 31 of b, bit 30 of a ORED with bit 30 of b, etc.). E.g. (25 | 11) is 27, since:

```
      11001 (binary)
      & 01011 (binary)
      -----
= 11011 (binary), which is 27 decimal.
```

6) ~a is the bit-wise complement of a (a is not changed).

Use these operations to create and manipulate machine-code. E.g. to look at bit 3 of the variable a, you might do: (a>>3) & 0x1. To look at bits (bits 15-12) of a 16-bit word, you could do: (a>>12) & 0xF. To put a 6 into bits 5-3 and a 3 into bits 2-1, you could do: (6<<3) | (3<<1). If you're not sure what an operation is doing, print some intermediate results to help you debug.

12. Example Run of Simulator

```
memory[0]=8454151
memory[1]=9043971
memory[2]=655361
memory[3]=16842754
memory[4]=16842749
memory[5]=29360128
memory[6]=25165824
```

```
memory[7]=5
memory[8]=-1
memory[9]=2
```

```
@@@
```

```
state:
```

```
    pc 0
```

```
    memory:
```

```
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
```

```
    registers:
```

```
        reg[ 0 ] 0
        reg[ 1 ] 0
        reg[ 2 ] 0
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
```

```
end state
```

```
@@@
```

```
state:
```

```
    pc 1
```

```
    memory:
```

```
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
```

```
    registers:
```

```
        reg[ 0 ] 0
        reg[ 1 ] 5
        reg[ 2 ] 0
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
```

```
end state
```



```

@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 5
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 4
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 4

```

```

memory:
    mem[ 0 ] 8454151
    mem[ 1 ] 9043971
    mem[ 2 ] 655361
    mem[ 3 ] 16842754
    mem[ 4 ] 16842749
    mem[ 5 ] 29360128
    mem[ 6 ] 25165824
    mem[ 7 ] 5
    mem[ 8 ] -1
    mem[ 9 ] 2
registers:
    reg[ 0 ] 0
    reg[ 1 ] 4
    reg[ 2 ] -1
    reg[ 3 ] 0
    reg[ 4 ] 0
    reg[ 5 ] 0
    reg[ 6 ] 0
    reg[ 7 ] 0
end state

```

@@@

```

state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 4
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

@@@

```

state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361

```

```

        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 4
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824

```

```

        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

@@@

state:

pc 3

memory:

```

        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2

```

registers:

```

        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0

```

end state

@@@

state:

pc 4

memory:

```

        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2

```

registers:

```
        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state
```

```
@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
```

end state

```
@@@
state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 1
        reg[ 2 ] -1
        reg[ 3 ] 0
```

```
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state
```

@@@

state:

pc 4

memory:

```
mem[ 0 ] 8454151
mem[ 1 ] 9043971
mem[ 2 ] 655361
mem[ 3 ] 16842754
mem[ 4 ] 16842749
mem[ 5 ] 29360128
mem[ 6 ] 25165824
mem[ 7 ] 5
mem[ 8 ] -1
mem[ 9 ] 2
```

registers:

```
reg[ 0 ] 0
reg[ 1 ] 1
reg[ 2 ] -1
reg[ 3 ] 0
reg[ 4 ] 0
reg[ 5 ] 0
reg[ 6 ] 0
reg[ 7 ] 0
```

end state

@@@

state:

pc 2

memory:

```
mem[ 0 ] 8454151
mem[ 1 ] 9043971
mem[ 2 ] 655361
mem[ 3 ] 16842754
mem[ 4 ] 16842749
mem[ 5 ] 29360128
mem[ 6 ] 25165824
mem[ 7 ] 5
mem[ 8 ] -1
mem[ 9 ] 2
```

registers:

```
reg[ 0 ] 0
reg[ 1 ] 1
reg[ 2 ] -1
reg[ 3 ] 0
reg[ 4 ] 0
reg[ 5 ] 0
reg[ 6 ] 0
reg[ 7 ] 0
```

end state

@@@

state:

pc 3

memory:

mem[0]	8454151
mem[1]	9043971
mem[2]	655361
mem[3]	16842754
mem[4]	16842749
mem[5]	29360128
mem[6]	25165824
mem[7]	5
mem[8]	-1
mem[9]	2

registers:

reg[0]	0
reg[1]	0
reg[2]	-1
reg[3]	0
reg[4]	0
reg[5]	0
reg[6]	0
reg[7]	0

end state

@@@

state:

pc 6

memory:

mem[0]	8454151
mem[1]	9043971
mem[2]	655361
mem[3]	16842754
mem[4]	16842749
mem[5]	29360128
mem[6]	25165824
mem[7]	5
mem[8]	-1
mem[9]	2

registers:

reg[0]	0
reg[1]	0
reg[2]	-1
reg[3]	0
reg[4]	0
reg[5]	0
reg[6]	0
reg[7]	0

end state

machine halted

total of 17 instructions executed

final state of machine:

```
@@@
state:
  pc 7
  memory:
    mem[ 0 ] 8454151
    mem[ 1 ] 9043971
    mem[ 2 ] 655361
    mem[ 3 ] 16842754
    mem[ 4 ] 16842749
    mem[ 5 ] 29360128
    mem[ 6 ] 25165824
    mem[ 7 ] 5
    mem[ 8 ] -1
    mem[ 9 ] 2
  registers:
    reg[ 0 ] 0
    reg[ 1 ] 0
    reg[ 2 ] -1
    reg[ 3 ] 0
    reg[ 4 ] 0
    reg[ 5 ] 0
    reg[ 6 ] 0
    reg[ 7 ] 0
end state
```