



bits 24-22: opcode  
bits 21-19: reg A  
bits 18-16: reg B  
bits 15-0: offsetField (16-bit, range of -32768 to 32767)

O-type instructions (halt, noop):  
bits 24-

-----  
-----  
4. LC3101 Assembly Language and Assembler (40%)

The first part of this project is to write a program to take an assembly-language program and translate it into machine language. You will translate assembly-language names for instructions, such as beq, into their numeric equivalent (e.g. 100), and you will translate symbolic names for addresses into numeric values. The final output will be a series of 32-bit instructions (instruction bits 31-25 are always 0).

The format for a line of assembly code is:

label instruction field0 field1 field2 comments





file, one instruction per line. Any deviation from this format (e.g. extra spaces or empty lines) will render your machine-code file ungradable. Any



As with the assembler, you will write a suite of test cases to validate the LC3101 simulator.

The test cases for the simulator part of this project will be short assembly-language programs that, after being assembled into machine code, serve as input to a simulator. You will submit your suite of test cases together with your simulator, and we will grade your test suite according to how thoroughly it exercises an LC3101 simulator. Each test case may execute at most 200 instructions on a correct simulator, and your test suite may contain up to 20 test cases. These limits are much larger than needed for full credit (the solution test suite is composed of a couple test cases, each executing less than 40 instructions). See Section 7 for how your test suite will be graded.

## 5.2. Simulator Hints

Be careful how you handle `offsetField` for `lw`, `sw`, and `beq`. Remember that it's a 2's complement 16-bit number, so you need to convert a negative `offsetField` to a negative 32-bit integer on the Sun workstations (by sign extending it). To do this, use the following function.

```
int
convertNum(int num)
{
    /* convert a 16-bit number into a 32-bit Sun integer */
    if (num & (1<<15) ) {
        num -= (1<<16);
    }
    return(num);
}
```

An example run of the simulator (not for the specified task of multiplication) is included at the end of this posting.

## 6. Assembly-Language Multiplication (20%)



program halts. You may assume that the two input numbers are at most 15 bits

For the simulator test suite, we will correctly assemble each test case, then use it as input to a set of buggy simulators. A test case exposes a buggy simulator by causing it to generate a different answer from a correct simulator. The test suite is graded based on how many of the buggy simulators were exposed by at least one test case.

## 8. Turning in the Project

Submit your files through blackboard.

Each part should be archived in a .tar or .zip file to help with grading.

Here are the files you should submit for each project part:

- 1) assembler (part 1a)
  - b. suite of test cases (each test case is an assembly-language program in a separate file)
- 2) simulator (part 1s)
  - a. C/C++ program for your simulator
  - b. suite of test cases (each test case is an assembly-language program in a

You may also choose to not use this fragment.

```
/* Assembler code fragment for LC3101 */

#include <stdlib.h>
#include <stdio.h>
#include <string.h>

#define MAXLINELENGTH 1000

int readAndParse(FILE *, char *, char *, char *, char *, char *);
int isNumber(char *);

int
main(int argc, char *argv[])
{
    char *inFileString, *outFileString;
    FILE *inFilePtr, *outFilePtr;
    char label[MAXLINELENGTH], opcode[MAXLINELENGTH],
    arg0[MAXLINELENGTH],
        arg1[MAXLINELENGTH], arg2[MAXLINELENGTH];

    if (argc != 3) {
        printf("error: usage: %s <assembly-code-file> <machine-code-
file>\n",
            argv[0]);
        exit(1);
    }

    inFileString = argv[1];
    outFileString = argv[2];

    inFilePtr = fopen(inFileString, "r");
    if (inFilePtr == NULL) {
        printf("error in opening %s\n", inFileString);
        exit(1);
    }
}
```

```

    /* after doing a readAndParse, you may want to do the following to
test the
        opcode */
    if (!strcmp(opcode, "add")) {
        /* do whatever you need to do for opcode "add" */
    }

    return(0);
}

/*
 * Read and parse a line of the assembly-language file. Fields are
returned
 * in label, opcode, arg0, arg1, arg2 (these strings must have memory
already
 * allocated to them).
 *
 * Return values:
 *     0 if reached end of file
 *     1 if all went well
 *
 * exit(1) if line is too long.
 */
int
readAndParse(FILE *inFilePtr, char *label, char *opcode, char *arg0,
             char *arg1, char *arg2)
{
    char line[MAXLINELENGTH];
    char *ptr = line;

    /* delete prior values */
    label[0] = opcode[0] = arg0[0] = arg1[0] = arg2[0] = '\0';

    /* read the line from the assembly-language file */
    if (fgets(line, MAXLINELENGTH, inFilePtr) == NULL) {
        /* reached end of file */
        return(0);
    }

    /* check for line too long (by looking for a \n) */
    if (strchr(line, '\n') == NULL) {
        /* line too long */
        printf("error: line too long\n");
        exit(1);
    }

    /* is there a label? */
    ptr = line;
    if (sscanf(ptr, "%[^\\t\\n ]", label)) {
        /* successfully read label; advance pointer over the label */
        ptr += strlen(label);
    }

    /*

```

```

        * Parse the rest of the line.  Would be nice to have real regular
        * expressions, but scanf will suffice.
        */
        sscanf(ptr, "%*[\t\n ]%[^\\t\\n ]%*[\t\n ]%[^\\t\\n ]%*[\t\n ]%[^\\t\\n
]%^*[\t\n ]%[^\\t\\n ]",
               opcode, arg0, arg1, arg2);
        return(1);
    }

int
isNumber(char *string)
{
    /* return 1 if string is a number */
    int i;
    return( (sscanf(string, "%d", &i)) == 1);
}

```

## 10. Code Fragment for Simulator

Here is some C code that may help you write the simulator. Again, you should take this merely as a hint. You may have to re-code this to make it do exactly what you want, but this should help you get started. Remember not to change stateStruct or printState.

```

/* instruction-level simulator for LC3101 */

#include <stdio.h>
#include <string.h>

#define NUMMEMORY 65536 /* maximum number of words in memory */
#define NUMREGS 8 /* number of machine registers */
#define MAXLINELENGTH 1000

typedef struct stateStruct {
    int pc;
    int mem[NUMMEMORY];
    int reg[NUMREGS];
    int numMemory;
} stateType;

void printState(stateType *);

int
main(int argc, char *argv[])
{
    char line[MAXLINELENGTH];
    stateType state;
    FILE *filePtr;

    if (argc != 2) {

```



bits. Neither a nor b are changed. E.g.  $(25 \gg 2)$  is 6. Note that 25 is 11001 in binary, and 6 is 110 in binary.

3) The value of the expression  $(a \ll b)$  is the number "a" shifted left by "b" bits. Neither a nor b are changed. E.g.  $(25 \ll 2)$  is 100. Note that 25 is 11001 in binary, and 100 is 1100100 in binary.

4) To find the value of the expression  $(a \& b)$ , perform a logical AND on each bit of a and b (i.e. bit 31 of a ANDED with bit 31 of b, bit 30 of a ANDED with bit 30 of b, etc.). E.g.  $(25 \& 11)$  is 9, since:

```
      11001 (binary)
      & 01011 (binary)
      -----
= 01001 (binary), which is 9 decimal.
```

5) To find the value of the expression  $(a | b)$ , perform a logical OR on each bit of a and b (i.e. bit 31 of a ORED with bit 31 of b, bit 30 of a ORED with bit 30 of b, etc.). E.g.  $(25 | 11)$  is 27, since:

```
      11001 (binary)
      & 01011 (binary)
      -----
= 11011 (binary), which is 27 decimal.
```

6)  $\sim a$  is the bit-wise complement of a (a is not changed).

Use these operations to create and manipulate machine-code. E.g. to look at bit 3 of the variable a, you might do:  $(a \gg 3) \& 0x1$ . To look at bits (bits 15-12) of a 16-bit word, you could do:  $(a \gg 12) \& 0xF$ . To put a 6 into bits 5-3 and a 3 into bits 2-1, you could do:  $(6 \ll 3) | (3 \ll 1)$ . If you're not sure what an operation is doing, print some intermediate results to help you debug.

-----  
-----

## 12. Example Run of Simulator

```
memory[0]=8454151
memory[1]=9043971
memory[2]=655361
memory[3]=16842754
memory[4]=16842749
memory[5]=29360128
memory[6]=25165824
```

```
memory[7]=5
memory[8]=-1
memory[9]=2
```

```
@@@
```

```
state:
```

```
    pc 0
```

```
    memory:
```

```
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
```

```
    registers:
```

```
        reg[ 0 ] 0
        reg[ 1 ] 0
        reg[ 2 ] 0
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
```

```
end state
```

```
@@@
```

```
state:
```

```
    pc 1
```

```
    memory:
```

```
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
```

```
    registers:
```

```
        reg[ 0 ] 0
        reg[ 1 ] 5
        reg[ 2 ] 0
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
```

```
end state
```



```

@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 5
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 4
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 4

```

```

memory:
    mem[ 0 ] 8454151
    mem[ 1 ] 9043971
    mem[ 2 ] 655361
    mem[ 3 ] 16842754
    mem[ 4 ] 16842749
    mem[ 5 ] 29360128
    mem[ 6 ] 25165824
    mem[ 7 ] 5
    mem[ 8 ] -1
    mem[ 9 ] 2
registers:
    reg[ 0 ] 0
    reg[ 1 ] 4
    reg[ 2 ] -1
    reg[ 3 ] 0
    reg[ 4 ] 0
    reg[ 5 ] 0
    reg[ 6 ] 0
    reg[ 7 ] 0
end state

```

@@@

```

state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 4
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

@@@

```

state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361

```

```

        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 4
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824

```

```

        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

@@@

state:

pc 3

memory:

```

        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2

```

registers:

```

        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0

```

end state

@@@

state:

pc 4

memory:

```

        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2

```

registers:

```
        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state
```

```
@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
```

end state

```
@@@
state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 1
        reg[ 2 ] -1
        reg[ 3 ] 0
```

```
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state
```

@@@

state:

pc 4

memory:

```
mem[ 0 ] 8454151
mem[ 1 ] 9043971
mem[ 2 ] 655361
mem[ 3 ] 16842754
mem[ 4 ] 16842749
mem[ 5 ] 29360128
mem[ 6 ] 25165824
mem[ 7 ] 5
mem[ 8 ] -1
mem[ 9 ] 2
```

registers:

```
reg[ 0 ] 0
reg[ 1 ] 1
reg[ 2 ] -1
reg[ 3 ] 0
reg[ 4 ] 0
reg[ 5 ] 0
reg[ 6 ] 0
reg[ 7 ] 0
```

end state

@@@

state:

pc 2

memory:

```
mem[ 0 ] 8454151
mem[ 1 ] 9043971
mem[ 2 ] 655361
mem[ 3 ] 16842754
mem[ 4 ] 16842749
mem[ 5 ] 29360128
mem[ 6 ] 25165824
mem[ 7 ] 5
mem[ 8 ] -1
mem[ 9 ] 2
```

registers:

```
reg[ 0 ] 0
reg[ 1 ] 1
reg[ 2 ] -1
reg[ 3 ] 0
reg[ 4 ] 0
reg[ 5 ] 0
reg[ 6 ] 0
reg[ 7 ] 0
```

end state

@@@

state:

pc 3

memory:

mem[ 0 ]	8454151
mem[ 1 ]	9043971
mem[ 2 ]	655361
mem[ 3 ]	16842754
mem[ 4 ]	16842749
mem[ 5 ]	29360128
mem[ 6 ]	25165824
mem[ 7 ]	5
mem[ 8 ]	-1
mem[ 9 ]	2

registers:

reg[ 0 ]	0
reg[ 1 ]	0
reg[ 2 ]	-1
reg[ 3 ]	0
reg[ 4 ]	0
reg[ 5 ]	0
reg[ 6 ]	0
reg[ 7 ]	0

end state

@@@

state:

pc 6

memory:

mem[ 0 ]	8454151
mem[ 1 ]	9043971
mem[ 2 ]	655361
mem[ 3 ]	16842754
mem[ 4 ]	16842749
mem[ 5 ]	29360128
mem[ 6 ]	25165824
mem[ 7 ]	5
mem[ 8 ]	-1
mem[ 9 ]	2

registers:

reg[ 0 ]	0
reg[ 1 ]	0
reg[ 2 ]	-1
reg[ 3 ]	0
reg[ 4 ]	0
reg[ 5 ]	0
reg[ 6 ]	0
reg[ 7 ]	0

end state

machine halted

total of 17 instructions executed

final state of machine:

```
@@@
state:
  pc 7
  memory:
    mem[ 0 ] 8454151
    mem[ 1 ] 9043971
    mem[ 2 ] 655361
    mem[ 3 ] 16842754
    mem[ 4 ] 16842749
    mem[ 5 ] 29360128
    mem[ 6 ] 25165824
    mem[ 7 ] 5
    mem[ 8 ] -1
    mem[ 9 ] 2
  registers:
    reg[ 0 ] 0
    reg[ 1 ] 0
    reg[ 2 ] -1
    reg[ 3 ] 0
    reg[ 4 ] 0
    reg[ 5 ] 0
    reg[ 6 ] 0
    reg[ 7 ] 0
end state
```