

Project 1--CDA 3101 (Spring 2014)

Worth: 100 points (10% of course grade)

Assigned: Friday, Jan 24, 2014

Due: 1:25 pm, Monday, Feb 24, 2014

1. Purpose

This project is intended to help you understand the instructions of a very simple assembly language and how to assemble programs into machine language.

2. Problem

This project has three parts. In the first part, you will write a program to take an assembly-language program and produce the corresponding machine language. In the second part, you will write a behavioral simulator for the resulting machine code. In the third part, you will write a short assembly-language program to multiply two numbers.

3. LC3101 Instruction-Set Architecture

For this project, you will be developing a simulator and assembler for the LC3101 (Little Computer, used in CDA 3101). The LC3101 is very simple, but it is general enough to solve complex problems. For this project, you will only need to know the instruction set and instruction format of the LC3101.

The LC3101 is an 8-register, 32-bit computer. All addresses are word-addresses (unlike MIPS which is byte-addressed). The LC3101 has 65536 words of memory. By assembly-language convention, register 0 will always contain 0 (i.e. the machine will not enforce this, but no assembly-language program should ever change register 0 from its initial value of 0).

There are 3 instruction formats (bit 0 is the least-significant bit). Bits 31-25 are unused for all instructions, and should always be 0.

R-type instructions (add, nand):

- bits 24-22: opcode
- bits 21-19: reg A
- bits 18-16: reg B
- bits 15-3: unused (should all be 0)
- bits 2-0: destReg

I-type instructions (lw, sw, beq):

bits 24-22: opcode
 bits 21-19: reg A
 bits 18-16: reg B
 bits 15-0: offsetField (16-bit, range of -32768 to 32767)

O-type instructions (halt, noop):
 bits 24-22: opcode
 bits 21-0: unused (should all be 0)

Table 1: Description of Machine Instructions

Assembly language name for instruction	Opcode in binary (bits 24, 23, 22)	Action
add (R-type format)	000	add contents of regA with contents of regB, store results in destReg.
nand (R-type format)	001	nand contents of regA with contents of regB, store results in destReg.
lw (I-type format)	010	load regB from memory. Memory address is formed by adding offsetField with the contents of regA.
sw (I-type format)	011	store regB into memory. Memory address is formed by adding offsetField with the contents of regA.
beq (I-type format)	100	if the contents of regA and regB are the same, then branch to the address PC+1+offsetField, where PC is the address of the beq instruction.
cmov (R-type)	101	copy the value regA into destReg if the contents of regB != 0
halt (O-type format)	110	increment the PC (as with all instructions), then halt the machine (let the simulator notice that the machine halted).
noop (O-type format)	111	do nothing except increment PC.

4. LC3101 Assembly Language and Assembler (40%)

The first part of this project is to write a program to take an assembly-language program and translate it into machine language. You will


```
negl .fill -1
stAddr .fill start          will contain the address of start (2)
```

And here is the corresponding machine language:

```
(address 0): 8454151 (hex 0x810007)
(address 1): 9043971 (hex 0x8a0003)
(address 2): 655361 (hex 0xa0001)
(address 3): 16842754 (hex 0x1010002)
(address 4): 16842749 (hex 0x100fffd)
(address 5): 29360128 (hex 0x1c00000)
(address 6): 25165824 (hex 0x1800000)
(address 7): 5 (hex 0x5)
(address 8): -1 (hex 0xffffffff)
(address 9): 2 (hex 0x2)
```

Be sure you understand how the above assembly-language program got translated to machine language.

Since your programs will always start at address 0, your program should only output the contents, not the addresses.

```
8454151
9043971
655361
16842754
16842749
29360128
25165824
5
-1
2
```

4.1. Running Your Assembler

Write your program to take two command-line arguments. The first argument is the file name where the assembly-language program is stored, and the second argument is the file name where the output (the machine-code) is written. For example, with a program name of "assemble", an assembly-language program in "program.as", the following would generate a machine-code file "program.mc":

```
assemble program.as program.mc
```

Note that the format for running the command must use command-line arguments for the file names (rather than standard input and standard output). Your program should store only the list of decimal numbers in the machine-code

file, one instruction per line. Any deviation from this format (e.g. extra spaces or empty lines) will render your machine-code file ungradable. Any other output that you want the program to generate (e.g. debugging output) can be printed to standard output.

4.2. Error Checking

Your assembler should catch the following errors in the assembly-language program: use of undefined labels, duplicate labels, offsetFields that don't fit in 16 bits, and unrecognized opcodes. Your assembler should exit(1) if it detects an error and exit(0) if it finishes without detecting any errors. Your assembler should NOT catch simulation-time errors, i.e. errors that would occur at the time the assembly-language program executes (e.g. branching to address -1, infinite loops, etc.).

4.3. Test Cases

An integral (and graded) part of writing your assembler will be to write a suite of test cases to validate any LC3101 assembler. This is common practice in the real world--software companies maintain a suite of test cases for their programs and use this suite to check the program's correctness after a change. Writing a comprehensive suite of test cases will deepen your understanding of the project specification and your program, and it will help you a lot as you debug your program.

The test cases for the assembler part of this project will be short assembly-language programs that serve as input to an assembler. You will submit your suite of test cases together with your assembler, and we will grade your test suite according to how thoroughly it exercises an assembler. Each test case may be at most 50 lines long, and your test suite may contain up to 20 test cases. These limits are much larger than needed for full credit (the solution test suite is composed of 5 test cases, each < 10 lines long). See Section 7 for how your test suite will be graded.

Hints: the example assembly-language program above is a good case to include in your test suite, though you'll need to write more test cases to get full credit. Remember to create some test cases that test the ability of an assembler to check for the errors in Section 4.2.

4.4. Assembler Hints

As with the assembler, you will write a suite of test cases to validate the LC3101 simulator.

The test cases for the simulator part of this project will be short assembly-language programs that, after being assembled into machine code, serve as input to a simulator. You will submit your suite of test cases together with your simulator, and we will grade your test suite according to how thoroughly it exercises an LC3101 simulator. Each test case may execute at most 200 instructions on a correct simulator, and your test suite may contain up to 20 test cases. These limits are much larger than needed for full credit (the solution test suite is composed of a couple test cases, each executing less than 40 instructions). See Section 7 for how your test suite will be graded.

5.2. Simulator Hints

Be careful how you handle `offsetField` for `lw`, `sw`, and `beq`. Remember that it's a 2's complement 16-bit number, so you need to convert a negative `offsetField` to a negative 32-bit integer on the Sun workstations (by sign extending it). To do this, use the following function.

```
int  
cETBT0ET( t)N(nu)7(owint n cE4(-)] TJETBT 0 0 1 320124 318.41 Tm( )] TJETEMC
```

-

program halts. You may assume that the two input numbers are at most 15 bits and are positive; this ensures that the (positive) result fits in an LC3101 word. See the algorithm on page 252 of the textbook for how to multiply. Remember that shifting left by one bit is the same as adding the number

You may also choose to not use this fragment.

```
/* Assembler code fragment for LC3101 */

#include <stdlib.h>
#include <stdio.h>
#include <string.h>

#define MAXLINELENGTH 1000

int readAndParse(FILE *, char *, char *, char *, char *, char *);
int isNumber(char *);

int
main(int argc, char *argv[])
{
    char *inFileString, *outFileString;
    FILE *inFilePtr, *outFilePtr;
    char label[MAXLINELENGTH], opcode[MAXLINELENGTH],
    arg0[MAXLINELENGTH],
```

```

    /* after doing a readAndParse, you may want to do the following to
test the
        opcode */
    if (!strcmp(opcode, "add")) {
        /* do whatever you need to do for opcode "add" */
    }

    return(0);
}

/*
 * Read and parse a line of the assembly-language file. Fields are
returned
 * in label, opcode, arg0, arg1, arg2 (these strings must have memory
already
 * allocated to them).
 *
 * Return values:
 *     0 if reached end of file
 *     1 if all went well
 *
 * exit(1) if line is too long.
 */
int
readAndParse(FILE *inFilePtr, char *label, char *opcode, char *arg0,
             char *arg1, char *arg2)
{
    char line[MAXLINELENGTH];
    char *ptr = line;

    /* delete prior values */
    label[0] = opcode[0] = arg0[0] = arg1[0] = arg2[0] = '\0';

    /* read the line from the assembly-language file */
    if (fgets(line, MAXLINELENGTH, inFilePtr) == NULL) {
        /* reached end of file */
        return(0);
    }

    /* check for line too long (by looking for a \n) */
    if (strchr(line, '\n') == NULL) {
        /* line too long */
        printf("error: line too long\n");
        exit(1);
    }

    /* is there a label? */
    ptr = line;
    if (sscanf(ptr, "%[^\\t\\n ]", label)) {
        /* successfully read label; advance pointer over the label */
        ptr += strlen(label);
    }

    /*

```

```

        * Parse the rest of the line.  Would be nice to have real regular
        * expressions, but scanf will suffice.
        */
        sscanf(ptr, "%*[\t\n ]%[^\\t\\n ]%*[\t\n ]%[^\\t\\n ]%*[\t\n ]%[^\\t\\n
]%^*[\t\n ]%[^\\t\\n ]",
               opcode, arg0, arg1, arg2);
        return(1);
    }

int
isNumber(char *string)
{
    /* return 1 if string is a number */
    int i;
    return( (sscanf(string, "%d", &i)) == 1);
}

```

10. Code Fragment for Simulator

Here is some C code that may help you write the simulator. Again, you should take this merely as a hint. You may have to re-code this to make it do exactly what you want, but this should help you get started. Remember not to change stateStruct or printState.

```

/* instruction-level simulator for LC3101 */

#include <stdio.h>
#include <string.h>

#define NUMMEMORY 65536 /* maximum number of words in memory */
#define NUMREGS 8 /* number of machine registers */
#define MAXLINELENGTH 1000

typedef struct stateStruct {
    int pc;
    int mem[NUMMEMORY];
    int reg[NUMREGS];
    int numMemory;
} stateType;

void printState(stateType *);

int
main(int argc, char *argv[])
{
    char line[MAXLINELENGTH];
    stateType state;
    FILE *filePtr;

    if (argc != 2) {

```


bits. Neither a nor b are changed. E.g. $(25 \gg 2)$ is 6. Note that 25 is 11001 in binary, and 6 is 110 in binary.

3) The value of the expression $(a \ll b)$ is the number "a" shifted left by "b" bits. Neither a nor b are changed. E.g. $(25 \ll 2)$ is 100. Note that 25 is 11001 in binary, and 100 is 1100100 in binary.

4) To find the value of the expression $(a \& b)$, perform a logical AND on each bit of a and b (i.e. bit 31 of a AND'ed with bit 31 of b, bit 30 of a AND'ed with bit 30 of b, etc.). E.g. $(25 \& 11)$ is 9, since:

```
      11001 (binary)
      & 01011 (binary)
      -----
= 01001 (binary), which is 9 decimal.
```

5) To find the value of the expression $(a | b)$, perform a logical OR on each bit of a and b (i.e. bit 31 of a OR'ed with bit 31 of b, bit 30 of a OR'ed with bit 30 of b, etc.). E.g. $(25 | 11)$ is 27, since:

```
      11001 (binary)
      & 01011 (binary)
      -----
= 11011 (binary), which is 27 decimal.
```

6) $\sim a$ is the bit-wise complement of a (a is not changed).

Use these operations to create and manipulate machine-code. E.g. to look at bit 3 of the variable a, you might do: $(a \gg 3) \& 0x1$. To look at bits (bits 15-12) of a 16-bit word, you could do: $(a \gg 12) \& 0xF$. To put a 6 into bits 5-3 and a 3 into bits 2-1, you could do: $(6 \ll 3) | (3 \ll 1)$. If you're not sure what an operation is doing, print some intermediate results to help you debug.

12. Example Run of Simulator

```
memory[0]=8454151
memory[1]=9043971
memory[2]=655361
memory[3]=16842754
memory[4]=16842749
memory[5]=29360128
memory[6]=25165824
```

```
memory[7]=5
memory[8]=-1
memory[9]=2
```

```
@@@
```

```
state:
```

```
pc 0
```

```
memory:
```

```
mem[ 0 ] 8454151
mem[ 1 ] 9043971
mem[ 2 ] 655361
mem[ 3 ] 16842754
mem[ 4 ] 16842749
mem[ 5 ] 29360128
mem[ 6 ] 25165824
mem[ 7 ] 5
mem[ 8 ] -1
mem[ 9 ] 2
```

```
registers:
```

```
reg[ 0 ] 0
reg[ 1 ] 0
reg[ 2 ] 0
reg[ 3 ] 0
reg[ 4 ] 0
reg[ 5 ] 0
reg[ 6 ] 0
reg[ 7 ] 0
```

```
end state
```

```
@@@
```

```
state:
```

```
pc 1
```

```
memory:
```

```
mem[ 0 ] 8454151
mem[ 1 ] 9043971
mem[ 2 ] 655361
mem[ 3 ] 16842754
mem[ 4 ] 16842749
mem[ 5 ] 29360128
mem[ 6 ] 25165824
mem[ 7 ] 5
mem[ 8 ] -1
mem[ 9 ] 2
```

```
registers:
```

```
reg[ 0 ] 0
reg[ 1 ] 5
reg[ 2 ] 0
reg[ 3 ] 0
reg[ 4 ] 0
reg[ 5 ] 0
reg[ 6 ] 0
reg[ 7 ] 0
```

```
end state
```



```

@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 5
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 4
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 4

```

```

memory:
    mem[ 0 ] 8454151
    mem[ 1 ] 9043971
    mem[ 2 ] 655361
    mem[ 3 ] 16842754
    mem[ 4 ] 16842749
    mem[ 5 ] 29360128
    mem[ 6 ] 25165824
    mem[ 7 ] 5
    mem[ 8 ] -1
    mem[ 9 ] 2
registers:
    reg[ 0 ] 0
    reg[ 1 ] 4
    reg[ 2 ] -1
    reg[ 3 ] 0
    reg[ 4 ] 0
    reg[ 5 ] 0
    reg[ 6 ] 0
    reg[ 7 ] 0
end state

```

@@@

```

state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 4
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

@@@

```

state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361

```

```

        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 4
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

```

@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824

```

```

        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 3
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state

```

@@@

state:

pc 3

memory:

```

        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2

```

registers:

```

        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0

```

end state

@@@

state:

pc 4

memory:

```

        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2

```

registers:

```
        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state
```

```
@@@
state:
    pc 2
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 2
        reg[ 2 ] -1
        reg[ 3 ] 0
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state
```

```
@@@
state:
    pc 3
    memory:
        mem[ 0 ] 8454151
        mem[ 1 ] 9043971
        mem[ 2 ] 655361
        mem[ 3 ] 16842754
        mem[ 4 ] 16842749
        mem[ 5 ] 29360128
        mem[ 6 ] 25165824
        mem[ 7 ] 5
        mem[ 8 ] -1
        mem[ 9 ] 2
    registers:
        reg[ 0 ] 0
        reg[ 1 ] 1
        reg[ 2 ] -1
        reg[ 3 ] 0
```

```
        reg[ 4 ] 0
        reg[ 5 ] 0
        reg[ 6 ] 0
        reg[ 7 ] 0
end state
```

@@@

state:

pc 4

memory:

```
mem[ 0 ] 8454151
mem[ 1 ] 9043971
mem[ 2 ] 655361
mem[ 3 ] 16842754
mem[ 4 ] 16842749
mem[ 5 ] 29360128
mem[ 6 ] 25165824
mem[ 7 ] 5
mem[ 8 ] -1
mem[ 9 ] 2
```

registers:

```
reg[ 0 ] 0
reg[ 1 ] 1
reg[ 2 ] -1
reg[ 3 ] 0
reg[ 4 ] 0
reg[ 5 ] 0
reg[ 6 ] 0
reg[ 7 ] 0
```

end state

@@@

state:

pc 2

memory:

```
mem[ 0 ] 8454151
mem[ 1 ] 9043971
mem[ 2 ] 655361
mem[ 3 ] 16842754
mem[ 4 ] 16842749
mem[ 5 ] 29360128
mem[ 6 ] 25165824
mem[ 7 ] 5
mem[ 8 ] -1
mem[ 9 ] 2
```

registers:

```
reg[ 0 ] 0
reg[ 1 ] 1
reg[ 2 ] -1
reg[ 3 ] 0
reg[ 4 ] 0
reg[ 5 ] 0
reg[ 6 ] 0
reg[ 7 ] 0
```

end state

@@@

state:

pc 3

memory:

mem[0]	8454151
mem[1]	9043971
mem[2]	655361
mem[3]	16842754
mem[4]	16842749
mem[5]	29360128
mem[6]	25165824
mem[7]	5
mem[8]	-1
mem[9]	2

registers:

reg[0]	0
reg[1]	0
reg[2]	-1
reg[3]	0
reg[4]	0
reg[5]	0
reg[6]	0
reg[7]	0

end state

@@@

state:

pc 6

memory:

mem[0]	8454151
mem[1]	9043971
mem[2]	655361
mem[3]	16842754
mem[4]	16842749
mem[5]	29360128
mem[6]	25165824
mem[7]	5
mem[8]	-1
mem[9]	2

registers:

reg[0]	0
reg[1]	0
reg[2]	-1
reg[3]	0
reg[4]	0
reg[5]	0
reg[6]	0
reg[7]	0

end state

machine halted

total of 17 instructions executed

final state of machine:

```
@@@
state:
  pc 7
  memory:
    mem[ 0 ] 8454151
    mem[ 1 ] 9043971
    mem[ 2 ] 655361
    mem[ 3 ] 16842754
    mem[ 4 ] 16842749
    mem[ 5 ] 29360128
    mem[ 6 ] 25165824
    mem[ 7 ] 5
    mem[ 8 ] -1
    mem[ 9 ] 2
  registers:
    reg[ 0 ] 0
    reg[ 1 ] 0
    reg[ 2 ] -1
    reg[ 3 ] 0
    reg[ 4 ] 0
    reg[ 5 ] 0
    reg[ 6 ] 0
    reg[ 7 ] 0
end state
```