

SKF 交叉销售规则 (Cross-Sell Association Rules)

数据说明：Confidence = 历史数据置信度；Priority = 推荐优先级。主产品既可以是具体 SKU，也可以是产品类别或应用场景。

Primary Product	Recommended Add-On	Confidence	Reason	Priority
22320 E	CR 100x120x12 Seal	94%	Dusty environment protection (粉尘环境保护)	High
22320 E	LGEP 2 Grease (18kg)	91%	Heavy load lubrication (重载润滑)	High
22320 E	TKTL 10 Heater	78%	Proper installation (正确安装)	Medium
Any Spherical Roller	Matching Seal	88%	Contamination prevention (防污染)	High
Any Spherical Roller	LGEP 2 or LGHP 2	85%	Extended bearing life (延长轴承寿命)	High
6205-2RS	TMBA 10 Tool Set	72%	Installation efficiency (安装效率)	Medium
6308-2RS	LGMT 2 Grease	80%	General purpose lubrication (通用润滑)	Medium
Any Bearing >100mm bore	TKTL 10 or TKTL 20	86%	Thermal installation required (需热装)	High
SY 50 TF	CR 80x100x10	79%	Shaft sealing (轴密封)	Medium
SNL 511	22212 E Bearing	95%	Complete assembly (完整装配)	High
SNL 511	CR Seal Set	82%	Housing seals (轴承座密封)	Medium
Pump Application	6205-2RS + LGHP 2	87%	High-speed, continuous duty (高速连续运行)	High
Motor Application	6205-2RS/C3 + LGMT 2	90%	Standard motor setup (标准电机配置)	High
Fan Application (High Temp)	22320 E/C3 + LGHP 2	93%	Temperature resistance (耐高温)	High
Conveyor Application	22216 E + LGEP 2 + Seal	91%	Heavy load, contaminated (重载污染环境)	High
Gearbox Application	32210/32212 + LGEP 2	88%	High torque, shock load (高扭矩冲击载荷)	High
Agricultural Machinery	Sealed Bearing + Extra Seal Kit	85%	Extreme contamination (极端污染)	High
Food Industry	Stainless Bearing + Food-Grade Grease	92%	Hygiene compliance (卫生合规)	High
Any Bearing Purchase	CMSS 200-VL Sensor	68%	Predictive maintenance upsell (预测性维护)	Low
Order >¥50K	TKTL 10 Heater (discounted)	75%	Tool adoption program (工具推广计划)	Medium

交叉销售逻辑 (Cross-Sell Logic)

- Mandatory (必推)**：所有开放式轴承必须推荐密封件 + 润滑脂 (目标附加率 90%+)
- Strong (强推)**：内径 >100mm 的轴承推荐安装工具 (目标附加率 70%+)
- Opportunistic (机会型)**：战略客户推荐状态监测设备 (目标附加率 30%+)
- Volume-based (组合优惠)**：3 件以上互补商品可享捆绑折扣

业务目标 (AOV Impact)

- 无交叉销售平均订单额：¥8,500

- 有交叉销售平均订单额：¥10,200 (+20%)
- 目标平均订单额：¥11,000 (+29%)