Week 3 · Surge Speed Control

USV Guidance, Navigation and Control (Graduate) · Department of Autonomous Vehicle System Engineering, Chungnam National University | revised 2026-09-21

ℹ Recordings of this semester's own classes

Every session of this course is recorded as it is given and posted to the playlist below. The written material here is the reference; the recording is the lecture, at the pace it was actually delivered. Use it to review a derivation, or to catch up on a missed week before the laboratory.

	Where
[충남대] 2026 센서신호처리 — this course, recorded live, 2026	playlist

★ Reference material — read this first

The five courses below are **taught by the instructor of this course** and are the assumed background for it. They run from the fundamentals down to the graduate material, so start wherever the gap is. Every frame, symbol and derivation used here is developed in them at length; anyone whose prerequisites are thin should work through them first, then return.

#	Course	Level	Lang.	Video	Slides and code
1	**Control Engineering** (제어공학) — the foundation: transfer functions, feedback, stability, root locus, PID	undergraduate	KO	playlist	drive
2	**Control System Design** (제어시스템설계) — design rather than analysis: specifications, loop shaping, discrete implementation	undergraduate	KO	playlist	drive
3	**Advanced Control Engineering** (제어공학특론) — reference frames, the 6-DOF equation of motion, rotation matrices and Euler angles, linearisation and trim, vehicle control design	graduate	EN	playlist	drive
4	**Sensor Signal Processing and Fusion** (센서신호처리 및 융합) — sensor models, noise, estimation and multi-sensor fusion	graduate	EN	playlist	drive
5	**Capstone Design** (캡스톤디자인) — a vehicle project carried end to end	undergraduate	KO	playlist	drive

Not fluent in MATLAB or Simulink yet? Do these before Part 2. Every laboratory in this course is Simulink, and the Onramp courses are free and take a few hours each.

Tool	Where to start
MATLAB	MATLAB Onramp · Core MATLAB Skills
Simulink	Simulink Onramp · instructor's Simulink lectures part 1 · part 2

✎ Getting the course files, and keeping them current (Windows)

The notes, models and scripts are kept in one Git repository that is updated through the semester. Clone it once; before every class, pull. A pull downloads only what has changed since the last one.

When	Where to run it	Command
once	PowerShell — installs Git for Windows	`winget install --id Git.Git -e`
once	the folder that will hold the course, e.g. `Documents`	`git clone https://github.com/wkyouncnu/Sensor-Signal-Processing-and-Fusion.git`
before every class	inside the cloned folder `Sensor-Signal-Processing-and-Fusion`	`git pull`

- `git pull` prints `Already up to date.` when nothing has changed, and otherwise lists the files it updated.
- The repository is private. When Git asks, sign in with the GitHub account the instructor has given access.
- Experiment on copies, not on the cloned files: copy a week's `WXX_simulink` folder elsewhere first, and a pull can never collide with local edits. If it already has, `git stash`, then `git pull`, then `git stash pop` sets the edits aside, updates, and puts them back.
- The MSS toolbox is not part of the repository. The weeks that simulate the Otter need it at `Tools\MSS` inside the cloned folder.

- **Course**: USV Guidance, Navigation and Control (Graduate)
- **Department**: Autonomous Vehicle System Engineering, Chungnam National University
- **This week**: ① the Week 2 controller around the Otter's surge speed, with no model of the vessel ② P, I and D read off the Scope, one at a time ③ an unreachable speed and anti-windup ④ the tuning order of Week 2, followed step by step on the vessel

★ Prerequisites from the previous week

- From Week 2: the five time-domain metrics (§2-4), what P, I and D each do (§2-6 to §2-8), the filtered derivative, back-calculation anti-windup (§2-11) and the tuning order (§2-12). This week uses all of them unchanged.
- From Week 1: the Otter model and the propeller curve $T = kn|n|$: a shaft speed produces a thrust.
- Nothing else. This week deliberately tunes **without a model of the plant**: every gain is chosen from what the Scope shows.

Learning Outcomes

Upon completion of this week, the learner is able to:

1. Characterise a plant from the outside — its steady gain, its speed and its limits — by applying a step input and reading the Scope.
2. Predict, before running it, how P, I and D will each change the speed response, using what they did in Week 2 and one difference in the plant.
3. Explain why the derivative term makes a speed loop worse, and decide from a measurement to leave it out.
4. Reproduce integrator windup on the vessel with an unreachable speed command, and remove it with back-calculation.


5. Tune the speed loop by the Week 2 tuning order, stating the measurement that fixed each gain, and check the thrust against the limit.
6. Derive the allocation of a surge force and a yaw moment onto two fixed propellers, invert the resulting $\mathbf{2 \times 2}$ matrix, and convert each thrust into a shaft speed through the square-law propeller curve.

Prerequisites and Setup

Item	Requirement
MATLAB	R2024b, with Simulink
MSS	`Tools/MSS`, found by `W03_0_setup` through `mss_path`
Course folder	`lectures/W03_simulink`
Models	one per example — `W03_C_open_loop`, `W03_D_P`, `W03_E_PID`, `W03_F_windup`, `W03_G_tuning` — all generated by `W03_1_build_speed`, never edited by hand
Time	lecture 40 min, laboratory 1 h 20 min

Where this week sits

Week 2 tuned a PID against a mass on a spring. This week the plant becomes a vessel, and with it comes something the spring never had: the controller's output is a **force**, and the vessel's actuators accept **shaft speeds**. The diagram below is the whole arrangement, and this week builds its upper row and the block on its right.



In the diagram	What it is	Where it is built
upper row, `speed loop`	**a PI on the speed error, with anti-windup, producing the surge force X**	**this week, §3-3 and §3-4**
`allocation`	**turns (X, N) into the two shaft speeds, in two steps**	**this week, §3-6**
lower row, `heading autopilot`	a PD producing the yaw moment N; this week $N = 0$	Week 4
`Otter`	the equations of motion	Week 1
dashed box, left	where u_d and ψ_d come from once a path exists	Week 5
feedback bus, bottom	the state vector; the speed loop reads only u from it	—

- Sections 3-1 to 3-5 treat the speed loop as Week 2 treated the spring, and §3-6 follows its output all the way to the propellers.
- The second controller is drawn now, greyed out by its own emptiness, so that nothing has to be rearranged when Week 4 fills it.

Part 1 · Principle and experiment, section by section

Every section states what is observed, says what follows from it, and then runs **the experiment that measures it**, on its own model. Nothing has to be looked up elsewhere: the numbers quoted in the text are printed by the run a few lines below it.

Part of a section	What it holds
What is observed	the effect itself, with the numbers it produces
What follows from it	numbered lines, one step each — this week the reasoning is model-free, so each line rests on a measurement rather than on an equation of the vessel
Experiment N-x	the model, the commands, the output actually obtained, the figure, and a table that reads every feature of the figure back to **the numbered line that predicts it**

3-0. Setting up (10 min)

```
cd lectures/W03_simulink
W03_0_setup
W03_1_build_speed
```

Expected output:

```
  W03_0_setup
    thrust   X in [-133.42, 239.36] N
    gains    Kp = 200   Ki = 200   Kd = 0   Nf = 20   Kb = 1
    command  u_d = 0 -> 1.5 m/s at t = 5 s

  built  W03_C_open_loop.slx  (overlapping lines: 0)
  built  W03_D_P.slx          (overlapping lines: 0)
  built  W03_E_PID.slx        (overlapping lines: 0)
  built  W03_F_windup.slx     (overlapping lines: 0)
  built  W03_G_tuning.slx     (overlapping lines: 0)
```

- `W03_0_setup.m` is the only file edited by hand. It also finds MSS; if it stops with an error from `mss_path`, the MSS toolbox is not at `Tools\MSS`.
- The first line of `W03_0_setup` is `clear`. Run it again whenever a Scope does not match these notes.

3-1. The same controller, a new plant

This section answers: what changes when the controller of Week 2 is placed around a vessel, and what does not?

Nothing in the controller changes. Every model of this week is a Week 2 model with the mass-spring-damper removed and the vessel put in its place. The error, the three terms, the derivative filter, the limit and the back-calculation path are the same blocks in the same places.

The plant becomes a chain of blocks. The controller computes a surge force X; the vessel has two propellers, each turned at a shaft speed n. The chain between them is:

Block in the model	What it does	Where it comes from
`thrust limit`	holds X inside $[-133.42,\ 239.36]$ N	the largest thrust the two propellers produce forward and backward; derived in Appendix A1
`allocation`	a MATLAB Function block, commented line by line: ① each propeller takes half of X, $T = X/2$; ② the thrust is turned into the shaft speed that produces it, $n = \mathrm{sign}(T)\sqrt{\lvert T\rvert/k}$; ③ both shafts get that speed	going straight, both propellers do the same work; the propeller curve $T = kn\lvert n\rvert$ of Week 1, solved for n, with k different ahead and astern
`Otter`	the MSS model `otter.m`, twelve states	Week 1
`surge speed u`	picks the first state, the surge speed u	Week 1: $\mathbf{x} = [u\ v\ w\ p\ q\ r\ \ldots]$

The controller is tuned without a model of this chain. Week 1 could supply one, but a controller that works only when its plant is known exactly is fragile. This week follows the practitioner's route: apply a step, read the Scope, and choose each gain from what is measured — **model-free tuning**. The five metrics of Week 2 §2-4 are the language, and the tuning order of Week 2 §2-12 is the procedure.

Experiment 3-1 · The Week 2 controller, with a vessel in place of the spring (10 min)


What it measures. Nothing yet: this experiment matches the canvas to the paragraphs above, so that the three blocks between the controller and the vessel are recognised before any of them matters.


The canvas. `W03_E_PID` — the fullest model of the week, read here and measured in Experiment 3-3b. Its left half is the Week 2 canvas unchanged; its right half is the chain of the table above.

Opening and running.

```
W03_0_setup
open_system('W03_E_PID')          % Run — 위 칸 속도, 아래 칸 힘 / speed above, force below
```

In the law	On the canvas	Which changed since Week 2
$e = u_d - u$	the circle `e`	only the letter: a speed instead of a position
$K_p e + K_i \int e + K_d \dot{e}$	`Kp`, `Ki` → `I`, `D filter`, `p+d`, `u`	nothing
the actuator's limit	`thrust limit`	the numbers, $[-133.42,\ 239.36]$ N instead of $\pm\tau_{\max}$
the plant	`allocation` → `Otter` → `surge speed u`	**all of it** — this is the new part of the week





In the figure	Meaning
`step` → `e`	the speed command u_d and the error $e = u_d - u$
`Kp` , `D filter` , `Ki` → `I` , `p+d` , `u`	the PID of Week 2, block for block; `u` is the sum of the three terms, the force demanded
`thrust limit`	the force the propellers can give, $[-133.42,\ 239.36]$ N
`allocation`	the force split between the two propellers and turned into shaft speeds; double-click it to read the commented code
green `Otter`	the MSS vessel model
`surge speed u` and the long line along the bottom	the speed, fed back to `e`
`speed` , `force` → Scope	top: u_d and u; bottom: the force X, the integral I, the derivative D

> ✎ **In class**
>
> - **Purpose** — show that the controller is literally the Week 2 controller; only the green block and the blocks in front of it are new.
> - **Point to** — the `thrust limit` , present in every model: a real actuator is never unlimited, so the models never pretend it is.
> - **Ask** — "Why is the force halved and then square-rooted?" Two propellers share the force, and each propeller's thrust grows with the square of its shaft speed.
> - **Take away** — a controller is not tied to its plant; the same blocks move from a spring to a vessel.

3-2. What the vessel does, measured from outside

This section answers: what can be learned about the plant from one step input, with no equations?

Model `W03_C_open_loop` has no controller. At $t = 5$ s both propellers are asked for a constant total force X, and the Scope shows the speed. Measured by Experiment 3-2, below:

X [N]	final u [m/s]	u per newton [(m/s)/N]	time to 63 % of the final speed [s]
50	0.645	0.01289	1.12
100	1.289	0.01289	1.12
200	2.579	0.01289	1.12

What follows from it, one line at a time. These three lines are all the tuning of this week needs, and no equation of the vessel is among them.

1. **The speed is proportional to the force.** The middle column is the same number at every force, 0.0129 m/s per newton. A plant whose output is proportional to its input is **linear** over this range, so a gain chosen at one speed will not misbehave at another.
2. **Holding a speed takes a force, and the number is known.** Reading line 1 backwards, 1.5 m/s needs $1.5/0.0129 = 116$ N — the drag at that speed. The controller must keep supplying it for as long as the speed is held, and a term that produces force from error alone cannot: this is the job of the integral (§3-3).
3. **The response is first order.** It rises without overshoot and reaches 63 % of its final value in 1.12 s, the **time constant**. In the language of Week 2 §2-3 the plant stores energy in one place only — the moving mass — because nothing pulls the vessel back to a position the way a spring does. With nothing to oscillate with, **P alone cannot make it ring**, and the tuning order of Week 2 will therefore skip D.

4. **The speed has a ceiling.** The largest force the propellers give, 239.36 N, holds at most $239.36 \times 0.01289 = 3.09$ m/s. No controller can command more, whatever its gains; §3-4 asks for more on purpose.


Experiment 3-2 · The plant seen from outside (10 min)

What it measures. The four lines above, from one step input each: the gain in (m/s)/N, the force a wanted speed costs, the time constant, and the ceiling.

The model. `W03_C_open_loop` — **no controller at all**. A constant force goes in at $t = 5$ s, the speed comes out. This is how a plant is measured on the water: push it and watch.

Opening and running.


```
W03_0_setup
open_system('W03_C_open_loop')      % Run — 50 N: 0.645 m/s 로 눕는다 / it levels off at 0.645 m/s
X_open = 200;                       % Run — 네 배 힘에 네 배 속도 / four times the force, four times the
speed
W03_C_plant_from_outside            % 세 힘을 한 번에 재고 표를 찍는다 / all three forces, and the table
```



In the figure	Meaning
`force X`	a step force of `X_open` newtons at $t = 5$ s
`allocation` → `Otter` → `surge speed u`	the plant chain of §3-1
Scope	top: the speed u; bottom: the force X

Expected output:

```
W03 Experiment 3-2  the plant seen from outside (no controller)
  X [N]   final u [m/s]   u per newton [(m/s)/N]   time to 63 % [s]
  50              0.645                  0.01289              1.12
  100             1.289                  0.01289              1.12
  200             2.579                  0.01289              1.12
```



Reading the figure against the four lines.

Where to look	What is there	Which line it gives
the **final height** of each curve	0.645, 1.289, 2.579 m/s — doubling with the force	line 1: the plant is linear, with a gain of 0.0129 (m/s)/N
the same heights **read backwards**	1.5 m/s would sit between the second and the third	line 2: 116 N holds 1.5 m/s
the **shape** of every curve	a bend with no overshoot, identical at all three forces	line 3: first order, time constant 1.12 s
how far up the largest curve could go	239.36 N is only $20\,\%$ more than 200 N	line 4: the ceiling is 3.09 m/s

What the figure says

- Doubling the force doubles the speed; the shape never changes. A first-order plant with a gain of 0.0129 (m/s)/N and a time constant of 1.12 s.

What to try	What to watch
`X_open = -100;` Run	the vessel backs up at -1.289 m/s: the same 0.01289 (m/s)/N. The hull is symmetric here; what differs astern is the **shaft speed** each newton costs, because the propeller coefficient k of Week 1 is smaller backwards
`X_open = 300;` Run	the speed stops at 3.086 m/s although 300 N was asked for: the thrust limit holds the command at 239.36 N, which is line 4

> ✎ **In class**
>
> - **Purpose** — learn the plant the way a field engineer does: push it and watch.
> - **Point to** — no overshoot in any curve; the 63 % point at the same 1.12 s for all three forces.
> - **Ask** — "How much force holds 1.5 m/s?" About $1.5/0.0129 = 116$ N. That number returns in Experiment 3-3b as the value the integral settles at.
> - **Ask** — "What is the fastest speed any controller can reach?" $239.36 \times 0.0129 = 3.09$ m/s.
> - **Take away** — one step input gives the gain, the speed and the ceiling; that is enough to tune.

3-3. P, I and D on a speed loop

This section answers: what does each term do here, and why does one of them behave differently from Week 2?

What is observed. With the same three terms as Week 2, on this plant:

- P alone leaves an error at every gain — 0.912 m/s at $K_p = 50$, still 0.133 m/s at $K_p = 800$ — and **never rings**, at most $0.2\,\%$ of overshoot.
- Adding I closes the error at every positive gain, and the integral always stops at the same number: 116.3 N.
- Adding D makes the result **worse** at every gain: overshoot $0.90 \rightarrow 8.28\,\%$, settling $1.30 \rightarrow 4.86$ s.

The last of the three is the opposite of Week 2, where D was the remedy. One missing part explains all three.

What follows from it, one line at a time.

1. **The spring is missing.** On the mass-spring-damper the plant pulled back towards a position; a vessel free-running in surge has nothing that pulls it back to a speed. It stores energy in one place, its motion, which is line 3 of §3-2.
2. **So P cannot ring.** Ringing is energy passed back and forth between two stores. With one store there is nowhere to pass it, and a proportional gain can only make the approach faster. Hence the overshoot column of $0.0\,\%$, and hence the tuning order will have **nothing for D to damp**.
3. **But P still leaves an error**, for the reason of Week 2 §2-6 line 7: force comes from error alone, and holding a speed costs force (line 2 of §3-2). At $K_p = 200$ the vessel settles at 1.081 m/s, where $200 \times 0.419 = 84$ N is exactly the drag at that lower speed, $1.081/0.0129 = 84$ N.
4. **The integral finds the drag.** By Week 2 §2-8 line 5 an integrator stops where the error is zero, so it stops at the force that holds the commanded speed: 116 N by line 2 of §3-2. It is the **same argument** as the spring force of Week 2, with drag in place of the spring.
5. **The derivative acts on an acceleration here, not on a velocity.** The output is a speed, so $\dot{e}$ is an acceleration, and a term that resists acceleration acts like **added mass**: the vessel becomes sluggish, the integral goes on charging while it is slow, and the result overshoots. The term did not change; the axis did. Week 4 returns to a position-like output, the heading, and there K_d damps again.
6. **Nothing above used a model of the vessel.** Each line rests on Week 2 and on one measurement of §3-2.

Term	On the mass-spring-damper (Week 2)	On the vessel's speed (this week)	Measured
P	a spring: faster, rings more, leaves an error	faster, leaves an error, **does not ring** — a first-order plant has nothing to oscillate with	Experiment 3-3a: error $0.912 \to 0.133$ m/s as K_p rises $50 \to 800$, overshoot at most $0.2\,\%$
I	a patient hand that finds the spring force	a patient hand that finds the **drag force**	Experiment 3-3b: every integral stops at 116.3 N, the drag at 1.5 m/s
D	a shock absorber on the position	acts on the **acceleration**: it pushes back whenever the vessel speeds up, as if the vessel were heavier	Experiment 3-3b: overshoot $0.90 \to 8.28\,\%$ and settling $1.30 \to 4.86$ s as K_d rises $0 \to 100$

Experiment 3-3a · P only (10 min)

What it measures. Lines 2 and 3: an error at every gain, and no ringing at any gain — plus what happens once the gain asks for more thrust than there is.


The model. `W03_D_P` — the loop of §3-1 with $K_i = K_d = 0$.

Opening and running.

```
W03_0_setup
open_system('W03_D_P')            % Run — 1.081 m/s 에서 멈춘다 / it stops at 1.081 m/s
Kp = 800;                         % Run — 더 가까워지지만 여전히 못 미친다 / closer, still short
W03_D_proportional_only           % 다섯 게인을 한 번에 / all five gains at once
```

Expected output:

```
W03 Experiment 3-3a  P only  (u_d = 1.5 m/s at t = 5 s)
  Kp    final u   error left   overshoot %   rise [s]   settle [s]   time at thrust limit [s]
  50      0.588        0.912           0.0       1.46         2.60                       0.00
  100     0.845        0.655           0.0       1.06         1.86                       0.00
  200     1.081        0.419           0.0       0.70         1.18                       0.12
  400     1.256        0.244           0.1       0.54         0.84                       0.38
  800     1.367        0.133           0.2       0.52         0.72                       0.56
```



In the figure	Meaning
top	the speed for $K_p = 50$ to 800 and the dashed command
bottom	the force; the dotted red line is the 239.36 N limit

Reading the figure against the derivation.

Where to look	What is there	Which line predicts it
top panel, the **gap** to the dashed command	$0.912 \to 0.133$ m/s, never zero	line 3: force comes from error, and holding a speed costs force
top panel, **no curve overshoots**	0.0 to $0.2\,\%$ at every gain	line 2: one energy store, nothing to ring with
top panel, the final speed at $K_p = 200$	1.081 m/s	line 3 in numbers: $200 \times 0.419 = 84$ N, the drag at 1.081 m/s
bottom panel, the **flat top** on the red line	from $K_p = 200$ on, and for longer at every larger gain	§3-2 line 4: the thrust ceiling. The gain may ask for more; the propellers cannot give it
top panel, the rise times $0.70 \to 0.54 \to 0.52$ s	they stop improving	the same ceiling: beyond it the extra gain is spent on a demand that never leaves the limit

What the figure says

- A larger gain leaves less error and never none, and no gain makes the speed ring. From $K_p = 200$ on, the step drives the thrust to its limit, and more gain buys less and less speed.

What to try	What to watch
`Kp = 2000;` Run	$0.12\,\%$ of overshoot and a rise time of 0.56 s — **no better** than $K_p = 800$: line 2 holds at any gain, and past the ceiling extra gain buys nothing
`u_step = 0.5; Kp = 200;` Run	the gap falls to 0.140 m/s: line 3 in numbers again, $200 \times 0.140 = 28$ N, the drag at the 0.360 m/s reached

> ✎ **In class**
>
> - **Purpose** — see P on a plant without a spring: the error of Week 2 remains, the ringing does not.
> - **Point to** — the error column falling but never reaching zero; the rise-time column flattening (0.70, 0.54, 0.52 s) as the thrust reaches its limit.
> - **Ask** — "Why no overshoot even at $K_p = 800$?" The vessel stores energy only as motion; there is no spring to throw it back.
> - **Ask** — "Why does raising K_p from 400 to 800 hardly help the rise time?" The thrusters are already giving all they have; the gain can ask for more, the vessel cannot deliver it.
> - **Take away** — P alone always leaves a speed error, and gains beyond the actuator's reach are wasted.

Experiment 3-3b · Add I, then try D (15 min)

What it measures. Lines 4 and 5: the integral closing the error and stopping at the drag of §3-2 line 2, and the derivative making every number worse because the axis is a speed.

The model. `W03_E_PID` — the full loop. First K_i is raised with $K_d = 0$, then K_d is raised with the gains fixed.


Opening and running.

```
W03_0_setup
open_system('W03_E_PID')
Ki = 0;                          % Run — 1.081 m/s: 실험 3-3a 그대로 / as in Experiment 3-3a
Ki = 50;                         % Run — 오차는 사라지지만 느리다 / the gap closes, slowly
Ki = 200;                        % Run — 1.30 s 에 정착 / settled in 1.30 s
Kd = 50;                         % Run — 나빠진다 / it gets worse
W03_E_integral_and_derivative    % 두 스윕을 한 번에 / both sweeps at once
```


Expected output:

```
W03 Experiment 3-3b  1) the integral  (Kp = 200, Kd = 0)
  Ki    u at 40 s   overshoot %   settle [s]   I at 40 s [N]
  0        1.0809           0.0          Inf            0.0
  50       1.4995           0.0        13.14          116.2
  100      1.5000           0.0         5.54          116.3
  200      1.5000           0.9         1.30          116.3
  400      1.5000          12.8         2.42          116.3

2) the derivative  (Kp = 200, Ki = 200)
  Kd    overshoot %   rise [s]   settle [s]
  0            0.90       0.86         1.30
  20           2.60       0.94         2.92
  50           4.97       1.06         3.96
  100          8.28       1.24         4.86
```



In the figure	Meaning
top	the speed for $K_i = 0$ to 400 at $K_p = 200$
bottom	the integral term; every curve with $K_i > 0$ levels off at the same force



In the figure	Meaning
traces	the speed for $K_d = 0, 20, 50, 100$ at $K_p = K_i = 200$

Reading the figures against the derivation.

Where to look	What is there	Which line predicts it
first figure, top panel, every curve with $K_i > 0$	reaches 1.5000 m/s	line 4: an integrator stops only where the error is zero
first figure, bottom panel, where the curves **level off**	116.2, 116.3, 116.3, 116.3 N — the same for every K_i	line 4 with §3-2 line 2: the drag at 1.5 m/s, found without being told. K_i sets **how fast** it is found, not **where**
first figure, top panel at $K_i = 400$	$12.8\,\%$ of overshoot	Week 2 §2-8 line 6: too much integral is late force, and late force arrives in phase with the swing
second figure, every trace with $K_d > 0$	later rise, more overshoot, longer settling	line 5: on a speed axis the derivative resists **acceleration** — it acts like added mass

What the figure says

- The integral removes the error at any positive gain, and stops at 116.3 N — the drag at 1.5 m/s, found without being told. Too much of it ($K_i = 400$) overshoots by $12.8\,\%$.
- Every derivative gain makes the response worse: more overshoot and a longer settling time.

What to try	What to watch
`Ki = 200; Kd = 0; u_step = 2.5;` Run	the integral levels off at 193.9 N instead of 116.3, which is $2.5/0.01289$: line 4 finds whatever the **commanded** speed costs
`Ki = 10; T_final = 120;` Run	the gap still closes, but the vessel is inside $2\,\%$ only after 71.8 s — the integral of line 4 always arrives, and K_i is only its patience

> ✎ **In class**
>
> - **Purpose** — see the one term that is different on this axis, and let the measurement decide.
> - **Point to** — the integral levelling off at 116 N, the number predicted in §3-2 from the open loop; the derivative curves rising later and overshooting more as K_d grows.
> - **Ask** — "The derivative braked the mass in Week 2. Why does it hurt here?" The error of a speed loop changes with the acceleration; resisting acceleration is like adding mass, and a heavier vessel is slower and lets the integral overshoot.
> - **Ask** — "Which K_i meets 'inside 2 % within 3 s'?" $K_i = 200$: 1.30 s. At 100 it takes 5.54 s; at 400 it overshoots.
> - **Take away** — PI is the speed controller; D is left out because the Scope says so.

3-4. The thrusters have a limit: windup on the vessel

This section answers: what happens when the command asks for more than the thrusters can give?

What is observed. The command asks for 3.5 m/s at $t = 5$ s — faster than the 3.09 m/s ceiling of §3-2 line 4 — and drops to a reachable 1.5 m/s at $t = 30$ s:

- every run reaches the same top speed, about 3.08 m/s, whatever the anti-windup,
- but without anti-windup the vessel then **keeps that speed for about seven more seconds** before it slows at all,
- and the integral is found holding 2747 N at $t = 30$ s, against thrusters that can give 239 N.

What follows from it, one line at a time.

1. From 5 to 30 s the thrusters sit on their limit, so the error cannot close: the vessel is as fast as it can be, and the command is still above it.

2. The integrator does not know about the limit. Its input is the error, which stays at about 0.4 m/s, so it goes on accumulating for 25 s — hence the 2747 N. This is **windup**, the experiment of Week 2 §2-11 on the vessel.
3. Stored force can be removed only by error of the opposite sign, that is, by the vessel going **faster than commanded**. After the command drops the thrust therefore stays on its limit until the store is spent, and the vessel ignores the order to slow down.
4. Back-calculation drains the store while the actuator is saturated: the integrator receives $K_i\,e + K_b\,(X - u)$, where $u = P + I + D$ is the demand and X the thrust actually given, so $X - u$ is exactly what the limit cut off. It is zero whenever the actuator is not saturated, which is why the remedy is invisible in every other experiment.
5. K_b sets how hard the store is drained, and **more is not better**: draining faster than the loop needs pulls the integral below the drag that cruising costs, and the vessel undershoots.

Measured by Experiment 3-4, below, $K_p = 200$, $K_i = 200$:

K_b	u at 30 s [m/s]	integral at 30 s [N]	back within 2 % of 1.5 m/s after [s]	lowest u afterwards [m/s]
0 (no anti-windup)	3.086	**2747.2**	**11.20**	1.500
0.2	3.086	570.0	4.34	1.500
1	3.073	238.3	1.38	1.491
5	3.070	172.3	3.10	1.405

- Line 1 in the first column: every run reaches the same top speed, because the thrust and the vessel are the same. What differs is only what the integral **remembers**.
- Line 2 in the second column: 2747 N stored, eleven times what the thrusters can give.
- Line 4 in the fourth: $K_b = 1$ returns to the commanded speed in 1.38 s instead of 11.20 s.
- Line 5 in the last: at $K_b = 5$ the store is drained too hard and the vessel undershoots to 1.405 m/s.

> **The symbol u appears twice on this page**
>
> In `u = P + I + D` it is the controller's **demand**, the name of the sum block in the model, as in Week 2. Elsewhere this week u is the **surge speed**. The distinction matters only in line 4 of the derivation, where both occur.

Experiment 3-4 · An unreachable speed, and anti-windup (15 min)

What it measures. Lines 2 to 5: how much the integral stores during 25 s of an impossible order, how long the vessel then ignores a reachable one, and what each K_b does about it.


The model. `W03_F_windup` — the tuned loop, given a command above the ceiling of §3-2 line 4, then a reachable one. The back-calculation path is the same as Week 2's, with $K_b = 0$ switching it off.

Opening and running.

```
W03_0_setup
u_step = 3.5; t_step2 = 30; u_step2 = 1.5; T_final = 60;
open_system('W03_F_windup')
Kb = 0;                          % Run — 30 s 뒤에도 속도가 안 준다 / it does not slow after 30 s
Kb = 1;                          % Run — 1.38 s 만에 돌아온다 / back in 1.38 s
W03_F_unreachable_speed          % 네 개의 Kb 를 한 번에 / all four values of Kb
```

Expected output:

```
W03 Experiment 3-4  3.5 m/s from 5 s (unreachable), 1.5 m/s from 30 s
  Kb     u at 30 s   I at 30 s [N]   back within 2 % of 1.5 m/s after [s]   lowest u [m/s]
  0          3.086          2747.2                                  11.20            1.500
  0.2        3.086           570.0                                   4.34            1.500
  1          3.073           238.3                                   1.38            1.491
  5          3.070           172.3                                   3.10            1.405
```





WEEK 3, SECTION F - AN UNREACHABLE SPEED, AND ANTI-WINDUP

e = u_d - u, X = Kp e + Ki * integral(e) + Kd (Nf s / (s + Nf)) e
X is limited to [X_lo, X_hi] by the thrusters (about -133 N to 239 N)
anti-windup: i_dot = Ki e + Kb (X - u), Kb = 0 switches it off
u_step = 3.5 is faster than the Otter can go; at t_step2 the command drops to u_step2

Change a gain in the Command Window (e.g. Kp = 400) and press Run:
the Scope shows the speed (top) and the force (bottom) at once.

In the figure	Meaning
`step` , `step 2` , `two steps`	the command: `u_step` at 5 s, then `u_step2` at `t_step2`
`X - u` , `Kb` , the line back to `into I`	back-calculation: the force cut off by the limit, fed back to drain the integral





In the figure	Meaning
top	the speed for four values of K_b and the dashed command
bottom	the integral term

Reading the figure against the derivation.

Where to look	What is there	Which line predicts it
top panel, 5 to 30 s: **the four curves are one flat line**	about 3.08 m/s	line 1: the thrusters are on their limit, and the limit is the same in every run
bottom panel, 5 to 30 s: the $K_b = 0$ curve **climbing steadily**	to 2747 N	line 2: the error never closes, and the integrator adds it up for 25 s
top panel, after 30 s: the $K_b = 0$ curve **staying at the top**	for about seven seconds	line 3: the store can be spent only by running faster than commanded
bottom panel, the $K_b > 0$ curves **bending over** while the thrust is limited	570, 238, 172 N at 30 s	line 4: $X - u$ is non-zero only while the limit is cutting, and it drains the store
top panel, the $K_b = 5$ curve **dipping below** the command	to 1.405 m/s	line 5: drained past the 116 N that cruising costs

What the figure says

- Until 30 s the four runs are one. After it, the vessel without anti-windup keeps full thrust for about seven more seconds, spending a store of 2747 N; with $K_b = 1$ it is back in 1.38 s.

What to try	What to watch
`u_step = 2.5;` Run with `Kb = 0`, then `Kb = 1`	a reachable command: the integral holds 193.2 N in **both** runs, the drag at 2.5 m/s. K_b makes no difference at all — line 4 is silent unless the limit is cutting
`t_step2 = 10;` Run with `Kb = 0`	5 s of impossible order instead of 25: 1085.6 N stored instead of 2747.2, and the vessel is back inside the band after 6.00 s instead of 11.20. The damage grows with **how long** the actuator was saturated

> ✎ **In class**
>
> - **Purpose** — windup on the vessel, where it has a consequence: an order to slow down that is ignored.
> - **Point to** — the blue integral climbing steadily from 5 to 30 s while the speed is flat; then the flat blue speed after 30 s.
> - **Ask** — "Why does the integral keep growing when the speed has stopped changing?" The error, $3.5 - 3.09$, never closes, and the integral adds it up for 25 s.
> - **Ask** — "Why is $K_b = 5$ worse than $K_b = 1$?" It drains the integral below the 116 N needed at 1.5 m/s, and the vessel dips to 1.405 m/s.
> - **Take away** — every loop with a real actuator needs anti-windup, and a moderate K_b is enough.

3-5. The tuning order, applied to the vessel

This section answers: how are the three gains chosen for this plant, without a model?

The procedure is Week 2 §2-12, step by step. The requirement: inside 2 % of 1.5 m/s within 3 s of the step, overshoot below 5 %, thrust inside $[-133.42,\ 239.36]$ N.

Step	What is done	What was measured	Decision
0	write down the requirement; check the plant is well behaved	§3-2: stable, first order, no delay	proceed
1	P only; choose the scale of K_p from the units	the plant needs about 116 N at 1.5 m/s, so K_p of order 100 N per m/s; above $K_p = 239.36/1.5 = 160$ the step already asks for the full thrust	start at $K_p = 200$
2	read the P response	overshoot $0.0\,\%$, rise 0.70 s, error left 0.419 m/s; raising K_p to 400 or 800 barely speeds the rise (0.54, 0.52 s) because the thrust is already on its limit	keep $K_p = 200$
3	add D only if the P response rings	it does not ring; Experiment 3-3b shows D only adds overshoot	$K_d = 0$
4	add I until inside the band in time	$K_i = 50$: 13.34 s; 100: 5.70 s; 200: 1.40 s with $0.6\,\%$ overshoot	$K_i = 200$
5	look at the thrust	at the step the thrust sits on its limit for 0.20 s; with anti-windup ($K_b = 1$) this is harmless. A smoothed command, $1/(s+1)$, keeps it at 119.4 N at the cost of settling in 4.24 s	keep the step command, $K_b = 1$

The result, $K_p = 200$, $K_i = 200$, $K_d = 0$, $K_b = 1$: overshoot $0.56\,\%$, inside 2 % after 1.40 s. These are the defaults in `W03_0_setup.m`. No transfer function of the vessel was written down to find them.

> **Model-free does not mean theory-free**
>
> The tuning used two things learned from theory: what each term does (Week 2), and the time-domain metrics that say when to stop (Week 2 §2-4). What it did not use is a model of this particular plant. That is the situation of most controllers tuned in the field — and the reason the tuning order exists.

Experiment 3-5 · The tuning order, step by step (15 min)

What it measures. The five steps of the table above, in order, each decision printed with the measurement it was taken from — and step 5, the thrust, which the response alone never shows.


The model. `W03_G_tuning` — the tuned loop, with a switch (`ref_filter`) that replaces the step command by a smoothed one.

Opening and running.

```
W03_0_setup
open_system('W03_G_tuning')        % Run — 0.56 % 오버슛, 1.40 s / the tuned result
ref_filter = 1;                    % Run — 추력은 낮아지고 정착은 늦어진다 / less thrust, later
W03_G_tuning_by_hand               % 단계마다의 근거를 찍는다 / prints the reason for each step
```

Expected output:

```
  W03 Experiment 3-5  the tuning order on the Otter
    1-2  Kp = 200: overshoot 0.0 %, rise 0.70 s, error left 0.419 m/s
    3    no ringing, so nothing for D to damp: Kd = 0 (Exp 3-3b: D only adds overshoot)
    4    Ki = 50: 13.34 s (0.0 %)   100: 5.70 s (0.0 %)   200: 1.40 s (0.6 %)   -> Ki = 200
    5    force: 239.4 N, on the thrust limit for 0.20 s (anti-windup on); smoothed command: 119.4 N, s
ettle 4.24 s
         final: Kp = 200, Ki = 200, Kd = 0, Kb = 1: overshoot 0.56 %, inside 2 % after 1.40 s
```



In the figure	Meaning
top	the speed for the step command and for the command smoothed by $1/(s+1)$
bottom	the thrust; the dotted red line is the limit

What the figure says

- The tuned loop meets the requirement with margin. The step touches the thrust limit for a fifth of a second; the smoothed command never does, and pays with a slower arrival.

> ✎ **In class**
>
> - **Purpose** — close the week with the full procedure on the vessel, and compare with Week 2: the same steps, different decisions, because the plant is different.
> - **Point to** — step 3, skipped here and needed in Week 2; step 4, where K_i is raised until the requirement is met and no further.
> - **Ask** — "Settling here is 1.40 s, in Experiment 3-3b 1.30 s, with the same gains. Why?" This model has anti-windup on, and the step touches the limit; back-calculation changes the first second slightly. Both meet the requirement.
> - **Ask** — "When would the smoothed command be the right choice?" When the thrust must stay below its limit — to save power, to avoid cavitation, or because passengers feel the jolt.
> - **Take away** — requirements, P, D only if it rings, I until the band is met, then the actuator: the same order on every plant.


3-6. Where the force actually goes: two propellers, two steps

What is observed. Every experiment so far has ended at a number called X — a surge force in newtons, produced by the `speed loop` block and drawn on the lower Scope trace. But the Otter has no actuator that accepts newtons. It has **two propellers**, and what each of them accepts is a shaft speed in rad/s. Something between the controller and the vessel turns one into the other, and that something has been running in every model of this week under the name `allocation`.

The result. It does two things, in this order, and they are different in kind:

	Step	What it is
1	$(X, N) \to (F_L, F_R)$	**linear** and exactly invertible — a 2×2 matrix
2	$F \to n$, each shaft on its own	**nonlinear** — a square-law curve, read backwards

This week $N = 0$, because nothing has yet asked the vessel to turn. Step 1 therefore reduces to "half each". Week 4 supplies the missing N and the full matrix earns its keep; the structure is written out now so that it does not have to be introduced twice.



In the diagram	What it is	Which week
the upper row, `speed loop`	the PI of §3-3 and the anti-windup of §3-4, producing X	**this week**
the lower row, `heading autopilot`	the PD that produces N, with its own error and its own feedback	Week 4
`allocation`	the two steps of this section	this week, with $N = 0$
`Otter`	the equations of motion of Week 1	Week 1
the dashed box on the left	where u_d and ψ_d come from once a path exists	Week 5
the feedback bus along the bottom	the state vector; each loop reads only the one or two entries it needs	—

- The two controllers never speak to each other. They meet **only in the allocator**, and the whole of their interaction is the sharing of two propellers.

Derivation.


1. **The two forces two propellers can make.** Body x is forward and body y is to starboard, so the port propeller sits at $y = -b$ and the starboard one at $y = +b$, where b is half the distance between the pontoons. Both thrusts act along x. A force F applied at y makes a yaw moment $-yF$, so

$$X = F_L + F_R, \qquad N = b\,(F_L - F_R)$$

Symbol	Quantity	Value · source
F_L, F_R	thrust of the port and starboard propeller	N
b	half the pontoon spacing	**0.3950** m, `otter.m`
X	surge force, the output of `speed loop`	N
N	yaw moment, zero this week	N·m

Written with the sideways force included, so that all three appear together:

$$\begin{bmatrix} X \\ Y \\ N \end{bmatrix} = \begin{bmatrix} F_L + F_R \\ 0 \\ b\,(F_L - F_R) \end{bmatrix}$$



1. read the three forces off the picture

$$\begin{bmatrix} X \\ Y \\ N \end{bmatrix} = \begin{bmatrix} F_L + F_R \\ 0 \\ b\,(F_L - F_R) \end{bmatrix}$$

both push forward, so they **add**

neither pushes sideways: **this row is empty, always**

opposite arms, so they **subtract**

2. drop the empty row — it is square now

$$\begin{bmatrix} X \\ N \end{bmatrix} = \underbrace{\begin{bmatrix} 1 & 1 \\ b & -b \end{bmatrix}}_{\mathbf{T}} \begin{bmatrix} F_L \\ F_R \end{bmatrix}$$

$\mathbf{T}$ is **geometry**, nothing else: it never changes while the propellers stay bolted where they are

3. invert it — that is the allocator

$$\begin{bmatrix} F_L \\ F_R \end{bmatrix} = \mathbf{T}^{-1} \begin{bmatrix} X \\ N \end{bmatrix} = \begin{bmatrix} \frac{1}{2} & \frac{1}{2b} \\ \frac{1}{2} & -\frac{1}{2b} \end{bmatrix} \begin{bmatrix} X \\ N \end{bmatrix}$$

known — what the two controllers asked for

$\det \mathbf{T} = -2b \neq 0$, **so the inverse exists and the split is unique: each propeller takes half of X, and the moment is added to one and taken from the other**

In the figure	Meaning
the hull, seen from above	both propellers bolted facing forward, one at each side, b from the centreline
the red arrows F_L, F_R	what the two propellers produce
the teal arrows X, N	what the **vessel** receives — the sum, and the turning moment the difference makes
line 1	those three, read off the drawing
line 2	the empty row deleted, leaving the square $\mathbf{T}$
line 3	$\mathbf{T}$ inverted, which is what the `allocation` block evaluates

Reading the figure against the derivation.

Where to look	What is there	What it says
both red arrows point the same way	the propellers are **fixed** facing forward	the first row is $F_L + F_R$: surge simply adds
the middle entry of line 1	exactly 0	this hull **cannot be pushed sideways**, for any pair of thrusts. Weeks 4 and 5 turn the vessel in order to move it, and this row is why
the two arms marked b	equal, on opposite sides	the third row subtracts: equal thrusts make no moment, and a difference makes one
line 2, under the brace	$\mathbf{T}$ contains only 1 and b	the matrix is **geometry**. Nothing in it depends on speed, gains, or what the controller is doing
line 3, "known"	$\mathbf{T}^{-1}$ is fixed once the propellers are bolted down	the allocator never has to solve anything at run time; it multiplies by a constant matrix
line 3, "what the two controllers asked for"	(X, N) arrives from outside	the allocator has no opinion about whether the demand is sensible — §3-4's limits are where that is decided

> **Where this comes from, and where it is proved**
>
> That the forces read off the drawing in that particular arrangement is not a coincidence of this hull. One thruster at (x_i, y_i) pushing along a unit vector $\mathbf{e}_i$ contributes exactly one column, $\mathbf{b}_i = [\,e_x \;\; e_y \;\; x_i e_y - y_i e_x\,]^\top$ — the **column rule**, derived and checked against a drawing in Appendix A1 §A1-2 and applied to this hull in Week 1's `w01-otter-layout` figure. `_tools/otter_B.m` evaluates it and returns $[1\;1;\;0\;0;\;b\;-b]$, the same matrix to zero difference. Nothing in this course transcribes a $\mathbf{B}$ by hand.

2. **Deleting the empty row leaves a square system.** Stacking the two that remain,

$$\begin{bmatrix} X \\ N \end{bmatrix} = \underbrace{\begin{bmatrix} 1 & 1 \\ b & -b \end{bmatrix}}_{\mathbf{T}} \begin{bmatrix} F_L \\ F_R \end{bmatrix}, \qquad \det \mathbf{T} = -2b \neq 0$$

The determinant is not zero, so $\mathbf{T}$ can be inverted and **the split is unique**: there is exactly one pair of thrusts that produces a demanded (X, N), with nothing left to choose. Two actuators, two things to control. Inverting,

$$\begin{bmatrix} F_L \\ F_R \end{bmatrix} = \mathbf{T}^{-1} \begin{bmatrix} X \\ N \end{bmatrix} = \begin{bmatrix} \frac{1}{2} & \frac{1}{2b} \\ \frac{1}{2} & -\frac{1}{2b} \end{bmatrix} \begin{bmatrix} X \\ N \end{bmatrix} \qquad \Longrightarrow \qquad F_{L,R} = \frac{X}{2} \pm \frac{N}{2b}$$

In words: **each propeller carries half the surge force, and the moment is added to one and taken from the other.** With $N = 0$ this week, both get $X/2$ — which is exactly what the `allocation` block does, and why §3-1's table could describe it in one line.


3. **From thrust to shaft speed.** A propeller's thrust goes as the square of its shaft speed, and the coefficient is different going astern because the blade is running the wrong way round:

$$F = \begin{cases} k_{pos}\, n|n|, & n \geq 0 \\ k_{neg}\, n|n|, & n < 0 \end{cases} \qquad \Longrightarrow \qquad n = \begin{cases} +\sqrt{F/k_{pos}}, & F \geq 0 \\ -\sqrt{|F|/k_{neg}}, & F < 0 \end{cases}$$

The $n|n|$ rather than n^2 is what makes the curve pass through the origin with the correct sign on both sides; writing n^2 would make a reversing propeller push the vessel forwards.

Symbol	Quantity	Value · source
k_{pos}	thrust coefficient, ahead	**0.011080** N per (rad/s)², `otter.m`
k_{neg}	thrust coefficient, astern	**0.006445** N per (rad/s)², `otter.m`
n_{max}, n_{min}	shaft-speed limits	**+103.9**, **−101.7** rad/s
F_{max}, F_{min}	the thrusts those limits reach	**+119.7**, **−66.7** N

STEP 1 two thrusts into two forces, and back



where the two thrusts act

both push forward, and the two arms are opposite

$$\begin{bmatrix} X \\ N \end{bmatrix} = \underbrace{\begin{bmatrix} 1 & 1 \\ b & -b \end{bmatrix}}_{\mathbf{T}} \begin{bmatrix} F_L \\ F_R \end{bmatrix}$$


$\det \mathbf{T} = -2b \neq 0$: the matrix is invertible, so the split is *unique*

$$\begin{bmatrix} F_L \\ F_R \end{bmatrix} = \mathbf{T}^{-1} \begin{bmatrix} X \\ N \end{bmatrix} = \begin{bmatrix} \frac{1}{2} & \frac{1}{2b} \\ \frac{1}{2} & -\frac{1}{2b} \end{bmatrix} \begin{bmatrix} X \\ N \end{bmatrix}$$

each propeller carries *half* the surge force, and the moment is added to one and taken from the other

linear, and exactly invertible

STEP 2 each force onto its own shaft — nonlinear, one propeller at a time



ahead $F = k_{pos}\, n|n|$
$k_{pos} = 0.01108$

flat at the origin. $dF/dn = 0$ there, so a slow shaft makes almost no thrust, and a small F needs a surprisingly large step in n

astern $F = k_{neg}\, n|n|$, $k_{neg} = 0.00645$
the same blade turned backwards: **41.8 % weaker**, which is why $|F_{min}| < F_{max}$

$$n = \begin{cases} +\sqrt{F/k_{pos}}, & F \geq 0 \\ -\sqrt{|F|/k_{neg}}, & F < 0 \end{cases}$$

read the curve *backwards*. Each propeller is read on its own, because each has its own F and neither can help the other

nonlinear, but still one-to-one: every reachable F has exactly one n

In the figure	Meaning
top left	where the two thrusts act, and the lever b that turns their difference into a moment
top right	the matrix of line 2 and its inverse
bottom, the orange branch	ahead: $F = k_{pos} n\|n\|$
bottom, the blue branch	astern: the same blade backwards, and visibly shallower
bottom, the dashed purple lines	the inversion read off the curve: $F_L = 38.16$ N is reached at $n_L = 58.69$ rad/s

Reading the figure against the derivation.

Where to look	What is there	Which line it settles
the two upward arrows, top left	both thrusts act along $+x$	line 1: that is why the first row of $\mathbf{T}$ is $[1 \;\; 1]$
the two arms marked b	equal and on opposite sides of the centreline	line 1: that is why the second row is $[b \;\; -b]$, with opposite signs
$\mathbf{T}^{-1}$, top right	$\frac{1}{2}$ in both rows of the first column	line 2: half the surge force each, whatever the moment is doing
the curve at the origin	**flat** — $\mathrm{d}F/\mathrm{d}n = 0$ there	line 3: near zero a large change in n buys almost no thrust, which is why a propeller is a poor actuator at low speed
the two branches, compared	astern is $41.8\,\%$ weaker for the same shaft speed	line 3: $k_{neg} < k_{pos}$, so $\lvert F_{\min}\rvert = 66.7 < 119.7 = F_{\max}$
the marked points	$(103.9,\ 119.7)$ and $(-101.7,\ -66.7)$	the limits: everything outside this range is a force the vessel cannot produce, and §3-4's windup is the consequence
the purple reading	38.16 N at 58.69 rad/s	$\sqrt{38.16/0.011080} = 58.69$, the inverse evaluated

The same two steps, inside the model

The figure is a drawing of one block. Below is the code that block actually holds, copied out of `W03_F_windup.slx` — double-clicking `allocation` in any model of this week shows exactly this text. The comments are the block's own.

```
function n = allocation(X, k_pos, k_neg)
%#codegen
%ALLOCATION  전진력 X [N] 를 두 프로펠러의 축 회전수 n [rad/s] 로 바꾼다.
%            Turn the surge force X [N] into the shaft speeds n [rad/s] of the two propellers.
%
%   k_pos, k_neg 는 작업공간 변수 (W03_0_setup) 에서 온다 — 블록의 포트가 아니다.
%   k_pos and k_neg come from the workspace (W03_0_setup), not from ports.

% 1) 똑바로 갈 때 두 프로펠러는 같은 일을 한다: 각자 X 의 절반.
%    Going straight, both propellers do the same work: half of X each.
T = X/2;

% 2) 프로펠러 곡선 T = k n|n| (1주차) 을 n 에 대해 푼다.
%    앞으로 밀 때와 뒤로 당길 때 계수가 다르다 (k_pos > k_neg).
%    Solve the propeller curve T = k n|n| (Week 1) for n; the coefficient
%    differs ahead and astern (k_pos > k_neg).
if T >= 0
    n1 =  sqrt( T / k_pos);      % 앞으로 / ahead
else
    n1 = -sqrt(-T / k_neg);      % 뒤로 / astern
end

% 3) 두 축에 같은 회전수. Otter 는 [좌현; 우현] 순서로 받는다.
%    The same speed on both shafts; the Otter takes [port; starboard].
n = [n1; n1];
end
```

In the code	In the figure	Note
`T = X/2;`	the $\frac{1}{2}$ in both rows of $\mathbf{T}^{-1}$, STEP 1	with $N = 0$ the whole matrix collapses to this one line; Week 4 restores the second column
the `if T >= 0` branch	the orange branch of STEP 2	$n = +\sqrt{F/k_{pos}}$
the `else` branch	the blue branch of STEP 2	$n = -\sqrt{\lvert F\rvert/k_{neg}}$, and the minus sign is what keeps a reversing propeller pulling backwards
`n = [n1; n1];`	the two equal arrows of STEP 1	the Otter's input is `[port; starboard]`, in that order
`k_pos`, `k_neg` as arguments	$k_{pos} = 0.01108$, $k_{neg} = 0.00645$ in the figure	they are workspace variables, not signals: changing them in `W03_0_setup` changes the curve without touching the diagram

The block has no clamp on n. It does not need one here, because `otter.m` clamps internally (lines 167–170) and this week never logs n; Week 5 §5-7 adds the clamp for the week that does.

What the figure says

- The allocator is not one operation but two, and only the first is linear; the limits of §3-4 live in the second.

> **ℹ Why the inverse exists at all, and when it stops existing**
>
> Two propellers, two demanded quantities, a square and nonsingular $\mathbf{T}$: the inverse is exact and unique. That is the easy case, and it holds for every vessel in Weeks 3 to 5. Week 6 removes it — with more thrusters than demanded forces the matrix is no longer square, there is no inverse, and the choice of which combination to use becomes the subject of its own week.

To check every number in this section

```
cd _tools
verify_w03_speed        % check 2 is the thrust range, check 5 the inversion
```

Actual output of the two lines that matter here:

```
    2 thrust limits [-133.42, 239.36] N          OK    [-133.42, 239.36]
    5 allocation inverts T = k n|n|              OK    1.4e-14 N
```

- Check 5 feeds a thrust through $n(F)$ and back through $F(n)$ and compares: the two agree to 1.4×10^{-14} N, so the inversion is exact to machine precision and not an approximation.
- The limits in check 2 are the **pair** $2F_{\max}$ and $2F_{\min}$, both propellers together, which is the surge force the vessel can produce and therefore the saturation the integrator of §3-4 runs into.

What to try	What to watch
`k_neg = k_pos;` then re-run `W03_F_unreachable_speed`	the astern branch becomes the mirror of the ahead branch, and the vessel can brake as hard as it accelerates. That is not the Otter, but it shows what the asymmetry costs
In `W03_F_windup`, double-click `allocation`	the two steps of this section, in nine lines of commented code — the matrix is not written out because $N = 0$ makes it $X/2$

> **✎ In class**
>
> - **Purpose** — close the gap between "the controller asks for 100 N" and "the propeller turns at 67 rad/s".
> - **Point to** — the flat spot at the origin of the curve. Ask what that means for a vessel holding station.
> - **Ask** — "The controller asks for -80 N. What happens?" The astern branch cannot reach it: $F_{\min} = -66.7$ N per propeller, so the demand is clipped and §3-4's anti-windup earns its keep.
> - **Ask** — "Why invert the matrix rather than just divide by two?" Because Week 4 adds N, and then the two propellers stop being equal. Writing the inverse now means nothing changes next week except that N stops being zero.
> - **Take away** — a controller produces forces; an allocator produces actuator commands; the two are not the same thing and the difference is where the limits live.

Part 2 · Laboratory run order

The experiments of Part 1 are worked through in order; this table is the index of what was run, for repeating the week at home.

Every example has **its own model**, and every model looks the same as in Week 2: the controller on the left, the vessel in the middle, **one Scope** on the right with the speed on top and the force below. Open a model, press **Run**, and the Scope shows the response. Change a gain in the Command Window and press Run again.

Experiment	Model	Script	What it shows
3-0	all of them	`W03_0_setup`, `W03_1_build_speed`	the parameters, and every model written from code
3-1	`W03_E_PID`	—	the Week 2 canvas with the vessel in place of the spring
3-2	`W03_C_open_loop`	`W03_C_plant_from_outside`	a step force, no controller
3-3a	`W03_D_P`	`W03_D_proportional_only`	P only
3-3b	`W03_E_PID`	`W03_E_integral_and_derivative`	P + I, then D
3-4	`W03_F_windup`	`W03_F_unreachable_speed`	an unreachable speed, then a reachable one
3-5	`W03_G_tuning`	`W03_G_tuning_by_hand`	the tuned loop, with a switch for a smoothed command
3-6	any of them	`verify_w03_speed`	the allocator: the matrix, its inverse, and the propeller curve

- The scripts only repeat what Run already shows, for several gains at once, and print the numbers quoted in Part 1.
- Each experiment ends with an **In class** note: purpose, what to point at, a question with its answer, and the sentence to take away.

Summary

Week Summary

Step	What was done	How it was verified
1	placed the Week 2 controller around the Otter's surge speed	the models differ from Week 2 only in the plant chain; `check_overlaps` 0
2	measured the plant from outside	Experiment 3-2: 0.01289 (m/s)/N at every force, time to 63 % 1.12 s, ceiling 3.09 m/s
3	P alone	Experiment 3-3a: error never zero; no ringing; more gain wasted at the thrust limit
4	I finds the drag; D hurts	Experiment 3-3b: integral 116.3 N at every K_i; overshoot $0.90 \rightarrow 8.28\,\%$ with K_d
5	windup on the vessel	Experiment 3-4: 2747 N stored, 11.20 s to return without anti-windup; 1.38 s with $K_b = 1$
6	the tuning order	Experiment 3-5: $K_p = 200$, $K_i = 200$, $K_d = 0$, $K_b = 1$; overshoot $0.56\,\%$, settled in 1.40 s

Progress Check

> ★ **Minimum condition for following Week 4**

Theory

- [ ] Able to state the three facts a step input gave about the vessel, and the force needed to hold 1.5 m/s.
- [ ] Able to explain why P does not ring on this plant and why D makes it worse.
- [ ] Able to explain what the integral remembers during an unreachable command, and what K_b does to it.

Laboratory

- [ ] `W03_1_build_speed` ran and every model reported `overlapping lines: 0`.
- [ ] A gain was changed in the Command Window and the model's Scope showed the new response.
- [ ] `W03_check(1)`, `(2)` and `(3)` pass on a model built from `W03_P1_start`.

Recorded observations

- [ ] The force the integral settled at in Experiment 3-3b, and where the same number appeared in Experiment 3-2.
- [ ] The time to return to 1.5 m/s with and without anti-windup in Experiment 3-4.

In-class laboratory — close the speed loop by hand

The second hour of the Week 3 session is spent building the loop in Simulink from a model that holds only the vessel. Three problems, one hour, with a checker that compares the result against the numbers measured above.

```
cd lectures/W03_simulink/problems
W03_P1_start                % creates W03_P1.slx — hull and thrust map only
W03_check(1)                % run this whenever, as often as needed
```

	Problem	Time	The number it must reproduce
1	The open loop — a constant force in, a log out	20 min	0.6447, 1.2894, 2.5788 m/s for 50, 100, 200 N
2	Proportional control — and the error that never closes	20 min	0.8448 m/s at $K_p = 100$, against $u_d = 1.5$
3	Add the integral — the tuned gains of §3-5	20 min	1.5 m/s with no error left, overshoot below 5 %

- The problem sheet is `W03_simulink/problems/README.md`, and reference answers are in `W03_simulink/solutions/`.

Assignment 3

- **Due**: before the Week 4 session
- **Submit**: the modified `W03_0_setup.m`, the numbers requested below, and two figures

① Requirements

Double the payload, `mp = 50` kg, in `W03_0_setup.m` and `W03_vars.m`, and tune the speed loop again by the tuning order of §3-5 with the requirement: inside 2 % of 2.0 m/s within 3 s, overshoot below 5 %, anti-windup on.

② Verification — mandatory

> **★ A claim is not a result. Numbers are required, with the tolerance band stated**

1. Repeat Experiment 3-2 with the new payload and report the speed per newton and the time to 63 %. State which of the two changed, and by how much.
2. For each step of the tuning order, the measurement that decided it, as in the table of §3-5.
3. The final gains, overshoot and 2 % settling time, measured with `step_metrics`.
4. Section F with the final gains at $K_b = 0$ and $K_b = 1$: the time to return.

③ Analysis (5–10 lines)

Compare the final gains with those of §3-5. Explain, from the measurement of ②.1 alone, why the gains moved in the direction they did.

Grading

Criterion	Weight
The model runs and produces the requested output	25%
Verification performed and numbers reported	40%
Correctness of the analysis	25%
Readability of the code	10%

Troubleshooting

Symptom	Cause	Fix
`W03_0_setup` stops in `mss_path`	the MSS toolbox is not at `Tools\MSS`	place MSS there; see the first page
the speed never reaches the command, however large the gains	the command exceeds the 3.09 m/s ceiling	expected; that is the experiment of §3-4
the speed returns seconds late after a lower command	$K_b = 0$	set `Kb = 1`
a Scope does not match these notes	a changed variable is still in the workspace	run `W03_0_setup` again
a `.slx` was edited by hand and now differs	the models are generated	run `W03_1_build_speed` again
`allocation` reports that `k_pos` is undefined	`W03_0_setup` was not run, so the block's parameters have no values	run `W03_0_setup`; the block reads `k_pos` and `k_neg` from the workspace

---

References

Primary

- Fossen, T. I. *Handbook of Marine Craft Hydrodynamics and Motion Control*, 2nd ed., Wiley, 2021, §12.2 (PID control of marine craft) and §12.2.6 (integrator anti-windup).
- Åström, K. J. and Hägglund, T. *Advanced PID Control*, ISA, 2006, Ch. 3 (derivative filtering and anti-windup).
- MSS toolbox, `Tools/MSS/VESSELS/otter.m` — the vessel model.

In this course

- Week 2 §2-4 (the metrics), §2-6 to §2-8 (P, D and I), §2-11 (anti-windup) and §2-12 (the tuning order).
- Appendix A1 — where the thrust limit $[-133.42,\ 239.36]$ N comes from.
- The previous, model-based version of this week — plant identification, pole placement, the three anti-windup schemes compared with the library block — is kept in `W03_simulink/_previous_version/` for reference.

Next Week

- **Week 4 — Heading Control**
- The same controller, around the heading. The heading is an angle, the integral of the yaw rate, so the plant has something like a position again, and the derivative term, harmful on the speed loop of §3-3, damps once more.
- The angle wraps at $\pm 180°$, and the smallest-signed-angle function `ssa` keeps the controller from steering the long way round.