RNP Y RWY 24

AD ELEV: 177' APP SÃO LUÍS GNDC D-ATIS TWR SÃO LUÍS NIL 119.10 118.90 NIL TEMP LNAV/VNAV FINAL CRS FAF LNAV/VNAV LNAV 240° 1790 MDA / (OCH): 620' / (480') MIN 10°C / MAX 45°C DA / (OCH): 496' / (353') APCH Perdida: Subir para 4000'. Manter rumo 240 até SL043 para espera. Missed APCH: Climb to 4000' . Maintain course 240 until SL043 for holding. (IAF) NOTES -(IAF) **SL023** SNCW SL021 ∢ RNP APCH. 4000 4000 (IF) 25 NM **SL019** 10NM 2500 296' 4000' 150 25 λ[^]266' 306' **♦**SL023 SL021 Ν ♦ IF 4000' て 240 394 (FAF) VAR (IAF) SL017 364' SL022 210 ALT, ELEV, HGT: FT 4000' DIST: NM BRG: MAG VA/CHG: 01'E 430 SL022 (APT) RWY24 4000 NM TO SLO22 (MAHF) SL043 SCALE 5 NM 4000 10 Km 1 0 NOT TO SCALE LNAV/VNAV ĪF FAF **TA** 4000' SL019 SL017 2500 1790 MAPT LNAV I RWY24 | €240 5.2% (3.0° LNAV 1700' RDH 50' MDA THR ELEV 143 TO THR 24 (NM) 0.010 5.0 10.0 RWY24 SL017 190 1.3 2,0 3.0 4.0 Ground Speed (KT) 090 110 130 1148 800 NA 620 830 1467 500 600 900 ALT 1790 700 FAF-MAP1 480 687 1324 1650 NΑ STRAIGHT-IN CAT В С Ε Α DA / (OCH) 496' / (353') LNAV/VNAV ALS/NO ALS/ RVR ALS (m) NIL / 1600 / NIL NA CHANGES: IDENT 620' / (480') MDA / (OCH) LNAV ALS/NO ALS/ RVR ALS (m) NIL / 1600 / NIL NIL / 2200 / NIL MDA / (OCH) CIRCLING NA VIS (m) AIRAC AMDT 2111A1 04 NOV 21