

Ruby 2.5 Information and Documentation

OCTOBER, 2018

wlharvey4

Published by:

wlharvey4

Address Line 1

Address Line 2

etc.

Email: wlharvey4@emac.com

URL: <http://www.example.com/>

Copyright © 2018

wlharvey4

All Rights Reserved.

The Ruby2.5 Information and Documentation program is copyright © 2018 by wlharvey4.
It is published under the conditions of the GNU General Public License, version 3.

This is Edition 0.1c of *Ruby 2.5 Information and Documentation*.

Table of Contents

Preface	1
Intended Audience	1
What Is Covered	1
Typographical Conventions	1
Acknowledgements	1
 1 Introduction	 2
 2 Documentation	 3
2.1 Installing Ruby	3
2.1.1 Package Management Systems	3
2.1.1.1 Homebrew (OS X)	3
2.1.2 Installers	3
2.1.2.1 <code>ruby-build</code>	4
2.1.2.2 <code>ruby-install</code>	4
2.1.3 Managers	4
2.1.3.1 <code>chruby</code>	4
2.1.3.2 <code>rbenv</code>	4
2.1.3.3 RVM (“Ruby Version Manager”)	4
2.1.3.4 <code>uru</code>	4
2.1.4 Building From Source	5
2.1.4.1 Releases Page	5
2.1.4.2 Branches Page	5
2.1.4.3 Ruby Issue Tracking System	6
2.2 Developing Ruby	7
2.3 Getting Started	8
2.3.1 Try Ruby!	8
2.3.2 Official FAQ	8
2.3.2.1 FAQ Iterators	8
2.3.2.2 FAQ Syntax	10
2.3.2.3 FAQ Methods	14
2.3.2.4 FAQ Classes and Modules	15
2.3.2.5 FAQ Built-In Libraries	15
2.3.2.6 FAQ Extension Library	16
2.3.2.7 FAQ Other Features	16
2.3.3 Ruby Koans	17
2.3.4 Whys (Poignant) Guide to Ruby	17
2.3.5 Ruby in Twenty Minutes	17
2.3.6 Ruby from Other Languages	17
2.3.7 Learning Ruby	17
2.3.8 Ruby Essentials	17
2.3.9 Learn to Program	17

2.4	Manuals.....	17
2.5	Reference Documentation.....	17
2.6	Editors and IDEs.....	18
2.7	Further Reading.....	18
Appendix A The Makefile		19
A.1	Makefile Variable Definitions.....	19
A.2	Default Rule.....	19
A.3	TWJR Rules	19
A.4	Clean Rules.....	20
Appendix B Code Chunk Summaries.....		21
B.1	Source File Definitions	21
B.2	Code Chunk Definitions.....	21
B.3	Code Chunk References	21
Bibliography.....		22
Index.....		23

Preface

Text here.

Intended Audience

Text here.

What Is Covered

Text and chapter by chapter description here.

Typographical Conventions

This book is written in an enhanced version of **Texinfo**, the GNU documentation formatting language. A single Texinfo source file is used to produce both the printed and online versions of a program’s documentation. Because of this, the typographical conventions are slightly different than in other books you may have read.

Examples you would type at the command-line are preceded by the common shell primary and secondary prompts, ‘\$’ and ‘>’. Input that you type is shown *like this*. Output from the command is preceded by the glyph “+”. This typically represents the command’s standard output. Error messages, and other output on the command’s standard error, are preceded by the glyph “`error`”. For example:

```
$ echo hi on stdout
+ hi on stdout
$ echo hello on stderr 1>&2
error hello on stderr
```

In the text, command names appear in **this font**, while code segments appear in the same font and quoted, ‘*like this*’. Options look like this: **-f**. Some things are emphasized *like this*, and if a point needs to be made strongly, it is done **like this**. The first occurrence of a new term is usually its *definition* and appears in the same font as the previous occurrence of “definition” in this sentence. Finally, file names are indicated like this: `/path/to/our/file`.

Acknowledgements

1 Introduction

Ruby is . . .

A dynamic, open source programming language with a focus on simplicity and productivity. It has an elegant syntax that is natural to read and easy to write.

2 Documentation

Here you will find pointers to manuals, tutorials and references that will come in handy when you feel like coding in Ruby.

2.1 Installing Ruby

Installation Methods

There are several ways to install Ruby:

- **Package Manager:** When you are on a UNIX-like operating system, using your systems package manager is the easiest way of getting started. However, the packaged Ruby version usually is not the newest one.
- **Installers:** can be used to install a specific or multiple Ruby versions. There is also an installer for Windows.
- **Managers** help you to switch between multiple Ruby installations on your system.
- **Source:** And finally, you can also build Ruby from source.

The following overview lists available installation methods for different needs and platforms.

2.1.1 Package Management Systems

If you cannot compile your own Ruby, and you do not want to use a third-party tool, you can use your systems package manager to install Ruby.

Certain members in the Ruby community feel very strongly that you should never use a package manager to install Ruby and that you should use tools instead. While the full list of pros and cons is outside of the scope of this page, the most basic reason is that most package managers have older versions of Ruby in their official repositories. If you would like to use the newest Ruby, make sure you use the correct package name, or use the tools described further below instead.

2.1.1.1 Homebrew (OS X)

Homebrew

On macOS (High) Sierra and OS X El Capitan, Ruby 2.0 is included.

Many people on OS X use Homebrew as a package manager. It is really easy to get a newer version of Ruby using Homebrew:

```
$ brew install ruby
```

This should install the latest Ruby version.

2.1.2 Installers

If the version of Ruby provided by your system or package manager is out of date, a newer one can be installed using a third-party installer. Some of them also allow you to install multiple versions on the same system; associated managers can help to switch between the different Rubies. If you are planning to use RVM as a version manager you do not need a separate installer, it comes with its own.

2.1.2.1 ruby-build

`ruby-build`

`rbenv`

`ruby-build` is a plugin for `rbenv` (see [Section 2.1.3.2 “`rbenv`”, page 4](#)), that allows you to compile and install different versions of Ruby into arbitrary directories. `ruby-build` can also be used as a standalone program without `rbenv`. It is available for OS X, Linux, and other UNIX-like operating systems.

2.1.2.2 ruby-install

`ruby-install` version manager `chruby` version switcher

`ruby-install`

`chruby`

`ruby-install` allows you to compile and install different versions of Ruby into arbitrary directories. There is also a sibling, `chruby` (see [Section 2.1.3.1 “`chruby`”, page 4](#)), which handles switching between Ruby versions. It is available for OS X, Linux, and other UNIX-like operating systems.

2.1.3 Managers

Many Rubyists use Ruby managers to manage multiple Rubies. They confer various advantages but are not officially supported. Their respective communities are very helpful, however.

2.1.3.1 chruby

`chruby` allows you to switch between multiple Rubies. `chruby` can manage Rubies installed by `ruby-install` (see [Section 2.1.2.2 “`ruby-install`”, page 4](#)) or even built from source.

2.1.3.2 rbenv

`rbenv`

`ruby-build`

`rbenv` allows you to manage multiple installations of Ruby. It does not support installing Ruby, but there is a popular plugin named `ruby-build` (see [Section 2.1.2.1 “`ruby-build`”, page 4](#)) to install Ruby. Both tools are available for OS X, Linux, or other UNIX-like operating systems.

2.1.3.3 RVM (“Ruby Version Manager”)

`RVM`

`RVM` allows you to install and manage multiple installations of Ruby on your system. It can also manage different gemsets. It is available for OS X, Linux, or other UNIX-like operating systems.

2.1.3.4 uru

`Uru`

`Uru` is a lightweight, multi-platform command line tool that helps you to use multiple Rubies on OS X, Linux, or Windows systems.

2.1.4 Building From Source

Ruby 2.5.1

Ruby Github

Of course, you can install Ruby from source. Download and unpack a tarball, then just do this:

```
$ ./configure
$ make
$ sudo make install
```

By default, this will install Ruby into `/usr/local`. To change, pass the `--prefix=DIR` option to the `./configure` script.

Using the third-party tools or package managers might be a better idea, though, because the installed Ruby won't be managed by any tools.

Installing from the source code is a great solution for when you are comfortable enough with your platform and perhaps need specific settings for your environment. It's also a good solution in the event that there are no other premade packages for your platform.

2.1.4.1 Releases Page

Releases Page

For more information about specific releases, particularly older releases or previews, see the Releases page.

This page lists individual Ruby releases.

Ruby 2.5.1 Released

[ruby-2.1.5.tar.gz](#)

Posted by naruse on 28 Mar 2018

This release includes some bug fixes and some security fixes.

- CVE-2017-17742: HTTP response splitting in WEBrick
- CVE-2018-6914: Unintentional file and directory creation with directory traversal in tempfile and tmpdir
- CVE-2018-8777: DoS by large request in WEBrick
- CVE-2018-8778: Buffer under-read in String#unpack
- CVE-2018-8779: Unintentional socket creation by poisoned NUL byte in UNIXServer and UNIXSocket
- CVE-2018-8780: Unintentional directory traversal by poisoned NUL byte in Dir
- Multiple vulnerabilities in RubyGems

2.1.4.2 Branches Page

Branches Page

Information about the current maintenance status of the various Ruby branches can be found on the Branches page.

This page lists the current maintenance status of the various Ruby branches. This is a preliminary list of Ruby branches and their maintenance status. The shown dates are inferred from the English versions of release posts or EOL announcements.

The Ruby branches or release series are categorized below into the following phases:

- normal maintenance (bug fix): Branch receives general bug fixes and security fixes.
- security maintenance (security fix): Only security fixes are backported to this branch.
- eol (end-of-life): Branch is not supported by the ruby-core team any longer and does not receive any fixes. No further patch release will be released.
- preview: Only previews or release candidates have been released for this branch so far.

Ruby 2.6

<https://cache.ruby-lang.org/pub/ruby/2.6/ruby-2.6.0-preview2.tar.gz>

ruby-2.6.0-preview2

status: preview

release date:

Ruby 2.5

<https://cache.ruby-lang.org/pub/ruby/2.5/ruby-2.5.1.tar.gz>

status: normal maintenance

release date: 2017-12-25

Ruby 2.4

<https://cache.ruby-lang.org/pub/ruby/2.4/ruby-2.4.4.tar.gz>

status: normal maintenance

release date: 2016-12-25

Ruby 2.3

<https://cache.ruby-lang.org/pub/ruby/2.3/ruby-2.3.7.tar.gz>

status: security maintenance

release date: 2015-12-25

EOL date: scheduled for 2019-03-31

Ruby 2.2

status: eol

release date: 2014-12-25

EOL date: 2018-03-31

2.1.4.3 Ruby Issue Tracking System

Bugs

How to report a bug

How To Report

Ruby Trunk

[Ruby Trunk](#)

[All Issues](#)

2.2 Developing Ruby

[Ruby Core](#)

Now is a fantastic time to follow Rubys development. With the increased attention Ruby has received in the past few years, theres a growing need for good talent to help enhance Ruby and document its parts. So, where do you start?

Ruby Core

The topics related to Ruby development covered here are:

- [“Developing Ruby”](#), page 7,
- [“Developing Ruby”](#), page 7,
- [“Patch by Patch”](#), page 7,
- Rules for Core Developers

Using Subversion to Track Ruby Development

Getting the latest Ruby source code is a matter of an anonymous checkout from the [Subversion](#) repository. From your command line:

```
$ svn co https://svn.ruby-lang.org/repos/ruby/trunk ruby
```

The `ruby` directory will now contain the latest source code for the development version of Ruby (`ruby-trunk`). Currently patches applied to the trunk are backported to the stable 2.5, 2.4, and 2.3 branches (see below).

If youd like to follow patching of Ruby 2.5, you should use the `ruby_2_5` branch when checking out:

```
$ svn co https://svn.ruby-lang.org/repos/ruby/branches/ruby_2_5
```

This will check out the respective development tree into a `ruby_2_5` directory. Developers working on the maintenance branches are expected to migrate their changes to Rubys trunk, so often the branches are very similar, with the exception of improvements made by Matz and Nobu to the language itself.

If you prefer, you may browse [Rubys Subversion repository via the web](#).

How to Use Git With the Main Ruby Repository

Those who prefer to use Git over Subversion can find instructions with the [mirror on GitHub](#), both for those with commit access and [everybody else](#).

Improving Ruby, Patch by Patch

The core team maintains an [issue tracker](#) for submitting patches and bug reports to Matz and the gang. These reports also get submitted to the [Ruby-Core mailing list](#) for discussion, so you can be sure your request wont go unnoticed. You can also send your patches straight to the mailing list. Either way, you are encouraged to take part in the discussion that ensues.

Please look over the [Patch Writers Guide](#) for some tips, straight from Matz, on how to get your patches considered.

[Steps for Building a Patch](#)

2.3 Getting Started

2.3.1 Try Ruby!

[Try Ruby!](#)

An interactive tutorial that lets you try out Ruby right in your browser. This 15-minute tutorial is aimed at beginners who want to get a feeling of the language.

2.3.2 Official FAQ

The official frequently asked questions.

[FAQ](#)

This document contains Frequently Asked Questions about Ruby with answers.

This FAQ is based on [The Ruby Language FAQ](#) originally compiled by Shugo Maeda and translated into English by Kentaro Goto. Thanks to Zachary Scott and Marcus Stollsteimer for incorporating the FAQ into the site and for a major overhaul of the content.

- General questions
- How does Ruby stack up against?
- Installing Ruby
- Variables, constants, and arguments
- [Section 2.3.2.1 “FAQ Iterators”](#), page 8,
- [Section 2.3.2.2 “FAQ Syntax”](#), page 10,
- Methods
- Classes and modules
- Built-in libraries
- Extension library
- Other features

2.3.2.1 FAQ Iterators

What is an iterator?

An iterator is a method which accepts a block or a `Proc` object. In the source file, the block is placed immediately after the invocation of the method. Iterators are used to produce user-defined control structures — especially loops.

Lets look at an example to see how this works. Iterators are often used to repeat the same action on each element of a collection, like this:

```
data = [1, 2, 3]
data.each do |i|
  puts i
end
```

The `each` method of the array `data` is passed the `do ... end` block, and executes it repeatedly. On each call, the block is passed successive elements of the array.

You can define blocks with `{ ... }` in place of `do ... end`.

```
data = [1, 2, 3]
data.each { |i|
  puts i
}
```

This code has the same meaning as the last example. However, in some cases, precedence issues cause `do ... end` and `{ ... }` to act differently.

```
foobar a, b do ... end # foobar is the iterator.
foobar a, b { ... } # b is the iterator.
```

This is because `{ ... }` binds more tightly to the preceding expression than does a `do ... end` block. The first example is equivalent to `'foobar(a, b) do ... end'`, while the second is `'foobar(a, b { ... })'`.

How can I pass a block to an iterator?

You simply place the block after the iterator call. You can also pass a `Proc` object by prepending `&` to the variable or constant name that refers to the `Proc`.

How is a block used in an iterator?

This section or parts of it might be out-dated or in need of confirmation.

There are three ways to execute a block from an iterator method:

1. the `yield` control structure;

The `yield` statement calls the block, optionally passing it one or more arguments.

```
def my_iterator
  yield 1, 2
end
```

```
my_iterator {|a, b| puts a, b }
```

2. calling a `Proc` argument (made from a block) with `call`;

If a method definition has a block argument (the last formal parameter has an ampersand (`&`) prepended), it will receive the attached block, converted to a `Proc` object. This may be called using `proc.call(args)`.

```
def my_iterator(&b)
  b.call(1, 2)
end
```

```
my_iterator {|a, b| puts a, b }
```

and

3. using `Proc.new` followed by a `call`.

`Proc.new` (or the equivalent `proc` or `lambda` calls), when used in an iterator definition, takes the block which is given to the method as its argument and generates a procedure object from it. (`proc` and `lambda` are effectively synonyms.)

[Update needed: lambda behaves in a slightly different way and produces a warning ‘tried to create Proc object without a block’.]

```
def my_iterator
  Proc.new.call(3, 4)
  proc.call(5, 6)
  lambda.call(7, 8)
end
```

```
my_iterator {|a, b| puts a, b }
```

Perhaps surprisingly, `Proc.new` and friends do not in any sense consume the block attached to the method — each call to `Proc.new` generates a new procedure object out of the same block.

You can tell if there is a block associated with a method by calling `block_given?`.

What does `Proc.new` without a block do?

`Proc.new` without a block cannot generate a procedure object and an error occurs. In a method definition, however, `Proc.new` without a block implies the existence of a block at the time the method is called, and so no error will occur.

How can I run iterators in parallel?

See <http://blade.nagaokaut.ac.jp/cgi-bin/scat.rb/ruby/ruby-talk/5252>

2.3.2.2 FAQ Syntax

List of FAQ items:

- “FAQ Syntax”, page 10,
- “FAQ Syntax”, page 11,
- “FAQ Syntax”, page 11,
- “FAQ Syntax”, page 11,
- “FAQ Syntax”, page 11,
- “FAQ Syntax”, page 12,
- “FAQ Syntax”, page 12,
- “FAQ Syntax”, page 12,
- “FAQ Syntax”, page 12,
- “FAQ Syntax”, page 13,
- “FAQ Syntax”, page 13,
- “FAQ Syntax”, page 13,
- “FAQ Syntax”, page 13,
- “FAQ Syntax”, page 13,
- “FAQ Syntax”, page 14,

What is the difference between an immediate value and a reference?

`Fixnum`, `true`, `nil`, and `false` are implemented as *immediate values*. With immediate values, variables hold the objects themselves, rather than references to them.

Singleton methods cannot be defined for such objects. Two `Fixnums` of the same value always represent the same object instance, so (for example) instance variables for the `Fixnum` with the value 1 are shared between all the 1's in the system. This makes it impossible to define a singleton method for just one of these.

What is the difference between `nil` and `false`?

First the similarity: `nil` and `false` are the only two objects that evaluate to `false` in a boolean context. (In other words: they are the only “falsy” values; all other objects are “truthy”.)

However, `nil` and `false` are instances of different classes (`NilClass` and `FalseClass`), and have different behavior elsewhere.

We recommend that *predicate methods* (those whose name ends with a question mark) return `true` or `false`. Other methods that need to indicate failure should return `nil`.

The Empty String

An empty string (`""`) returns `true` in a conditional expression! In Perl, it's `false`. Its very simple: in Ruby, only `nil` and `false` are `false` in conditional contexts.

You can use `empty?`, compare the string to `""`, or compare the string's size or length to 0 to find out if a string is empty.

A Symbol Object

What does `:name` mean?

A colon followed by a name generates a *Symbol object* which corresponds one-to-one with the identifier. During the duration of a program's execution the same Symbol object will be created for a given name or string. Symbols can also be created with `"name".intern` or `"name".to_sym`.

Symbol objects can represent identifiers for methods, variables, and so on. Some methods, like `define_method`, `method_missing`, or `trace_var`, require a symbol. Other methods, e.g. `attr_accessor`, `send`, or `autoload`, also accept a string.

Due to the fact that they are created only once, Symbols are often used as hash keys. String hash keys would create a new object for every single use, thereby causing some memory overhead. There is even a special syntax for symbol hash keys:

```
person_1 = { :name => "John", :age => 42 }
person_2 = { name: "Jane", age: 24 }      # alternate syntax
```

Symbols can also be used as enumeration values or to assign unique values to constants:

```
status = :open # :closed, ...
```

```
NORTH = :NORTH
SOUTH = :SOUTH
```

How can I access the value of a symbol?

To get the value of the variable corresponding to a symbol, you can use `symbol.to_s` or `"#{symbol}"` to get the name of the variable, and then `eval` that in the scope of the symbol to get the variables contents:

```
a = "This is the content of 'a'"
b = eval("#{:a}")
a.object_id == b.object_id # => true
```

You can also use:

```
b = binding.local_variable_get(:a)
```

If your symbol corresponds to the name of a method, you can use `send`:

```
class Demo
  def hello
    "Hello, world"
  end
end

demo = Demo.new
demo.send(:hello)
```

Or you can use `Object#method` to return a corresponding `Method` object, which you may then call:

```
m = demo.method(:hello) # => #<Method: Demo#hello>
m.call                  # => "Hello, world"
```

Is loop a control structure?

Although `loop` looks like a control structure, it is actually a method defined in `Kernel`. The block which follows introduces a new scope for local variables.

Ruby doesnt have a post-test loop

Ruby does not have a `do { ... } while` construct, so how can I implement loops that test the condition at the end?

Clemens Hintze says: “You can use a combination of Rubys `begin ... end` and the `while` or `until` statement modifiers to achieve the same effect:

```
i = 0
begin
  puts "i = #{i}"
  i += 1
end until i > 4
```

Why cant I pass a hash literal to a method: `p {}`?

The `{}` is parsed as a block, not a `Hash` constructor. You can force the `{}` to be treated as an expression by making the fact that it's a parameter explicit: `p({})`.

I cant get `def pos=(val)` to work!

I have the following code, but I cannot use the method `pos = 1`.

```
def pos=(val)
  @pos = val
  puts @pos
end
```

Methods with `=` appended must be called with an explicit receiver (without the receiver, you are just assigning to a local variable). Invoke it as `self.pos = 1`.

What is the difference between `\1` and `\\1`?

They have the same meaning. In a single quoted string, only `\'` and `\\` are transformed and other combinations remain unchanged.

However, in a double quoted string, `"\1"` is the byte `\001` (an octal bit pattern), while `"\\1"` is the two character string containing a backslash and the character `"1"`.

What is the difference between `..` and `...`?

`..` includes the right hand side in the range, while `...` does not:

```
(5..8).to_a  # => [5, 6, 7, 8]
(5...8).to_a # => [5, 6, 7]
```

What is the difference between `or` and `||`?

`p(nil || "Hello")` prints `"Hello"`, while `p(nil or "Hello")` gives a parse error. Why?

`or` has a very low precedence; `p((nil or "Hello"))` will work.

The precedence of `or` is for instance also lower than that of `=`, whereas `||` has a higher precedence:

```
foo = nil || "Hello" # parsed as: foo = (nil || "Hello")
foo # => "Hello"
```

but perhaps surprisingly:

```
foo = nil or "Hello" # parsed as: (foo = nil) or "Hello"
foo # => nil
```

`or` (and similarly `and`) is best used, not for combining boolean expressions, but for control flow, like in:

```
do_something or raise "some error!"
```

where `do_something` returns `false` or `nil` when an error occurs.

Does Ruby have function pointers?

A `Proc` object generated by `Proc.new`, `proc`, or `lambda` can be referenced from a variable, so that variable could be said to be a function pointer. You can also get references to methods within a particular object instance using `object.method`.

What is the difference between load and require?

`load` will load and execute a Ruby program (*.rb).

`require` loads Ruby programs as well, but will also load *binary Ruby extension modules* (shared libraries or DLLs). In addition, `require` ensures that a feature is never loaded more than once.

Does Ruby have exception handling?

Ruby supports a flexible exception handling scheme:

```
begin
  statements which may raise exceptions
rescue [exception class names]
  statements when an exception occurred
rescue [exception class names]
  statements when an exception occurred
ensure
  statements that will always run
end
```

If an exception occurs in the `begin` clause, the `rescue` clause with the matching exception name is executed. The `ensure` clause is executed whether an exception occurred or not. `rescue` and `ensure` clauses may be omitted.

If no exception class is designated for a `rescue` clause, `StandardError` exception is implied, and exceptions which are in a `is_a?` relation to `StandardError` are captured.

This expression returns the value of the `begin` clause.

The latest exception is accessed by the global variable `$!` (and so its type can be determined using `$!.type`).

2.3.2.3 FAQ Methods

How does Ruby choose which method to invoke?

Are +, -, *, ... operators?

Where are ++ and -- ?

What is a singleton method?

All these objects are fine, but does Ruby have any simple functions?

So where do all these function-like methods come from?

Can I access an objects instance variables?

Whats the difference between private and protected?

How can I change the visibility of a method?

Can an identifier beginning with a capital letter be a method name?

Calling `super` gives an `ArgumentError`.

How can I call the method of the same name two levels up?

How can I invoke an original built-in method after redefining it?

What is a destructive method?

Why can destructive methods be dangerous?

Can I return multiple values from a method?

2.3.2.4 FAQ Classes and Modules

Can a class definition be repeated?

Are there class variables?

What is a class instance variable?

What is the difference between class variables and class instance variables?

Does Ruby have class methods?

What is a singleton class?

What is a module function?

What is the difference between a class and a module?

Can you subclass modules?

Give me an example of a mixin

Why are there two ways of defining class methods?

What is the difference between `include` and `extend`?

What does `self` mean?

2.3.2.5 FAQ Built-In Libraries

What does `instance_methods(false)` return?

How do random number seeds work?

I read a file and changed it, but the file on disk has not changed.

How can I process a file and update its contents?

I wrote a file, copied it, but the end of the copy seems to be lost.

How can I get the line number in the current input file?

How can I use `less` to display my programs output?

What happens to a `File` object which is no longer referenced?

I feel uneasy if I don't close a file.

How can I sort files by their modification time?

How can I count the frequency of words in a file?

How can I sort strings in alphabetical order?

How can I expand tabs to spaces?

How can I escape a backslash in a regular expression?

What is the difference between `sub` and `sub!`?

Where does `\Z` match?

What is the difference between `thread` and `fork`?

How can I use `Marshal`?

How can I use `trap`?

2.3.2.6 FAQ Extension Library

How can I use Ruby interactively?

Is there a debugger for Ruby?

How can I use a library written in C from Ruby?

Can I use `Tcl/Tk` in Ruby?

`Tk` won't work. Why?

Can I use `gtk+` or `xforms` interfaces in Ruby?

How can I do date arithmetic?

2.3.2.7 FAQ Other Features

What does `a ? b : c` mean?

How can I count the number of lines in a file?

What do `MatchData#begin` and `MatchData#end` return?

How can I sum the elements in an array?

How can I use continuations?

2.3.3 Ruby Koans

[Ruby Koans](#)

2.3.4 Whys (Poignant) Guide to Ruby

[Why's Guide to Ruby](#)

An unconventional but interesting book that will teach you Ruby through stories, wit, and comics. Originally created by *why the lucky stiff*, this guide remains a classic for Ruby learners.

2.3.5 Ruby in Twenty Minutes

[Ruby in Twenty Minutes](#)

A nice tutorial covering the basics of Ruby. From start to finish it shouldnt take you more than twenty minutes.

2.3.6 Ruby from Other Languages

[Ruby from Other Languages](#)

2.3.7 Learning Ruby

[Learning Ruby](#)

A thorough collection of Ruby study notes for those who are new to the language and in search of a solid introduction to Rubys concepts and constructs.

2.3.8 Ruby Essentials

[Ruby Essentials](#)

2.3.9 Learn to Program

[Learn to Program](#)

A wonderful little tutorial by Chris Pine for programming newbies. If you dont know how to program, start here.

[Learn Ruby the Hard Way](#)

2.4 Manuals

2.5 Reference Documentation

2.6 Editors and IDEs

2.7 Further Reading

Appendix A The Makefile

```
{Makefile} ≡
    <Makefile—Variable Definitions>
    <Makefile—Default Rule>
    <Makefile—TWJR Rules>
    <Makefile—Clean Rules>
```

The following table lists called chunk definition points.

Chunk name	First definition point
<Makefile—Clean Rules>	See “Clean Rules”, page 20.
<Makefile—Default Rule>	See “Default Rule”, page 19.
<Makefile—TWJR Rules>	See “TWJR Rules”, page 19.
<Makefile—Variable Definitions>	See “Makefile Variable Definitions”, page 19.

A.1 Makefile Variable Definitions

```
<Makefile—Variable Definitions> ≡
    FILE := Ruby2_5
```

This chunk is called by {Makefile}; see its first definition at “The Makefile”, page 19.

A.2 Default Rule

```
<Makefile—Default Rule> ≡
    .PHONY : default TANGLE WEAVE TEXI PDF HTML
    default : WEAVE TEXI PDF HTML
```

This chunk is called by {Makefile}; see its first definition at “The Makefile”, page 19.

A.3 TWJR Rules

```
<Makefile—TWJR Rules> ≡
    TANGLE : tangle
    tangle : $(FILE).twjr
            jrtangle $(FILE).twjr

    WEAVE : weave
    weave : TEXI
    TEXI : texi
    texi : $(FILE).texi

    $(FILE).texi : $(FILE).twjr
                jrweave $(FILE).twjr > $(FILE).texi

    PDF : pdf
    pdf : $(FILE).pdf
    $(FILE).pdf : $(FILE).texi
```

```
pdftexi2dvi $(FILE).texi
make distclean

HTML : html
html : $(FILE)/
$(FILE)/ : $(FILE).texi
        makeinfo --html $(FILE).texi
```

This chunk is called by {Makefile}; see its first definition at [“The Makefile”, page 19](#).

A.4 Clean Rules

<Makefile—Clean Rules> ≡

```
.PHONY : clean distclean worldclean
clean :
    rm -f *~ \#*\#

distclean : clean
    rm -f *.{aux,log,toc,cp,cps}

worldclean : distclean
    rm -f $(FILE).{texi,info,pdf}
    rm -fr $(FILE)/
```

This chunk is called by {Makefile}; see its first definition at [“The Makefile”, page 19](#).

Appendix B Code Chunk Summaries

This appendix presents alphabetical lists of all the file definitions, the code chunk definitions, and the code chunk references.

B.1 Source File Definitions

`{Makefile}`

This chunk is defined in “The Makefile”, page 19.

B.2 Code Chunk Definitions

<Makefile—Clean Rules>

This chunk is defined in “Clean Rules”, page 20.

<Makefile—Default Rule>

This chunk is defined in “Default Rule”, page 19.

<Makefile—TWJR Rules>

This chunk is defined in “TWJR Rules”, page 19.

<Makefile—Variable Definitions>

This chunk is defined in “Makefile Variable Definitions”, page 19.

B.3 Code Chunk References

<Makefile—Clean Rules>

This chunk is called by `{Makefile}`; see its first definition at “The Makefile”, page 19.

<Makefile—Default Rule>

This chunk is called by `{Makefile}`; see its first definition at “The Makefile”, page 19.

<Makefile—TWJR Rules>

This chunk is called by `{Makefile}`; see its first definition at “The Makefile”, page 19.

<Makefile—Variable Definitions>

This chunk is called by `{Makefile}`; see its first definition at “The Makefile”, page 19.

Bibliography

Index

"

"#symbol" 12
 "name".intern 11
 "name".to_sym 11

+

++ and -- 14

.

.. vs. 13

<

<Makefile—Clean Rules>, definition 20
 <Makefile—Clean Rules>, use 19
 <Makefile—Default Rule>, definition 19
 <Makefile—Default Rule>, use 19
 <Makefile—TWJR Rules>, definition 19
 <Makefile—TWJR Rules>, use 19
 <Makefile—Variable Definitions>, definition 19
 <Makefile—Variable Definitions>, use 19

‘

“falsey” values 11
 “truthy” values 11

\

\Z 16

{

{Makefile}, definition 19

A

ArgumentError, after calling super 15
 arithmetic 16
 array, sum elements in 17

B

binary Ruby extension modules 14
 binding of { ... } 9
 binding.local_variable_get(:symbol) 12
 block object, passed to iterator 8
 block, used in an iterator 9
 block_given? 10
 boolean context 11
 branches page 5

C

C library, use 16
 calling method 2 levels up 15
 chruby 4
 class definition, repeating 15
 class instance variable? 15
 class methods, defining, 2 ways 15
 class methods? 15
 class variables vs class instance variables 15
 class variables? 15
 class vs module 15
 conditional expression, false values 11
 continuations, using 17

D

dangerous, destructive methods 15
 debugger for Ruby 16
 destructive method 15
 developing Ruby 7
 DLLs 14
 do ... } while 12
 Documentation 3

E

each method of iterator 9
 empty string 11
 ensure clause 14
 eval 12
 exception handling 14

F

false and nil 11
 FalseClass 11
 File object, no reference 16
 file, copy 16
 file, count lines in 17
 file, line number 16
 file, process and update contents 16
 files, closing 16
 files, counting words 16
 files, reading vs modifying 15
 files, sorting by modification time 16
 fork vs thread 16
 function pointers 13
 function-like methods, where from? 14

G

gemsets, manage different using RVM 4
 GitHub, ruby repository 7
 gtk+ 16

I

identifier with capital letter, method?	15
immediate values	11
include vs extend	15
installer, third party	3
instance variables, accessing	14
instance_methods(false)	15
interactively use Ruby	16
invoking original method after redefinition	15
issue tracker	7
issue tracking	6
iterator, block	9
iterators	8

K

Kernel	12
---------------------	----

L

lambda as a synonym of Proc	9
line number of input file	16
load	14
loop	12

M

mailing lists	7
manage Rubies using chruby	4
Marshal	16
MatchData#begin and MatchData#end	17
method, destructive	15
method, invoking	14
mixin example	15
module function?	15
modules, subclassing?	15
multiple installations, manage using RVM	4
multiple Rubies, command-line tool uru	4

N

nil and false , similarities and differences	11
NilClass	11

O

operators?	14
------------------	----

P

Patch Writer's Guide	8
patching of Ruby	7
precedence of or	13
precedence, iterators, different results	9
predicate methods	11
private vs protected	14
Proc object, passed to iterator	8
Proc.new , followed by call	9
program output, display using less	16

R

random number seeds	15
rbenv	4
rbenv version manager	4
regular expression, escaping a backslash	16
releases	5
repository, Subversion	7
require	14
rescue clause	14
repository, GitHub	7
return multiple values	15
Rubies, switch between	3
Ruby core	7
Ruby Core mailing list	7
Ruby development, tracking	7
ruby-build plugin	4
RVM version manager	3

S

self , meaning	15
send	12
shared libraries	14
simple functions?	14
singleton class?	15
singleton method	14
source, building	5
strings, sort alphabetically	16
sub vs sub!	16
Subversion	7
Subversion repository	7
super gives ArgumentError	15
Symbol object	11
symbol, access value of	12
symbol.to_s	12
symbols as enumeration values	11
symbols as hash keys	11
symbols, unique constants	11

T

tabs, expand into spaces	16
Tcl/Tk, use	16
ternary operator	17
Texinfo document formatting language	1
thread vs fork	16
Tk, won't work	16
track Ruby development	7
trap	16

U

uru	4
-----------	---

V

version managers	3
versions, multiple installations using <code>rbenv</code>	4
versions, switch between using <code>chruby</code>	4
versions,multiple	3
visibility, changing	14

X

xforms	16
--------------	----

Y

yield control structor, or statement	9
yield control structure in iterator	9