

The interests of single-sensor ultrasound imaging today

Luc Jonveaux
Open source tinkerer
Independant
Milly, France
contact@un0rick.cc

Abstract—This document is a model and instructions for L^AT_EX. This and the IEEEtran.cls file define the components of your paper [title, text, heads, etc.]. *CRITICAL: Do Not Use Symbols, Special Characters, Footnotes, or Math in Paper Title or Abstract.

Index Terms—ultrasound imaging, open source, hardware, ultrasound

I. INTRODUCTION

Previous work was done on an arduino-like approach [1].

A. Ultrasound as part of medical imaging

Ultrasound is:

- * cost-efficiency. Signal generation uses a piezoelectric material, requiring much less than setting up for example a large magnetic field for an MRI scan.
- * relatively safe: as there are no ionizing radiation, ultrasound devices do not need special safety equipment like shields, or expensive supplies.
- * light: on the sense that compared to other imaging modalities, devices can be made relatively portable
- * dynamic

B. Open source medical hardware

Open hardware lowers some barriers: having a full design under an open-source license provides the key to all to contribute and improve a design. This in turns allows a possible rapid spread of the design, customisation for specific uses, and ad-hoc modification. A design being open means that a higher number of contributors can help inspect and improve it.

Repairs are also easier with the code, with several types of impact (social, environmental and economics) that enhance the lifecycle of a product.

The open source movement has been facilitated by the numerous platforms and communication means, that allow these designs to be copied, but also for robust storage and distribution means.

[?]

Open source hardware can be a disruptive tool on the medical device market. Of course, a caveat has to be made on the non-certification of most of these devices, which in turn would hint at open-source being a major tool in innovation, leaving the industrialisation of such devices to professionals. Shorter development cycles, even for hardware, with open source permits quick iterations over a product.

A study by Niezen [?] lists a selection of open-source medical projects. Most are working with Arduino or Raspberry Pi, showing the importance of existing projects and the way open-source allows for reuse of previous projects. Dedicated hardware is developped for this project, leaving the specifics of the project to be developped by the contributor.

II. ULTRASOUND IMAGING

A

III. A-MODE IMAGING

This modality can be used for example in image free systems for evaluation of vascular stiffness. [?]

Probes [10] Systems

but these have not been open-sourced.

IV. ACQUISITION MODALITIES

A. Pulse echo

B. Compressed sensing

Traditional 2-D and 3D ultrasound require the use of hundreds of delicates sensors, with matching hardware.

Ultrasound 2D arrays, or matrices, have developped available, however this also require more hardware (AFE, ADC units, cabling, etc..) and hence become more complex and expensive to produce, and require heavy data processing.

@todo add [?] thesis

It appears that classical sampling is challenged by the signal processing "compressive sensing" field. This shows that most signals have a sparse representation - a finite sparse signal can be reconstructed from a small set of linear, non-adaptive measurements.

The recent development of compressive sensing shows that one can encode individual voxels through a 'chaotic' intermediary (eg a lense), and allows to design simple ultrasound imaging equipment that can provide 3D imaging using a single-element ultrasound sensor.

Imaging is then offloaded to the processing domain supported by constantly growing electronic devices' capabilities (memory, GPU's).

This open doors to simpler hardware - and new applications [2].

[?]

C. Time reversal focusing

@adapt N.Etaix et.al [19] presented an idea of a low-profile acoustic imaging device with only one transmit/receive element. According to the theory, if the medium is reciprocal and the channels impulse response is known, the latter can be re-emitted in time-reversed order. Mathematically, this results in the response auto-convolution [20]. Knowing that the auto-convolution has a peak in the origin, focusing is effectively achieved. The time reversal result is equivalent to matched filtering energy maximization at the desired location in space and time.

D. Basics for US machine

- 1) specs from who:
- 2) key figures:

E. Use case

Even if relatively simple, the A-mode enables not imaging, but rather measurements, enabling the examination of paranasal sinuses, transkull fluid detection, sinus pathology, skeletal muscle detection in the guided wrist extension, automatic measurement of lumen diameter of carotid artery [3], or bone porosit [4].

F. Results

G. Tomography

[?]

V. B-MODE IMAGING

A. Basics for US machine

- 1) specs from who:
- 2) key figures:

B. Architecture

Configurable hardware makes the system resilient to future changes. Beyond this hardware designs can be adjusted without reprinting the circuit board.

FPGAs improve the ability for ultrasound imaging systems to create small form factor and high-performance products with reduced power consumption [5]. In the latter case, it enables the control of a 8 channels platform.

Others use an additional microcontroller is set up between the FPGA and the USB and provide configuration on the fly, providing access to the platform through Matlab. It can interface to an array using several Octal Ultrasound ADC/LNA/VGA/AAF (AD9272) [6], [7].

C. 2D imaging ..

- 1) *Sweeping means*: mechanical sweeping example [8].

One would note however, that for power-usages, plane wave imaging, made possible because of GPUs [9], would limit the formation of an image to a single pulse/receive event.

With high frequency transducers (c. 50 MHz), imaging transducers are relatively smaller, which makes mechanical scanning a great solution. This implies however strong positionning control and motors [10]. In this article, a piezoelectric motor is used in conjunction with an optical encoder.

- 2) *Arrays*: However, the need heavier setup, for example to use up to 128 channels setups [11].

D. MSAS/MFFS

[?]

[?]

E. Use case

1) *Ultrasound capsule*: Swallowable capsule : capsule endoscopy using high frequency microultrasound (US). This is a great example of miniaturisation fitting all in a 10 mm diameter 30 mm long capsule , with all the constraints discussed above [12].

further develops mechanics used in such a capsule [13].

- 2) *Fingers movement*: [?]

F. Results

G. To go further

[14] proposes a design usable on a smartphone, connected through USB. Plane-wave acquisition, mentioned earlier [9] also enables smarter captures.

Proof of concept for a portable 32-channel ultrasound unit [15]

VI. DOCUMENTATION

A. Why documenting

B. How to document

C. Results

VII. BYPRODUCTS

A. ADCs

B. phantoms

[?] from SPAM

C. Suppliers

D. Materials

On most designs, an acoustic window is needed to seal the scanhead while minimizing signal loss.

An oftne used material is the TPX (polymethylpentene), used for example on an hand-held high frequency ultrasound scanner [16] or on another bimorph design [17]. In the latter, the scanhead is located inside a 3D printed plastic probe housing and filled with de-ionized water.

VIII. OPEN SOURCE HARDWARE COMMUNITY

A. Hackaday

B. ice40

C. Business-like

- 1) *Certification*:
- 2) *Tindie*:

IX. EASE OF USE

A. *Maintaining the Integrity of the Specifications*

The IEEEtran class file is used to format your paper and style the text. All margins, column widths, line spaces, and text fonts are prescribed; please do not alter them. You may note peculiarities. For example, the head margin measures proportionately more than is customary. This measurement and others are deliberate, using specifications that anticipate your paper as one part of the entire proceedings, and not as an independent document. Please do not revise any of the current designations.

X. PREPARE YOUR PAPER BEFORE STYLING

Before you begin to format your paper, first write and save the content as a separate text file. Complete all content and organizational editing before formatting. Please note sections X-A–X-E below for more information on proofreading, spelling and grammar.

Keep your text and graphic files separate until after the text has been formatted and styled. Do not number text heads— \LaTeX will do that for you.

A. *Abbreviations and Acronyms*

Define abbreviations and acronyms the first time they are used in the text, even after they have been defined in the abstract. Abbreviations such as IEEE, SI, MKS, CGS, ac, dc, and rms do not have to be defined. Do not use abbreviations in the title or heads unless they are unavoidable.

B. *Units*

- Use either SI (MKS) or CGS as primary units. (SI units are encouraged.) English units may be used as secondary units (in parentheses). An exception would be the use of English units as identifiers in trade, such as “3.5-inch disk drive”.
- Avoid combining SI and CGS units, such as current in amperes and magnetic field in oersteds. This often leads to confusion because equations do not balance dimensionally. If you must use mixed units, clearly state the units for each quantity that you use in an equation.
- Do not mix complete spellings and abbreviations of units: “Wb/m²” or “webers per square meter”, not “webers/m²”. Spell out units when they appear in text: “. . . a few henries”, not “. . . a few H”.
- Use a zero before decimal points: “0.25”, not “.25”. Use “cm³”, not “cc”).

C. *Equations*

Number equations consecutively. To make your equations more compact, you may use the solidus (/), the exp function, or appropriate exponents. Italicize Roman symbols for quantities and variables, but not Greek symbols. Use a long dash rather than a hyphen for a minus sign. Punctuate

equations with commas or periods when they are part of a sentence, as in:

$$a + b = \gamma \quad (1)$$

Be sure that the symbols in your equation have been defined before or immediately following the equation. Use “(1)”, not “Eq. (1)” or “equation (1)”, except at the beginning of a sentence: “Equation (1) is . . .”

D. *\LaTeX -Specific Advice*

Please use “soft” (e.g., `\eqref{Eq}`) cross references instead of “hard” references (e.g., (1)). That will make it possible to combine sections, add equations, or change the order of figures or citations without having to go through the file line by line.

Please don’t use the `{eqnarray}` equation environment. Use `{align}` or `{IEEEeqnarray}` instead. The `{eqnarray}` environment leaves unsightly spaces around relation symbols.

Please note that the `{subequations}` environment in \LaTeX will increment the main equation counter even when there are no equation numbers displayed. If you forget that, you might write an article in which the equation numbers skip from (17) to (20), causing the copy editors to wonder if you’ve discovered a new method of counting.

\BIBTeX does not work by magic. It doesn’t get the bibliographic data from thin air but from .bib files. If you use \BIBTeX to produce a bibliography you must send the .bib files.

\LaTeX can’t read your mind. If you assign the same label to a subsection and a table, you might find that Table I has been cross referenced as Table IV-B3.

\LaTeX does not have precognitive abilities. If you put a `\label` command before the command that updates the counter it’s supposed to be using, the label will pick up the last counter to be cross referenced instead. In particular, a `\label` command should not go before the caption of a figure or a table.

Do not use `\nonumber` inside the `{array}` environment. It will not stop equation numbers inside `{array}` (there won’t be any anyway) and it might stop a wanted equation number in the surrounding equation.

E. *Some Common Mistakes*

- The word “data” is plural, not singular.
- The subscript for the permeability of vacuum μ_0 , and other common scientific constants, is zero with subscript formatting, not a lowercase letter “o”.
- In American English, commas, semicolons, periods, question and exclamation marks are located within quotation marks only when a complete thought or name is cited, such as a title or full quotation. When quotation marks are used, instead of a bold or italic typeface, to highlight a word or phrase, punctuation should appear outside of the quotation marks. A parenthetical phrase or statement at the end of a sentence is punctuated outside of the closing parenthesis (like this). (A parenthetical sentence is punctuated within the parentheses.)

- A graph within a graph is an “inset”, not an “insert”. The word alternatively is preferred to the word “alternately” (unless you really mean something that alternates).
- Do not use the word “essentially” to mean “approximately” or “effectively”.
- In your paper title, if the words “that uses” can accurately replace the word “using”, capitalize the “u”; if not, keep using lower-cased.
- Be aware of the different meanings of the homophones “affect” and “effect”, “complement” and “compliment”, “discreet” and “discrete”, “principal” and “principle”.
- Do not confuse “imply” and “infer”.
- The prefix “non” is not a word; it should be joined to the word it modifies, usually without a hyphen.
- There is no period after the “et” in the Latin abbreviation “et al.”.
- The abbreviation “i.e.” means “that is”, and the abbreviation “e.g.” means “for example”.

An excellent style manual for science writers is .

F. Authors and Affiliations

The class file is designed for, but not limited to, six authors. A minimum of one author is required for all conference articles. Author names should be listed starting from left to right and then moving down to the next line. This is the author sequence that will be used in future citations and by indexing services. Names should not be listed in columns nor group by affiliation. Please keep your affiliations as succinct as possible (for example, do not differentiate among departments of the same organization).

G. Identify the Headings

Headings, or heads, are organizational devices that guide the reader through your paper. There are two types: component heads and text heads.

Component heads identify the different components of your paper and are not topically subordinate to each other. Examples include Acknowledgments and References and, for these, the correct style to use is “Heading 5”. Use “figure caption” for your Figure captions, and “table head” for your table title. Run-in heads, such as “Abstract”, will require you to apply a style (in this case, italic) in addition to the style provided by the drop down menu to differentiate the head from the text.

Text heads organize the topics on a relational, hierarchical basis. For example, the paper title is the primary text head because all subsequent material relates and elaborates on this one topic. If there are two or more sub-topics, the next level head (uppercase Roman numerals) should be used and, conversely, if there are not at least two sub-topics, then no subheads should be introduced.

H. Figures and Tables

a) *Positioning Figures and Tables:* Place figures and tables at the top and bottom of columns. Avoid placing them in the middle of columns. Large figures and tables may span

across both columns. Figure captions should be below the figures; table heads should appear above the tables. Insert figures and tables after they are cited in the text. Use the abbreviation “Fig. 1”, even at the beginning of a sentence.

TABLE I
TABLE TYPE STYLES

Table Head	Table Column Head		
	Table column subhead	Subhead	Subhead
copy	More table copy ^a		

^aSample of a Table footnote.

Fig. 1. Example of a figure caption.

Figure Labels: Use 8 point Times New Roman for Figure labels. Use words rather than symbols or abbreviations when writing Figure axis labels to avoid confusing the reader. As an example, write the quantity “Magnetization”, or “Magnetization, M”, not just “M”. If including units in the label, present them within parentheses. Do not label axes only with units. In the example, write “Magnetization (A/m)” or “Magnetization {A[m(1)]}”, not just “A/m”. Do not label axes with a ratio of quantities and units. For example, write “Temperature (K)”, not “Temperature/K”.

ACKNOWLEDGMENT

The preferred spelling of the word “acknowledgment” in America is without an “e” after the “g”. Avoid the stilted expression “one of us (R. B. G.) thanks ...”. Instead, try “R. B. G. thanks...”. Put sponsor acknowledgments in the unnumbered footnote on the first page.

REFERENCES

Please number citations consecutively within brackets . The sentence punctuation follows the bracket . Refer simply to the reference number, as in —do not use “Ref. ” or “reference ” except at the beginning of a sentence: “Reference was the first ...”

Number footnotes separately in superscripts. Place the actual footnote at the bottom of the column in which it was cited. Do not put footnotes in the abstract or reference list. Use letters for table footnotes.

Unless there are six authors or more give all authors’ names; do not use “et al.”. Papers that have not been published, even if they have been submitted for publication, should be cited as “unpublished” . Papers that have been accepted for publication should be cited as “in press”. Capitalize only the first word in a paper title, except for proper nouns and element symbols.

For papers published in translation journals, please give the English citation first, followed by the original foreign-language citation [18].

REFERENCES

- [1] L. Jonveaux, "Arduino-like development kit for single-element ultrasound imaging," *Journal of Open Hardware*, vol. 1, Mar. 2017.
- [2] P. Kruizinga, P. v. d. Meulen, A. Fedjajevs, F. Mastik, G. Springeling, N. d. Jong, J. G. Bosch, and G. Leus, "Compressive 3d ultrasound imaging using a single sensor," *Science Advances*, vol. 3, p. e1701423, Dec. 2017.
- [3] H. Li, Y. Zhou, L. Wang, and X. Wen, "A New Implementation of A-Mode Ultrasound Pulser-Receiver System," in *Modelling and Simulation 2014 5th International Conference on Intelligent Systems*, pp. 187–190, Jan. 2014.
- [4] M. A. A. Wahab, R. Sudirman, C. Omar, and I. Ariffin, "Design of an A-mode ultrasound amplifier for bone porosity detection," in *2016 International Symposium on Electronics and Smart Devices (ISESD)*, pp. 79–84, Nov. 2016.
- [5] C. Dusa, P. Rajalakshmi, S. Puli, U. B. Desai, and S. N. Merchant, "Low complex, programmable FPGA based 8-channel ultrasound transmitter for medical imaging researches," in *2014 IEEE 16th International Conference on e-Health Networking, Applications and Services (Healthcom)*, pp. 252–256, Oct. 2014.
- [6] J. R. Raj, S. M. K. Rahman, and S. Anand, "Microcontroller USB interfacing with MATLAB GUI for low cost medical ultrasound scanners," *Collection of Engineering Science and Technology, an International Journal*, Apr. 2017.
- [7] J. Raj, R. Smk, and S. Anand, *8051 microcontroller to FPGA and ADC interface design for high speed parallel processing systems Application in ultrasound scanners*, vol. 19, May 2016.
- [8] L. Svilainis, V. Dumbrava, S. Kitov, A. Aleksandrovas, P. Tervydis, and D. Liaukonis, "Electronics for Ultrasonic Imaging System," *Elektronika ir Elektrotechnika*, vol. 20, pp. 51–56, Sept. 2014.
- [9] H. Hewener and S. Tretbar, "Mobile ultrafast ultrasound imaging system based on smartphone and tablet devices," in *2015 IEEE International Ultrasonics Symposium (IUS)*, pp. 1–4, Oct. 2015.
- [10] R. Carotenuto, G. Caliano, and A. Caronti, "Very fast scanning probe for ophthalmic echography using an ultrasound motor," in *IEEE Ultrasonics Symposium, 2004*, vol. 2, pp. 1310–1313 Vol.2, Aug. 2004.
- [11] A. A. Assef, J. M. Maia, and E. T. Costa, "A flexible multichannel FPGA and PC-Based ultrasound system for medical imaging research: initial phantom experiments," *Research on Biomedical Engineering*, vol. 31, pp. 277–281, Sept. 2015.
- [12] B. F. Cox, F. Stewart, H. Lay, G. Cummins, I. P. Newton, M. P. Y. Desmulliez, R. J. C. Steele, I. Nthke, and S. Cochran, "Ultrasound capsule endoscopy: sounding out the future," *Annals of Translational Medicine*, vol. 5, p. 201, May 2017.
- [13] X. Wang, V. Seetohul, R. Chen, Z. Zhang, M. Qian, Z. Shi, G. Yang, P. Mu, C. Wang, Z. Huang, Q. Zhou, H. Zheng, S. Cochran, and W. Qiu, "Development of a Mechanical Scanning Device With High-Frequency Ultrasound Transducer for Ultrasonic Capsule Endoscopy," *IEEE Transactions on Medical Imaging*, vol. 36, pp. 1922–1929, Sept. 2017.
- [14] J. H. Kim, S. Yeo, M. Kim, S. Kye, Y. Lee, and T. k. Song, "A smart-phone based portable ultrasound imaging system for point-of-care applications," in *2017 10th International Congress on Image and Signal Processing, BioMedical Engineering and Informatics (CISP-BMEI)*, pp. 1–5, Oct. 2017.
- [15] G. Kim, C. Yoon, S.-B. Kye, Y. Lee, J. Kang, Y. Yoo, and T.-k. Song, *A Single FPGA-Based Portable Ultrasound Imaging System for Point-of-Care Applications*, vol. 59, July 2012.
- [16] S. Erickson, D. Kruse, and K. Ferrara, "A hand-held, high frequency ultrasound scanner," in *2001 IEEE Ultrasonics Symposium. Proceedings. An International Symposium (Cat. No.01CH37263)*, vol. 2, pp. 1465–1468 vol.2, 2001.
- [17] J. A. Brown, J. Leadbetter, M. Leung, A. Bezanson, and R. Adamson, "A low cost open source high frame-rate high-frequency imaging system," in *2013 IEEE International Ultrasonics Symposium (IUS)*, pp. 549–552, July 2013.
- [18] R. K. Megalingam, A. B. E. Alinkeezhil, G. Pocklassery, H. Menon, A. A. Thulasi, and T. C. Kattakayam, "FPGA PCI device design for ultrasound scanning system in prenatal healthcare," in *2016 10th International Conference on Intelligent Systems and Control (ISCO)*, pp. 1–6, Jan. 2016.