

# Examples of SQL

## (query)

查询语句的多样性

# 关系模式

顾客

**Customers (cid, cname, city, discnt)**

供应商

**Agents (aid, aname, city, percent)**

产品

**Products (pid, pname, city, quantity, price)**

订单

**Orders (ordno, month, cid, aid, pid, qty, dollars)**

**Customers (cid, cname, city, discont)**

**Agents (aid, aname, city, percent)**

**Products (pid, pname, city, quantity, price)**

**Orders (ordno, month, cid, aid, pid, qty, dollars)**

**【例】 Retrieve the city names containing customers who order product p01.**

---

**【Answer 1】 表的连接查询**

```
SELECT city  
FROM customers c, orders o  
WHERE c.cid = o.cid and o.pid = 'p01' ;
```

**Customers (cid, cname, city, discnt)**

**Agents (aid, aname, city, percent)**

**Products (pid, pname, city, quantity, price)**

**Orders (ordno, month, cid, aid, pid, qty, dollars)**

**【例】 Retrieve the city names containing customers who order product p01.**

**【Answer 2】 IN谓词 + 独立子查询**

```
SELECT city
FROM customers
WHERE cid IN ( SELECT cid
                FROM orders
                WHERE pid = 'p01' ) ;
```

**Customers (cid, cname, city, discont)**

**Agents (aid, aname, city, percent)**

**Products (pid, pname, city, quantity, price)**

**Orders (ordno, month, cid, aid, pid, qty, dollars)**

**【例】 Retrieve the city names containing customers who order product p01.**

---

**【Answer 3】 IN谓词 + 相关子查询**

```
SELECT city
FROM customers c
WHERE 'p01' IN (SELECT o.pid
                FROM orders o
                WHERE o.cid = c.cid ) ;
```

**Customers (cid, cname, city, discnt)**

**Agents (aid, aname, city, percent)**

**Products (pid, pname, city, quantity, price)**

**Orders (ordno, month, cid, aid, pid, qty, dollars)**

**【例】 Retrieve the city names containing customers who order product p01.**

---

**【Answer 4】 = ANY (SOME) + 子查询**

```
SELECT city
FROM customers
WHERE cid = ANY (
    SELECT cid
    FROM orders
    WHERE pid = 'p01' ) ;
```

**Customers (cid, cname, city, discont)**

**Agents (aid, aname, city, percent)**

**Products (pid, pname, city, quantity, price)**

**Orders (ordno, month, cid, aid, pid, qty, dollars)**

**【例】 Retrieve the city names containing customers who order product p01.**

---

**【Answer 5】 EXISTS + 相关子查询**

```
SELECT city
FROM customers c
WHERE EXISTS (
    SELECT *
    FROM orders o
    WHERE o.cid = c.cid and
          o.pid = 'p01' );
```