



The Retail Innovators

GK/Retail Solution Model Omni-Channel POS

Export POSLog Structure v3 (Version 2.5) - 01240215126

Datum 09.10.2025

Copyright

© GK Software Gruppe 2025. Alle Rechte bleiben vorbehalten.

Die vorliegenden Unterlagen werden von GK Software SE und/oder von mit GK Software SE verbundenen Unternehmen (GK Software Gruppe) bereitgestellt und dienen ausschließlich zu Informationszwecken. Die GK Software Gruppe übernimmt keinerlei Haftung oder Gewährleistung für Fehler oder Unvollständigkeiten in dieser Publikation.

Die einzigen Gewährleistungen der GK Software Gruppe werden in den ausdrücklichen Gewährleistungsregelungen der jeweiligen Verträge zwischen der GK Software Gruppe und ihren Kunden oder Partnern getroffen. Aus den in dieser Publikation enthaltenen Informationen ergibt sich keine weiterführende Gewährleistung.

Die Materialien dürfen ohne vorherige ausdrückliche Zustimmung der GK Software Gruppe nicht auf irgendeine Weise vervielfältigt oder an Dritte übermittelt werden. Die hier enthaltenen Informationen können ohne Vorankündigung geändert werden.

Alle Firmennamen der GK Software Gruppe, Bezeichnungen von Produkten oder Dienstleistungen der GK Software Gruppe, sowie hier erwähnte Logos sind eingetragene Marken und geistiges Eigentum der GK Software Gruppe.

Inhalt

1	History	Fehler! Textmarke nicht definiert.
2	Page History	Fehler! Textmarke nicht definiert.
3	Linked Content	5
4	Table of Contents	5
5	Summary	8
6	Structure	8
6.1	XSD	8
6.2	Extensibility	8
6.2.1	Custom elements and attributes (customExtension)	8
6.2.2	Additional Enumeration values	8
6.3	Transaction	9
6.3.1	SES:OperatorBypassApproval	11
6.3.2	SES:ReceiptHeaderAddonList	11
6.3.2.1	Addon	11
6.3.3	SES:ReceiptTimerList	11
6.3.3.1	Timer	11
6.3.4	SES:LoyaltyAccount	12
6.3.4.1	LoyaltyProgram	12
6.3.5	SES:TransactionBinaryDataList	12
6.3.5.1	BinaryData	12
6.3.6	RetailTransaction	12
6.3.6.1	LineItem	14
6.3.6.2	BinaryData	29
6.3.6.3	Customer	29
6.3.6.4	TransactionLink	31
6.3.6.5	SES:CouponSummary	31
6.3.7	TenderControlTransaction	32
6.3.7.1	SES:TenderLoan	32
6.3.7.2	Deposit	33
6.3.7.3	TillSettle	34
6.3.7.4	SafeDrop	35
6.3.7.5	SES:TenderPickup	35
6.3.7.6	SES:PaidIn	36
6.3.7.7	SES:PaidOut	36
6.3.7.8	SES:TenderInterchange	36
6.3.7.9	SES:TenderLoanCarriedForward	37

6.3.7.10	SES:SafeSettle	37
6.3.8	ControlTransaction	38
6.3.8.1	BusinessEOD	39
6.3.8.2	TillEOD	39
6.3.8.3	OperatorSignOn	42
6.3.8.4	OperatorSignOff	42
6.3.8.5	SES:CashierStatistics	42
6.3.8.6	SES:StoreEODSummary	43
6.3.8.7	SES:TaxRefund	44
6.3.8.8	SES:TransactionLink	44

1 Linked Content

- Business Concept
- Business Process
- Technical Model
- Test Model

2 Table of Contents

- History
- Page History
- Linked Content
- Table of Contents
- Summary
- Structure
 - XSD
 - Extensibility
 - Custom elements and attributes (customExtension)
 - Additional Enumeration values
 - Transaction
 - SES:OperatorBypassApproval
 - SES:ReceiptHeaderAddonList
 - Addon
 - SES:ReceiptTimerList
 - Timer
 - SES:LoyaltyAccount
 - LoyaltyProgram
 - SES:TransactionBinaryDataList
 - BinaryData
 - RetailTransaction
 - LinelItem
 - Sale
 - POSIdentity
 - Associate
 - RetailPriceModifier
 - Tax
 - TransactionLink
 - SES:ExternalReceiptReferenceList
 - SES:GiftCertificateData
 - SES:SalesOrderData

- Return
 - TransactionLink
 - Rounding
 - SES:Rounding
 - Voids
 - ItemLink
 - LoyaltyReward
 - GiftCertificate
 - SES:Voucher
 - SES:PriceDerivationRule
 - Tax
 - TaxExemption
 - Tender
 - TenderChange
 - Authorization
 - ForeignCurrency
 - Check
 - CreditDebit
 - Coupon
 - Voucher
 - SES:LoyaltyRedemption
 - SES:OperatorBypassApproval
 - SES:ReceiptPositionAddonList
 - SES:LineItemBinaryDataList
- BinaryData
- Customer
 - CustomerName
 - Address
 - Telephone
 - Email
- TransactionLink
- SES:CouponSummary
 - SES:CouponSerialSummary
- TenderControlTransaction
 - SES:TenderLoan
 - SES:Totals
 - Deposit
 - DepositDetail
 - SES:DepositForeignCurrency
 - TillSettle

- TenderSummary
 - Over
 - Short
 - SES:Nominal
 - SES:Ending
- SafeDrop
- SES:TenderPickup
- SES:PaidIn
- SES:PaidOut
- SES:TenderInterchange
- SES:TenderLoanCarriedForward
- SES:SafeSettle
 - TenderSummary
 - Over
 - Short
 - SES:Nominal
 - SES:Ending
- ControlTransaction
 - BusinessEOD
 - TillEOD
 - TenderSummary
 - Beginning
 - Pickup
 - Over
 - Short
 - SES:Nominal
 - SES:SalesTenderNominal
 - SES:Ending
 - SES:SalesSummary
 - SES:RebateSummary
 - SES:TaxSummary
 - OperatorSignOn
 - OperatorSignOff
 - SES:CashierStatistics
 - TotalMeasures
 - LineItemVoids
 - PostTransactionVoids
 - SES:TransactionCancellations
 - SES:DirectLineItemVoids
 - SES:StoreEODSummary

- SES:TaxRefund
- SES:TransactionLink

3 Summary

This document describes the XML structure of export POSLog v3.

There is a versioning of POSLog export because in future different versions of export should be supported.

Specification based on namespace:

"http://www.gk-software.com/storeweaver/sdc/pos_upload/pos_upload/2.5"

4 Structure

Under root element POSLog there is a element Transaction for each transaction.

Data types are according to the XML schema (XSD).

4.1 XSD

POSLog 2.5 XSDs - v.5.14.zip

4.2 Extensibility

4.2.1 Custom elements and attributes (customExtension)

For many elements and attributes the XSD contains a customExtension option, which is represented by an "any" element or attribute in the XSD (with the "customExtension" namespace).

The use cases for these customExtensions are:

- In the GK Product POSLog the XXCustom fields from the Transaction DO are exported without having defined them as elements or attributes in the XSD. The namespace prefix for exporting the XXCustom fields is "CST", e.g. "CST:XXCustom01". If necessary, within the project it is possible to deactivate exporting all XXCustom fields:
 - This deactivation is not possible for single/specific XXCustom fields, only for all of them together.
 - This deactivation cannot be done via configuration, but requires a small implementation in the project.
- In the projects, any required field can be added to the POSLog. The recommended namespace prefix to be used for the project specific elements and attributes is also "CST". (Note: Such additional fields can be used in case the export of the XXCustom fields is generally deactivated, but some content of the XXCustom fields still needs to be exported.)

4.2.2 Additional Enumeration values

All enumeration data types have the TypeCodeExtension, which means there can be implemented additional values for the corresponding elements and attributes without extending the XSD. This TypeCodeExtension uses the following regular expression, which is the standard POSLog enumeration extension pattern:

- [0-9A-Za-z][0-9A-Za-z]*:[A-Z][0-9A-Za-z]*
 - Namespace prefix: Any alphanumeric string (not using special characters).
 - After the namespace and the colon: The first character needs to be a capital letter. All other characters can be alphanumeric (not using special characters).

4.3 Transaction

Attributes

Attribute	optional	Description	Comment
MajorVersion		major version of POSLog export	fix value = 3
MinorVersion	x	minor version of POSLog export	fix value = 0
FixVersion	x	fix version of POSLog export	fix value = 0
SES:InternalMajorVersion		internal major version of POSLog export interface	fix value = 2
SES:InternalMinorVersion		internal minor version of POSLog export interface	fix value = 5
SES:InternalFixVersion		internal fix version of POSLog export interface	fix value = 9
CancelFlag	x	Flag for canceled transaction boolean	
TrainingModeFlag	x	Flag for transaction, made in training mode boolean	

XML elements

XML element	optional	Description	Comment
RetailStoreID		A unique retailer assigned identifier for a RetailStore	
WorkstationID		Identifier for the workstation/POS within the store. (WorkstationID = 0 is used for transactions created by POS Server.)	
TillID	x	Identifier for the tender repository (drawer) within the store. In case of transactions that don't relate to a drawer, the element TillID won't be created.	
SequenceNumber		SequenceNumber is the receipt number (that is also printed on the receipt). It's a counter used to uniquely identify an individual transaction within a transaction set identified by: BusinessUnitID (RetailStoreID, store number), BusinessDayDate (date when transaction was created), WorkstationID (terminal, register where transaction was entered) and SequenceNumber. The sequence number counter is reset to 1 after a (configured) maximum number is reached. Alternatively it can be configured to reset the sequence number to 1 every calendar day. The export process adds a prefix to the SequenceNumber in following cases: • For voiding offline rebooking (RetailTransactionTypeCode "RE" and TransactionAssociation.TransactionAssociationTypeCode= VOID): "109" (prefix) + Transaction.SequenceNumber • For offline rebooking (RetailTransactionTypeCode "RE"): "108" (prefix) + Transaction.SequenceNumber	
BusinessDayDate		The calendar date of the BusinessDay.	
BeginDateTime		The time and date a transaction is initiated.	
EndDateTime		The time and date stamp a transaction is completed.	
OperatorID	x	ID of the operator who created the transaction. The element OperatorID itself is empty, but the attribute WorkerID is used. attributes: • OperatorName (optional) • WorkerID (optional)	
CurrencyCode		The unique identifier of the Currency.	

		String; 3 digits (EUR, USD, ...)	
ControlTransaction		XML-container: created in case of control transaction	
RetailTransaction		XML-container: created in case of retail transaction	
TenderControlTransaction		XML-container: created in case of tender control transaction	
SES:TenantID	x	The unique identifier for the TENANT.	
SES:LocationID	x	won't be created	not supported on POS side
SES:OperatorBypassApproval	x	XML-container: created in case of approval by another operator	see SES:OperatorBypassApproval
SES:ReceiptHeaderAddonList	x	XML-container: created in case of addition header information	see SES:ReceiptHeaderAddonList
SES:ReceiptTimerList	x	XML-container: created in case of time information	see SES:ReceiptTimerList
SES:PriceInformationList	x	won't be created	
SES:BusinessBeginDateTime	x	The time and date when the accounting period of drawer/store started (only exported for StoreEODSummary or TillEOD).	
SES:BusinessEndDateTime	x	The time and date when the accounting period of drawer/store ended (only exported for StoreEODSummary or TillEOD).	
SES:InternalSequenceNumber	x	won't be created	
SES:ReceiptReturnedFlag		True in case of return transaction.	
SES:ReasonCode	x	XML-container: created in case of canceled or voided transactions. attribute: - ReasonType - Description	
SES:PostVoidedFlag		A flag denoting that the entire original transaction has been voided (and reversed) after it was completed at the POS. (SES:PostVoidedFlag = true for the voiding transaction that voids the original transaction.)	
SES:TransactionSoftwareVersion	x	application version with which the transaction was created.	
SES:SoftwareVersion		string of composite terms (GK + release version)	
SES:LoyaltyAccount	x	XML-container: created in case of loyalty program.	see SES:LoyaltyAccount
SES:KeyedOfflineCode	x	A code that indicates the online/offline state when transaction was completed. possible values: - OnLineReferenceItem - OffLine - Both (Online/Offline)	
SES:InternalTransactionID		A universally unique identifier (UUID) for the Transaction.	
SES:FiscalSequenceNumber	x	A identifier being created either by the POS, the fiscal printer, or other device used for fiscalization.	
SES:FiscalFlag		A flag denoting that this is a fiscal transaction.	
SES:FiscalDayNumber	x	The fiscal day counter.	
SES:FiscalPrinterID	x	The identifier of the fiscal printer.	
SES:FiscalSignature	x	Fiscal signature of the transaction.	
SES:TransactionBinaryDataList	x	XML-container: created in case of binary data attached to the transaction	see SES:TransactionBinaryDataList
SES:LayawayFlag		A flag denoting that this is a layaway transaction.	
SES:LayawayTransactionType	x	The type of the layaway transaction. Possible values: 'FullyPay' - fully paid layaways 'Claiming' - claimed layaway 'DownPayment' - down payment layaway 'Modify' - partial voided / modified layaway 'Void' - complete voided layaway 'Terminate' - terminated layaway 'Expire' - expired layaway 'Rebooking' - rebooked layaway 'Create' - create layaway 'Extend' - extended layaway (extension of expiration date)	
CST:XXCustom01 ... CST:XXCustom15	x	A separate element is created for every XXCustom field from 01 to 15.	

customExtension	x	Any elements can be added to the XML.	
-----------------	---	---------------------------------------	--

4.3.1 SES:OperatorBypassApproval

Attributes

Attribute	optional	Description	Comment
ApprovalTypeCode		shows, how authorization was triggered fix value: "CODE" (operator number)	

XML-Elements

XML element	optional	Description	Comment
ApprovalCode	x	won't be created	
ApproverID	x	ID of authorizing operator attributes: - WorkerID (optional) - ApproverName (optional)	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.2 SES:ReceiptHeaderAddonList

XML-Elements

XML element	optional	Description	Comment
Addon			see Addon

4.3.2.1 Addon

XML-Elements

XML element	optional	Description	Comment
AddonPos	x	addon sequence number per Key	
Key		addon key possible values: e.g. "TransactionTypeCode" "TransactionCategoryCode" "FIRSTLOGIN" - ONLINE - OFFLINE	
Value		possible values: e.g. - value of TransactionTypeCode - value of TransactionCategoryCode "true" (FIRSTLOGIN) - timestamp of switch the connection status (Online/Offline)	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.3 SES:ReceiptTimerList

XML-Elements

XML element	optional	Description	Comment
Timer		XML-container:	see Timer

4.3.3.1 Timer

XML-Elements

XML element	optional	Description	Comment
TimerID		"76" (first item registration to first tender registration) "77" (first tender registration to end of receipt)	
StartTimestamp		receipt begin timestamp ("76")	

		tender begin timestamp ("77")	
Duration		duration from receipt begin timestamp to tender begin timestamp ("76") duration from tender begin timestamp to end of receipt timestamp ("77") seconds with 3 decimals	
customExtension	x	Any elements can be added to the XML.	

4.3.4 SES:LoyaltyAccount

XML element	optional	Description	Comment
CustomerID	x	Customer ID	
LoyaltyProgram	x	XML-container:created in case of loyalty program information.	see LoyaltyProgram

4.3.4.1 LoyaltyProgram

XML element	optional	Description	Comment
LoyaltyAccountID	x	The identifier of the loyalty account.	
EffectiveDate	x	Effective date	
Points	x	Type of points Attributes: Type	
LoyaltyAccountTypeCode		Determines the kind of customer account. e.g. 00 - turnover of the (current) year 01 - rebate amount which was granted during the (current) year 02 - bonus points - VP - Valuephone transaction - GC - not used / partial returned gift certificates	
LoyaltyAccountTransactionID	x	The external identifier of the accounting transaction of the the loyalty account.	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.5 SES:TransactionBinaryDataList

XML-Elements

XML element	optional	Description	Comment
BinaryData			see BinaryData

4.3.5.1 BinaryData

XML-Elements

XML element	optional	Description	Comment
Name		The name of the binary data entry.	
Content		The binary object (Base64 encoded). e.g.: - Journal - GraphicalJournal	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.6 RetailTransaction

Attributes

Attribute	optional	Description	Comment
TransactionStatus		status of transaction possible values:	

		• PostVoided • Suspended • Unknown • SES:ItemInfo • Replaced • SES:Invoice • Finished • SES:LayawayPostVoided • SES:Ordered • SES:Moved • SES:Scale • SES:ScalePostVoided	
--	--	--	--

XML-elements

XML element	optional	Description	Comment
ReceiptDateTime	x	date and time of receipt	
LineItem	x	XML-container: contains information about line items and tender line items	see LineItem
Total	x	total amount of the transaction attributes: • TotalType (optional) = "TransactionGrandAmount" • CST:XXCustom01 ... CST:XXCustom05 (optional) • customExtension (optional)	
Total	x	total net amount of the transaction attribute: • TotalType (optional) = "TransactionNetAmount"	
Total	x	total tax amount of the transaction attribute: • TotalType (optional) = "TransactionTaxAmount"	
Customer	x	XML-container: will be created in case the receipt includes customer data	see Customer
TransactionLink	x	XML-container: will be created in following cases: • voiding receipt - link to original receipt • invoice - link to original sales receipt • offline rebooking - link to original sales receipt • voiding offline rebooking - link original offline rebooking receipt • layaway relevant receipt (except layaway create receipt) - link to original layaway create receipt • retrieving receipt - link to retrieved suspended receipt • replacing transaction - link to replaced transaction	see TransactionLink
SES:CustomerSurvey	x	XML-container: will be created in case the receipt includes data from a customer survey	currently not supported
SES:NegativeTotalFlag		"false" in case of total amount >=0 "true" in case of total amount <0	
SES:AmendmentFlag	x	"true" in case of amendment (former AmendmentTypeCode 01 and 02) otherwise "false"	
SES:EmailRequestedFlag	x	"true" in case of send receipt as mail is activated	
SES:EmailAddress	x	email address	
SES:InvoicePrintoutTypeCode	x	invoice printout is activated will be created if invoice is activate or printed	
SES:InvoiceNumber	x	number of the invoice will be created if invoice number was generated	
SES:CouponSummary	x	XML-container: will be created for each coupon	see SES:CouponSummary
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	

customExtension	x	Any elements can be added to the XML.	
-----------------	---	---------------------------------------	--

4.3.6.1 LinelItem

Attributes

Attribute	optional	Description	Comment
VoidFlag	x	"true" in case of - former GK_BONPOSITION.STORNOTYP=4 - former GK_BONZAHLUNG.STORNOTYP=4 otherwise "false"	
EntryMethod	x	will be created only in case of - sale - return possible values: "Scanned" "SES:KeyedPerDuplicate" "Keyed"	
customExtension	x	Any attributes can be added to the XML.	

XML-Elements

	XML element	optional	Description	Comment
	SequenceNumber		for additional down payment line items for immediate pickups: - consecutive number starting with 100 001 Else sequence number of original receipt position - no consecutive number over all LinelItems (item, tax and tender positions) - starts with '0' - can have holes, because of technical reasons not all line items are exported - certain line items have a number range for sequence number (e.g. tax line items with sequence number range 25001 - 30000)	
	BeginDateTime	x	date time of position creation	
choice	Sale		XML-container: will be created in case of sale positions	see Sale
	Return		XML-container: will be created in case of return positions	see Return
	Rounding		rounding total; will be created only in case of existing rounding difference for the sum of - subtotal rounding - tender change rounding	
	SES:Rounding		XML-container: rounding line item; will be created only in case of existing rounding difference for - subtotal rounding - tender change rounding	see SES:Rounding
	Voids		XML-container: will be created only in case of void position	see Voids
	LoyaltyReward		XML-container: will be created only in case of non-financial bonus	see LoyaltyReward
	Tax		XML-container: will be created for each used tax group	see Tax
	Tender		XML-container: will be created for each used tender	see Tender
	SES:OperatorBypassApproval	x	XML-container: created in case of approval by another operator	see SES:OperatorBypassApproval
	SES:DirectVoidFlag	x	will be created in case of voided original receipt position value depends on cancellation type of voiding position possible values true: in case of direct void otherwise false	
	SES:NegativeAmountFlag	x	Rounding: will be created in case of existing rounding differences; true: in case of negative sign of the rounding amount otherwise false Tax: will be created if TaxableAmount <> 0 true: if TaxableAmount < 0 otherwise false	
	SES:KeyedOfflineCode	x	A code that indicates the online/offline state when the line item was completed. possible values: - OnLineReferenceltem - OffLine - Both (Online/Offline)	

	SES:ReceiptPositionAddonList	x	XML-container: contains all information about position addons	see SES:ReceiptPositionAddonList
	SES:LineItemBinaryDataList	x	XML-container: created in case of binary data attached to the line item	see LineItemBinaryDataList
	CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
	customExtension	x	Any elements can be added to the XML.	

Sale

Element will be created in case of sales transaction (no returns, no empties, no voids).

Attributes

Attribute	optional	Description	Comment
ItemType		Type of line item Possible values: • "Stock" • "Deposit" • "ItemCollection" • "SES:GiftCertificate" • "SES:Inpayment" • "SES:Outpayment" • "SES:PhoneCard" • "SES:RebateGiftCertificate" • "SES:CustomerOrder" • "SES:Pickup" • "SES:Downpayment" • "SES:DownpaymentClearing" • "SES:InvoicePayment" • "SES:Donation" • "SES:Other" • "Fee" • "SES:ComboMeal"	
customExtension	x	Any attributes can be added to the XML.	

XML-Elements

XML element	optional	Description	Comment	
POSIdentity	x		see POSIdentity	
ItemID	x	item ID attribute: • Name (optional)		
SpecialOrderNumber	x	will be created in case of existing • invoice number • customer order number		
MerchandiseHierarchy	x	will be created in case of assigned merchandise hierarchy group		
EPC	x	EPC will be used to identify individual items, e.g.: • stores EPC from RFID scanning		
Description	x	item description		
TaxIncludedInPriceFlag	x	true: in case of tax is included otherwise false		
RegularSalesUnitPrice	x	regular sales unit price of item (or package price) attribute: • Currency (not created) • ForeignAmount (not created) • Quantity (optional, only created in case of package prices) • UnitOfMeasureCode (not created)		
ExtendedAmount		discounted price		
ExtendedDiscountAmount	x	won't be created		
Quantity	x	quantity of item attributes: • Units (optional, will be used in case of length, area, space, weight and depth) • UnitOfMeasureCode (optional, will be used in case of unit of		

		measure)		
Associate	x	XML-container: will be created in case of assigned seller	see Associate	
RetailPriceModifier	x	XML-container: will be created in case of modifications of position price and proportionate receipt conditions	see RetailPriceModifier	
Tax	x	XML-container: line item related tax	see Tax	
SerialNumber	x	serial number or gift certificate number		
TransactionLink	x	XML-container: will be created in following cases: - order receipt - link from food order line item in food order or sales transaction to the food order line item in food order transaction (used for Hospitality) - order quantity change - link from new food order line item to partial voided food order line item (in case of belated partial void of food order line items)	see Sale.TransactionLink	
Foodservice	x	XML-container: will be created in case of line item related food service information exists	see Foodservice	
SES:ExtendedPositionAmount		discounted price of position		
SES:MerchandiseStructureItemFlag	x	true in case of generic article number otherwise false		
SES:ItemLink	x	will be created in case of empties links to item attribute: LinkType		
SES:ConcessionSupplierID	x	supplier ID of concessionaire		
SES:SpecialOfferNumber	x	will be created in case of special offer If Offline Rebooking (RetailTransaction.RetailTransactionTypeCode="RE") and if an entry exists in SaleReturnLineItemPrice for the considered receipt line item If an entry exists in SaleReturnLineItemPrice for the considered receipt line item with PriceTypeCode = '01' (promotion price)		
SES:AgeTypeCode	x	won't be created		
SES:AuthorizedForSalesFlag	x	false in case of blocking period was discontinued by operator		
SES:PriceOrigin	x	value "1" in case of price was revaluated		
SES:LoyaltyReward	x	XML-container: will be created only in case of position specific bonus points	see SES:LoyaltyReward	
SES:ExternalReceiptReferenceList	x	XML-container: will be created only in case of external receipt (e.g. scale receipt)	see SES:ExternalReceiptReferenceList	
SES:ItemNotFoundList	x	won't be created		
SES:InvoiceNumber	x	will be created only in case of bill payment on POS		
SES:ReasonCode	x	will be created only in case of paid in and paid out attribute: ReasonType - fix value: "InOutpayment"		
SES:GiftCertificateData	x	XML-container: additional data for gift certificate line items	see SES:GiftCertificateData	
SES:SalesOrderData	x	XML-container: additional data for sales order line items	see SES:SalesOrderData	
SES:PriceGroupID	x	The identifier of the price group the item belongs to in terms of split pricing.		
CST:XXCustom01 ... CST:XXCustom15	x	A separate element is created for every XXCustom field from 01 to 15.		
customExtension	x	Any elements can be added to the XML.		

POSIdentity

Attributes

Attribute	optional	Description	Comment
POSIDType		fix values:	

		• "RegistrationNumber" • "MasterData"	
--	--	--	--

XML-Elements

XML element	optional	Description	Comment
POSItemID		POSIDType="RegistrationNumber": on POS entered registration number POSIDType="MasterData" main POS item ID	
Qualifier	x	will be created only in case of a magazine/newspaper line item value: registration number from digit 14 to end	

Associate

Attributes

Attribute	optional	Description	Comment
CommissionGivenFlag	x	won't be created	

XML-Elements

	XML element	optional	Description	Comment
	AssociateID		seller ID attribute: • OperatorName (optional) • WorkerID (optional, won't be created)	

RetailPriceModifier

XML-elements

XML element	optional	Description	Comment
SequenceNumber		continuous number over all price modifications of one position starts with "1"	
Amount		absolut amount of price modification attribute: • Action ○ "Add" ○ "Substract"	
PromotionID	x	will be created in case of existing position condition value: description of positon condition	
PriceDerivationRule	x	XML-container: price derivation rule data; will be created only in case of price condition	see PriceDerivationRule
ReasonCode		reason of corresponding price modification default: '0000'	
SES:RebateMethod		type code in case of position condition property value in case of price change otherwise "0000"	
SES:RebateID		external promotion ID in case of position condition property value in case of price change otherwise "0"	
SES:Percent	x	discount percentage (only in case of promotions that have a percentage rule)	
SES:ExternalOfferID	x	identifier of the external offer in case of position condition property value in case of price change	
SES:AdditionalPriceTypeCode	x	price type code of the additional price which got applied in case of customer specific prices	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

PriceDerivationRule

Attributes

Attribute	optional	Description	Comment
-----------	----------	-------------	---------

customExtension	x	Any attributes can be added to the XML.	
-----------------	---	---	--

XML-elements

XML element	optional	Description	Comment
PriceDerivationRuleID		first 40 digits of price derivation rule ID	
Eligibility	x	XML-container: will be created only in case of existing coupon number	see Eligibility
Amount		attribute: Action	
SES:Origin	x		
SES:AppliedQuantity	x		
SES:RuleDescription	x	will be created only in case of existing rule description	
CST:XXCustom01 ... CST:XXCustom15	x	A separate element is created for every XXCustom field from 01 to 15.	
customExtension	x	Any elements can be added to the XML.	

Eligibility

XML element	optional	Description	Comment
ReferenceID	x	coupon reference number attribute: Type (fix value: "StoreCoupon")	
SES:CouponSerialNumber	x	won't be created	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

Tax

Attributes

Attribute	optional	Description	Comment
TaxType	x	fix value: "Common"	
TaxSubType	x	"ZeroRated" in case of rate of tax = 0 otherwise "Standard"	
TypeCode	x	possible values: "Refund" "Sale"	
customExtension	x	Any attributes can be added to the XML.	

XML-elements

XML element	optional	Description	Comment
TaxAuthority	x	ID of the tax authority	
TaxableAmount	x	taxable amount without sign	
Amount	x	tax amount In case of tax on transaction level, the tax amount on sale/return line item level is calculated by the export process.	
Percent	x	tax percentage	
TaxExemption	x	XML-container: created in case of a tax exemption	see TaxExemption
TaxOverride	x	XML-container: created in case of a tax override	see TaxOverride
TaxGroupID	x	tax group ID	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

TaxExemption

Attributes

Attribute	optional	Description	Comment
customExtension	x	Any attributes can be added to the XML.	

XML-elements

XML element	optional	Description	Comment
CustomerExemptionID		tax certificate ID	
ExemptTaxAmount		fix value = 0 (not supported)	
ReasonCode	x	reason code for the tax exemption	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

TaxOverride

Attributes

Attribute	optional	Description	Comment
customExtension	x	Any attributes can be added to the XML.	

XML-elements

XML element	optional	Description	Comment
OriginalPercent		original tax percentage	
OriginalTaxAmount		original tax amount	
NewTaxPercent		new tax percentage	
NewTaxAmount		new tax amount	
ReasonCode	x	reason code for the tax override	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

TransactionLink

Attributes

Attribute	optional	Description	Comment
ReasonCode	x	Possible values: - SES:Order - SES:OrderQuantityChange	

XML-Elements

XML element	optional	Description	Comment
RetailStoreID		retail store number of the original transaction	
WorkstationID		workstation/POS number of the original transaction	
SequenceNumber		receipt number of the original transaction	
LineItemSequenceNumber	x	line item sequence number of the original line item	
BusinessDayDate		date of business day of the original transaction	
BeginDateTime		begin date and time of the original transaction	
EndDateTime	x	end date and time of the original transaction	
SES:InternalSequenceNumber	x	won't be created	
SES:ReceiptDateTime	x	receipt date and time of the original transaction	
SES:InternalTransactionID		universally unique identifier (UUID) of the original transaction	
customExtension	x	Any elements can be added to the XML.	

Foodservice

Attributes

Attribute	optional	Description	Comment
DestinationType	x	won't be created	
SalesMetrics	x	won't be created	
ProcessMode	x	won't be created	

XML-elements

XML element	optional	Description	Comment
TableSection	x	won't be created	
TableID	x	identifier of the table	
SeatID	x	won't be created	
PartyName	x	won't be created	
PartySize	x	won't be created	
Tray	x	won't be created	
CheckInTime	x	won't be created	
CheckOutTime	x	won't be created	
OrderTime	x	won't be created	
DelayDateTime	x	won't be created	
CookStartTime	x	won't be created	
CookEndTime	x	won't be created	
ServeTime	x	won't be created	
Gratuity	x	won't be created Attribute:	

		• Currency • ForeignAmount	
TableCharge	x	won't be created Attribute: • Currency • ForeignAmount	

SES:ExternalReceiptReferenceList

XML-elements (in sub element ExternalReceiptReference)

XML element	optional	Description	Comment
SES:ItemOrigin	x	possible values: • 06 (offline rebooking of suspended position) • 05 (empties) • 04 (scale) • otherwise: type code of line item association (e.g. SUSP - suspend, RETU - return, LIRE - line item repetition, DEPO - deposit)	
SES:ReceiptReferenceNumber		references to external document (invoice; customer order etc.)	
SES:ExternalTransactionOfflineRedemptionFlag	x		
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

SES:GiftCertificateData

will be created only in case of gift certificate line item

XML-Elements

Attribute	optional	Description	Comment
SES:GiftCertificateType	x	possible values: • SES:PaperGiftCertificate • SES:ElectronicGiftCertificate	
CST:XXCustom01 ... CST:XXCustom15	x	A separate element is created for every XXCustom field from 01 to 15.	
customExtension	x	Any elements can be added to the XML.	

SES:SalesOrderData

XML-Elements

Attribute	optional	Description	Comment
SES:SpecialOrderSystem	x	possible values: • ERP • Store	
SES:SpecialOrderType	x	possible values: • Reservation • SalesSelection • Pickup • Delivery • ImmediatePickup • SES:Layaway	
SES:SpecialOrderPositionNumber	x	will be created only in case of external position numbers of customer order	
CST:XXCustom01 ... CST:XXCustom15	x	A separate element is created for every XXCustom field from 01 to 15.	
customExtension	x	Any elements can be added to the XML.	

Return

Attributes

- See Sale.

XML-Elements

- See Sale.

The only deviations compared to Sale are the following:

XML element	optional	Description	Comment
TransactionLink	x	XML-container: reference to the original sales transaction and line item	see TransactionLink
SES:ReasonCode	x	Return reason code (default: "0000"). Attribute: • ReasonType - fix value: ○ "Return"	

TransactionLink

Attributes

Attribute	optional	Description	Comment
ReasonCode	x	fix value "Return"	

XML-elements

XML element	optional	Description	Comment
RetailStoreID		retail store number of the original transaction	
WorkstationID		workstation/POS number of the original transaction	
SequenceNumber		receipt number of the original transaction	
LineItemSequenceNumber	x	line item sequence number of the original line item	
BusinessDayDate		date of business day of the original transaction	
BeginDateTime		begin date and time of the original transaction	
EndDateTime	x	won't be created	
SES:InternalSequenceNumber	x	won't be created	
SES:ReceiptDateTime	x	won't be created	
SES:InternalTransactionID		universally unique identifier (UUID) of the original transaction	
customExtension	x	Any elements can be added to the XML.	

Rounding

Attributes

Attribute	optional	Description	Comment
Currency	x		won't be created
ForeignAmount	x		won't be created

SES:Rounding

XML-Elements

XML element	optional	Description	Comment
SES:RoundingTypeCode		type of the rounding. Possible values: • 00 (subtotal rounding) • 01 (tender change rounding)	
SES:Amount		rounding amount	
SES:RoundingDirection		rounding direction. Possible values: • Up • Down	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

Voids

XML-Elements

XML element	optional	Description	Comment
ItemLink			see ItemLink

ItemLink

Attributes

Attribute	optional	Description	Comment
ReasonCode		fix value: "Voided"	

XML-Elements

XML element	optional	Description	Comment
SequenceNumber		the same content as in Transaction.SequenceNumber	
LineItemSequenceNumber		LineItem SequenceNumber of the voided original position	
SES:VoidReasonCode		Void reason code default: "0000" attributes: - ReasonType "Void" "SES:BelatedVoid" "SES:BelatedInternalVoid" - Description	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

LoyaltyReward

XML-Elements

	XML element	optional	Description	Comment
	PromotionID	x	description of receipt condition	
	ReasonCode		reason code according db entry default: "0000"	
choice	PointsAwarded	x	will be created only in case of existing bonus points	
	GiftCertificate	x	XML-container: created in case of a discount as gift certificate	see GiftCertificate
	SES:Voucher	x	XML-container: created in case of a discount as coupon	see SES:Voucher
	SequenceNumber		will be used only in case of position specific bonus points. Continuous number over all LoyaltyReward elements of one line item, starting with "1".	
	SES:PriceDerivationRule	x	XML-container: price derivation rule data	see SES:PriceDerivationRule
	SES:CustomerCardNumber	x	won't be created	
	SES:IncentiveTurnover	x	won't be created	
	SES:AliasType	x	won't be created	
	SES:RebateMethod		possible values: - type code of the position condition - otherwise "0000"	
	SES:RebateID		possible values: "0" in case of non loyalty trigger - external promotion ID (first 40 digits without any prefix)	
	SES:ExternalOfferID	x	identifier of the external offer in case of loyalty trigger	
	CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
	customExtension	x	Any elements can be added to the	

			XML.	
--	--	--	------	--

GiftCertificate

Attributes

Attribute	optional	Description	Comment
MediaType		possible values: 'SES:ElectronicGiftCertificate' 'SES:PaperGiftCertificate'	

XML-Elements

XML element	optional	Description	Comment
SerialNumber	x	gift card number	
FaceValue		gift card value	
GiftCertificateID		empty string	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

SES:Voucher

XML-Elements

XML element	optional	Description	Comment
SES:VoucherID		coupon number	
SES:Amount		coupon amount	
SES:CouponSerial	x	XML-container: will be created only in case of existing coupon serial	see SES_CouponSerial
customExtension	x	Any elements can be added to the XML.	

SES:CouponSerial

XML element	optional	Description	Comment
SES:CouponSerialNumber		The coupon serial number.	
SES:BookingSuccessfulTypeCode	x	Determines whether the coupon redemption was successfully posted to the Couponing Service. - null - in case that no Couponing Service is used 00 - ok 01 - error	
SES:BookingTransactionUUID	x	The couponing service transaction ID.	
CST:XXCustom01 ... CST:XXCustom30	x	A separate element is created for every XXCustom field from 01 to 30.	
customExtension	x	Any elements can be added to the XML.	

SES:PriceDerivationRule

Attributes

Attribute	optional	Description	Comment
customExtension	x	Any attributes can be added to the XML.	

XML-Elements

XML element	optional	Description	Comment
PriceDerivationRuleID		first 40 digits of price derivation rule ID	
Eligibility	x	XML-container: will be created only in case of existing coupon number	see Eligibility
Amount		attribute: - Action possible values: "Substract" in case of negative amount "Add" in case of positive amount	
SES:Origin	x	"ORIGIN" in case of loyalty trigger	
SES:AppliedQuantity	x	will be created only in case of applied quantity	
SES:RuleDescription	x	will be created in case of existing rule description	

CST:XXCustom01 ... CST:XXCustom15	x	A separate element is created for every XXCustom field from 01 to 15.	
customExtension	x	Any elements can be added to the XML.	

Eligibility

XML element	optional	Description	Comment
ReferenceID	x	coupon reference number attribute: Type (fix value: "StoreCoupon")	
SES:CouponSerialNumber	x	won't be created	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

Tax

Attributes

Attribute	optional	Description	Comment
TaxType	x	fix value: "Common"	
TaxSubType	x	"ZeroRated" in case of rate of tax = 0 otherwise "Standard"	
TypeCode	x	possible values: "Refund" "Sale"	
customExtension	x	Any attributes can be added to the XML.	

XML-Elements

XML element	optional	Description	Comment
TaxAuthority	x	ID of the tax authority	
TaxableAmount	x	taxable amount without sign	
Amount	x	tax amount	
Percent	x	tax percent	
TaxExemption	x	XML-container: created in case of a tax exemption	see TaxExemption
TaxOverride	x	not used for the tax on transaction level	
TaxGroupID	x	tax group ID	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

TaxExemption

Attributes

Attribute	optional	Description	Comment
customExtension	x	Any attributes can be added to the XML.	

XML-Elements

XML element	optional	Description	Comment
CustomerExemptionID		tax certificate ID	
ExemptTaxAmount		fix value = 0 (not supported)	
ReasonCode	x	reason code for the tax exemption	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

Tender

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	
TypeCode		TypeCode possible values: "Refund" "Sale"	
TenderDescription	x	Tender description	

customExtension	x	Any attributes can be added to the XML.	
-----------------	---	---	--

XML-elements

	XML element	optional	Description	Comment
	TenderID	x	Tender ID for main currency or foreign currency	
	Amount		amount in main currency; in case of foreign currency following attributes are used: - Currency (optional) - ForeignAmount (optional)	
	TenderChange	x	will be created only within RetailTransaction	
	Cashback	x	will be created only within RetailTransaction amount in main currency; in case of foreign currency following attributes are used: - Currency (optional) - ForeignAmount (optional)	
	Authorization	x	XML-container: will be created for tenders with external authorization	see Authorization
	Tip	x	The amount being collected as tip for serving staff in main currency; in case of foreign currency following attributes are used - Currency (optional) - ForeignAmount (optional)	
	ForeignCurrency	x	XML-container: will be created only in case of foreign currency	see ForeignCurrency
choice	Check	x	XML-container: will be created only in usage of check	see Check
	CreditDebit	x	XML-container: will be created only in usage of credit debit	see CreditDebit
	Coupon	x	XML-container: will be created only in usage of coupon	see Coupon
	Voucher	x	XML-container: will be created only in usage of voucher	see Voucher
	SES:LoyaltyRedemption	x	XML-container: will be created only in usage of loyalty redemption	see SES:LoyaltyRedemption
	CST:XXCustom01 ... CST:XXCustom15	x	A separate element is created for every XXCustom field from 01 to 15.	
	customExtension	x	Any elements can be added to the XML.	

TenderChange

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	
customExtension	x	Any attributes can be added to the XML.	

XML-elements

XML element	optional	Description	Comment
TenderID	x	Tender ID for main currency or foreign currency	
Amount		amount in main currency in case of foreign currency following attributes are used: - Currency (optional) - ForeignAmount (optional)	

Authorization

Attributes

Attribute	optional	Description	Comment
HostAuthorized	x	boolean value depends on code of authoization code: e.g. - ,1' = EDD authorization = offline debit memo - ,2' =	

		ODD online or POG (POS without payment guarantee) = online debit memo (if applicable, credit card online for special terminal types, e.g. REA) - ,8' = Credit card online payment - NULL = The terminal is not connected to the cash register. • true (3, 8,10 or 11) • false (with all other codes of authorization type)	
ElectronicSignature	x	boolean value depends on code of authoization code: e.g. - ,1' = EDD authorization = offline debit memo - ,2' = ODD online or POG (POS without payment guarantee) = online debit memo (if applicable, credit card online for special terminal types, e.g. REA) - ,8' = Credit card online payment - NULL = The terminal is not connected to the cash register. • true (3, 10 or 11) • false (with all other codes of authorization type)	
ForceOnline	x	boolean value depends on code of transaction type e.g. - ,0' = offline - ,1' = online • true (online) • false (offline)	
customExtension	x	Any attributes can be added to the XML.	

XML-Elements

XML element	optional	Description	Comment
RequestedAmount	x	absolut value of transaction in case of foreign currency following attributes are used: Currency (optional) ForeignAmount (optional)	
AuthorizationCode		code of authorization code Payment Terminal Type Codes - 01180100027	
ReferenceNumber	x	number of transaction	
AuthorizationDateTime	x	timestamp of authorization	
AuthorizingTermID	x	ID of used terminal	
SES:ActivationSequenceNumber	x	activation sequence number	
SES:TransactionReferenceNumber	x	Transaction Reference Number used for transaction types 'Purchase Reservation' and 'Reservation Adjustment'	
SES:TransactionType		transaction type possible values: • credit • debit	
SES:TerminalTenderDescription	x	terminal tender description	
ApplicationID	x	application identifier	
SES:EncryptedPAN	x	Application PAN (coded)	
SES:TransactionCurrencyCode	x	transaction currency	
SES:TerminalTransactionToken	x	unique number assigned by the payment processor when an EFT transaction is processed	
SES:ApprovalCode	x	terminal authorization number	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

ForeignCurrency

XML elements

XML element	optional	Description	Comment
CurrencyCode	x	code of foreign currency	
OriginalFaceAmount		origin amount in foreign currency	

ExchangeRate	x	exchange rate, rounded to 5 decimals	
--------------	---	--------------------------------------	--

Check

Attributes

Attribute	optional	Description	Comment
customExtension	x	Any attributes can be added to the XML.	

XML elements

XML element	optional	Description	Comment
BankID	x	bank ID	
CheckNumber	x	cheque number	will not be exported anymore (SES:CheckNumber have to be used instead)
AccountNumber	x	account number	
CheckCardNumber	x	bank card number	
FullMICR	x	full string of characters read from MICR strip	
SES:BankIdentifierCode	x	bank identifier code (SWIFT code)	
SES:InternationalBankAccountNumber	x	international bank account number	
SES:CheckNumber	x	cheque number	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

CreditDebit

Attributes

Attribute	optional	Description	Comment
customExtension	x	Any attributes can be added to the XML.	

XML-elements

XML element	optional	Description	Comment
IssuerIdentificationNumber	x	bank ID	
PrimaryAccountNumber		account number bank card number (default "0000")	
IssueSequence	x	card suffix	
ExpirationDate	x	expiration date of card	
ReconciliationCode	x	code of transaction result Payment Terminal Type Codes - 01180100027	
StartDate	x	date of transaction start	
SES:TraceNumber	x	trace number	
SES:InternationalBankAccountNumber	x	IBAN - International Bank Account Number for SEPA Direct Debit (ELV)	
SES:BankIdentifierCode	x	BIC - Bank Identifier Code. Also known as SWIFT Code for SEPA Direct Debit (ELV).	
SES:CreditorID	x	Creditor ID for SEPA Direct Debit (ELV)	
SES:MandateID	x	Mandate ID for SEPA Direct Debit (ELV)	
SES:PrenotificationText	x	Pre-notification text for SEPA Direct Debit (ELV)	
customExtension	x	Any elements can be added to the XML.	

Coupon

Attributes

Attribute	optional	Description	Comment
customExtension	x	Any attributes can be added to the XML.	

XML-elements

XML element	optional	Description	Comment
Quantity		fix value: 1	
PrimaryLabel		coupon number	
ManufacturerID	x	manufacturer ID that is funding the offer in case of manufacturer coupons	
PromotionCode	x	offer number (promotion code) in case of manufacturer coupons	
SES:CouponSingleAmount		single amount of coupon	

SES:TaxPercent		rate of taxation	
SES:Origin		flag internal/external coupon	
SES:ReferenceltemList		XML-container: will be created for each linked item	see SES:ReferenceltemList
SES:CouponSerialNumber	x	won't be created	
customExtension	x	Any elements can be added to the XML.	

SES:ReferenceltemList

XML-elements

XML element	optional	Description	Comment
ItemID		EAN of discounted item	
ItemQuantity		quantity of discounted item	
ItemRebateShare		rebate share of item	
ItemLink		link to positionnumber of item in POSLog attribute: LinkType fix value: "Coupon"	
customExtension	x	Any elements can be added to the XML.	

Voucher

Attributes

Attribute	optional	Description	Comment
TypeCode		possible values: SES:ElectronicGiftCertificate SES:PaperGiftCertificate	

XML-elements

XML element	optional	Description	Comment
SerialNumber		EAN of voucher	

SES:LoyaltyRedemption

Attributes

Attribute	optional	Description	Comment
customExtension	x	Any attributes can be added to the XML.	

XML-elements

XML element	optional	Description	Comment
PointsRedeemed		redeemed bonus points	
TransactionID		ID of bonus point redeem transaction	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

SES:OperatorBypassApproval

Attributes

Attribute	optional	Description	Comment
ApprovalTypeCode		shows, how authorization was triggered fix value: "CODE" (operator number)	

XML-Elements

XML element	optional	Description	Comment
ApprovalCode	x	won't be created	
ApproverID	x	ID of authorizing operator attribute: - WorkerID (optional) - ApproverName (optional)	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

SES:ReceiptPositionAddonList

XML-Elements (in sub element SES:Addon)

XML element	optional	Description	Comment
AddonPos	x	addon position	
Key		addon name	
Value		addon text	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

SES:LineItemBinaryDataList

XML-Elements

XML element	optional	Description	Comment
BinaryData			see BinaryData

4.3.6.2 BinaryData

XML-Elements

XML element	optional	Description	Comment
Name		The name of the binary data entry.	
Content		The binary object (Base64 encoded).	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.6.3 Customer

Element will be created only in case of customer assignment.

Attributes

Attribute	optional	Description	Comment
customExtension	x	Any attributes can be added to the XML.	

XML-elements

XML element	optional	Description	Comment
CustomerID	x	will be created in case of existing customer id	
CustomerName	x	XML-container: customer name	see CustomerName
Address	x	XML-container: customer address	see Address
Telephone	x	XML-container: customer telephone number	see Telephone
EMail	x	XML-container: customer email address	see Email
Age	x	won't be created	
Birthdate	x	birthdate	
Gender	x	gender	
SES:CustomerType		possible values: "EM" in case of employees - adress type	
SES:CustomerTypeDescription	x	adress type description	
SES:CustomerIdentifier	x	will be created only in case of existing adress type	
SES:EntryMethod	x	won't be created in case of employee customers for all other customers following values are possible: "Scanned" "SES:Searched" "Keyed" depends on registration source	
SES:CustomerLockingTypeCode	x	customer locking type code	
SES:CustomerTaxID	x	customer tax ID	
SES:CustomerGenericFlag	x	customer generic flag	
SES:CustomerBusinessNumber	x	customer business number	
SES:CustomerLocationNumber	x	customer location number	

SES:CustomerRequisitionRequired	x	customer requisition required flag	
SES:CustomerBuyerRequiredFlag	x	customer buyer required flag	
SES:CustomerBuyerName	x	customer buyer name	
SES:CustomerContactRequiredFlag	x	customer contact required flag	
SES:CustomerContactPersonName	x	customer contact person name	
SES:CustomerGroup	x	will be created in case of existing customer group attributes: - CST:XXCustom01 ... - CST:XXCustom05 (optional) - customExtension (optional)	
SES:CustomerGroupDefaultBonusPointsCount	x	customer group default bonus points count	
SES:ParentCustomerID	x	Number of the customer to which this buyer / contact person belongs.	
SES:ParentCustomerName1	x	First name line of the customer to which this buyer / contact person belongs.	
SES:ParentCustomerName2	x	Second name line of the customer to which this buyer / contact person belongs.	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

CustomerName

XML-elements

XML element	optional	Description	Comment
Salutation	x	salutation of customer	
Name	x	customer name attribute: - Location (optional) possible values: "First" "Last"	
FullName		string consisting of max. both customer name entries or of organization name	

Address

XML-elements

XML element	optional	Description	Comment
AddressLine		attribute: - TypeCode (optional) possible values: "Street" "SES:District" "SES:AddressLine1" "SES:AddressLine2"	
City	x	city	
PostalCode	x	postal code	
Country	x	country	
Name	x	name of organisation	
State	x	won't be created	

Telephone

Attributes

Attribute	optional	Description	Comment
TypeCode	x	possible values: "Work" "Mobile" "Home" "WorkFax"	

XML-Elements

XML element	optional	Description	Comment
FullTelephoneNumber		telephone number	

Email

XML-Elements

XML element	optional	Description	Comment
EEmailAddress		email adress	

4.3.6.4 TransactionLink

Attributes

Attribute	optional	Description	Comment
ReasonCode	x	Possible values: • Voided • SES:Invoice • SES:OfflineRebooking • LayAway • SES:RetrievedSuspend • SES:Replace	

XML-Elements

XML element	optional	Description	Comment
RetailStoreID		retail store number of the original transaction	
WorkstationID		workstation/POS number of the original transaction	
SequenceNumber		receipt number of the original transaction	
LineItemSequenceNumber	x	won't be created	
BusinessDayDate		date of business day of the original transaction	
BeginDateTime		begin date and time of the original transaction	
EndDateTime	x	end date and time of the original transaction	
SES:InternalSequenceNumber	x	won't be created	
SES:ReceiptDateTime	x	receipt date and time of the original transaction	
SES:InternalTransactionID		universally unique identifier (UUID) of the original transaction	
customExtension	x	Any elements can be added to the XML.	

4.3.6.5 SES:CouponSummary

XML-Elements

SES:CouponNumber		The coupon number	
SES:InputCount		Count of registered coupons	
SES:AppliedCount	x	Number of used coupons	
SES:CustomerID	x	Identifier of the customer	
SES:CustomerAddressTypeCode	x	The customer type code	
SES:CouponSerialSummary	x	XML-container: will be created for each coupon serial	see SES:CouponSerialSummary
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	
XML element	optional	Description	Comment

SES:CouponSerialSummary

XML-Elements

XML element	optional	Description	Comment
SES:CouponSerialNumber		The coupon serial number.	
SES:BookingSuccessfulTypeCode	x	Determines whether the coupon redemption was successfully posted to the Couponing Service. • null - in case that no Couponing Service is used • 00 - ok • 01 - error	

SES:BookingTransactionUUID	x	The couponing service transaction ID	
SES:UsedFlag	x	Defines if the coupon serial triggered a promotion price derivation rule.	
CST:XXCustom01 ... CST:XXCustom30	x	A separate element is created for every XXCustom field from 01 to 30.	
customExtension	x	Any elements can be added to the XML.	

4.3.7 TenderControlTransaction

XML-elements

	XML element	optional	Description	Comment
choice	SES:TenderLoan		XML-container: information about change transaction (tender transfer from safe to drawer)	see SES:TenderLoan
	Deposit		XML-container: information about safe bag or bank deposit transaction (tender transfer from safe to bank)	see Deposit
	TillSettle		XML-container: information about drawer settlement transaction (during accounting) or drawer cash check transaction	see TillSettle
	SafeDrop		XML-container: information about safe drop transaction (cash transfer from bank to safe)	see SafeDrop
	SES:TenderPickup		XML-container: information about tender pickup transaction (tender transfer from drawer to safe)	see SES:TenderPickup
	SES:PaidIn		XML-container: information about paid in transaction (tender deposit into drawer or into safe) or safe opening balance transaction (safe amount at the beginning of the accounting period) or safe correction (pay-in) transaction	see SES:PaidIn
	SES:PaidOut		XML-container: information about paid out transaction (tender disbursement from drawer or from safe) or safe correction (pay-out) transaction	see SES:PaidOut
	SES:TenderInterchange		Will not be generated. Tender exchange will be exported as RetailTransaction.	
	SES:TenderLoanCarriedForward		XML-container: information about "tender loan/change carried forward" transaction (tender amount in the drawer at the beginning of an accounting period)	see SES:TenderLoanCarriedForward
	SES:SafeSettle		XML-container: information about safe settlement transaction (safe accounting)	see SES:SafeSettle
	SES:TransactionLink	x	XML-container: reference to another transaction; will be created in following cases: voiding receipt - link to original receipt	see TransactionLink
	SES:ReceiptPositionAddonList	x	XML-container: contains all information about position addons	see SES:ReceiptPositionAddonList
	SES:AccountedOperatorID	x	OperatorID of the operator, for which exists a one-to-one assignment of operator to drawer Attribute: Name (optional)	
	CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
	customExtension	x	Any elements can be added to the XML.	

4.3.7.1 SES:TenderLoan

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	
TenderDescription	x	Tender description	

XML-Elements

XML element	optional	Description	Comment
SES:Totals		XML-container: sum of tenders of tendergroup cash in main currency	see SES:Totals
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

SES:Totals

XML-Elements

XML element	optional	Description	Comment
Amount		amount = 0 in case of no tender line item in the transaction. in case of foreign currency following attributes are used: - Currency (optional) - ForeignAmount (optional)	
Reason	x	will be created in case of change correction optional attributes: - Description - Name	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.7.2 Deposit

XML-Elements

XML element	optional	Description	Comment
Bank		not used (empty string)	
Account		not used (empty string)	
BagID		In case of safe bag: safe bag number In case of bank deposit: not used (empty string)	
Amount		amount in main currency in case of foreigncurrency following attributes are used: - Currency (optional) - ForeignAmount (optional)	
Depositor		employee who transferred safe bag to bank following attribut is used: WorkerID	
DepositDetail		XML-container: contains totals of tenders	see DepositDetail
SES:DepositForeignCurrency	x	XML-container: will be created if there are tenders used in foreign currency	see SES:DepositForeignCurrency
SES:SafebagStatus	x	1 = created safe bag 2 = deleted safe bag 3 = safe bag was picked up 4 = created safe bag caused by change order	
SES:SafebagDocumentNumber	x	will be created if safe bag document number exist	
SES:PickupSafebagNumber	x	will be created in case of SES:SafebagStatus = 3	
SES:SafebagTypeCode	x	1 = common safe bag 3 = safe bag caused by change order	
SES:StatusTimestamp	x	timestamp of the safe bag status change	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

DepositDetail

XML-elements

XML element	optional	Description	Comment
TenderTotal		amount of tender of picked up safe bag in main currency includes attribut TenderType	
Reason		fix value "0000"	

SES:DepositForeignCurrency

XML-elements

XML element	optional	Description	Comment
TenderTotal		amount of tender of picked up safe bag in main currency includes attribut - TenderType - Currency - ForeignAmount (amount in foreign currency)	

4.3.7.3 TillSettle

XML-elements

XML element	optional	Description	Comment
TenderSummary		XML-container: will be created for each tender in the transaction	see TenderSummary
SES:TransactionCategoryCode	x	Indicator of the category of the drawer counting transaction: "CHECK" = cash check transaction "SETTLE" = settlement transaction (during accounting)	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

TenderSummary

XML-elements

XML element	optional	Description	Comment
Over		XML-container: will be created if count difference >=0	see Over
Short		XML-container: will be created if count difference <0	see Short
SES:Nominal	x	XML-container: closing/target balance of the drawer	see SES:Nominal
SES:Ending	x	XML-container: counted/actual balance of the drawer	see SES:Ending
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

Over

XML-Elements

XML element	optional	Description	Comment
TenderType		Tender type	
Amount		positive amount of the drawer count difference, in main currency. In case of foreign currency following attributes are used additionally: - Currency (optional) - ForeignAmount (optional)	
Count	x	will be created, if there is count difference >=0	

Short

XML-Elements

XML element	optional	Description	Comment
TenderType		Tender type	
Amount		negative amount of the drawer count difference, in main currency. In case of foreign currency following attributes are used additionally: • Currency (optional) • ForeignAmount (optional)	
Count	x	will be created, if there is count difference <0	

SES:Nominal

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	
TypeCode		TypeCode to distinguish between positive and negative amount possible values: • "Refund" - negative • "Sale" - positive	

XML-elements

XML element	optional	Description	Comment
Amount		closing/target amount of the drawer, in main currency. In case of foreign currency following attributes are used additionally: • Currency (optional) • ForeignAmount (optional)	
Count	x	created in case of Count <> 0	

SES:Ending

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	
TypeCode		TypeCode to distinguish between positive and negative amount possible values: • "Refund" - negative • "Sale" - positive	

XML-elements

XML element	optional	Description	Comment
Amount		counted/actual amount of the drawer, in main currency. In case of foreign currency following attributes are used additionally: • Currency (optional) • ForeignAmount (optional)	
Count	x	created in case of Count <> 0	

4.3.7.4 SafeDrop

XML-Elements

XML element	optional	Description	Comment
DropAmount		amount of cash receipt	
EnvelopeID		empty string because of mandatory field	
DropNumber		empty string because of mandatory field	
Tender	x	won't be created	

4.3.7.5 SES:TenderPickup

XML-Elements

XML element	optional	Description	Comment
SES:TenderAmount		amount of tender in main currency attributes: - TenderType - TypeCode (optional) will be created only in case of "Refund" - Currency (optional) will be created only in case of foreign currency - ForeignAmount (optional) will be created only in case of foreign currency - TenderDescription (option) will be created only in case of tender description - CST:XXCustom01 ... CST:XXCustom05 (optional) - customExtension (optional)	
SES:TotalAmount		sum of all tenders attributes: TypeCode (optional) will be created only in case of "Refund"	
SES:Reason	x	won't be created	
SES:EnvelopeID	x	The identifier of the Envelope that was used for this Pickup.	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.7.6 SES:PaidIn

XML-Elements

XML element	optional	Description	Comment
SES:Amount		amount of paid in	
SES:Reason		entered reason for paid in in case of no entry: default="0000"	
SES:Tender	x	XML-container: will be created for each tender position of paid in transaction	see Tender
SES:TransactionCategoryCode	x	Indicator of the category of the PaidIn transaction: "PAYIN" = paid in transaction (tender deposit into drawer or into safe) "OPEN" = safe opening balance transaction "CORR" = safe correction transaction	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.7.7 SES:PaidOut

XML-Elements

XML element	optional	Description	Comment
Amount		amount of paid out	
Reason		entered reason for paid out in case of no entry: default="0000"	
Tender	x	XML-container: will be created for each tender position of paid out transaction	see Tender
SES:TransactionCategoryCode	x	Indicator of the category of the PaidOut transaction: "PAYOUT" = paid out transaction (tender disbursement from drawer or from safe) "CORR" = safe correction transaction	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.7.8 SES:TenderInterchange

Will not be generated. Tender exchange will be exported as RetailTransaction.

4.3.7.9 SES:TenderLoanCarriedForward

XML-Elements

XML element	optional	Description	Comment
Amount		carryforward of tender loan	ending balance of last accounting period will be the opening balance of next accounting period
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.7.10 SES:SafeSettle

XML-elements

XML element	optional	Description	Comment
TenderSummary		XML-container: will be created for each tender in the safe accounting transaction	see TenderSummary
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

TenderSummary

XML-elements

XML element	optional	Description	Comment
Over		XML-container: will be created if count difference >=0	see Over
Short		XML-container: will be created if count difference <0	see Short
SES:Nominal	x	XML-container: closing/target balance of the safe	see SES:Nominal
SES:Ending	x	XML-container: counted/actual balance of the safe	see SES:Ending
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

Over

XML-Elements

XML element	optional	Description	Comment
TenderType		Tender type	
Amount		positive amount of safe count difference, in main currency. In case of foreign currency following attributes are used additionally: - Currency (optional) - ForeignAmount (optional)	
Count	x	will be created, if there is count difference >=0	

Short

XML-Elements

XML element	optional	Description	Comment
TenderType		Tender type	
Amount		negative amount of safe count difference, in main currency. In case of foreign currency following attributes are used additionally: - Currency (optional) - ForeignAmount (optional)	
Count	x	will be created, if there is count difference <0	

SES:Nominal

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	
TypeCode		TypeCode to distinguish between positive and negative amount possible values: "Refund" - negative "Sale" - positive	

XML-elements

XML element	optional	Description	Comment
Amount		closing/target amount of the safe, in main currency. In case of foreign currency following attributes are used additionally: - Currency (optional) - ForeignAmount (optional)	
Count	x	created in case of Count <> 0	

SES:Ending

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	
TypeCode		TypeCode to distinguish between positive and negative amount possible values: "Refund" - negative "Sale" - positive	

XML-elements

XML element	optional	Description	Comment
Amount		counted/actual amount of the safe, in main currency. In case of foreign currency following attributes are used additionally: - Currency (optional) - ForeignAmount (optional)	
Count	x	created in case of Count <> 0	

4.3.8 ControlTransaction

XML elements

	XML element	optional	Description	Comment
choice	ReasonCode	x	reason code in case of existing reason	
	BusinessEOD		XML-container: created in case of an EOD transaction	see BusinessEOD
	TillEOD		XML-container: total/summary values (drawer related)	see TillEOD
	POSSStartup		won't be created	
	POSSShutdown		won't be created	
	NoSale		time stamp for NoSale	
	OperatorLock		won't be created	
	OperatorUnLock		won't be created	
	OperatorSignOn		XML-container: operator log-in	see OperatorSignOn/Off
	OperatorSignOff		XML-container: operator log-out	see OperatorSignOn/Off
	SES:CashierStatistics		XML-container: cashier statistics values includes statistics about accounting period of drawer	see SES:CashierStatistics
	SES:StoreEODSummary		XML-container: total/summary values (store related) includes sum values about accounting period of store	see SES:StoreEODSummary

	SES:StartTraining		won't be created	
	SES:EndTraining		won't be created	
	SES:AwardOrder		won't be created	
	SES:LoyaltyPointsInformation		won't be created	
	SES:TaxRefund		XML-container: tax refund issue values	see SES:TaxRefund
	SES:OtherTransactionType		created for all transaction types with which won't be exported in other tag of POSLog. So its sure that all transactions will be exported, without any leak.	
	SES:ForcedSignOffFlag	x	Flag, created in case of OperatorSignOff "true", if forced logout "false", if logout	
	SES:ForcedSignOffWorkstationID	x	Identifier of the workstation, which is forced to log out (created only in case of forced logout).	
	SES:AccountedOperatorID	x	OperatorID of the operator, for which exists a one-to-one assignment of operator to drawer Attribute: Name (optional)	
	SES:TransactionLink	x	XML-container: reference to another transaction; will be created in following cases: - invoice duplicate - link to original invoice - tax refund issue - link to original sales receipt (links to multiple sales receipts possible) - voiding receipt - link to voided original receipt (e.g. voided pay-in/pay-out or voided tax refund issue)	see TransactionLink
	CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
	customExtension	x	Any elements can be added to the XML.	

4.3.8.1 BusinessEOD

XML-Elements

XML element	optional	Description	Comment
StartDateTimestamp		date and time of beginning of business day (of accounting period)	

4.3.8.2 TillEOD

XML-elements

XML element	optional	Description	Comment
SessionSettle		XML-container: includes sum values per accounting period of /store	see SessionSettle

SessionSettle

XML-elements

XML element	optional	Description	Comment
TenderSummary	x	XML-container: includes sum values of tenders per accounting period of /store	see TenderSummary
SES:SalesSummary	x	XML-container: includes sum values of sales per accounting period of /store	see SES:SalesSummary
SES:RebateSummary	x	Not generated at this time.	
SES:TaxSummary	x	XML-container: includes sum values of taxes per accounting period of /store	see SES:TaxSummary

TenderSummary

XML element	optional	Description	Comment
-------------	----------	-------------	---------

Beginning	x	XML-container: opening balance	see Beginning
Pickup	x	XML-container: tender pickup	see Pickup
Over		XML-container: created in case of positive difference	see Over
Short		XML-container: created in case of negative difference	see Short
SES:Nominal	x	XML-container: closing/target balance of drawer	see SES:Nominal
SES:SalesTenderNominal	x	XML-container: tender totals of all sales/return receipts	see SES:SalesTenderNominal
SES:Ending	x	XML-container: counted/actual balance of drawer	see SES:Ending
customExtension	x	Any elements can be added to the XML.	

Beginning

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	

XML-Elements

XML element	optional	Description	Comment
Amount		opening balance in main currency. In case of foreign currency following attributes are used additionally: - Currency (optional) - ForeignAmount (optional)	
Count	x	created in case of Count <> 0	

Pickup

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	

XML-Elements

XML element	optional	Description	Comment
Amount		manual pickup amount in main currency. In case of foreign currency following attributes are used additionally: - Currency (optional) - ForeignAmount (optional)	
Count	x	created in case of Count <> 0	

Over

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	

XML-elements

XML element	optional	Description	Comment
Amount		positive amount of the drawer count difference, in main currency. in case of foreign currency following attributes are used: - Currency (optional) - ForeignAmount (optional)	
Count	x	created in case of Count <> 0	

Short

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	

XML-elements

XML element	optional	Description	Comment
Amount		negative amount of the drawer count difference, in main currency. In case of foreign currency following attributes are used additionally: • Currency (optional) • ForeignAmount (optional)	
Count	x	created in case of Count <> 0	

SES:Nominal

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	
TypeCode		TypeCode to distinguish between positive and negative amount possible values: • "Refund" - negative • "Sale" - positive	

XML-elements

XML element	optional	Description	Comment
Amount		closing/target amount of the safe, in main currency. In case of foreign currency following attributes are used additionally: • Currency (optional) • ForeignAmount (optional)	
Count	x	created in case of Count <> 0	

SES:SalesTenderNominal

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	
TypeCode		TypeCode to distinguish between positive and negative amount possible values: • "Refund" - negative • "Sale" - positive	

XML-elements

XML element	optional	Description	Comment
Amount		tender totals of all sales/return receipts, in main currency. In case of foreign currency following attributes are used additionally: • Currency (optional) • ForeignAmount (optional)	
Count	x	created in case of Count <> 0	

SES:Ending

Attributes

Attribute	optional	Description	Comment
TenderType		Tender type	
TypeCode		TypeCode to distinguish between positive and negative amount possible values: • "Refund" - negative • "Sale" - positive	

XML-elements

XML element	optional	Description	Comment
Amount		counted/actual amount of the safe, in main currency. In case of foreign currency following attributes are used additionally: • Currency (optional)	

		• ForeignAmount (optional)	
Count	x	created in case of Count <= 0	

SES:SalesSummary

Attributes

Attribute	optional	Description	Comment
TypeCode	x	Type code of sales transaction possible values: "Refund" "Sale"	

XML-Elements

XML element	optional	Description	Comment
Amount		sales of sales receipts	
Count		quantity of sales receipts	
Reason		possible values: Sales: Reason = "2001" Subtotal rounding: Reason = "2011" Sold gift certificates: Reason = "2020" Down payments: Reason = "3101" Cleared down payments: Reason = "3102" Invoices: Reason = "3103" Pay-ins: Reason = "3104" Pay-outs: Reason = "3201" attribute: Name fix value: "SalesID"	

SES:RebateSummary

Not generated at this time.

SES:TaxSummary

Attributes

Attribute	optional	Description	Comment
TenderType	x	Tender type possible values: "Refund" "Sale"	

XML-Elements

XML element	optional	Description	Comment
Amount		sales per tax code	
Count		quantity of taxed positions	
SES:TaxAuthorityID		ID of tax authority	
SES:TaxGroupID		ID of tax group	

4.3.8.3 OperatorSignOn

XML element	optional	Description	Comment
StartDateTimestamp	x	date and time of sign on receipt	

4.3.8.4 OperatorSignOff

XML element	optional	Description	Comment
StartDateTimestamp	x	date and time of sign off receipt	

4.3.8.5 SES:CashierStatistics

SessionSettle

XML-elements

XML element	optional	Description	Comment
TransactionCount	x	quantity of receipts with revision type = 'TRANSACTION_COUNT'	see TransactionCount

TotalMeasures	x	XML-container: includes some statistics	see TotalMeasures
LinItemVoids		XML-container: includes sum and quantity of line item voids	see LinItemVoids
PostTransactionVoids		XML-container: includes sum and quantity of post item voids	see PostTransactionVoids
SES:TransactionCancellations		XML-container: includes sum and quantity of transaction cancellations	see SES:TransactionCancellations
SES:DirectLinItemVoids		XML-container: includes sum and quantity of direct line item voids	see SES:DirectLinItemVoids
SES:AccountedOperatorID	x	OperatorID of the operator, for which exists a one-to-one assignment of operator to drawer Attribute: Name (optional)	

TotalMeasures

XML-elements

XML element	optional	Description	Comment
SaleLinItemCount	x	won't be created	
NoSaleTransactionCount	x	quantity of "open Till" receipts	
LinItemScannedCount	x	quantity of scanned positions	
LinItemOpenDepartmentCount	x	quantity of value items	
RingTime	x	won't be created	
IdleTime	x	won't be created	
LockTime	x	won't be created	
SES:LogonTime	x	total time of sign on time	
SES:RegistrationTime	x	total time of item registration	
SES:TenderTime	x	total time of tender record	
SES:FailedLogonCount	x	won't be created	

LinItemVoids

XML-Elements

XML element	optional	Description	Comment
Amount		sum of line item voids	
Count		quantity of line item voids	

PostTransactionVoids

XML-Elements

XML element	optional	Description	Comment
Amount		sum of post transaction voids	
Count		quantity of post transaction voids	

SES:TransactionCancellations

XML-Elements

XML element	optional	Description	Comment
Amount		sum of post transaction cancellations	
Count		quantity of post transaction cancellations	

SES:DirectLinItemVoids

XML-Elements

XML element	optional	Description	Comment
Amount		sum of direct line item voids	
Count		quantity of direct line item voids	

4.3.8.6 SES:StoreEODSummary

XML-elements

XML element	optional	Description	Comment
-------------	----------	-------------	---------

SessionSettle		XML-container: includes sum values per accounting period of /store	see SessionSettle
---------------	--	--	-------------------

SessionSettle

XML-elements

XML element	optional	Description	Comment
TenderSummary	x	Not generated at this time.	
SES:SalesSummary	x	XML-container: includes sum values of sales per accounting period of /store	see SES:SalesSummary
SES:RebateSummary	x	Not generated at this time.	
SES:TaxSummary	x	XML-container: includes sum values of taxes per accounting period of /store	see SES:TaxSummary

4.3.8.7 SES:TaxRefund

Attributes

Attribute	optional	Description	Comment
TypeCode	x	Type code of tax refund issue possible values: "Refund" "Sale"	

XML-Elements

XML element	optional	Description	Comment
SES:TaxRefundDocumentID		The unique identifier of the tax refund document returned from tax refund service.	
SES:ExternalTransactionID	x	A universally unique identifier (UUID) for the transaction in the external system, which is provided by the service provider.	
SES:StoreInvoiceID	x	Fiscal invoice number for countries, where this is required.	
SES:TotalGrossAmount		The summarized gross amount for all sale transactions of this tax refund (exported as absolute value).	
SES:TotalTaxAmount	x	The summarized gross amount for all sale transactions of this tax refund (exported as absolute value).	
SES:TotalRefundAmount		The resulting tax refund amount (exported as absolute value).	
CST:XXCustom01 ... CST:XXCustom05	x	A separate element is created for every XXCustom field from 01 to 05.	
customExtension	x	Any elements can be added to the XML.	

4.3.8.8 SES:TransactionLink

All elements in TransactionLink refer to the linked document.

Attributes

Attribute	optional	Description	Comment
ReasonCode	x	attributes: In case of a ControlTransaction and invoice duplicate: - SES:InvoiceDuplicate In case of a TenderControlTransaction (mainly in case of POS Payin/Payout) and in case of a ControlTransaction and voiding tax refund: - Voided In case of a ControlTransaction and tax refund issue: - SES:TaxRefund	

XML-elements

XML element	optional	Description	Comment
RetailStoreID		retail store number of the original transaction	
WorkstationID		workstation/POS number of the original transaction	
SequenceNumber		receipt number of the original transaction	

LineItemSequenceNumber	x	won't be created for transaction link under control transaction and tender control transaction	
BusinessDayDate		date of business day of the original transaction	
BeginDateTime		begin date and time of the original transaction	
EndDateTime	x	end date and time of the original transaction	
SES:InternalSequenceNumber	x	won't be created	
SES:ReceiptDateTime	x	won't be created for transaction link under control transaction and tender control transaction	
SES:InternalTransactionID		universally unique identifier (UUID) of the original transaction	
customExtension	x	Any elements can be added to the XML.	

Bestätigung

Mit der Unterschrift des Business Konzept Dokuments wird die Vollständigkeit und Richtigkeit bestätigt.

GK/Retail Solution Model Omni-Channel
POS

GK/Retail Solution Model Omni-Channel
POS – Projektmanager

GK – Konsultant

GK – Projektmanager

Datum:

GK Software SE
Waldstraße 7
08261 Schöneck
Deutschland

T +49 (0) 3 74 64 84 – 0
F +49 (0) 3 74 64 84 – 15

www.gk-software.com



The Retail Innovators