



# Clustering Analysis and K-Means

Mahdi Roozbahani  
Georgia Tech

# Outline


- Clustering 
- Distance Function
- K-Means Algorithm
- Analysis of K-Means

# Clustering Images



## Goal of clustering:

Divide object into groups,  
and objects within a group  
are more similar than  
those outside the group



# Clustering Other Objects




Belarusian **Piotr**  
 Azerbaijani **Pyotr**  
 Greek **Petros**  
 Italian **Pietro**  
 Portuguese **Pedro**  
 French **Pierre**  
 Italian **Piero**  
 Dutch **Peter**  
 Danish **Peder**  
 Couldn't find it – Finish? **Peka**  
 Irish **Peadar**

Linguistic Similarity






# Clustering Hand Digits




# Clustering is Subjective



What is consider similar/dissimilar?

## Clustering is subjective



Simpson's Family



School Employees



Females



Males



Are they similar or not?




# So What is Clustering in General?

- You pick your similarity/dissimilarity function
- The algorithm figures out the grouping of objects based on the chosen similarity/dissimilarity function
  - Points within a cluster is similar
  - Points across clusters are not so similar
- Issues for clustering
  - How to represent objects? (Vector space? Normalization?)
  - What is a similarity/dissimilarity function for your data?
  - What are the algorithm steps?



# Outline

- Clustering
- Distance Function 
- K-Means Algorithm
- Analysis of K-Means

# Properties of Similarity Function


- Desired properties of dissimilarity function
  - Symmetry:  $d(x, y) = d(y, x)$ 
    - *Otherwise you could claim "Alex looks like Bob, but Bob looks nothing like Alex"*
  - Positive separability:  $d(x, y) = 0$ , if and only if  $x = y$ 
    - *Otherwise there are objects that are different, but you cannot tell apart*
  - Triangular inequality:  $d(x, y) \leq d(x, z) + d(z, y)$ 
    - *Otherwise you could claim "Alex is very like Bob, and Alex is very like Carl, but Bob is very unlike Carl"*

# Distance Functions for Vectors

- Suppose two data points, both in  $R^d$ 
  - $x = (x_1, x_2, \dots, x_d)$
  - $y = (y_1, y_2, \dots, y_d)$
- Euclidean distance:  $d(x, y) = \sqrt{\sum_{i=1}^d (x_i - y_i)^2}$
- Minkowski distance:  $d(x, y) = \sqrt[p]{\sum_{i=1}^d (x_i - y_i)^p}$ 
  - Euclidean distance:  $p = 2$
  - Manhattan distance:  $p = 1, d(x, y) = \sum_{i=1}^d |x_i - y_i|$
  - “inf”-distance:  $p = \infty, d(x, y) = \max_{i=1}^d |x_i - y_i|$




# Example





- Euclidean distance:  $\sqrt{4^2 + 3^2} = 5$
- Manhattan distance:  $4 + 3 = 7$
- “inf”-distance:  $\max\{4, 3\} = 4$

# Some problems with Euclidean distance



$d(x,y)$  and  $d(x,z)$  ?



# Hamming Distance

- Manhattan distance is also called *Hamming distance* when all features are binary
  - Count the number of difference between two binary vectors
  - Example,  $x, y \in \{0,1\}^{17}$

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
$x$	0	1	1	0	0	1	0	0	1	0	0	1	1	1	0	0	1
$y$	0	1	1	1	0	0	0	0	1	1	1	1	1	1	0	1	1

$$d(x, y) = 5$$



# Edit Distance

- Transform one of the objects into the other, and measure how much effort it takes

$x$	I	N	T	E	*	N	T	I	O	N
$y$	*	E	X	E	C	U	T	I	O	N
	d	s	s		i	s				

d: deletion (cost 5)


s: substitution (cost 1)

i: insertion (cost 2)

$$d(x, y) = 5 \times 1 + 3 \times 1 + 1 \times 2 = 10$$

d: deletion (cost 5)  
s: substitution (cost 1)  
i: insertion (cost 2)

# Outline

- Clustering
- Distance Function
- K-Means Algorithm 
- Analysis of K-Means



# Results of K-Means Clustering:



Image



Clusters on intensity



Clusters on color

K-means clustering using intensity alone and color alone




Image



Clusters on color


K-means using color alone, 11 segments (clusters)





# K-Means Algorithm

Start!



[Visualizing K-Means Clustering](#)

# K-Means Algorithm

- Initialize  $k$  cluster centers,  $\{c_1, c_2, \dots, c_k\}$  , randomly
- Do
  - Decide the cluster memberships of each data point,  $x_i$  by assigning it to the nearest cluster center (**cluster assignment**)


$$\pi(i) = \operatorname{argmin}_{j=1,\dots,k} \|x_i - c_j\|^2$$

- Adjust the cluster centers (**center adjustment**)


$$c_j = \frac{1}{|\{i: \pi(i) = j\}|} \sum_{i: \pi(i)} x_i$$

- While any cluster center has been changed


# K-Means: Step 1



# K-Means: Step 2




# K-Means: Step 3







# K-Means: Step 4



# K-Means: Step 5



# Outline

- Clustering
- Distance Function
- K-Means Algorithm
- Analysis of K-Means 

# Questions

- Will different initialization lead to different results?
  - Yes
  - No
  - Sometimes
- Will the algorithm always stop after some iteration?
  - Yes
  - No (we have to set a maximum number of iterations)
  - Sometimes

# Formal Statement of the Clustering Problem

- Given  $n$  data points,  $\{x_1, x_2, \dots, x_n\} \ x \in R^d$
- Find  $k$  cluster centers,  $\{c_1, c_2, \dots, c_k\} \ c \in R^d$
- And assign each datapoint  $i$  to one cluster,  $\pi(i) \in \{1, \dots, k\}$
- Such that the averaged square distances from each datapoint to its respective cluster center is small

$$\min_{c, \pi} \sum_{i=1}^n \|x_i - c_{\pi(i)}\|^2$$




# Clustering is NP-Hard

- Find  $k$  cluster centers,  $\{c_1, c_2, \dots, c_k\} c \in R^d$ , and assign each data point  $i$  to one cluster,  $\pi(i) \in \{1, \dots, k\}$ , to minimize

$$\min_{c, \pi} \sum_{i=1}^n \|x_i - c_{\pi(i)}\|^2$$

NP-hard!

- A search problem over the space of discrete assignments
  - For all  $n$  data point together, there are  $k^n$  possibility
  - The cluster assignment determines cluster centers, and vice versa



- For all  $n$  data point together, there are  $k^n$  possibility

$X = \{A, B, C\}$

$n=3$  (data points)

$k=2$  clusters of two members

Cluster 1

Cluster 2

# Convergence of K-Means

- Will kmeans objective oscillate?

$$\min_{c, \pi} \sum_{i=1}^n \|x_i - c_{\pi(i)}\|^2$$


- The minimum value of the objective is finite
- Each iteration of kmeans algorithm decrease the objective
  - Cluster assignment step decreases objective
    - $\pi(i) = \operatorname{argmin}_{j=1, \dots, k} \|x_i - c_{\pi(j)}\|^2$  for each data point  $i$
  - Center adjustment step decreases objective
    - $c_i = \frac{1}{|\{i: \pi(i)=j\}|} \sum_{i: \pi(i)=j} x_i = \operatorname{argmin}_c \sum_{i: \pi(i)=j} \|x_i - c_{\pi(j)}\|^2$

# Time Complexity

- Assume computing distance between two instances is  $O(d)$  where  $d$  is the dimensionality of the vectors.
- Reassigning clusters for all datapoints:
  - $O(kn)$  distance computations (when there is one feature)
  - $O(knd)$  (when there is  $d$  features)
- Computing centroids: Each instance vector gets added once to some centroid (Finding centroid for each feature):  $O(nd)$ .
- Assume these two steps are each done once for  $I$  iterations:  $O(Iknd)$ .

# How to Choose K?

Elbow method



**Distortion score:** computing the sum of squared distances from each point to its assigned center