

bso2 Monitor Reference

Target: W65C02EDU | Source: SRC/bso2.asm | Generated: 2026-02-14

0) Naming

bso2 is the preferred written form in this manual.

It is intentionally dual-meaning and retro-styled:

- b = Basic
- s = System
- 0 = Operations (also read as letter O)
- 2 = /2 and 6502 lineage

Stylized-glyph note: 6 can stand in for lowercase b, and 5 can stand in for lowercase s.

That makes 6502 a visual shorthand for bso2 (6=b, 5=s, 0=o, 2=/2).

Expanded meaning: Basic System Operations/2.

1) Startup / Prompt Behavior

On reset with valid reset cookie, boot choices are C/W/M:

C = clear RAM (confirm Y/N)

W = warm start

M = enter monitor

After clear/startup, the sign-on banner (BS02_INIT) is printed:

```
**** basic system operations/2 ****
****   b s o / 2  v0 . 9   ****
****       6 5 0 2       ****
```

Monitor prompt is a single - character on a new line.

2) Command Summary

Cmd	Syntax	Behavior / Output	Flags / Notes
?	?	Short help line.	Quick command list only.
H	H	Full multi-line help.	Includes interactive caveats.
Z	Z	Clear RAM after Y/N confirmation.	Zeroes \$0200-\$7EFF. Does not zero \$0000-\$01FF (ZP/stack) or \$7F00-\$7FFF (I/O area).
W	W	Warm start back into monitor.	No args.

D	D [START [END]]	Hex+ASCII dump. END is inclusive.	D alone repeats last span from next address. Hex/ASCII fields show an 8+8 split.
U	U START END	Disassemble as 65C02 mnemonics and operands.	END is inclusive. Emits ADDR: MNM OPERAND .
A	A START [INSN]	Tiny 65C02 assembler, interactive at next address.	Example: A 1000 LDA #FF then prompt A 1002: . . exits. No labels/forward refs. Relative branches accept absolute hex targets and are range-checked. Explicit accumulator form like INC A is supported.
X	X START	Execute from absolute address.	Transfers control via RTS trampoline. NMI while running under X breaks back to monitor; target RTS also returns to monitor.
R	R [A=HH] [X=HH] [Y=HH]	Resume last debug context.	Restores A/X/Y/P/SP/PC from latest debug snapshot and resumes via RTI . Optional A/X/Y overrides are applied first. Up-arrow repeat is useful for single-step resume loops.
N	N	Run to next sequential instruction.	Implements next-stop by patching a temporary BRK at PC+len(opcode) . RAM only; ROM/I/O patch targets are rejected. Debug output restores and displays the original stepped-to instruction in PREV: .

M	M [START [B0..B15]]	Modify/deposit memory. Inline deposit supports up to 16 bytes.	Interactive mode: CR/LF = next, . ends. CRLF pair counts as one next.
F	F START END B0..B15	Fill inclusive range with repeating 1..16 byte pattern.	No interactive mode. Verifies each write.
C	C SRC_START SRC_END DST_START	Copy inclusive source range to destination.	Overlap-safe (forward/backward selection). Verifies each write.
!	!F ..., !M ..., !C ..., !A ..., !N	Force-prefix for protected commands.	Allows access to protected low RAM (\$0000-\$03FF).
Q	Q	Enter WAI halt loop.	IRQ masked. Resume by NMI (or Reset). NMI latch returns cleanly to monitor.
V	V	Show vector jump chains.	Displays HW vector to final code path.

3) Interactive Caveats

- M interactive: two hex digits are required per byte write (00..FF).
- A interactive: type one mnemonic/operand per prompt, . exits assembler mode.
- . exits interactive modify and retains next-address state for subsequent M.
- CR or lone LF advances to next address.
- CRLF pair is consumed as a single next-step.
- F does not support interactive mode.
- At an empty monitor prompt, Up Arrow (ESC [A) repeats and executes the previous command.
- F/M/C/A/N block access to \$0000-\$03FF unless prefixed with !. D is always allowed.

4) Verify / Error Outputs

Operation	Message / Behavior
Modify verify fail	M VERIFY FAILED AT ADDR + failing address.
Fill verify fail	F VERIFY FAILED AT ADDR + failing address.
Copy verify fail	C VERIFY FAILED AT ADDR + failing address.
Dump range error	D RANGE ERROR .
Unassemble range error	U RANGE ERROR .
Assembler branch range error	A BRANCH RANGE ERROR .
BRK debug context	Printed as three lines: PREV: (instruction at BRK opcode), TRAP: (register/status line), then NEXT: (instruction at resume PC). For

	N-generated temporary breaks, PREV: shows the restored original instruction.
Bad syntax	Per-command usage lines (e.g. USAGE: M [START [B0..B15]]).

5) API Reference (Macros and Functions)

Use this section when calling monitor functionality from your own assembly code.

5.1) Macro Reference (macros.inc)

Macro	Parameters	Behavior / Notes
PUSH	PUSH p1 [,p2] [,p3] [,p4]	Pushes listed registers in given order. Supported tokens: A/X/Y/P (case-insensitive).
PULL	PULL p1 [,p2] [,p3] [,p4]	Pops listed registers in given order. Keep ordering compatible with prior PUSH.
REPEAT	REPEAT Routine, Count	Calls JSR Routine repeatedly Count times. Preserves X via push/pull.
PRT_CSTRING	PRT_CSTRING Label	Prints null-terminated string at Label via PRT_C_STRING.
DUMP	DUMP Start, EndExclusive	Convenience wrapper for MEM_DUMP with explicit exclusive end.
FILL	FILL Start, EndInclusive, B0 [,B1] [,B2] [,B3] [,B4]	Loads pattern bytes (1..5) and calls MEM_FILL_PATTERN. End is inclusive in macro syntax.
COPY	COPY SrcStart, SrcEndInclusive, DstStart	Calls overlap-safe MEM_COPY_RANGE. Source end is inclusive in macro syntax.
COPY_BLOCK	COPY_BLOCK SrcStart, Length, DstStart	Compatibility wrapper that expands to COPY SrcStart,(SrcStart+Length-1),DstStart.
CMP_CSTRING	CMP_CSTRING AddrA, AddrB	Wrapper for project-specific string compare symbols/routine (STRCMP_PTR*, STR_COMPARE). Use only when those symbols are provided by your build.

5.2) Callable Function Reference

Practical entry points for extensions and integration.

Routine	Input	Output	Flags	ZP / Memory Use
INIT_SERIAL	None	UART initialized	Unchanged	None
WRITE_BYTE	A=char	Char sent to UART, LED updated	Unchanged	None
READ_BYTE	None	A=received char (ROM read)	ROM-defined	None
CHECK_BYTE	None	A=status	C=1 if RX empty	None

RBUF_INIT	None	Input ring reset	Unchanged	Uses generic buffer descriptor core
BUF_INIT	Active descriptor pointers set	Head/Tail/Count zeroed	Unchanged	Uses BUF_*_PTR
BUF_PUT_A	A =byte	Byte queued	C=0 stored, C=1 full	Uses BUF_*_PTR , BUF_SIZE
BUF_GET_A	None	A =byte	C=0 byte, C=1 empty	Uses BUF_*_PTR , BUF_SIZE
CMD_DISPATCH	A =command letter	Handler called from table	C=0 handled, C=1 unknown	Uses CMD_TABLE , CMD_POST_ACTION
MEM_DUMP	PTR_DUMP_CUR =start (inc), PTR_TEMP =end (exc)	Formatted hex+ASCII dump with 8+8 separator	Unchanged	Uses PTR_DUMP_CUR , PTR_DUMP_END , PTR_LEG , MEM_DUMP_CNT
MEM_DISASM_65C02	PTR_DUMP_CUR =start (inc), PTR_TEMP =end (inc)	65C02 disassembly output (ADDR: MNM OPERAND)	Unchanged	Uses PTR_DUMP_CUR , PTR_DUMP_END , PTR_TEMP , PTR_LEG , DIS_*
MEM_FILL_PATTERN	PTR_DUMP_CUR =start (inc), PTR_DUMP_END =end (exc), F_COUNT =pattern length, F_PATTERN =pattern bytes	Fills range with repeating pattern	C=0 complete, C=1 aborted (verify/protect)	Uses PTR_DUMP_CUR , PTR_DUMP_END , F_COUNT , F_PATTERN , F_PAT_IDX
MEM_COPY_RANGE	PTR_LEG =src start (inc), PTR_DUMP_END =src end (exc), PTR_TEMP =dst start	Copies source to destination (overlap-safe)	C=0 complete, C=1 aborted (verify/protect)	Uses PTR_LEG , PTR_DUMP_CUR , PTR_DUMP_END , PTR_TEMP , CMD_PARSE_VAL
CMD_DO_ASM	CMD_LINE = A START [INSN]	Interactive tiny assembler	. exits	Uses CMD_LINE , PTR_TEMP , opcode tables, and ASM_* / DIS_* scratch

6) Parser and Buffer Limits

- CMD_MAX_LEN = 31 characters (excluding null terminator).
- RBUF_SIZE = 32 bytes.
- One-command history is kept for up-arrow repeat (CMD_LAST_LINE).
- Hex token parser accepts 1..4 hex digits, optional \$ prefix.

- `M` and `F` inline byte lists: max 16 bytes each.
- `!` is consumed as a command prefix, then normal parsing continues.

7) Memory Usage

Build Section Usage (current)

Section	ORG	Size (hex)	Size (dec)
PAGE0	\$0040	\$4A	74
CODE	\$8000	\$1A22	6690
KDATA	\$E000	\$B25	2853
UDATA	\$0200	\$7A	122
Total	-	\$260B	9739

RAM Layout Highlights

- PAGE0 starts at \$0040. Includes parser state, dump state, debug snapshot, vector hooks, and active buffer descriptor pointers.
- UDATA starts at \$0200:

```

RBUF_DATA    32 bytes
CMD_LINE     32 bytes (31 + NUL)
CMD_LAST_LINE 32 bytes (31 + NUL)
RESET_COOKIE  4 bytes
F_PATTERN    16 bytes
DBG_TAG_BUF   6 bytes

```

8) Notes for Integrators

- Command parser uppercases incoming command bytes before parse/dispatch.
- Command execution is table-driven via `CMD_TABLE`.
- Input buffering now uses a generic descriptor-based core bound to the ring buffer.
- `Q` path relies on NMI latch (`SYSF_NMI_FLAG_M`) and then re-enters monitor cleanly.

9) Planned Commands (Appendix, Provisional)

This appendix documents planned command architecture and roadmap intent only.

Proviso: change is constant. These plans are not stable API and may change before publish.

9.1) Grammar Direction

- Primary model: noun verb [args...] (namespace first, action second).
- Direct-action commands may still exist where practical (for example jump/execute style flow).
- Parser should accept both spaced and fused forms for operator speed.

9.2) Canonical Input Compatibility

- `X S` and `XS` should map to the same internal command key.
- `X R` and `XR` should map to the same internal command key.
- `M D` and `MD` should map to the same internal command key.
- `I O V` and `IOV` should map to the same internal command key.
- One canonical dispatch representation is preferred to avoid duplicate handlers.

9.3) Namespace Plan

Root	Planned Role	Notes
B	Bank / FLASH	Reserved for FLASH-related operations (read/program/erase/verify family).
I	Info root	Carries nested subfamilies such as time and I/O.
I T	Time	Time moves under Info; top-level T is freed.
T	Terminal	Repurposed top-level namespace for terminal-related operations.
I O P	PIA	Top-level P is freed; PIA moves under Info/I/O.
I O V	VIA	Top-level V is freed; VIA moves under Info/I/O.
I O V T	VIA timers	Hardware timers are expected under VIA tree.
J	Jump / Execute	Preferred home for execute flow if top-level execute letter changes.
X	Transfer / XMODEM	At minimum: send and receive support.
S	Search	Text and binary search families.
M	Memory family	Supports compact forms such as MD/MM as aliases.
O	Deferred decision	Candidate: chained execution wrapper; decision postponed.

9.4) Search Family Detail

- Planned base forms: **S C** START END <text> and **S B** START END <pattern...>.
- S C** mode: unquoted text stops at first whitespace.
- S C** mode: quoted delimiters can include `"`, `'`, and ```.
- S C** mode: delimiter escape by doubling delimiter character.
- S C** mode wildcards: `?` matches exactly one character, `*` matches zero or more characters.
- S C** mode literals: `??` matches literal `?`, and `**` matches literal `*`.
- S B** mode tokens: **HH** byte, **HHHH** little-endian word, nibble wildcard (`?A/A?/??`), and `*` byte wildcard.
- Candidate extensions: Pascal strings and high-bit-set text search modes.

9.5) XMODEM Requirement

- Before publish, provide both XMODEM receive and send paths.
- Preferred forms: **X R ...** and **X S ...** with fused aliases (**XR**, **XS**).

9.6) Vector + Safety Direction (Pre-Publish Requirement)

- Vector updates must support dynamic atomic update behavior.
- Critical windows include vector commit and FLASH routines.
- During critical windows, all EDU LEDs should flash to signal that NMI should not be pressed.
- NMI path should be guarded/deferred during critical windows instead of normal debug flow.
- Staged-update plus atomic-commit behavior is the intended implementation pattern.
- Mandate (non-changing requirement): any operation that mutates FLASH state or vector state must assert critical indication/guard behavior, including module/transient load paths; implementation detail may change, requirement does not.

9.7) Deferred Item

- O** command semantics are intentionally deferred.

- If adopted as an operation chain wrapper, error policy and guard policy must be defined explicitly.

9.8) Compression + TX Ring (Priority 0)

- Priority 0 roadmap item: reduce monitor-text ROM footprint with compression.
- Planned model: tokenized text plus RLE.
- RLE threshold: encode runs of 3 or more consecutive bytes.
- Frequent-byte run tokens are planned for `space`, `-`, `0`, `1`, and `*`.
- Historical design note: RLE was a practical production tool in ASMF1/System/36 COLD work, where throughput and overnight windows mattered more than perfect compression ratios. The implementation was rushed and not elegant, but it was successful in production. That same tradeoff applies here: favor simple, fast, streamable compression with manageable code complexity over maximum ratio.
- Decompression direction is ROM compressed stream to output sink (UART stream directly or TX/RAM staging).
- A dedicated TX ring buffer is planned for nonblocking output.
- Decoder should be pausable/resumable when TX ring space is exhausted.
- RX and TX buffers remain separate.
- Default virtual-stream plan: one shared TX ring with scheduling/priority policy.
- Per-stream TX rings are optional and should be introduced only if stream isolation/QoS is required.
- Raw/uncompressed source strings remain in assembly source as authoring truth.
- Planned build flow: marked header/trailer string regions are consumed by a GNU C packer that generates an assembler include.

10) Legal Notice

- WDC, W65C02, and W65C02EDU are names associated with Western Design Center, Inc.
- This project is independent and is not affiliated with or endorsed by Western Design Center, Inc.
- This repository does not redistribute WDC tool binaries or WDC ROM images.
- Any third-party source code or text should be included only under its original license terms.