bso2 Monitor Reference

Target: W65C02EDU | Source: SRC/bso2.asm | Generated: 2026-02-18

0) Naming

bso2 is the preferred written form in this manual.

It is intentionally dual-meaning and retro-styled:

- b = 6 = Basic
- s = 5 = System
- o = 0 = Operations
- 2 = 2 = /2 (homage to IBM System/36)

That makes 6502 a visual shorthand for bso2.

Expanded meaning: Basic System Operations/2.

1) Startup / Prompt Behavior

On reset with valid reset cookie, boot choices are C/W/M:

C = clear RAM (confirm Y/N)
W = warm start
M = enter monitor

Power-on prompt uses C/M with a 6-second wait and > tick markers; timeout defaults to C.

Reset-cookie prompt uses C/W/M with a 6-second wait and < tick markers; LEDs blink every ~333ms while waiting and timeout defaults to M.

Boot-choice and clear-confirm prompts echo keypresses in uppercase.

C/W/M Decision Truth Table

Condition	Input	Result
Power-on (no valid reset cookie)	C	Enter clear path.
Power-on (no valid reset cookie)	M	Enter monitor path.
Power-on (no valid reset cookie)	Timeout	Default to clear path (C).
Power-on (no valid reset cookie)	Invalid key	Ignored; prompt/countdown continues.
Reset with valid cookie	C	Enter clear confirmation prompt Y/N.
Clear confirmation	Y	Run clear-memory path.
Clear confirmation	N	Abort clear and continue warm path (W-equivalent branch).
Reset with valid cookie	W	Warm start path (no clear).
Reset with valid cookie	M	Monitor path.
Reset with valid cookie	Invalid key	Ignored; prompt/countdown continues.

Reset with valid cookie	Timeout	Default to monitor path (`M`).

Note: this is the default behavior for the currently installed vector trampolines/handlers; future trampolines or handlers may implement different startup policy.

A terminal-width prompt follows boot selection: `TERM WIDTH 4=40 8=80 1=132 [8]?` .

Width prompt timeout uses fixed byte `$007B` (`TERM_WIDTH_TIMEOUT`): `00=wait forever` , `01-FF=seconds` , default `08` .

Width persistence policy: `W/M` restore prior width before prompting; `C` starts from default 80 before prompting.

After clear/startup, the sign-on banner (`BSO2_INIT`) is printed:

```
**** basic system operations/2 ****
****       b s o / 2  v0 . 9   ****
****         6 5 0 2           ****
```

Monitor prompt is a single `-` character on a new line.

2) Command Summary

Cmd	Syntax	Behavior / Output	Flags / Notes
`?`	`?`	Short help line.	Quick command list only.
`H`	`H [A|P|M|S]`	Help index or scoped help sections.	`H` =index, `H A` =all, `H P` =protection, `H M` =memory/tools, `H S` =steering.
`Z`	`Z`	Clear RAM after Y/N confirmation.	Zeroes `$0200-$7EFF` . Does not zero `$0000-$01FF` (ZP/stack) or `$7F00-$7FFF` (I/O area).
`W`	`W`	Warm start back into monitor.	No args.
`D`	`D [START [END]]`	Hex+ASCII dump. `END` is inclusive.	`D` alone repeats last span from next address. Hex/ASCII fields show an 8+8 split.
`U`	`U [START END]`	Disassemble as 65C02 mnemonics and operands.	`END` is inclusive. Bare `U` repeats from saved next-instruction address. Emits `ADDR: MNM OPERAND` .
`A`	`A START [INSN]`	Tiny 65C02 assembler, interactive at next address.	Example: `A 1000 LDA #FF` then prompt `A 1002:` . `.` exits. No labels/forward refs. Relative

			branches accept absolute hex targets and are range-checked. Explicit accumulator form like `INC A` is supported.
`X`	`X START`	Execute from absolute address.	Transfers control via RTS trampoline. NMI while running under `X` breaks back to monitor; target `RTS` also returns to monitor.
`I`	`I C <RPN...>` or `IC <RPN...>`	Evaluate 16-bit hex RPN expression.	Values are 1..4 hex digits (optional `$`). Operators: `+ - * / & | ^ ~`. Prints top-of-stack as `I C = $HHHH`.
`R`	`R [A=HH] [X=HH] [Y=HH]`	Resume last debug context.	Restores `A/X/Y/P/SP/PC` from latest debug snapshot and resumes via `RTI`. Optional `A/X/Y` overrides are applied first. Up-arrow repeat is useful for single-step resume loops.
`N`	`N`	Run to next sequential instruction.	Implements next-stop by patching a temporary `BRK` at `PC+len(opcode)`. RAM only; ROM/I/O patch targets are rejected. Debug output restores and displays the original stepped-to instruction in `CURR:`.
`M`	`M [START [B0..B15]]`	Modify/deposit memory. Inline deposit supports up to 16 bytes.	Interactive mode: `CR/LF = next`, `.` ends. CRLF pair counts as one next.
`F`	`F START END B0..B15`	Fill inclusive range with repeating 1..16 byte pattern.	No interactive mode. Verifies each write.

`C`	`C SRC_START SRC_END DST_START`	Copy inclusive source range to destination.	Overlap-safe (forward/backward selection). Verifies each write.
`!`	`!F ...`, `!M ...`, `!C ...`, `!A ...`, `!N`	Force-prefix for protected commands.	Allows access to protected low RAM (`$0000-$03FF`).
`Q`	`Q`	Enter WAI halt loop.	IRQ masked. Resume by NMI (or Reset). NMI latch returns cleanly to monitor.
`V`	`V`	Show vector jump chains.	Spaced format: `RST: FFFC > F818 > 8004 > 9F31 > [0080] > 800D`. IRQ now appends sub-dispatch lines: `BRK: XXXX <name>` and `HW: YYYY <name>`. Bracketed links use `[addr16]` and indicate a patchable 16-bit RAM trampoline address.

3) Interactive Caveats

- `M` interactive: two hex digits are required per byte write (00..FF).
- `A` interactive: type one mnemonic/operand per prompt, `.` exits assembler mode.
- `.` exits interactive modify and retains next-address state for subsequent `M`.
- `CR` or lone `LF` advances to next address.
- `CRLF` pair is consumed as a single next-step.
- `F` does not support interactive mode.
- At an empty monitor prompt, `Up Arrow` (`ESC [ A`) repeats and executes the previous command.
- Special repeat behavior: if the previous command was a `D ...` or `U ...` form, up-arrow replays bare `D`/`U`; `D` continues by saved span, `U` by saved next-instruction address.
- `F/M/C/A/N` block access to `$0000-$03FF` unless prefixed with `!`. `D` is always allowed.
- Direct vector-hook edits with `!M` are non-atomic and debug-only. Writing live bytes at `$0080-$0088` (especially `$0083-$0085`) can produce mixed-byte jumps, wrong dispatch, hangs/crashes, or temporary vector-name mismatch while patching.
- Game ask hook (`GAME ASK`, older text: `POST ASK`) is one-shot: it is set on Reset and when NMI returns to monitor, then cleared after first use.
- Hook flag is fixed/reserved at `$0078` (`GAME_ASK_PENDING`). Manual control: `!M 78 01` sets pending; `!M 78 00` clears pending.
- Terminal width byte is fixed/reserved at `$007A` (`TERM_COLS`): `28/50/84` for `40/80/132` columns.
- Terminal-width prompt timeout byte is fixed/reserved at `$007B` (`TERM_WIDTH_TIMEOUT`): `00=wait forever`, `01-FF=seconds`, default `08`.
- User ZP range is reserved at `$0090-$00FF`.
- User-program origin policy: avoid `$0000-$03FF` in normal operation (protected by default for write/execute-adjacent commands).
- Minimum practical user-program origin is `$0800`.
- Preferred default user-program origin is `$1000` (recommended for demos and monitor interoperability).

4) Verify / Error Outputs

Operation	Message / Behavior
Modify verify fail	`M VERIFY FAILED AT ADDR` + failing address.
Fill verify fail	`F VERIFY FAILED AT ADDR` + failing address.
Copy verify fail	`C VERIFY FAILED AT ADDR` + failing address.
Dump range error	`D RANGE ERROR`.
Unassemble range error	`U RANGE ERROR`.
Assembler branch range error	`A BRANCH RANGE ERROR`.
BRK debug context	Printed as two lines: `CURR:` and `NEXT:` on one line, then `STATE:` on the next line. For `N`-generated temporary breaks, `CURR:` shows the restored original instruction.
Bad syntax	Per-command usage lines (e.g. `USAGE: M [START [B0..B15]]`).

5) API Reference (Macros and Functions)

Use this section when calling monitor functionality from your own assembly code.

5.1) Macro Reference (`macros.inc`)

Macro	Parameters	Behavior / Notes
`PUSH`	`PUSH p1 [,p2] [,p3] [,p4]`	Pushes listed registers in given order. Supported tokens: `A/X/Y/P` (case-insensitive).
`PULL`	`PULL p1 [,p2] [,p3] [,p4]`	Pops listed registers in given order. Keep ordering compatible with prior `PUSH`.
`REPEAT`	`REPEAT Routine, Count`	Calls `JSR Routine` repeatedly `Count` times. Preserves `X` via push/pull.
`PRT_CSTRING`	`PRT_CSTRING Label`	Prints null-terminated string at `Label` via `PRT_C_STRING`.
`DUMP`	`DUMP Start, EndExclusive`	Convenience wrapper for `MEM_DUMP` with explicit exclusive end.
`FILL`	`FILL Start, EndInclusive, B0 [,B1] [,B2] [,B3] [,B4]`	Loads pattern bytes (1..5) and calls `MEM_FILL_PATTERN`. End is inclusive in macro syntax.
`COPY`	`COPY SrcStart, SrcEndInclusive, DstStart`	Calls overlap-safe `MEM_COPY_RANGE`. Source end is inclusive in macro syntax.
`COPY_BLOCK`	`COPY_BLOCK SrcStart, Length, DstStart`	Compatibility wrapper that expands to `COPY SrcStart,(SrcStart+Length-1),DstStart`.
`CMP_CSTRING`	`CMP_CSTRING AddrA, AddrB`	Wrapper for project-specific string compare symbols/routine (`STRCMP_PTR_*`, `STR_COMPARE`). Use only when those symbols are provided by your build.

5.2) Callable Function Reference

Practical entry points for extensions and integration.

Routine	Input	Output	Flags	ZP / Memory Use
`INIT_SERIAL`	None	UART initialized	Unchanged	None
`WRITE_BYTE`	`A` =char	Char sent to UART, LED updated	Unchanged	None
`READ_BYTE`	None	`A` =received char (ROM read)	ROM-defined	None
`CHECK_BYTE`	None	`A` =status	`C=1` if RX empty	None
`RBUF_INIT`	None	Input ring reset	Unchanged	Uses generic buffer descriptor core
`BUF_INIT`	Active descriptor pointers set	Head/Tail/Count zeroed	Unchanged	Uses `BUF_*_PTR`
`BUF_PUT_A`	`A` =byte	Byte queued	`C=0` stored, `C=1` full	Uses `BUF_*_PTR`, `BUF_SIZE`
`BUF_GET_A`	None	`A` =byte	`C=0` byte, `C=1` empty	Uses `BUF_*_PTR`, `BUF_SIZE`
`CMD_DISPATCH`	`A` =command letter	Handler called from table	`C=0` handled, `C=1` unknown	Uses `CMD_TABLE`, `CMD_POST_ACTION`
`MEM_DUMP`	`PTR_DUMP_CUR` =start (inc), `PTR_TEMP` =end (exc)	Formatted hex+ASCII dump with 8+8 separator	Unchanged	Uses `PTR_DUMP_CUR`, `PTR_DUMP_END`, `PTR_LEG`, `MEM_DUMP_CNT`
`MEM_DISASM_65C02`	`PTR_DUMP_CUR` =start (inc), `PTR_TEMP` =end (inc)	65C02 disassembly output (`ADDR: MNM OPERAND`)	Unchanged	Uses `PTR_DUMP_CUR`, `PTR_DUMP_END`, `PTR_TEMP`, `PTR_LEG`, `DIS_*`
`MEM_FILL_PATTERN`	`PTR_DUMP_CUR` =start (inc), `PTR_DUMP_END` =end (exc), `F_COUNT` =pattern length, `F_PATTERN` =pattern bytes	Fills range with repeating pattern	`C=0` complete, `C=1` aborted (verify/protect)	Uses `PTR_DUMP_CUR`, `PTR_DUMP_END`, `F_COUNT`, `F_PATTERN`, `F_PAT_IDX`
`MEM_COPY_RANGE`	`PTR_LEG` =src start (inc), `PTR_DUMP_END` =src end (exc), `PTR_TEMP` =dst start	Copies source to destination (overlap-safe)	`C=0` complete, `C=1` aborted (verify/protect)	Uses `PTR_LEG`, `PTR_DUMP_CUR`, `PTR_DUMP_END`, `PTR_TEMP`, `CMD_PARSE_VAL`

`CMD_DO_ASM`	`CMD_LINE = A START [INSN]`	Interactive tiny assembler	`.` exits	Uses `CMD_LINE`, `PTR_TEMP`, opcode tables, and `ASM_*` / `DIS_*` scratch

6) Parser and Buffer Limits

- `CMD_MAX_LEN = 31` characters (excluding null terminator).
- `RBUF_SIZE = 32` bytes.
- One-command history is kept for up-arrow repeat (`CMD_LAST_LINE`).
- Hex token parser accepts 1..4 hex digits, optional `$` prefix.
- `M` and `F` inline byte lists: max 16 bytes each.
- `!` is consumed as a command prefix, then normal parsing continues.

7) Memory Usage

Build Section Usage (current)

Section	ORG	Size (hex)	Size (dec)
PAGE0	`$0030`	`$60`	96
CODE	`$8000`	`$2725`	10021
KDATA	`$A725`	`$12A8`	4776
UDATA	`$0200`	`$7F`	127
Total	-	`$3AAC`	15020

RAM Layout Highlights

- PAGE0 starts at `$0030`. Includes parser state, dump state, debug snapshot, vector hooks, and active buffer descriptor pointers.
- Guard policy reserves monitor PAGE0 through `$008F`; user ZP is reserved at `$0090-$00FF`.
- `KDATA` floats directly behind `CODE` (current build start: `$A725`).
- Fixed/pinned bytes: `GAME_ASK_PENDING=$0078`, `BRK_FLAG=$0079`, `TERM_COLS=$007A`, `TERM_WIDTH_TIMEOUT=$007B`, `RST_HOOK=$0080`, `NMI_HOOK=$0083`, `IRQ_HOOK=$0086`, `BRK_HOOK=$0089`, `HW_HOOK=$008C`.
- Hardware vectors are fixed at the top page: `NMI=$FFFA`, `RST=$FFFC`, `IRQ/BRK=$FFFE`.
- Detailed zero-page map: `ZERO_PAGE_USAGE.md` and `ZERO_PAGE_USAGE.pdf`.
- UDATA starts at `$0200`:

```
RBUF_DATA    32 bytes
CMD_LINE     32 bytes (31 + NUL)
CMD_LAST_LINE 32 bytes (31 + NUL)
RESET_COOKIE  4 bytes
F_PATTERN    16 bytes
DBG_TAG_BUF   6 bytes
```

8) Notes for Integrators

- Command parser uppercases incoming command bytes before parse/dispatch.
- Command execution is table-driven via `CMD_TABLE`.
- Input buffering now uses a generic descriptor-based core bound to the ring buffer.
- `Q` path relies on NMI latch (`SYSF_NMI_FLAG_M`) and then re-enters monitor cleanly.

9) Planned Commands (Appendix, Provisional)

This appendix documents planned command architecture and roadmap intent only.

Proviso: change is constant. These plans are not stable API and may change before publish.

9.1) Grammar Direction

- Primary model: `noun verb [args...]` (namespace first, action second).
- Direct-action commands may still exist where practical (for example jump/execute style flow).
- Parser should accept both spaced and fused forms for operator speed.

9.2) Canonical Input Compatibility

- Parser policy: token 1 selects namespace and remains locked for that line (no cross-namespace fallback).
- `X S` and `XS` should map to the same internal command key.
- `X R` and `XR` should map to the same internal command key.
- `M D` and `MD` should map to the same internal command key.
- `I O V` and `IOV` should map to the same internal command key.
- `I C` and `IC` should map to the same internal command key.
- One canonical dispatch representation is preferred to avoid duplicate handlers.
- Aliases are spelling variants only (same meaning); command override behavior is intentionally avoided.

9.3) Namespace Plan

Root	Planned Role	Notes
`B`	Bank / FLASH	Reserved for FLASH-related operations (read/program/erase/verify family).
`I`	Info root	Carries nested subfamilies such as time and I/O.
`I T`	Time	Time moves under Info; top-level `T` is freed.
`I C`	Calculator	Implemented baseline (`I C` / `IC`) with 16-bit hex RPN tokens; future expansion remains planned.
`T`	Terminal	Repurposed top-level namespace for terminal-related operations.
`I O P`	PIA	Top-level `P` is freed; PIA moves under Info/IO.
`I O V`	VIA	Top-level `V` is freed; VIA moves under Info/IO.
`I O V T`	VIA timers	Hardware timers are expected under VIA tree.
`J`	Jump / Execute	Preferred home for execute flow if top-level execute letter changes.
`X`	Transfer / XMODEM	At minimum: send and receive support.
`S`	Search	Text and binary search families.
`M`	Memory family	Supports compact forms such as `MD` / `MM` as aliases.
`O`	Deferred decision	Candidate: chained execution wrapper; decision postponed.

9.4) Search Family Detail

- Planned base forms: `S C START END <text>` and `S B START END <pattern...>`.

- Current hit display format is `<HIT_ADDR>{ |*}<ROW_BASE>: ...`; `HIT_ADDR` is exact match start, and `ROW_BASE = HIT_ADDR & $FFF0`.
- Separator marker: `*` means the match continues into the next 16-byte row (for example `$B8AF*$B8A0` implies continuation at `$B8B0`).
- `S C` mode: unquoted text stops at first whitespace.
- `S C` mode: quoted delimiters can include `"`, `'`, and `` ` ``.
- `S C` mode: delimiter escape by doubling delimiter character.
- `S C` mode wildcards: `?` matches exactly one character, `*` matches zero or more characters.
- `S C` mode literals: `??` matches literal `?`, and `**` matches literal `*`.
- `S B` mode tokens: `HH` byte, `HHHH` little-endian word, nibble wildcard (`?A` / `A?` / `??`), and `*` byte wildcard.
- Candidate extensions: Pascal strings and high-bit-set text search modes.

9.5) XMODEM Requirement

- Before publish, provide both XMODEM receive and send paths.
- Preferred forms: `X R ...` and `X S ...` with fused aliases (`XR`, `XS`).
- Planned loader workflow shortcut: `L G S` / `LGS` (load Motorola S-record stream, then auto-jump to the S7/S8/S9 start address).

9.6) Vector + Safety Direction (Pre-Publish Requirement)

- Vector updates must support dynamic atomic update behavior.
- Handler-name contract direction: every patchable target exports `<HANDLER>` and `<HANDLER>_NAME` (ASCIIZ); retarget operations update target address and name pointer together.
- Critical windows include vector commit and FLASH routines.
- During critical windows, all EDU LEDs should flash to signal that NMI should not be pressed.
- NMI path should be guarded/deferred during critical windows instead of normal debug flow.
- Staged-update plus atomic-commit behavior is the intended implementation pattern.
- NMI retargeting direction: patch inactive slot fully, then commit via single-byte active-slot selector flip (no in-place live NMI hook rewrite).
- Direct `!M` edits to live vector hook bytes are allowed for bring-up/debug but are intentionally outside the production-safe retarget path.
- Mandate (non-changing requirement): any operation that mutates FLASH state or vector state must assert critical indication/guard behavior, including module/transient load paths; implementation detail may change, requirement does not.

9.7) Deferred Item

- `O` command semantics are intentionally deferred.
- If adopted as an operation chain wrapper, error policy and guard policy must be defined explicitly.

9.8) Active TODO (Pressing)

Now

- TODO: wrap `WDCMONv2` FLASH routine calls behind `bso2` wrapper/trampoline entry points.
- TODO: add a post-link map check that enforces `END_KDATA < $F000`.

Soon

- TODO: get the ACIA port on the EDU board running.

Before Publish

- TODO: provide XMODEM receive and send paths before publish (`X R` / `XR`, `X S` / `XS`).
- TODO: implement staged vector update plus atomic commit flow for runtime retargeting.
- TODO: enforce critical-window behavior for FLASH/vector mutation paths (LED warning plus NMI guard/defer).

- TODO: enforce dangerous `B` operation policy (`!` required, explicit confirmation, and fail-closed behavior without mutation).
- TODO: add deterministic status reporting for dangerous operations (status code byte plus `OK` / `ABORTED` / `VERIFY_FAIL` / `FLASH_FAIL` / `DENIED`).
- Deferred (not current TODO): text compression/decompression, tokenization/RLE, and TX ring architecture while 32K FLASH headroom is sufficient.

9.9) Flash / Bank Safety Policy (Critical, Non-Negotiable)

- `B` must not execute dangerous operations by default.
- `bso2` plans to use `WDCMONv2` FLASH routines through wrappers/trampolines.
- Integration intent is behavioral/protocol compatibility via wrapper entry points, not direct source-text copy.
- Any dangerous `B` operation requires both force-prefix `!` and explicit user confirmation.
- Dangerous operations include at minimum erase, program/write, monitor self-update, vector commit, and bank activation/commit transitions.
- If `!` is absent, dangerous operations fail closed with no side effects.
- Confirmation must be operation-specific (typed intent token), not an implicit continue.
- During dangerous operations: enter critical guard mode before mutation starts, flash all LEDs, and guard/defer NMI debug flow until critical mode exits.
- On verify/check failure: abort mutation, exit critical mode cleanly, and report explicit status.
- Required output for dangerous operations: status code byte plus textual result (`OK`, `ABORTED`, `VERIFY_FAIL`, `FLASH_FAIL`, `DENIED`).

9.10) Board Self-Update Policy

- Board self-update is always dangerous and always requires `!` plus explicit confirmation.
- Before final commit, display target region, byte count, and integrity value (checksum/hash when available).
- Preferred execution shape: preflight validation, stage payload, erase/program, verify, then commit/activate.
- Avoid in-place blind overwrite as the only strategy; preserve a recovery path.
- Self-update is fully covered by the non-changing mandate: any FLASH/vector mutation path (including module/transient load/activation) must assert critical indication and guard behavior.

9.11) Host Tooling Direction (Linux GNU C)

- Critical FLASH workflows are expected to have a Linux GNU C host path.
- Python helpers may exist for convenience, but they are not the required path for critical FLASH operations.
- Preferred host model: raw serial protocol wrappers in C with explicit timeout/error handling and deterministic status reporting.

10) Legal Notice

- `WDC`, `W65C02`, and `W65C02EDU` are names associated with Western Design Center, Inc.
- This project is independent and is not affiliated with or endorsed by Western Design Center, Inc.
- This repository does not redistribute WDC tool binaries or WDC ROM images.
- Any third-party source code or text should be included only under its original license terms.