

Lecture 10 - Class Activity: Multiple Regression

Bill Perry

Analysis of Net Primary Production in Forests: A Modern Tidyverse Approach

Based on Michaletz et al. (2014) data

Introduction

This analysis examines the relationships between Net Primary Production (npp) and various climate and forest characteristics across global forest sites. We'll explore multicollinearity, model selection, and variable transformations.

Key Learning Objectives:

- Understand multicollinearity in multiple regression
- Learn model diagnostics and assumption checking
- Practice variable selection techniques
- Apply data transformations appropriately

Load Required Packages

```
# Load required packages
library(tidyverse) # For data manipulation and visualization
library(car)       # For regression diagnostics (VIF, etc.)
library(corrplot)  # For correlation plots
library(GGally)    # For pairs plots
library(broom)     # For tidy model outputs
library(performance) # For model performance metrics
library(see)       # For better diagnostic plots
```

Load and Explore the Data

```
# Load the forest npp data
forest_df <- read_csv("data/michaletz_etal_2014_clean.csv")
```

```
Rows: 1220 Columns: 8
— Column specification —————
Delimiter: ","
chr (1): leaf
dbl (7): npp, age, biomass, season, temp, precip, teb
```

```
i Use `spec()` to retrieve the full column specification for this data.
i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
# Display top lines
head(forest_df)
```

```
# A tibble: 6 × 8
  npp    age biomass season  temp precip   teb leaf
<dbl> <dbl>   <dbl>   <dbl> <dbl>   <dbl> <dbl> <chr>
1  2084  104.  18198.    11 25.3   1888   0.55 broadleaf
2  2234  333.  54523.    12 26.9   2348   0.6  broadleaf
3  2714  213.  41358.    12 26.9   2348   0.6  broadleaf
4  2828  114.  31557.    12 26.7   2784   1.25 broadleaf
5  2882  113.  21417    12 26.7   2784   1.25 broadleaf
6   774   79  11188     3 -3.53   408   1.8  broadleaf
```

Data Preparation

Following the original analysis, we'll focus on the key variables from a cleaned dataframe

1. Initial Exploration: Variable Relationships and Multicollinearity

Correlation Matrix and Visualization


```
# Create correlation matrix for numeric variables only
num_vars <- forest_df %>%
  select_if(is.numeric)

# Calculate correlation matrix
cor_matrix <- cor(num_vars, use = "complete.obs")

# Display correlation matrix
cor_matrix
```


	npp	age	biomass	season	temp	precip
npp	1.0000000	-0.153215979	0.4591083	0.5614272	0.5520590	0.531186333
age	-0.1532160	1.000000000	0.5923809	-0.2715014	-0.2307658	0.003642104
biomass	0.4591083	0.592380901	1.0000000	0.1317097	0.1551923	0.353901541
season	0.5614272	-0.271501387	0.1317097	1.0000000	0.9226905	0.567630275
temp	0.5520590	-0.230765849	0.1551923	0.9226905	1.0000000	0.576659967
precip	0.5311863	0.003642104	0.3539015	0.5676303	0.5766600	1.000000000
teb	-0.3167187	-0.011779155	-0.2748724	-0.2491779	-0.2495479	-0.291376661
teb						
npp	-0.31671865					
age	-0.01177916					
biomass	-0.27487245					
season	-0.24917787					
temp	-0.24954794					
precip	-0.29137666					
teb	1.00000000					

```
# Create a visual correlation plot
corrplot(cor_matrix, method = "color", type = "upper",
  addCoef.col = "grey45", tl.cex = 0.8, number.cex = 0.7)
```



Pairs Plot for Visual Inspection

```
# Create pairs plot to visualize relationships
# This replaces the original pairs() function with ggplot2
forest_df %>%
  select(-leaf) %>% # Exclude categorical variable for pairs plot
  ggpairs(
    upper = list(continuous = wrap("cor", size = 5)),
    lower = list(continuous = wrap("points", alpha = 0.6, size = 0.8))
  ) +
  theme_minimal()
```



2. Initial Multiple Regression Model

Let's start with a full model including all predictors:

```
# Fit initial model with all predictors (Model 1)
model_init <- lm(npp ~ age + biomass + season + temp +
  precip + teb + leaf, data = forest_df)

# Get model summary
summary(model_init)
```

Call:

```
lm(formula = npp ~ age + biomass + season + temp + precip + teb +
  leaf, data = forest_df)
```

Residuals:

Min	1Q	Median	3Q	Max
-1331.10	-206.27	-34.09	166.94	2760.41

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	583.92959	53.81169	10.851	< 2e-16 ***
age	-4.78822	0.28518	-16.790	< 2e-16 ***
biomass	0.03154	0.00122	25.848	< 2e-16 ***
season	41.18220	9.49073	4.339	1.55e-05 ***
temp	4.61281	4.37372	1.055	0.291788
precip	0.09674	0.02852	3.392	0.000716 ***
teb	-2.12880	1.08408	-1.964	0.049794 *
leafneedle	-267.00569	22.43078	-11.904	< 2e-16 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 351.7 on 1212 degrees of freedom

Multiple R-squared: 0.6415, Adjusted R-squared: 0.6394

F-statistic: 309.8 on 7 and 1212 DF, p-value: < 2.2e-16


Check for Multicollinearity

```
# Calculate Variance Inflation Factors (VIF)
vif_values <- vif(model_init)
vif_values
```

age	biomass	season	temp	precip	teb	leaf
1.993348	2.061766	7.079004	6.972147	1.831127	1.167007	1.236588

```
# Create a data frame for better visualization
vif_df <- data.frame(
  Variable = names(vif_values),
  VIF = as.numeric(vif_values)
) %>%
  arrange(desc(VIF))

# Visualize VIF values
ggplot(vif_df, aes(x = reorder(Variable, VIF), y = VIF)) +
  geom_col(fill = "steelblue", alpha = 0.7) +
  geom_hline(yintercept = 10, color = "red", linetype = "dashed",
    linewidth = 1) +
  geom_hline(yintercept = 5, color = "orange", linetype = "dashed",
    linewidth = 1) +
  coord_flip() +
  labs(
    title = "Variance Inflation Factors",
    subtitle = "Red line: VIF = 10 (serious concern), Orange line: VIF = 5 (moderate concern)",
    x = "Variables",
    y = "VIF"
  ) +
  theme_minimal()
```



Address Multicollinearity by Removing Growing Season

Based on the original analysis, season and Temperature are highly correlated. Let's remove season:

```
# Model 2: Remove season due to multicollinearity
model_2 <- lm(npp ~ age + biomass + temp + precip + teb + leaf,
              data = forest_df)

# Model summary
summary(model_2)
```

Call:

```
lm(formula = npp ~ age + biomass + temp + precip + teb + leaf,
    data = forest_df)
```

Residuals:

Min	1Q	Median	3Q	Max
-1309.94	-209.40	-42.65	167.71	2898.47

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	7.511e+02	3.785e+01	19.845	< 2e-16 ***
age	-5.004e+00	2.829e-01	-17.690	< 2e-16 ***
biomass	3.180e-02	1.228e-03	25.905	< 2e-16 ***
temp	2.112e+01	2.173e+00	9.718	< 2e-16 ***
precip	1.120e-01	2.851e-02	3.929	9.02e-05 ***
teb	-2.255e+00	1.092e+00	-2.066	0.039 *
leafneedle	-2.634e+02	2.258e+01	-11.666	< 2e-16 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 354.3 on 1213 degrees of freedom

Multiple R-squared: 0.6359, Adjusted R-squared: 0.6341

F-statistic: 353.1 on 6 and 1213 DF, p-value: < 2.2e-16

```
# Check VIF again
vif_values2 <- vif(model_2)
vif_values2
```


age	biomass	temp	precip	teb	leaf
1.932806	2.056724	1.696787	1.803266	1.166162	1.234906

3. Exploring Variable Transformations

Check the Shape of Relationships with Partial Regression Plots

```
# Create partial regression plots (Added Variable Plots)
# This helps us see the relationship between each predictor and response
# after accounting for other variables

par(mfrow = c(2, 3))
avPlots(model_2, main = "Partial Regression Plots")
```



```
par(mfrow = c(1, 1))
```

Apply Log Transformation to age

The original analysis found that age showed a curvy relationship. Let's try log transformation: Really what you should do is log transform of the response variable first..

```
# Create dataset with log-transformed age
forest_df <- forest_df %>%
  mutate(log_age = log10(age))

# Model 3: With log-transformed age
model_3 <- lm(npp ~ log_age + biomass + temp + precip + teb + leaf,
  data = forest_df)

# Model summary
summary(model_3)
```

Call:

```
lm(formula = npp ~ log_age + biomass + temp + precip + teb +
  leaf, data = forest_df)
```

Residuals:

Min	1Q	Median	3Q	Max
-----	----	--------	----	-----

```
-1282.97 -203.31 -23.13 163.75 2810.76
```

Coefficients:


	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	2.237e+03	8.961e+01	24.962	< 2e-16 ***
log_age	-1.012e+03	5.064e+01	-19.973	< 2e-16 ***
biomass	3.313e-02	1.194e-03	27.755	< 2e-16 ***
temp	1.723e+01	2.159e+00	7.982	3.33e-15 ***
precip	7.194e-02	2.781e-02	2.587	0.00981 **
teb	-2.315e+00	1.061e+00	-2.183	0.02925 *
leafneedle	-2.852e+02	2.177e+01	-13.105	< 2e-16 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 344.7 on 1213 degrees of freedom
 Multiple R-squared: 0.6553, Adjusted R-squared: 0.6536
 F-statistic: 384.4 on 6 and 1213 DF, p-value: < 2.2e-16

```
# Compare partial regression plots
par(mfrow = c(2, 3))
avPlots(model_3, main = "Partial Regression Plots (Log age)")
```

Partial Regression Plots (Log age)




```
par(mfrow = c(1, 1))
```

4. Model Diagnostics and Assumption Checking

```
# Create diagnostic plots
par(mfrow = c(1, 1))
plot(model_3, main = "Model Diagnostics")
```


Model Diagnostics

Residuals vs Fitted




Fitted values

$p \sim \log_age + biomass + temp + precip -$

Model Diagnostics

Q-Q Residuals




Theoretical Quantiles

$p \sim \log_age + biomass + temp + precip -$

Model Diagnostics

Scale-Location




Fitted values

$p \sim \log_age + biomass + temp + precip -$

Model Diagnostics

Residuals vs Leverage



Leverage

$p \sim \log_age + biomass + temp + precip -$


```
par(mfrow = c(1, 1))
```

Residuals - its the upper left above

```
# Check for normality of residuals
residuals_data <- data.frame(
  Fitted = fitted(model_3),
  Residuals = residuals(model_3),
  Standardized_Residuals = rstandard(model_3)
)

# Residuals vs Fitted plot using ggplot
ggplot(residuals_data, aes(x = Fitted, y = Residuals)) +
  geom_point(alpha = 0.6) +
  geom_smooth(method = "lm", color = "red") +
  geom_hline(yintercept = 0, linetype = "dashed") +
  labs(
    title = "Residuals vs Fitted Values",
    x = "Fitted Values",
    y = "Residuals"
  ) +
  theme_minimal()
```

```
`geom_smooth()` using formula = 'y ~ x'
```



Try Response Variable Transformation

Following the original analysis, let's try a cube root transformation of npp:

```
# Model 4: Cube root transformation of npp
forest_df <- forest_df %>%
  mutate(npp_cuberoot = npp^(1/3))

model_4 <- lm(npp_cuberoot ~ log_age + biomass + temp + precip +
  teb + leaf, data = forest_df)

summary(model_4)
```

Call:

```
lm(formula = npp_cuberoot ~ log_age + biomass + temp + precip +
    teb + leaf, data = forest_df)
```

Residuals:

Min	1Q	Median	3Q	Max
-4.0936	-0.5916	-0.0030	0.6463	5.0795

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	1.391e+01	2.601e-01	53.489	< 2e-16 ***
log_age	-3.151e+00	1.470e-01	-21.436	< 2e-16 ***
biomass	1.032e-04	3.464e-06	29.791	< 2e-16 ***
temp	4.507e-02	6.265e-03	7.194	1.10e-12 ***
precip	6.361e-05	8.072e-05	0.788	0.431
teb	-1.273e-02	3.078e-03	-4.135	3.79e-05 ***
leafneedle	-1.029e+00	6.317e-02	-16.283	< 2e-16 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 1 on 1213 degrees of freedom

Multiple R-squared: 0.6793, Adjusted R-squared: 0.6777


F-statistic: 428.2 on 6 and 1213 DF, p-value: < 2.2e-16

```
# Check diagnostics
```


```
par(mfrow = c(1, 1))
```

```
plot(model_4, main = "Model Diagnostics (Cube Root npp)")
```


Model Diagnostics (Cube Root npp)




Model Diagnostics (Cube Root npp)



Model Diagnostics (Cube Root)



Model Diagnostics (Cube Root)



```
par(mfrow = c(1, 1))
```

5. Model Simplification and Comparison

Remove Non-significant Variables

```
# Model 5: Remove non-significant Precipitation
model_5 <- lm(npp_cuberoot ~ log_age + biomass + temp + teb + leaf,
              data = forest_df)

summary(model_5)
```

```
Call:
lm(formula = npp_cuberoot ~ log_age + biomass + temp + teb +
    leaf, data = forest_df)
```

```
Residuals:
    Min       1Q   Median       3Q      Max
-4.1085 -0.5919  0.0019  0.6459  5.1261
```

```
Coefficients:
              Estimate Std. Error t value Pr(>|t|)
(Intercept)  1.396e+01  2.532e-01  55.120 < 2e-16 ***
log_age      -3.159e+00  1.465e-01 -21.559 < 2e-16 ***
biomass       1.040e-04  3.306e-06  31.465 < 2e-16 ***
temp          4.719e-02  5.658e-03   8.342 < 2e-16 ***
```

```

teb          -1.296e-02  3.064e-03  -4.231  2.5e-05 ***
leafneedle   -1.040e+00  6.150e-02 -16.910  < 2e-16 ***
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

Residual standard error: 1 on 1214 degrees of freedom
Multiple R-squared: 0.6791, Adjusted R-squared: 0.6778
F-statistic: 513.9 on 5 and 1214 DF, p-value: < 2.2e-16

```

# Compare models using AIC
model_comparison <- data.frame(
  Model = c("Model 4 (Full)", "Model 5 (No precip)"),
  AIC = c(AIC(model_4), AIC(model_5)),
  R_squared = c(summary(model_4)$r.squared, summary(model_5)$r.squared),
  Adj_R_squared = c(summary(model_4)$adj.r.squared, summary(model_5)$adj.r.squared)
)

model_comparison

```

	Model	AIC	R_squared	Adj_R_squared
1	Model 4 (Full)	3472.092	0.6792946	0.6777082
2	Model 5 (No precip)	3470.717	0.6791304	0.6778089

Model Performance and Interpretation

```

# Get tidy summary of final model
summary(model_5, conf.int = TRUE)

```

Call:
lm(formula = npp_cuberooot ~ log_age + biomass + temp + teb +
leaf, data = forest_df)

Residuals:

	Min	1Q	Median	3Q	Max
	-4.1085	-0.5919	0.0019	0.6459	5.1261

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	1.396e+01	2.532e-01	55.120	< 2e-16 ***
log_age	-3.159e+00	1.465e-01	-21.559	< 2e-16 ***
biomass	1.040e-04	3.306e-06	31.465	< 2e-16 ***
temp	4.719e-02	5.658e-03	8.342	< 2e-16 ***
teb	-1.296e-02	3.064e-03	-4.231	2.5e-05 ***
leafneedle	-1.040e+00	6.150e-02	-16.910	< 2e-16 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 1 on 1214 degrees of freedom
Multiple R-squared: 0.6791, Adjusted R-squared: 0.6778
F-statistic: 513.9 on 5 and 1214 DF, p-value: < 2.2e-16

using the sensemaker package

```
library(sensemakr)
# Calculate partial R-squared for all variables at once
partial_r2_sensemakr <- partial_r2(model_5)
partial_r2_sensemakr
```

```
(Intercept)    log_age    biomass    temp    teb    leafneedle
0.71450239 0.27686109 0.44919401 0.05421045 0.01453129 0.19064332
```

```
# Calculate partial R-squared for each variable
# Using the car package
print("Using car package Anova() with Type III sums of squares:")
```

```
[1] "Using car package Anova() with Type III sums of squares:"
```

```
anova_type2 <- Anova(model_5, type = "III")
print(anova_type2)
```

Anova Table (Type III tests)

Response: npp_cuberoot

	Sum Sq	Df	F value	Pr(>F)
(Intercept)	3039.52	1	3038.225	< 2.2e-16 ***
log_age	464.99	1	464.792	< 2.2e-16 ***
biomass	990.47	1	990.043	< 2.2e-16 ***
temp	69.61	1	69.584	< 2.2e-16 ***
teb	17.91	1	17.901	2.502e-05 ***
leaf	286.08	1	285.957	< 2.2e-16 ***
Residuals	1214.52	1214		

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```
# Convert F-statistics to partial R-squared
# Partial R² = F * df_num / (F * df_num + df_den)
f_stats <- anova_type2$`F value`[!is.na(anova_type2$`F value`)]
df_num <- anova_type2$Df[!is.na(anova_type2$`F value`)]
df_den <- anova_type2$Df[nrow(anova_type2)] # Residual df

partial_r2_from_f <- f_stats * df_num / (f_stats * df_num + df_den)

results_table <- data.frame(
  Variable = rownames(anova_type2)[!is.na(anova_type2$`F value`)],
  F_statistic = f_stats,
  p_value = anova_type2$`Pr(>F)`[!is.na(anova_type2$`F value`)],
  Partial_R_squared = partial_r2_from_f
)

print("Complete results with partial R-squared:")
```

```
[1] "Complete results with partial R-squared:"
```

```
print(results_table)
```

	Variable	F_statistic	p_value	Partial_R_squared
1	(Intercept)	3038.22472	0.000000e+00	0.71450239
2	log_age	464.79225	1.532052e-87	0.27686109
3	biomass	990.04285	2.085787e-159	0.44919401
4	temp	69.58365	1.967636e-16	0.05421045
5	teb	17.90111	2.501886e-05	0.01453129
6	leaf	285.95672	9.100842e-58	0.19064332

6. Alternative Approach: Standardized Variables

Following the original analysis, let's also try the standardized approach:

```
# Create standardized variables
forest_standardized <- forest_df %>%
  mutate(
    npp_sqrt_scaled = scale(sqrt(npp))[,1],
    log_age_scaled = scale(log10(age))[,1],
    biomass_scaled = scale(biomass)[,1],
    temp_scaled = scale(temp)[,1],
    precip_scaled = scale(precip)[,1],
    teb_scaled = scale(teb)[,1]
  )

# Standardized model
model_std <- lm(npp_sqrt_scaled ~ log_age_scaled + biomass_scaled +
  temp_scaled * precip_scaled + teb_scaled,
  data = forest_standardized)

# Summary
summary(model_std)
```

Call:

```
lm(formula = npp_sqrt_scaled ~ log_age_scaled + biomass_scaled +
  temp_scaled * precip_scaled + teb_scaled, data = forest_standardized)
```

Residuals:

Min	1Q	Median	3Q	Max
-3.14438	-0.38836	-0.03068	0.39178	3.01216

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)	
(Intercept)	-0.064952	0.020075	-3.235	0.001247	**
log_age_scaled	-0.543699	0.024500	-22.192	< 2e-16	***
biomass_scaled	0.691415	0.025313	27.315	< 2e-16	***
temp_scaled	0.215693	0.023304	9.256	< 2e-16	***
precip_scaled	-0.008188	0.028714	-0.285	0.775563	
teb_scaled	-0.071775	0.018879	-3.802	0.000151	***
temp_scaled:precip_scaled	0.112727	0.017068	6.605	5.94e-11	***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 0.6113 on 1213 degrees of freedom

Multiple R-squared: 0.6281, Adjusted R-squared: 0.6263
F-statistic: 341.5 on 6 and 1213 DF, p-value: < 2.2e-16

7. Key Findings and Conclusions

1. MULTICOLLINEARITY:

- Growing season length and temperature were highly correlated
- Removed growing season to address multicollinearity

2. VARIABLE TRANSFORMATIONS:

- Log transformation of age improved model fit
- Cube root transformation of npp addressed assumption violations

3. FINAL MODEL RESULTS:

- Significant predictors: age (negative), biomass (positive), temp (positive)
- teb had negative effect, Leaf type differences were significant

4. BIOLOGICAL INTERPRETATION:

- Younger stands had higher npp (for given biomass)
- Higher biomass associated with higher npp
- temp positively related to npp
- Coniferous forests had lower npp than broadleaf forests

References and Additional Notes

This analysis is based on:

- **Michaletz, S.T., Cheng, D., Kerkhoff, A.J. & Enquist, B.J.** (2014). Convergence of terrestrial plant production across global climate gradients. *Nature*, 512, 39-43.

Key Learning Points:

1. **Multicollinearity Detection:** Use VIF values and correlation matrices
2. **Variable Transformations:** Log and power transformations can improve model fit
3. **Model Diagnostics:** Always check residual plots and assumption violations
4. **Model Comparison:** Use AIC and other criteria for model selection
5. **Interpretation:** Focus on biologically meaningful relationships

```
# Session information for reproducibility  
sessionInfo()
```

```
R version 4.5.1 (2025-06-13)  
Platform: aarch64-apple-darwin20  
Running under: macOS Tahoe 26.0.1
```

```
Matrix products: default  
BLAS: /Library/Frameworks/R.framework/Versions/4.5-arm64/Resources/lib/libRblas.0.dylib  
LAPACK: /Library/Frameworks/R.framework/Versions/4.5-arm64/Resources/lib/libRlapack.dylib;  
LAPACK version 3.12.1
```

```
locale:  
[1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
```

```
time zone: America/Chicago
```


tzcode source: internal

attached base packages:

[1] stats graphics grDevices utils datasets methods base

other attached packages:

[1] sensemakr_0.1.6	see_0.12.0	performance_0.15.1	broom_1.0.10
[5] GGally_2.4.0	corrplot_0.95	car_3.1-3	carData_3.0-5
[9] lubridate_1.9.4	forcats_1.0.1	stringr_1.5.2	dplyr_1.1.4
[13] purrr_1.1.0	readr_2.1.5	tidyr_1.3.1	tibble_3.3.0
[17] ggplot2_4.0.0	tidyverse_2.0.0		

loaded via a namespace (and not attached):

[1] gtable_0.3.6	xfun_0.53	insight_1.4.2	lattice_0.22-7
[5] tzdb_0.5.0	vctrs_0.6.5	tools_4.5.1	generics_0.1.4
[9] parallel_4.5.1	pkgconfig_2.0.3	Matrix_1.7-4	RColorBrewer_1.1-3
[13] S7_0.2.0	lifecycle_1.0.4	compiler_4.5.1	farver_2.1.2
[17] codetools_0.2-20	htmltools_0.5.8.1	yaml_2.3.10	Formula_1.2-5
[21] pillar_1.11.1	crayon_1.5.3	abind_1.4-8	nlme_3.1-168
[25] ggstats_0.11.0	tidyselect_1.2.1	digest_0.6.37	stringi_1.8.7
[29] labeling_0.4.3	splines_4.5.1	fastmap_1.2.0	grid_4.5.1
[33] cli_3.6.5	magrittr_2.0.4	utf8_1.2.6	withr_3.0.2
[37] scales_1.4.0	backports_1.5.0	bit64_4.6.0-1	timechange_0.3.0
[41] rmarkdown_2.30	bit_4.6.0	hms_1.1.3	evaluate_1.0.5
[45] knitr_1.50	mgcv_1.9-3	rlang_1.1.6	glue_1.8.0
[49] rstudioapi_0.17.1	vroom_1.6.6	jsonlite_2.0.0	R6_2.6.1