

머신러닝 프로그래밍

Machine Learning Programming

Lecture 13 : 이상감지 관련 논문



충북대학교
CHUNGBUK NATIONAL UNIVERSITY





충북대학교
산업인공지능연구센터

시간-주파수 마스크 오토인코더를 위한 시계열 이상 탐지

IEEE ICDE 2024

Motivation: The Limits of Current SSL

- ▶ **Labeled Data Scarcity:** Real-world industrial data rarely has comprehensive fault labels.
- ▶ **Limitations of Contrastive Learning (CL):**
 - ✓ **Abnormal Bias:** If unlabeled training data contains hidden anomalies, CL models mistakenly learn them as 'normal' patterns.
 - ✓ **False Alarms:** Minor environmental shifts are often misclassified as anomalies.
- ▶ **Why Masked Autoencoders (MAE)?** By focusing on reconstructing masked inputs rather than comparing samples, MAEs learn the intrinsic normal prototype, showing strong immunity to abnormal bias.




Problem Definition: The Missing Piece

- ▶ Existing MAEs in TSAD focus solely on the **Temporal domain**.
- ▶ However, 1D time-series data carries crucial physical properties in its **Frequency domain** (e.g., periodic vibrations, spectral amplitudes).
- ▶ Temporal-only reconstruction often fails to capture subtle, frequency-level anomalies.
- ▶ **Goal:** To develop a Dual-Branch MAE that captures both temporal trends and spectral periodicities.

TFMAE 건축

II III IV V




Dual-Branch Masked Autoencoder


- ▶ The TFMAE framework processes data through two parallel branches:
- ▶ **Temporal Branch:** Masks and reconstructs temporal patches.
- ▶ **Frequency Branch:** Converts to the frequency domain via FFT, then masks and reconstructs amplitude components.
- ▶ **Cross-Domain Alignment:** Ensures representations from both domains are consistent.

방법: 마스킹 전략

II III IV V



Overview of window-based temporal masking




Overview of amplitude-based frequency masking

- ▶ **Temporal Masking:** Divides the signal into non-overlapping patches.
 - ✓ **Masks patches with larger variations** to eliminate 75% of observed anomalies.
- ▶ **Frequency Masking:**
 - ✓ Computes the amplitude spectrum using Fast Fourier Transform (FFT).
 - ✓ **Masks components with smaller amplitudes** to remove pattern anomalies.
- ▶ **Efficiency:** Only the unmasked ('visible') patches/components are fed into the Transformer encoders.

방법: 트랜스포머 기반 오토인코더

II III IV V



Transformer-based Autoencoders

- Left: Transformer-based decoder-only autoencoder for recovering masked frequencies, where $\oplus$ indicates elementwise addition.
- Right: Transformer-based autoencoder for recovering masked observations, where $||$ denotes inserting masked representations into learned unmasked representations.

방법: 모델 훈련

▶ Joint Training Loss:

- ✓ **Reconstruction Loss:** Mean Squared Error (MSE) between original and reconstructed data in both domains.
- ✓ **Contrastive Loss:** Minimizes the discrepancy between Temporal and Frequency embeddings to align cross-domain knowledge.


▶ Anomaly Scoring (Inference):

- ✓ The model attempts to reconstruct incoming data as 'normal'.
- ✓ **Anomaly Score = Temporal Recon Error + Frequency Recon Error.**
(Higher error = Anomaly).

- ▶ **Datasets & Baselines**
- ▶ **5 Benchmark Datasets:**
 - ✓ **SMD** (Server Machine Dataset)
 - ✓ **MSL / SMAP** (NASA Spacecraft Telemetry)
 - ✓ **SWAT / WADI** (Water Treatment & Distribution Systems)
- ▶ **Baselines:** Compared against 10+ SOTA models including Anomaly Transformer, DCdetector, TimesNet, and TranAD.
- ▶ **Evaluation Metrics:** Precision, Recall, and F1-Score.

실험 결과

I II III IV V




Robustness to Abnormal Bias

- ▶ **Experiment:** Training data was intentionally contaminated with a high ratio of anomalies (up to 10%).
- ▶ **Result:** While Contrastive Learning models (like Anomaly Transformer) suffered severe performance drops due to abnormal bias, **TFMAE maintained stable accuracy.**
- ▶ **Reason:** The masked reconstruction task forces the model to learn only the dominant, normal physical structure.

실험 결과

I II III IV V



Qualitative & Computational Analysis

- ▶ **Reconstruction Plot:** Visualizations show TFMAE successfully reconstructs normal patterns but completely fails to reconstruct anomalous spikes (which is ideal for AD).
- ▶ **Feature Distribution (t-SNE):** Normal and anomalous features are distinctly separated in the latent space.
- ▶ **Efficiency:** Processing only the unmasked tokens (25% of data) makes TFMAE computationally lighter and faster to train than full-sequence Transformers.

- **A Novel Paradigm:** Proposed TFMAE, successfully integrating Time and Frequency domain representations within a Masked Autoencoder framework.
- **Solving Abnormal Bias:** Effectively mitigated the abnormal bias and distribution shift problems prevalent in contrastive learning-based AD models.
- **SOTA Performance:** Achieved state-of-the-art anomaly detection accuracy and high robustness across multiple real-world industrial datasets.
- **Efficiency:** Demonstrated that high-ratio masking significantly reduces computational overhead while actually improving representational learning.