

# SQL-Python

Sean Sall

May 12th, 2016

# Objectives:

Today's objectives:

- Learn how to connect and run Postgres queries from Python
- Understand psycopg2's cursors, specifically executes and commits
- Learn how to generate dynamic queries from within Python

# Agenda

- SQL-Python motivation
- psycopg2 introduction and workflow
  - ▶ Creating databases
  - ▶ Executing queries (static and dynamic)

# SQL-Python Motivation

- Why write SQL queries from within Python?
  - ▶ Allows for the combination of data sources all in one place (e.g. you can use Python to pull data from other databases as well)
  - ▶ Allows for use of all our Python tools when working with the data (dataframes, machine learning models, etc.)
  - ▶ Allows for more easy dynamic query generation and hence automations

- psycopg is the Python library that we'll use to interface to a Postgres database from within Python
- There are Python libraries to connect to almost any database that you might want to:
  - ▶ MySQL : `mysql-connector-python`
  - ▶ SQLite : `sqlite`
  - ▶ MongoDB : `pymongo`

- There are five general steps to a pyscopg2 workflow:
  - 1 Open a connection
  - 2 Create a cursor object
  - 3 Use the cursor to execute SQL queries
  - 4 Commit SQL actions
  - 5 Close the cursor and connection

# Open a Connection

```
import psycopg2

conn = psycopg2.connect(dbname='my_playground',
                        user='sallamander', host='localhost')
```

- The host can be used to connect to a remote database as well
- Sometimes we have to put in the password or port arguments as well

# Create a cursor Object

```
cur = conn.cursor()
```

- A **cursor** is a control structure that enables traversal over the records in a database
  - ▶ Executes queries to fetch data
  - ▶ Handles transactions with our SQL database
- When results are returned from a cursor object, they are returned as a generator (e.g. it gives back the results lazily)
- Furthermore, each result in the result set can only be accessed **once** (if we want it again we have to re-run the query)



# Use the cursor to execute SQL queries

```
query = '''SELECT name
            FROM users
            INNER JOIN disney_chars
                ON users.fav_disney_char = disney_chars.id
            WHERE disney_chars.prince = 'true';'''
cur.execute(query)
```

- The cursor object (cur) will now hold the results

# Getting results from the cursor

- There are a number of ways to grab results from the cursor:
  - ▶ `cur.fetchone()` - Returns the next result
  - ▶ `cur.next()` - Returns the next result
  - ▶ `cur.fetchmany(n)` - Returns the next `n` results
  - ▶ `cur.fetchall()` - Returns all results in the result set
  - ▶ `for res in cur:` - Iterates over all results in the cursor

# Commit the Results

- Data changes are not actually stored until you **commit** them
  - ▶ This is only important if you are creating a database/datatable, or altering the data in an existing database/datable

```
query='''ALTER TABLE disney_chars  
        RENAME mulan TO the_best;'''  
cur.execute(query)  
conn.commit()
```

- The column's name is **not changed in the db** until we **issue the commit**
  - ▶ It is, however, **changed on the connection and cursor** as soon as we **issue the execute**

# Rollback

- If you make a mistake on a query, you need to use the rollback function to restart the transaction

```
conn.rollback()
```

# Close the connection

- Don't forget to do this!!

```
cur.close()  
conn.close()
```

- Closing the cursor is technically optional because closing the connection closes all cursor objects, but it is good practice to close both

# A Short Note

- Anything executed through the `.query` method on the cursor is done so as a **temporary transaction**. Since Postgres doesn't have these at the database level, we have to specify an additional attribute on the connection before trying to perform database level operations (create/dropping databases)

```
conn = psycopg2.connect(dbname='my_playground',  
                        user='sallamander', host='localhost')  
conn.autocommit = True
```

# Dynamic Queries

- `psycopg2` gives us the ability to create dynamic queries, where we can insert certain values into our queries on the fly.

# Dynamic Queries - The Wrong Way

- **THE WRONG WAY** to write a dynamic query:

```
unsafe_query = '''SELECT * FROM users
                WHERE name =
                ''' + name_var
```

```
other_unsafe_query = '''SELECT * FROM
                      users WHERE name = %s
                      ''' % name_var
```

What happens if somebody inputs a `name_var` equal to " 'Sean'; DROP TABLE users; "?

Something like this is referred to as **SQL INJECTION**.



# Dynamic Queries - The Right Way

- The **RIGHT WAY** to write a dynamic query is to use the `.execute()` method on our `cursor()` object, passing the dynamic part as the second argument:

```
cursor.execute(''SELECT * FROM  
               users WHERE name = %s'', (name_var, ))
```

- This ensures that the variables you are inserting are kept as the same variable type. If we tried to perform **SQL INJECTION** using " 'Sean'; DROP TABLE users;", using the `.execute()` method means that we look for a `name` exactly equal to this string (and we don't end up finding one, nor deleting the data table).