

## @file.dreaminfo.biz (NIS 서버 설정)

```
# apt-get install nis
```

```
+-----| Configuring nis |-----+
| Please choose the NIS "domainname" for this system. If you want this |
| machine to just be a client, you should enter the name of the NIS domain |
| you wish to join. |
| |
| Alternatively, if this machine is to be a NIS server, you can either |
| enter a new NIS "domainname" or the name of an existing NIS domain. |
| |
| NIS domain: |
| dreaminfo.biz |
| |
| <Ok> |
+-----+
```

```
# vim /etc/default/nis
```

```
5 # Are we a NIS server an
6 NISSERVER=master
7
8 # Are we a NIS client?
9 NISCLIENT=false
// 빨스다
```

```
# vim /etc/ypserv.securenets
```

```
12 # Always allow access for localhost
13 255.255.255.0 172.16.0.0
14 255.255.255.0 192.168.1.0
15 255.255.255.0 192.168.0.0
16
17 # This line gives access to everybody
18 0.0.0.0 0.0.0.0
```

```
# vim /var/yp/Makefile
```

```
52 MERGE_PASSWD=true
53
54 # Should we merge the
55 # MERGE_GROUP=true|fal
56 MERGE_GROUP=true
57
```

```
# /usr/lib/yp/ypinit -m
```

next host to add 라고 물으면 Ctrl+D을 눌러라.

Is this correct? [y/n:y] y

```
# systemctl restart nis
```

```
# cd /var/yp
```

```
# make
```

## @ NIS Client 설정

```
apt-get -y install nis
```

NIS domain 이름은 dreaminfo.biz로 설정.

```
# vim /etc/default/nis
```

```
6 NISSERVER=false
7
8 # Are we a NIS client?
9 NISCLIENT=true
10
```

```
# vim /etc/yp.conf
```

```
13 # ypserver ypserver.network.com
14 domain dreaminfo.biz server file.dreaminfo.biz
```

```
# vim /etc/nsswitch.conf
```

```
7 passwd:          compat nis
8 group:           compat nis
9 shadow:          compat nis
10 gshadow:         files
11
```

```
# systemctl restart nis
```