

@ca.worldsign.org

Adding user01~05

apt-get install dovecot-imapd sensible-mda sendmail sasl2-bin

vim /etc/default/saslauthd

```
6 # Should saslauthd run
7 START=yes
8
```

vim /etc/mailname

```
1 mail.worldsign.org
```

vim /etc/mail/local-host-names

```
1 localhost
2 ca.worldsign.org
3 mail.worldsign.org
```

vim /etc/mail/access //상대 도메인 사용자와 메일 송-수신 가능하도록 relay 설정

```
140 mail.dreaminfo.biz RELAY
```

vim /etc/mail/sendmail.mc

```
57 DAEMON_OPTIONS(`Family=inet, Name=MTA-v4, Port=smtp')dnl
58 dnl DAEMON_OPTIONS(`Family=inet6, Name=MSP-v6, Port=submission, M=Ea, Addr=::1')dnl
59 DAEMON_OPTIONS(`Family=inet, Name=MSP-v4, Port=submission, M=Ea')dnl
```

```
98 dnl #
99 include(`/etc/mail/m4/dialup.m4')dnl
100 include(`/etc/mail/m4/provider.m4')dnl
101 include(`/etc/mail/sasl/sasl.m4')dnl
102 dnl #
103
104
105 dnl # Masquerading options
106 FEATURE(`always_add_domain')dnl
107 MASQUERADE_AS(`mail.worldsign.org')dnl
108 FEATURE(`allmasquerade')dnl
109 FEATURE(`masquerade_envelope')dnl
110 _
111 dnl # Default Mailer setup
112 MAILER_DEFINITIONS
113 MAILER(`local')dnl
114 MAILER(`smtp')dnl
115 MAILER(`procmail')dnl
```

```
# sendmailconfig
```

```
# systemctl restart sendmail
```

```
# netstat -nl | grep 25
```

```
# vim /etc/dovecot/conf.d/10-auth.conf
```

```
10 disable_plaintext_auth = no
```

```
# systemctl restart dovecot
```