

Command	Explanation	Package
mean()	gives the mean	modeest
sd()	gives the standard deviation	
mfv()	gives the mode (m ost f requent v alue)	
min()	gives the minimum value	
max()	gives the maximum value	
quantile()	gives the specified quantile value	
IQR()	gives the inter-quartile range	stargazer
stargazer()	shows nicely formatted statistics for data frames	
str()	shows structure of object	
subset()	shows a specified subset of the data	moments
skewness()	gives skewness of data	
kurtosis()	gives kurtosis of data	
hist()	makes histogram of data	
pie()	makes a pie chart	
barplot()	makes a bar plot	
boxplot()	makes a box plot	
table()	gives tabular results of categorical variables	

Examples

```
quantile(donuts, .25, type = 6)
```

Gives the first quartile of vector `donuts`. Always use `type = 6` option; same with `IQR()`.

```
str(perkins, vec.len = 1)
```

Shows names, types of data in `perkins` data frame; shows one observation.

```
subset(perkins, default_rate == 100)
```

Shows the subset of schools with a 100% default rate in `perkins` data frame.

```
hist(
  perkins$default_rate,
  xlab = "Default Rate",
  main = "Perkins Loan Default Rate Histogram"
)
```

Displays histogram for `default_rate` variable from `perkins` data frame, setting custom labels.

```
table(nytoilets$Borough)
```

Tabulates number of observations for each category in `nytoilets` variable `Borough`.