

Exploring data using R

Kamarul Imran Musa, Wan Nor Arifin

March 17, 2018

Contents

1	Introduction to R	5
1.1	R and RStudio	5
1.2	Functions and objects	9
1.3	Working with packages	9
1.4	Working directory	10
1.5	Data management	11
1.6	More about data management	12
1.7	Summary	18
2	Descriptive statistics	19
2.1	Preliminaries	19
2.2	One variable	20
2.3	Two variables and more	23
2.4	Groups and cross-tabulations	28
2.5	Summary	37
3	Visual exploration	39
3.1	Preliminaries	39
3.2	One variable	41
3.3	Two variables	42
3.4	Multiple plots in one go	47
3.5	Summary	49
4	Reporting results	51
4.1	cbind and data.frame	51
4.2	paste and paste0	51
4.3	kable	51
4.4	stargazer	51
5	Practicals	53
5.1	data 1	53
5.2	data 2	53
5.3	data 3	53
5.4	Summary	53
6	References	55

Chapter 1

Introduction to R

This chapter introduces readers to the basics of working with data in R. We will start with installing R in your computer and getting familiar with RStudio interface. These will be followed by the basics of handling data in R.

1.1 R and RStudio

1.1.1 Installation of R

- The latest version of R is R version 3.4.3 (2017-11-30), Kite-Eating Tree.
- R is available for Windows, Mac OS and Linux.
- The installation files can be downloaded from <https://cran.r-project.org/>.
- Users can install different versions of R in a same machine or computer.
- There is no need to uninstall if you want to upgrade the currently installed R.

1.1.2 Starting R

Double click on R icon and you should get this

You should see an R console.

1.1.3 Installation of RStudio

RStudio installation files can be downloaded from <http://www.rstudio.com/>. First, make sure you have RStudio successfully installed.

1.1.3.1 Starting RStudio

You can double click on RStudio icon and you will see this:




Figure 1.1: R console

1.1.3.2 Why RStudio?

- Working with R console is alright.
- But for many people, they prefer to communicate with R using a graphical user interface (GUI).
- RStudio is the popular GUI and integrated development environment (IDE) for R.
- Other R IDE includes Microsoft R

Check this links for more info:

1. RStudio <https://www.rstudio.com/>
2. Microsoft R <http://blog.revolutionanalytics.com/2016/01/microsoft-r-open.html>

1.1.3.3 RStudio interface

You should be able to see 4 panes in the layout. You should see that

1. Console - the lower left pane. It tells you about your R information.
2. Source - the upper left pane. It shows the active files.
3. Environment and History - the upper right pane. It shows the currently loaded data files and values, and command history.
4. Miscellaneous - the lower right pane. It contains most important tabs, which are Files, Plots, Packages, Help and Viewer. It list file names, show plots, show packages, display help document and view outputs.




Figure 1.2: RStudio




Figure 1.3: Panes in RStudio

1.2 Functions and objects

Before we start, there are a number of basics that you must know to understand the syntax in R. These are functions and objects.

1.2.1 Functions

R commands are in form of `function()`. You can think of MS Excel function. Inside a function, there will be a number of options. We will see this as we go through the examples later.

1.2.2 Objects

Object is a sort of like container. You assign an object by giving it a name on left side of `<-` or `=`. For the sake of consistency, we will use `<-` throughout, although `=` is perfectly fine (some might argue about this though). `#` - variable, data (data frame, matrix, list)

```
x <- 1
y = 2
z <- x + y
z # type object name, you'll get the value
```

```
## [1] 3
```

But later you will see that `=` is used to set values for options of a function, i.e. inside the bracket after the function's name. For example, `function(option1 = value, option2 = value, ...)`. Thus, some prefer using `<-` to avoid confusion with `=` for options.

1.3 Working with packages

1.3.1 About packages

R uses packages to perform its tasks.

There are two common packages:

1. base packages
 2. user-contributed packages
- The base packages come with the installation of R
 - The base package provides basic but adequate functions to perform many standard data management, visualization and analysis.
 - However, user needs to install user-contributed packages if they need to perform functions (tasks) not available in the base package
 - User-contributed packages allow users to perform more advanced and more complicated functions
 - There are more than 10200 packages as of March 2017

For a complete list of packages, see <https://cran.r-project.org/web/packages/>

1.3.2 Package installation

You can install user-contributed packages through:

1. Internet (to cran)
2. Github packages
3. Local zip files

We will learn to install a few small packages.

Basically, a function to install a package will look like this

```
install.packages("package.name")
```

To install a package, saya car 1. put your cursor in the CONSOLE pane 2. type the codes below

```
install.packages("car")
```

3. press Ctrl + ENTER

1.3.3 Loading packages

Basically, to utilize a package, it has to be loaded using `library()` function,

```
library("package.name")
```

For example, we load the newly installed car package

```
library("car")
```

1.4 Working directory

In general, R reads and saves data and other files into a working directory. Therefore, a user must create or specify the working directory to work with R. This is a good practice.

A working directory:

1. stores all the outputs such as the plots, html files, pdf files
2. contains your data

Creating a working directory is a simple BUT an important step.

Unfortunately, many users do not pay attention to this and forget to set it. So, remember, this is a very important step to work in R.

1.4.1 Setting a working directory

To set your working directory:

1. Go back to RStudio's Miscellaneous pane.
2. In the Files tab, click ...
3. Navigate to the folder containing your data or any folder you want to work in.
4. Click *More*
5. Click *Set as working directory*

or simply use `setwd` function to do so.

```
setwd("path to your folder")
```

for example in Windows

```
setwd("C:/myfolder")
```

or in Mac OS/Linux

```
setwd("~/myfolder")
```

1.5 Data management

This section is concerned with reading data from dataset and displaying data.

1.5.1 Reading data set

Easiest is to read .csv file,

```
data <- read.csv("cholest.csv")
```

For SPSS and STATA files, we need foreign package,

```
library("foreign")  
data <- read.spss("cholest.sav", as.data.frame = TRUE)  
data <- read.dta("cholest.dta", convert.factors = TRUE)
```

For Excel file, we need `readxl` package,

```
library("readxl")  
data <- read_excel("cholest.xlsx", sheet = 1)
```

1.5.2 Viewing data set

Easy, just type the name,

```
data
```

Nicer, using `View()`

```
View(data)
```

View only the first six observations,

```
head(data)
```

```
##      chol age exercise sex categ
## 1  6.5  38          6   1      0
## 2  6.6  35          5   1      0
## 3  6.8  39          6   1      0
## 4  6.8  36          5   1      0
## 5  6.9  31          4   1      0
## 6  7.0  38          4   1      0
```

and the last six observations,

```
tail(data)
```

```
##      chol age exercise sex categ
## 75  9.4  45          4   0      2
## 76  9.5  52          4   0      2
## 77  9.6  35          4   0      2
## 78  9.8  43          3   0      2
## 79  9.9  47          3   0      2
## 80 10.0  44          3   0      2
```

Important tasks

```
dim(data)
```

```
str(data)
```

```
names(data)
```

1.5.3 Exporting data set from R

You can also export data into various formats using similar packages.

For example,

1. to export data into a *comma separated version* (.csv) file, we can use `write.csv` function.
2. to export data into stata format, we can use `write.dta` function

```
write.csv(data, 'data.csv')
```

```
write.dta(data, 'data.dta')
```

1.6 More about data management

In this section, we will deal with more advanced data management (subsetting, recoding and creating new variables) and direct data entry (especially useful for tables).

Let say we use `cholest.csv`,

```
data <- read.csv("cholest.csv")
dim(data)

## [1] 80 5

str(data)

## 'data.frame': 80 obs. of 5 variables:
## $ chol : num 6.5 6.6 6.8 6.8 6.9 7 7 7.2 7.2 7.2 ...
## $ age : int 38 35 39 36 31 38 33 36 40 34 ...
## $ exercise: int 6 5 6 5 4 4 5 5 4 6 ...
## $ sex : int 1 1 1 1 1 1 1 1 1 1 ...
## $ categ : int 0 0 0 0 0 0 0 0 0 0 ...

names(data)

## [1] "chol" "age" "exercise" "sex" "categ"

head(data); tail(data)

## chol age exercise sex categ
## 1 6.5 38 6 1 0
## 2 6.6 35 5 1 0
## 3 6.8 39 6 1 0
## 4 6.8 36 5 1 0
## 5 6.9 31 4 1 0
## 6 7.0 38 4 1 0

## chol age exercise sex categ
## 75 9.4 45 4 0 2
## 76 9.5 52 4 0 2
## 77 9.6 35 4 0 2
## 78 9.8 43 3 0 2
## 79 9.9 47 3 0 2
## 80 10.0 44 3 0 2
```

1.6.1 Subsetting

Subsetting means “selecting parts of data”. It allows selecting only a number of variables (columns) or observations (rows) from a dataframe. There are ways to do that.

1.6.1.1 Selecting a column (variable) or a row (observation)

Let say, to select age

```
data$age

## [1] 38 35 39 36 31 38 33 36 40 34 38 40 40 28 37 38 49 29 40 38 34 46 42
## [24] 38 32 43 42 40 38 39 39 39 35 38 40 38 45 36 31 34 44 35 40 37 33 46
## [47] 42 40 45 42 45 38 34 44 39 38 39 47 41 44 30 48 47 42 42 49 31 38 38
```

```
## [70] 48 34 45 45 36 45 52 35 43 47 44
```

to select the 7th observation,

```
data[7, ]
```

```
##   chol age exercise sex categ
## 7    7  33          5   1     0
```

1.6.1.2 Selecting columns

Let us create a new data frame with only `chol`, `age` and `sex` as the variables

```
data_col <- subset(data, select = c("chol", "age", "sex"))
str(data_col)
```

```
## 'data.frame':    80 obs. of  3 variables:
## $ chol: num  6.5 6.6 6.8 6.8 6.9 7 7 7.2 7.2 7.2 ...
## $ age : int  38 35 39 36 31 38 33 36 40 34 ...
## $ sex : int   1 1 1 1 1 1 1 1 1 1 ...
```

alternatively, we can use square brackets

```
data_col <- data[ , c("chol", "age", "sex")]
str(data_col)
```

```
## 'data.frame':    80 obs. of  3 variables:
## $ chol: num  6.5 6.6 6.8 6.8 6.9 7 7 7.2 7.2 7.2 ...
## $ age : int  38 35 39 36 31 38 33 36 40 34 ...
## $ sex : int   1 1 1 1 1 1 1 1 1 1 ...
```

you may even select by the column numbers

```
data_col <- data[ , c(1:2, 4)]
str(data_col)
```

```
## 'data.frame':    80 obs. of  3 variables:
## $ chol: num  6.5 6.6 6.8 6.8 6.9 7 7 7.2 7.2 7.2 ...
## $ age : int  38 35 39 36 31 38 33 36 40 34 ...
## $ sex : int   1 1 1 1 1 1 1 1 1 1 ...
```

selecting column 1 to 2, and column 4.

1.6.1.3 Selecting rows

To select 7th to 14th observations,

```
data_row <- data[7:14, ]
data_row
```

```
##   chol age exercise sex categ
## 7  7.0  33          5   1     0
```

```
## 8    7.2  36      5    1    0
## 9    7.2  40      4    1    0
## 10   7.2  34      6    1    0
## 11   7.3  38      6    1    0
## 12   7.3  40      5    1    0
## 13   7.3  40      4    1    0
## 14   7.3  28      5    1    0
```

Practically, we want to choose observations based on certain criteria, for example those aged > 35 year old,

```
data_row <- subset(data, age > 35)
str(data_row)
```

```
## 'data.frame':    62 obs. of  5 variables:
## $ chol      : num  6.5 6.8 6.8 7 7.2 7.2 7.3 7.3 7.3 7.3 ...
## $ age       : int  38 39 36 38 36 40 38 40 40 37 ...
## $ exercise: int  6 6 5 4 5 4 6 5 4 5 ...
## $ sex       : int  1 1 1 1 1 1 1 1 1 1 ...
## $ categ     : int  0 0 0 0 0 0 0 0 0 0 ...
```

alternatively, we can use square brackets,

```
data_row <- data[data$age > 35, ]
str(data_row)
```

```
## 'data.frame':    62 obs. of  5 variables:
## $ chol      : num  6.5 6.8 6.8 7 7.2 7.2 7.3 7.3 7.3 7.3 ...
## $ age       : int  38 39 36 38 36 40 38 40 40 37 ...
## $ exercise: int  6 6 5 4 5 4 6 5 4 5 ...
## $ sex       : int  1 1 1 1 1 1 1 1 1 1 ...
## $ categ     : int  0 0 0 0 0 0 0 0 0 0 ...
```

1.6.1.4 Select rows and columns together

Select those aged > 35, and chol, age, sex variables,

```
data_rc <- subset(data, age > 35 & sex == 1, select = c("chol", "age", "sex"))
str(data_rc)
```

```
## 'data.frame':    29 obs. of  3 variables:
## $ chol: num  6.5 6.8 6.8 7 7.2 7.2 7.3 7.3 7.3 7.3 ...
## $ age : int  38 39 36 38 36 40 38 40 40 37 ...
## $ sex : int  1 1 1 1 1 1 1 1 1 1 ...
```

1.6.1.5 Creating a new variable

For example, create age in months,

```
data$age_month <- data$age * 12
data$age_month

## [1] 456 420 468 432 372 456 396 432 480 408 456 480 480 336 444 456 588
## [18] 348 480 456 408 552 504 456 384 516 504 480 456 468 468 468 420 456
## [35] 480 456 540 432 372 408 528 420 480 444 396 552 504 480 540 504 540
## [52] 456 408 528 468 456 468 564 492 528 360 576 564 504 504 588 372 456
## [69] 456 576 408 540 540 432 540 624 420 516 564 528
```

1.6.2 Recoding

1.6.3 Categorize into new variables

1.6.3.1 From a numerical variable

```
data$age_cat <- cut(data$age, breaks = c(-Inf,40,50,Inf),
                    labels = c("< 40", "40-49", "> 50"))
table(data$age_cat)

##
## < 40 40-49 > 50
##    51    28     1
str(data$age_cat)

## Factor w/ 3 levels "< 40","40-49",...: 1 1 1 1 1 1 1 1 1 1 ...
```

1.6.3.2 From a categorical variable

Using age_cat variable,

```
levels(data$age_cat)

## [1] "< 40" "40-49" "> 50"
table(data$age_cat)

##
## < 40 40-49 > 50
##    51    28     1
```

Only one observation labeled as > 50. We want to combine 40-49 with > 50.

```
library(car)
data$age_cat1 <- recode(data$age_cat, "c('40-49','> 50') = '40 & above'")
table(data$age_cat1) # combined

##
## < 40 40 & above
```



```
##          51          29
```

1.6.4 Direct data entry

We may also enter short data directly using `read.table`.

For example, a standard data frame,

ID	Group	BMI
1	Fat	30
2	Fat	31
3	Fat	32
4	Thin	20
5	Thin	19
6	Thin	18

```
data_frame <- read.table(header = TRUE, text = "
ID Group BMI
1 Fat 30
2 Fat 31
3 Fat 32
4 Thin 20
5 Thin 19
6 Thin 18
")
str(data_frame)

## 'data.frame':    6 obs. of  3 variables:
## $ ID      : int  1 2 3 4 5 6
## $ Group: Factor w/ 2 levels "Fat","Thin": 1 1 1 2 2 2
## $ BMI     : int  30 31 32 20 19 18

data_frame
```

```
##   ID Group BMI
## 1  1   Fat  30
## 2  2   Fat  31
## 3  3   Fat  32
## 4  4  Thin  20
## 5  5  Thin  19
## 6  6  Thin  18
```

or a table,

	Cancer	No Cancer
Smoker	80	10
Non-smoker	5	100

```
data_table <- read.table(header = FALSE, text = "
80 10
5 100
                                ")
colnames(data_table) <- cancer <- c("Cancer", "No Cancer")
rownames(data_table) <- c("Smoker", "Non-smoker")
str(data_table)  # still a data frame, but laid out in form of a table.
```

```
## 'data.frame':    2 obs. of  2 variables:
## $ Cancer      : int  80 5
## $ No Cancer: int  10 100
```

```
data_table
```

```
##           Cancer No Cancer
## Smoker         80         10
## Non-smoker      5         100
```

The numbers are separated by space. We set the row and column names by `rownames` and `colnames` respectively.

1.7 Summary

In this chapter, we learned some basics in using R effectively. In the next chapter, we are going to learn about how to explore the variables by means of basic descriptive statistics.

Chapter 2

Descriptive statistics

In this chapter, we will go through a number of R functions for basic statistics. The focus will be on the results that are presented in form of numbers in text or tables (textual). We will mostly use the builtin functions (from R standard library). Extra packages will be introduced whenever necessary.

2.1 Preliminaries

In this part, we are going to use the functions as applied to a variable. For this purpose, we are going to use builtin datasets in R. You can view the available datasets by

```
data()
```

```
## Data sets in package 'datasets':
```

## AirPassengers	Monthly Airline Passenger Numbers 1949-1960
## BJsales	Sales Data with Leading Indicator
## BJsales.lead (BJsales)	Sales Data with Leading Indicator
## BOD	Biochemical Oxygen Demand
## CO2	Carbon Dioxide Uptake in Grass Plants
## ...	

We can view any dataset description by appending “?” to the dataset name. For example,

```
?chickwts
```

We will start by using chickwts dataset that contains both numerical (weight) and categorical (feed) variables. We can view the first six observations,

```
head(chickwts)
```

##	weight	feed
## 1	179	horsebean
## 2	160	horsebean
## 3	136	horsebean
## 4	227	horsebean
## 5	217	horsebean

```
## 6      168 horsebean
```

the last six observations,

```
tail(chickwts)
```

```
##      weight  feed
## 66      352 casein
## 67      359 casein
## 68      216 casein
## 69      222 casein
## 70      283 casein
## 71      332 casein
```

and the dimension of the data (row and column).

```
dim(chickwts)
```

```
## [1] 71  2
```

Here we have 71 rows (71 subjects) and two columns (two variables).

Next, view the names of the variables,

```
names(chickwts)
```

```
## [1] "weight" "feed"
```

and view the details of the data,

```
str(chickwts)
```

```
## 'data.frame':   71 obs. of  2 variables:
## $ weight: num  179 160 136 227 217 168 108 124 143 140 ...
## $ feed : Factor w/ 6 levels "casein","horsebean",...: 2 2 2 2 2 2 2 2 2 2 ...
```

which shows that weight is a numerical variable and feed is a factor, i.e. a categorical variable. feed consists of six categories or levels.

We can view the levels in feed,

```
levels(chickwts$feed)
```

```
## [1] "casein"      "horsebean" "linseed"    "meatmeal"   "soybean"    "sunflower"
```

2.2 One variable

2.2.1 A numerical variable

A numerical variable is described by a number of descriptive statistics below.

To judge the central tendency of the weight variable, we obtain its mean,

```
mean(chickwts$weight)
```

```
## [1] 261.3099
```

and median,

```
median(chickwts$weight)
```

```
## [1] 258
```

To judge its spread and variability, we can view its minimum, maximum and range

```
min(chickwts$weight)
```

```
## [1] 108
```

```
max(chickwts$weight)
```

```
## [1] 423
```

```
range(chickwts$weight)
```

```
## [1] 108 423
```

and obtain its standard deviation (SD)

```
sd(chickwts$weight)
```

```
## [1] 78.0737
```

variance,

```
var(chickwts$weight)
```

```
## [1] 6095.503
```

quantile,

```
quantile(chickwts$weight)
```

```
##      0%   25%   50%   75%  100%
## 108.0 204.5 258.0 323.5 423.0
```

and interquartile range (IQR)

```
IQR(chickwts$weight)
```

```
## [1] 119
```

There are nine types of quantile algorithms in R (for `quantile` and `IQR`), the default being type 7. You may change this to type 6 (Minitab and SPSS),

```
quantile(chickwts$weight, type = 6)
```

```
##      0%   25%   50%   75%  100%
##   108   203   258   325   423
```

```
IQR(chickwts$weight, type = 6)
```

```
## [1] 122
```

In addition to SD and IQR, we can obtain its median absolute deviation (MAD),

```
mad(chickwts$weight)
```

```
## [1] 91.9212
```

It is actually simpler to obtain most these in a single command,

```
summary(chickwts$weight)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##  108.0   204.5   258.0   261.3   323.5   423.0
```

even simpler, obtain all of the statistics using describe in the psych package

```
install.packages("psych")
```

```
library(psych)
```

```
describe(chickwts$weight)
```

```
##      vars  n   mean    sd median trimmed   mad min max range  skew kurtosis
## X1      1 71 261.31 78.07   258      261 91.92 108 423   315 -0.01    -0.97
##          se
## X1 9.27
```

2.2.2 A categorical variable

A categorical variable is described by its count, proportion and percentage by categories.

We obtain the count of the feed variable,

```
summary(chickwts$feed)
```

```
##      casein horsebean  linseed  meatmeal   soybean sunflower
##          12         10         12         11         14         12
```

```
table(chickwts$feed)
```

```
##
##      casein horsebean  linseed  meatmeal   soybean sunflower
##          12         10         12         11         14         12
```

both summary and table give the same result.

prop.table gives the proportion of the result from the count.

```
prop.table(table(chickwts$feed))
```

```
##
##      casein horsebean  linseed  meatmeal   soybean sunflower
## 0.1690141 0.1408451 0.1690141 0.1549296 0.1971831 0.1690141
```

the result can be easily turned into percentage,

```
prop.table(table(chickwts$feed))*100
```

```
##
##      casein horsebean   linseed  meatmeal   soybean sunflower
## 16.90141  14.08451  16.90141  15.49296  19.71831  16.90141
```

To view the count and the percentage together, we can use `cbind`,

```
cbind(n = table(chickwts$feed), "%" = prop.table(table(chickwts$feed))*100)
```

```
##           n      %
## casein    12 16.90141
## horsebean 10 14.08451
## linseed   12 16.90141
## meatmeal  11 15.49296
## soybean   14 19.71831
## sunflower 12 16.90141
```

We need the quotation marks `" "` around the percentage sign `%`, because `%` also serves as a mathematical operator in R.

2.3 Two variables and more

Just now, we viewed all the statistics as applied to a variable. In this part, we are going to view the statistics on a number of variables. This includes viewing a group of numerical variables or categorical variables, or a mixture of numerical and categorical variables. This is relevant in a sense that, most of the time, we want to view everything in one go (e.g. the statistics of all items in a questionnaire), compare the means of several groups and obtain cross-tabulation of categorical variables.

2.3.1 Numerical variables

Let us use `women` dataset,

```
head(women)
```

```
##      height weight
## 1       58    115
## 2       59    117
## 3       60    120
## 4       61    123
## 5       62    126
## 6       63    129
```

```
names(women)
```

```
## [1] "height" "weight"
```

```
str(women)
```

```
## 'data.frame':   15 obs. of  2 variables:
## $ height: num  58 59 60 61 62 63 64 65 66 67 ...
## $ weight: num 115 117 120 123 126 129 132 135 139 142 ...
```

which consists of weight and height numerical variables.

The variables can be easily viewed together by summary,

```
summary(women)
```

```
##      height      weight
## Min.   :58.0   Min.   :115.0
## 1st Qu.:61.5   1st Qu.:124.5
## Median :65.0   Median :135.0
## Mean   :65.0   Mean   :136.7
## 3rd Qu.:68.5   3rd Qu.:148.0
## Max.   :72.0   Max.   :164.0
```

even better using describe (psych),

```
describe(women)
```

```
##      vars  n   mean    sd median trimmed   mad min max range skew
## height   1 15  65.00  4.47    65   65.00   5.93  58  72    14 0.00
## weight   2 15 136.73 15.50   135  136.31  17.79 115 164    49 0.23
##      kurtosis   se
## height   -1.44 1.15
## weight   -1.34 4.00
```

2.3.2 Categorical variables

Let us use infert dataset,

```
head(infert)
```

```
##   education age parity induced case spontaneous stratum pooled.stratum
## 1    0-5yrs  26     6      1     1           2         1           3
## 2    0-5yrs  42     1      1     1           0         2           1
## 3    0-5yrs  39     6      2     1           0         3           4
## 4    0-5yrs  34     4      2     1           0         4           2
## 5    6-11yrs 35     3      1     1           1         5          32
## 6    6-11yrs 36     4      2     1           1         6          36
```

```
names(infert)
```

```
## [1] "education"      "age"            "parity"         "induced"
## [5] "case"           "spontaneous"    "stratum"        "pooled.stratum"
```

```
str(infert)
```



```
## 'data.frame':    248 obs. of  8 variables:
## $ education      : Factor w/ 3 levels "0-5yrs","6-11yrs",...: 1 1 1 1 2 2 2 2 2 ...
## $ age            : num  26 42 39 34 35 36 23 32 21 28 ...
## $ parity         : num   6 1 6 4 3 4 1 2 1 2 ...
## $ induced        : num   1 1 2 2 1 2 0 0 0 0 ...
## $ case           : num   1 1 1 1 1 1 1 1 1 1 ...
## $ spontaneous    : num   2 0 0 0 1 1 0 0 1 0 ...
## $ stratum        : int   1 2 3 4 5 6 7 8 9 10 ...
## $ pooled.stratum: num   3 1 4 2 32 36 6 22 5 19 ...
```

We notice that induced, case and spontaneous are not yet set as categorical variables, thus we need to factor the variables. We view the value labels in the dataset description,

```
?infert
```

We label the values in the variables according to the description as

```
infert$induced <- factor(infert$induced, levels = 0:2, labels = c("0", "1", "2 or more"))
infert$case <- factor(infert$case, levels = 0:1, labels = c("control", "case"))
infert$spontaneous <- factor(infert$spontaneous, levels = 0:2, labels = c("0", "1", "2 or more"))
str(infert)
```

```
## 'data.frame':    248 obs. of  8 variables:
## $ education      : Factor w/ 3 levels "0-5yrs","6-11yrs",...: 1 1 1 1 2 2 2 2 2 ...
## $ age            : num  26 42 39 34 35 36 23 32 21 28 ...
## $ parity         : num   6 1 6 4 3 4 1 2 1 2 ...
## $ induced        : Factor w/ 3 levels "0","1","2 or more": 2 2 3 3 2 3 1 1 1 1 ...
## $ case           : Factor w/ 2 levels "control","case": 2 2 2 2 2 2 2 2 2 2 ...
## $ spontaneous    : Factor w/ 3 levels "0","1","2 or more": 3 1 1 1 2 2 1 1 2 1 ...
## $ stratum        : int   1 2 3 4 5 6 7 8 9 10 ...
## $ pooled.stratum: num   3 1 4 2 32 36 6 22 5 19 ...
```

and we now all these variables are turned into factors.

Again, the variables can be easily viewed together by summary,

```
summary(infert[c("education", "induced", "case", "spontaneous")])
```

```
##      education      induced      case      spontaneous
## 0-5yrs : 12    0          :143  control:165    0          :141
## 6-11yrs:120    1          : 68   case   : 83    1          : 71
## 12+ yrs:116    2 or more: 37                2 or more: 36
```

We do not use table here in form of table(infert[c("education", "induced", "case", "spontaneous")]) because table used in this form will give us 3-way cross-tabulation instead of count per categories. Cross-tabulation of categorical variables will be covered later.

To obtain the proportion and percentage results, we have to use lapply,

```
lapply(infert[c("education", "induced", "case", "spontaneous")],
       function(x) summary(x)/length(x))
```

```
## $education
```

```
##      0-5yrs   6-11yrs   12+ yrs
## 0.0483871 0.4838710 0.4677419
##
## $induced
##           0           1 2 or more
## 0.5766129 0.2741935 0.1491935
##
## $case
##   control      case
## 0.6653226 0.3346774
##
## $spontaneous
##           0           1 2 or more
## 0.5685484 0.2862903 0.1451613
```

```
lapply(infert[c("education", "induced", "case", "spontaneous")],
       function(x) summary(x)/length(x)*100)
```

```
## $education
##      0-5yrs   6-11yrs   12+ yrs
## 4.83871 48.38710 46.77419
##
## $induced
##           0           1 2 or more
## 57.66129 27.41935 14.91935
##
## $case
##   control      case
## 66.53226 33.46774
##
## $spontaneous
##           0           1 2 or more
## 56.85484 28.62903 14.51613
```

because we need `lapply` to obtain the values for each of the variables. `lapply` goes through each variable and performs this particular part,

```
function(x) summary(x)/length(x)
```

`function(x)` is needed to specify some extra operations to any basic function in R, in our case `summary(x)` divided by `length(x)`, in which the summary results (the counts) are divided by the number of subjects (`length(x)` gives us the “length” of our dataset).

Now, since we already learned about `lapply`, we may also obtain the same results by using `summary` (within `lapply`), `table` and `prop.table`.

```
lapply(infert[c("education", "induced", "case", "spontaneous")], summary)
```

```
## $education
##      0-5yrs 6-11yrs 12+ yrs
##         12    120    116
```

```
##
## $induced
##      0      1 2 or more
##    143      68      37
##
## $case
## control    case
##    165      83
##
## $spontaneous
##      0      1 2 or more
##    141      71      36
lapply(infert[c("education", "induced", "case", "spontaneous")], table)
```

```
## $education
##
## 0-5yrs 6-11yrs 12+ yrs
##    12    120    116
##
## $induced
##
##      0      1 2 or more
##    143      68      37
##
## $case
##
## control    case
##    165      83
##
## $spontaneous
##
##      0      1 2 or more
##    141      71      36
```

```
lapply(infert[c("education", "induced", "case", "spontaneous")],
       function(x) prop.table(table(x)))
```

```
## $education
## x
## 0-5yrs 6-11yrs 12+ yrs
## 0.0483871 0.4838710 0.4677419
##
## $induced
## x
##      0      1 2 or more
## 0.5766129 0.2741935 0.1491935
##
## $case
```

```
## x
##   control      case
## 0.6653226 0.3346774
##
## $spontaneous
## x
##           0           1 2 or more
## 0.5685484 0.2862903 0.1451613

lapply(infert[c("education", "induced", "case", "spontaneous")],
       function(x) prop.table(table(x))*100)

## $education
## x
##   0-5yrs  6-11yrs 12+ yrs
## 4.83871 48.38710 46.77419
##
## $induced
## x
##           0           1 2 or more
## 57.66129 27.41935 14.91935
##
## $case
## x
##   control      case
## 66.53226 33.46774
##
## $spontaneous
## x
##           0           1 2 or more
## 56.85484 28.62903 14.51613
```

Notice here, whenever we do not need to specify extra operations on a basic function, e.g. `summary` and `table`, all we need to write after the comma in `lapply` is the basic function without `function(x)` and `(x)`.

2.4 Groups and cross-tabulations

We intentionally went through the descriptive statistics of a variable, followed by a number of variables of the same type. This will give you the basics in dealing with the variables. Most commonly, the variables are described by groups or in form cross-tabulated counts/percentages.

2.4.1 By groups

To obtain all the descriptive statistics by group, we can use `by` with the relevant functions. Let say we want to obtain the statistics by case and control (`case`). We start with numerical variables

```
by(infert[c("age", "parity")], infert$case, summary)
```

```
## infert$case: control
##      age      parity
##  Min.   :21.00   Min.   :1.000
##  1st Qu.:28.00   1st Qu.:1.000
##  Median :31.00   Median :2.000
##  Mean   :31.49   Mean   :2.085
##  3rd Qu.:35.00   3rd Qu.:3.000
##  Max.   :44.00   Max.   :6.000
## -----
## infert$case: case
##      age      parity
##  Min.   :21.00   Min.   :1.000
##  1st Qu.:28.00   1st Qu.:1.000
##  Median :31.00   Median :2.000
##  Mean   :31.53   Mean   :2.108
##  3rd Qu.:35.50   3rd Qu.:3.000
##  Max.   :44.00   Max.   :6.000
```

```
by(infert[c("age", "parity")], infert$case, describe)
```

```
## infert$case: control
##      vars  n mean  sd median trimmed  mad min max range skew kurtosis
## age      1 165 31.49 5.25    31   31.34 5.93  21  44    23 0.23    -0.72
## parity   2 165  2.08 1.24     2    1.88 1.48   1   6     5 1.32     1.42
##      se
## age    0.41
## parity 0.10
## -----
## infert$case: case
##      vars  n mean  sd median trimmed  mad min max range skew kurtosis
## age      1  83 31.53 5.28    31   31.39 5.93  21  44    23 0.21    -0.77
## parity   2  83  2.11 1.28     2    1.90 1.48   1   6     5 1.32     1.34
##      se
## age    0.58
## parity 0.14
```

We can also use `describeBy`, which is an the extension of `describe` in the `psych` package.

```
describeBy(infert[c("age", "parity")], group = infert$case)
```

```
##
## Descriptive statistics by group
## group: control
##      vars  n mean  sd median trimmed  mad min max range skew kurtosis
## age      1 165 31.49 5.25    31   31.34 5.93  21  44    23 0.23    -0.72
## parity   2 165  2.08 1.24     2    1.88 1.48   1   6     5 1.32     1.42
##      se
```

```
## age      0.41
## parity 0.10
## -----
## group: case
##      vars  n mean   sd median trimmed  mad min max range skew kurtosis
## age      1 83 31.53 5.28    31   31.39 5.93  21 44   23 0.21   -0.77
## parity   2 83  2.11 1.28     2    1.90 1.48   1  6    5 1.32    1.34
##      se
## age      0.58
## parity 0.14
```

which gives us an identical result.

If you want to obtain results using the basic functions (i.e. mean, median, quantile, IQR and mad), you need to use `lapply` within `by`, because they could not handle many variables, for example for mean and IQR,

```
by(infert[c("age", "parity")], infert$case, function(x) lapply(x, mean))
```

```
## infert$case: control
## $age
## [1] 31.49091
##
## $parity
## [1] 2.084848
##
## -----
## infert$case: case
## $age
## [1] 31.53012
##
## $parity
## [1] 2.108434
```

```
by(infert[c("age", "parity")], infert$case, function(x) lapply(x, IQR))
```

```
## infert$case: control
## $age
## [1] 7
##
## $parity
## [1] 2
##
## -----
## infert$case: case
## $age
## [1] 7.5
##
## $parity
## [1] 2
```

For categorical variables, using summary

```
by(infert[c("education", "induced", "spontaneous")], infert$case, summary)
```

```
## infert$case: control
##      education      induced      spontaneous
## 0-5yrs : 8    0          :96    0          :113
## 6-11yrs:80    1          :45    1          : 40
## 12+ yrs:77    2 or more:24    2 or more: 12
## -----
## infert$case: case
##      education      induced      spontaneous
## 0-5yrs : 4    0          :47    0          :28
## 6-11yrs:40    1          :23    1          :31
## 12+ yrs:39    2 or more:13    2 or more:24
```

```
by(infert[c("education", "induced", "spontaneous")], infert$case,
    function(x) lapply(x, function(x) summary(x)/length(x)))
```

```
## infert$case: control
## $education
##      0-5yrs      6-11yrs      12+ yrs
## 0.04848485 0.48484848 0.46666667
##
## $induced
##           0           1 2 or more
## 0.5818182 0.2727273 0.1454545
##
## $spontaneous
##           0           1 2 or more
## 0.68484848 0.24242424 0.07272727
##
## -----
## infert$case: case
## $education
##      0-5yrs      6-11yrs      12+ yrs
## 0.04819277 0.48192771 0.46987952
##
## $induced
##           0           1 2 or more
## 0.5662651 0.2771084 0.1566265
##
## $spontaneous
##           0           1 2 or more
## 0.3373494 0.3734940 0.2891566
```

```
by(infert[c("education", "induced", "spontaneous")], infert$case,
    function(x) lapply(x, function(x) summary(x)/length(x)*100))
```

```
## infert$case: control
```

```
## $education
##    0-5yrs    6-11yrs    12+ yrs
##  4.848485 48.484848 46.666667
##
## $induced
##           0           1 2 or more
## 58.18182 27.27273 14.54545
##
## $spontaneous
##           0           1 2 or more
## 68.484848 24.242424 7.272727
##
## -----
## infert$case: case
## $education
##    0-5yrs    6-11yrs    12+ yrs
##  4.819277 48.192771 46.987952
##
## $induced
##           0           1 2 or more
## 56.62651 27.71084 15.66265
##
## $spontaneous
##           0           1 2 or more
## 33.73494 37.34940 28.91566
```

or by using table

```
by(infert[c("education", "induced", "spontaneous")], infert$case,
   function(x) lapply(x, table))
```

```
## infert$case: control
## $education
##
##    0-5yrs 6-11yrs 12+ yrs
##      8     80     77
##
## $induced
##
##           0           1 2 or more
##          96          45          24
##
## $spontaneous
##
##           0           1 2 or more
##         113          40          12
##
## -----
## infert$case: case
```



```
## $education
##
## 0-5yrs 6-11yrs 12+ yrs
##      4      40      39
##
## $induced
##
##      0      1 2 or more
##     47      23      13
##
## $spontaneous
##
##      0      1 2 or more
##     28      31      24

by(infert[c("education", "induced", "spontaneous")], inferter$case,
    function(x) lapply(x, function(x) prop.table(table(x))))
```

```
## inferter$case: control
## $education
## x
##      0-5yrs      6-11yrs      12+ yrs
## 0.04848485 0.48484848 0.46666667
##
## $induced
## x
##      0      1 2 or more
## 0.5818182 0.2727273 0.1454545
##
## $spontaneous
## x
##      0      1 2 or more
## 0.68484848 0.24242424 0.07272727
##
## -----
## inferter$case: case
## $education
## x
##      0-5yrs      6-11yrs      12+ yrs
## 0.04819277 0.48192771 0.46987952
##
## $induced
## x
##      0      1 2 or more
## 0.5662651 0.2771084 0.1566265
##
## $spontaneous
## x
```

```
##           0           1 2 or more
## 0.3373494 0.3734940 0.2891566

by(infert[c("education", "induced", "spontaneous")], infert$case,
   function(x) lapply(x, function(x) prop.table(table(x))*100))

## infert$case: control
## $education
## x
##   0-5yrs   6-11yrs   12+ yrs
## 4.848485 48.484848 46.666667
##
## $induced
## x
##           0           1 2 or more
## 58.18182 27.27273 14.54545
##
## $spontaneous
## x
##           0           1 2 or more
## 68.484848 24.242424 7.272727
##
## -----
## infert$case: case
## $education
## x
##   0-5yrs   6-11yrs   12+ yrs
## 4.819277 48.192771 46.987952
##
## $induced
## x
##           0           1 2 or more
## 56.62651 27.71084 15.66265
##
## $spontaneous
## x
##           0           1 2 or more
## 33.73494 37.34940 28.91566
```

Please note that simply replacing `table` for `summary` as in `by(infert[c("education", "induced", "spontaneous")], infert$case, table)` will not work as intended. `education` will be nested in `induced`, which is nested in `spontaneous`, listed by `case` instead. And yes, to obtain the proportions and percentages, it gets slightly more complicated as we have to specify `function` twice in `by`.

2.4.2 Cross-tabulation

As long as the categorical variables are already factored properly, there should not be a problem to obtain the cross-tabulation tables. For example between `education` and `case`,

```
table(infert$education, infert$case)
```

```
##
##           control case
## 0-5yrs           8    4
## 6-11yrs          80   40
## 12+ yrs          77   39
```

We may also include row and column headers, just like `cbind`,

```
table(education = infert$education, case = infert$case)
```

```
##           case
## education control case
## 0-5yrs           8    4
## 6-11yrs          80   40
## 12+ yrs          77   39
```

Since we are familiar with the powerful `lapply`, we can use it to get cross-tabulation of all of the factors with case status,

```
lapply(infert[c("education", "induced", "spontaneous")], function(x) table(x, infert$case))
```

```
## $education
##
## x           control case
## 0-5yrs           8    4
## 6-11yrs          80   40
## 12+ yrs          77   39
##
## $induced
##
## x           control case
## 0             96   47
## 1             45   23
## 2 or more     24   13
##
## $spontaneous
##
## x           control case
## 0           113   28
## 1            40   31
## 2 or more    12   24
```

We may also view subgroup counts (nesting). Here, the cross-tabulation of education and case is nested within induced

```
table(infert$education, infert$case, infert$induced)
```

```
## , , = 0
##
```

```
##
##           control case
## 0-5yrs      4      0
## 6-11yrs     57     21
## 12+ yrs     35     26
##
## , , = 1
##
##
##           control case
## 0-5yrs      0      2
## 6-11yrs     16     11
## 12+ yrs     29     10
##
## , , = 2 or more
##
##
##           control case
## 0-5yrs      4      2
## 6-11yrs     7      8
## 12+ yrs     13     3
```

which will look nicer if we apply by

```
by(infert[c("education", "case")], infert$induced, table)
```

```
## infert$induced: 0
##           case
## education control case
## 0-5yrs      4      0
## 6-11yrs     57     21
## 12+ yrs     35     26
## -----
## infert$induced: 1
##           case
## education control case
## 0-5yrs      0      2
## 6-11yrs     16     11
## 12+ yrs     29     10
## -----
## infert$induced: 2 or more
##           case
## education control case
## 0-5yrs      4      2
## 6-11yrs     7      8
## 12+ yrs     13     3
```

2.5 Summary

In this chapter, we learned about how to handle numerical and categorical variables and obtain the basic and relevant statistics. In the next chapter, we are going to learn about how to explore the variables visually in form of the relevant graphs and plots.

Chapter 3

Visual exploration

[elaborate here] In this chapter, we will explore the data visually by plots. In plotting the data, you must ask yourselves these:

1. Which variable do you want to plot?
2. What is the type of that variable? Factor? Numerical?
3. Are you going to plot another variable together?

3.1 Preliminaries

3.1.1 Reading dataset

We will use `qol.sav` dataset in this chapter. Create an object namely `dataSPSS` to the data read into R.

```
library(foreign)
dataSPSS <- read.spss('qol.sav', to.data.frame = TRUE)
```

3.1.2 Describing data

Let us examine the data

```
str(dataSPSS)

## 'data.frame':   365 obs. of  13 variables:
## $ id          : num  308 335 94 329 350 22 171 274 332 147 ...
## $ sex         : Factor w/ 2 levels "female","male": 1 2 1 1 1 2 1 1 2 2 ...
## $ age        : num   55 41 50 47 67 57 60 54 60 45 ...
## $ tahundx    : num   14 4 5 10 13 4 4 15 13 3 ...
## $ tx         : Factor w/ 4 levels "diet only","OHA and diet only",...: 3 4 2 4 4 2 2 2 4 2 ...
## $ group      : Factor w/ 2 levels "\"group A\"",...: 2 2 1 2 2 1 1 1 2 1 ...
## $ complica   : Factor w/ 2 levels "no","yes": 2 1 1 2 1 2 1 1 2 1 ...
## $ hba1c      : num   8.1 8 7.5 9.4 11.7 8.1 7.5 9.2 NA NA ...
```

```
## $ fbs      : num  6.9 4.8 8 3.6 12.5 8.5 NA NA NA NA ...
## $ rbs      : num  16.7 7.4 13.2 7.4 NA 7.8 9.4 7.8 NA 12.4 ...
## $ tg_total : num  0.92 1.66 0.74 0.94 3.01 1.3 NA 1.9 NA NA ...
## $ choleste : num  7.09 2.91 5.94 3.27 7.1 3.54 NA 5.7 NA NA ...
## $ ADDQSCORE: num  0 -0.222 -0.333 -0.36 -0.44 ...
## - attr(*, "variable.labels")= Named chr  "id_no" "sex" "" "" ...
##   ..- attr(*, "names")= chr  "id" "sex" "age" "tahundx" ...
## - attr(*, "codepage")= int 65001
```

Now, let us summarize our data

```
summary(dataSPSS)
```


```
##           id           sex           age           tahundx
## Min.      : 1.0    female:153    Min.      :21.00    Min.      : 1.000
## 1st Qu.:126.0    male  :212    1st Qu.:47.00    1st Qu.: 4.000
## Median :227.0                                Median :53.00    Median : 7.000
## Mean     :221.5                                Mean     :52.75    Mean     : 8.795
## 3rd Qu.:325.0                                3rd Qu.:59.00    3rd Qu.:12.000
## Max.      :416.0                                Max.      :80.00    Max.      :38.000
##
##           tx           group    complica    hba1c
## diet only           : 10    "group A":248    no :225    Min.      : 4.100
## OHA and diet only   :238    "group B":117    yes:140    1st Qu.: 7.500
## insulin and diet only: 26                                Median : 9.050
## all                  : 91                                Mean     : 9.301
##                                     3rd Qu.:10.775
##                                     Max.      :19.900
##                                     NA's      :111
##           fbs           rbs           tg_total           choleste
## Min.      : 2.700    Min.      : 3.900    Min.      :0.380    Min.      : 2.020
## 1st Qu.: 5.700    1st Qu.: 7.925    1st Qu.:1.125    1st Qu.: 4.308
## Median : 8.000    Median :11.300    Median :1.570    Median : 5.210
## Mean     : 9.003    Mean     :12.045    Mean     :2.002    Mean     : 5.437
## 3rd Qu.:11.900    3rd Qu.:15.000    3rd Qu.:2.385    3rd Qu.: 6.423
## Max.      :29.200    Max.      :31.500    Max.      :8.020    Max.      :13.100
## NA's      :178      NA's      :83      NA's      :191    NA's      :181
## ADDQSCORE
## Min.      :-9.000
## 1st Qu.: -5.590
## Median : -3.944
## Mean     : -4.179
## 3rd Qu.: -2.556
## Max.      : 0.000
##
```


3.2 One variable

3.2.1 A categorical variable

We can create a simple barchart


```
dist.sex<-table(dataSPSS$sex)
barplot(dist.sex,
        main='Sex distribution',
        xlab='Sex')
```



3.2.2 A numerical variable

Histogram

```
hist(dataSPSS$age, main = 'Age',
     xlab = 'Age in years',
     ylab = 'Count')
```




3.3 Two variables

3.3.1 A numerical with another numerical variable


We will use `scatterplot` to plot

```
plot(dataSPSS$tahundx, dataSPSS$age,  
     main = 'Duration having DM VS age',  
     xlab = 'Duration of DM', ylab = 'Age',  
     pch = 19)
```




Let us make a fit line

```
plot(dataSPSS$tahundx, dataSPSS$age,  
     main = 'Duration having DM VS age',  
     xlab = 'Duration of DM', ylab = 'Age',  
     pch = 19)  
abline(lm(dataSPSS$age~dataSPSS$tahundx), col = 'red')
```



and a lowess

```
plot(dataSPSS$tahundx, dataSPSS$age,  
     main = 'Duration having DM VS age',  
     xlab = 'Duration of DM', ylab = 'Age',  
     pch = 19)  
lines(lowess(dataSPSS$tahundx,dataSPSS$age), col = 'blue')
```




3.3.2 A categorical variable with a categorical variable

Now, we will plot 2 categorical variables simultaneously. First, we will use stacked barchart

```
compl.sex<-table(dataSPSS$complica,dataSPSS$sex)
compl.sex
```

```
##
##      female male
##  no      105  120
##  yes      48   92
```

```
barplot(compl.sex,
        main='Complications by sex',
        xlab='Sex',
        col=c('blue','red'),
        legend=c('No','Yes'))
```




Next, we will use grouped barchart

```
compl.sex
```

```
##
##      female male
##  no      105  120
##  yes      48   92


barplot(compl.sex,
        main = 'Complications according to sex',
        xlab = 'Sex',
        col = c('blue', 'red'),
        legend = c('no', 'yes'),
        beside = TRUE)
```



3.4 Multiple plots in one go


Here we will use some tricks, to show multiple plots in one go.

```
dataSPSS.4 <- dataSPSS[,c("age", "hba1c", "fbs", "choleste")]  
par(mfrow = c(2, 2)) # two rows and two columns  
mapply(hist, dataSPSS.4) # not nice, no proper labels
```



```
##          age          hba1c          fbs
## breaks   Integer,13      Integer,9      Numeric,7
## counts   Integer,12      Integer,8      Integer,6
## density  Numeric,12      Numeric,8      Numeric,6
## mids     Numeric,12      Numeric,8      Numeric,6
## xname    "dots[[1L]][[1L]]" "dots[[1L]][[2L]]" "dots[[1L]][[3L]]"
## equidist TRUE            TRUE            TRUE
##
## choleste
## breaks   Integer,13
## counts   Integer,12
## density  Numeric,12
## mids     Numeric,12
## xname    "dots[[1L]][[4L]]"
## equidist TRUE
```

```
mapply(hist, dataSPSS.4,
       main = paste("Histogram of ", colnames(dataSPSS.4)),
       xlab = colnames(dataSPSS.4)) # nice with labels
```

```
##          age          hba1c          fbs
## breaks  Integer,13      Integer,9      Numeric,7
## counts  Integer,12      Integer,8      Integer,6
## density  Numeric,12     Numeric,8      Numeric,6
## mids     Numeric,12     Numeric,8      Numeric,6
## xname    "dots[[1L]][[1L]]" "dots[[1L]][[2L]]" "dots[[1L]][[3L]]"
## equidist TRUE          TRUE          TRUE
##          cholest
## breaks  Integer,13
## counts  Integer,12
## density  Numeric,12
## mids     Numeric,12
## xname    "dots[[1L]][[4L]]"
## equidist TRUE
```

```
par(mfrow = c(1, 1)) # reset back to only one plot per view
```

As you can see, we used paste. We will learn more about paste later.

3.5 Summary

[summary here]

Chapter 4

Reporting results

In this chapter, we will learn how to combine bits and parts of your results into custom-made texts, labels and tables. This will be useful for reporting and summarizing your results for publication, as well as labeling specific axes on your plots. There are a number of ways to achieve this. We will do this by basic functions and packages.

4.1 `cbind` **and** `data.frame`

4.2 `paste` **and** `paste0`

4.3 `kable`

4.4 `stargazer`

Chapter 5

Practicals

In this chapter, using a number of additional data sets, we will conduct full exploration of the data from data description, descriptive statistics, plots and reporting.

5.1 data 1

5.2 data 2

5.3 data 3

5.4 Summary

[summary here]

Chapter 6

References

R Core Team. (2017). *R: A language and environment for statistical computing*. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from <https://www.R-project.org/>

Xie, Y. (2015). *Dynamic documents with R and knitr* (2nd ed.). Boca Raton, Florida: Chapman; Hall/CRC. Retrieved from <http://yihui.name/knitr/>