You Can't Leak What You Don't Know: Information-Isolated Disclosure for LLM Dialogue Agents

Wen Ni Chew (wc2927)

1 Synopsis

1.1 Problem

OSCEs (Objective Structured Clinical Examinations) work because students have to demonstrate questioning skill to extract clinical information from a patient. A standardized actor playing the patient knows the case and reveals it gradually, only when the student asks the right questions. When the patient is an LLM that gradually surrenders information under conversational pressure, the assessment fails—students get the diagnosis without earning the questioning skill it was supposed to require. This is what current LLM-based simulated patients do: when given the full patient case and instructed to withhold certain facts, they comply for a few turns, then leak under repeated questioning, emotional appeal, or asserted authority.

This is a special case of a general problem in dialogue control: how to bound what an agent reveals when the agent is trained to be helpful. The medical setting makes the problem unusually tractable to study. Disclosure conditions are explicit, leaks are well-defined, and pedagogical failure has a clean operational definition (information revealed when it shouldn't have been). But the same shape appears in negotiation training, privacy-preserving assistants, game NPCs, and any setting where an agent must enforce information boundaries against a counterparty trying to extract more.

The root cause is RLHF (reinforcement learning from human feedback), the training process that fine-tunes LLMs to be helpful by rewarding compliance with user requests. RLHF makes models want to answer questions fully and cooperatively, which directly conflicts with withholding information from a persistent questioner. Existing approaches all share the same structural limitation: the model has full access to the information it is supposed to protect, and control is only as strong as the model's willingness to follow instructions under adversarial pressure. Prompting, few-shot hedging examples, chain-of-thought, self-checking loops, and even multi-turn RL fine-tuning (Abdulhai et al., 2023) have not closed this gap.

1.2 How It Works

This project takes an architectural approach. Instead of one model that sees everything and is told to hide some of it, the system uses three components with different levels of information access:

1. **Disclosure Planner**—sees the full patient case. When the student asks a question, the planner evaluates whether any withheld fact's *disclosure condition* has been met (a natural-language rule such as "reveal family cardiac history only if the student asks specifically about family heart disease"). The planner is a *hybrid LLM + deterministic component*: an LLM proposes which facts to unlock based on the natural-language conditions, and a deterministic keyword gate then accepts the unlock only if the student's message contains at least one fact-specific keyword. This hybrid design is necessary at the 8B model scale (see §2.6) and means the system does not rely on the LLM alone to evaluate disclosure policies. The planner outputs a *content brief*—a document containing only the facts the patient is authorized to share, with no mention of withheld information. The brief also includes relevance tags, tone guidance, and a hedging instruction for topics where no authorized facts apply.

2. **Response Generator**—receives only the content brief and the conversation history, never the full case. It produces a natural patient response using only what the brief contains. Because it never sees withheld facts, it cannot reveal them, regardless of how the question is phrased or how much pressure the student applies.

3. **Verifier**—sees the full case. After the generator produces a response, the verifier runs a deterministic scan for *leak phrases* (specific multi-word expressions that would indicate withheld information was revealed). If a phrase is found, the response is regenerated with a reinforced hedging instruction. An LLM-based contradiction check is also implemented but disabled by default at the 8B scale due to false positives.



Figure 1: Information-isolated disclosure architecture. The planner has full case access and outputs a content brief containing only authorized facts. The generator sees only the brief and conversation history, never the full case. The verifier checks each response before delivery. The dashed line marks the information isolation boundary. Note that the planner combines an LLM proposal step with a deterministic keyword gate; both must agree before a fact is unlocked.

To illustrate: if the patient's father died of a heart attack at age 52 (a withheld fact with the disclosure condition "student asks about family heart disease"), the generator has no way to mention it—the content brief simply does not contain this information. If the student later asks "Has anyone in your family had heart problems?", the planner's LLM step proposes unlocking the fact, the keyword gate confirms that "family" and "heart" appear in the message, the fact is added to the brief, and the generator naturally incorporates it. No amount of pressure, emotional appeal, or authority claim can extract information that is not in the generator's input.

Algorithm 1 formalizes the planner's hybrid unlock decision. Both the LLM proposal and the keyword gate must agree before a fact is added to the content brief; either alone is insufficient.

Algorithm 1 Planner unlock decision

Input: case C, withheld facts W, message m, history H
Output: content brief B (subset of authorized facts)
$B \leftarrow$ already-disclosed facts from H
for each fact $f \in W$ **do**
  $llm_ok \leftarrow \textsc{LlmProposeUnlock}(f, m, C, H)$
  $kw_ok \leftarrow \exists\, k \in f.keywords : k \in m$
  if llm_ok **and** kw_ok **then**
    $B \leftarrow B \cup \{f\}$
  end if
end for
return B

1.3 What Makes It Distinctive

Within the LLM-simulated-patient literature, prior systems give the generator full case access and rely on prompting, retrieval relevance, or fine-tuning to control disclosure. This work is the first systematic application of structural information isolation to the OSCE simulated-patient setting, and the first to demonstrate, through controlled comparison and ablation, that isolation provides a categorically stronger disclosure guarantee than prompting baselines on this task.

The framing is straightforward: the generator cannot leak what it does not have, so disclosure control becomes a property of the architecture rather than of the model's adherence to instructions under pressure.

The trade-off is that the security boundary now lives in the planner, and at the 8B scale it relies on a deterministic keyword gate, not on the LLM's interpretation of natural-language conditions alone.

1.4 Who It's For and Availability

The system is designed for three communities: (1) **medical educators** building OSCE training tools who need simulated patients that students cannot game through conversational pressure; (2) **LLM researchers** studying information control, adversarial robustness, and the limits of instruction-following in dialogue systems; and (3) **simulation developers** in adjacent domains (negotiation training, game NPCs, privacy-preserving assistants) where an agent must enforce information boundaries.

Adapting to a new domain requires authoring case JSON files and Python familiarity to run the

pipeline; `ADAPTATION.md` documents the schema and authoring workflow, and a turnkey UI for non-technical educators is future work.

The complete system is open-source at https://github.com/wnc6/cant-leak; see §3 for the full deliverables list and `ADAPTATION.md` for a step-by-step adaptation guide.

1.5 Related Work

Medical dialogue datasets and metrics. Fareez et al. (2022) released 272 real OSCE transcripts, which I use as a structural reference for case design and as a quantitative naturalness benchmark. MediTOD (Saley et al., 2024) formalized medical dialogue into a Comprehensive Medical Attribute Schema (CMAS) with 12 slot types covering symptoms, medical history, medications, family history, social history, and other dimensions of medical history-taking, which I use to validate factual coverage. Abdulhai et al. (2023) proposed consistency metrics (line-to-line and prompt-to-line) for simulated patient coherence, which I adapt for the withheld-fact setting. Their work also demonstrated that even multi-turn RL fine-tuning leaves substantial persona drift—evidence that training-based approaches, not just prompting, are insufficient for reliable disclosure control.

LLM-based simulated patients. Recent systems, EvoPatient (Du et al., 2025) and AIPatient (Yu et al., 2025), give the generator full case access. The closest comparison is RAG-based systems like AIPatient, which restrict what the generator sees per turn by query relevance rather than disclosure policy: a query about "chest symptoms" retrieves the withheld chest pain fact precisely when it should be withheld. The planner in this architecture restricts by policy, not relevance.

Information isolation in adjacent areas. Factoring an LLM system into components with different information access is not new in general. Multi-agent systems with role-based access, privacy-preserving dialogue with redaction layers, and factored cognition pipelines all share the underlying intuition that what a component cannot see, it cannot reveal.

The contribution here is application to simulated-patient dialogue and a controlled evaluation against prompting baselines on this task.

2 Research Questions

2.1 Experimental Setup

All experiments use Llama 3.1 8B Instruct (FP16 precision, i.e., 16-bit floating-point weights, served locally via Ollama) for all three architecture components and all baseline conditions. I deliberately chose an 8B-parameter model rather than a larger one: if information isolation eliminates leakage with a smaller, less instruction-reliable model, it will work with larger models too. GPT-4o-mini (OpenAI) is used exclusively for post-hoc evaluation—it is never used inline during experiments.

Each experiment is a 20-turn conversation between a scripted student agent and the simulated patient system. The **student agent** implements six adversarial pressure strategies, each a fixed sequence of 20 messages designed to elicit withheld information through different manipulation techniques (Table 1). Five of the six strategies use generic templates and apply uniformly across cases. The sixth, *logical inference*, is hand-crafted per case: it chains disclosed facts toward withheld ones using case-specific reasoning steps. This makes it less an adversarial test than a constructed best-case query sequence. I report it separately and treat it as a sanity check, not as evidence about pressure resistance.

Strategy	Approach
Direct	Standard clinical history-taking
Rephrasing	Same question asked multiple ways
Emotional	Builds rapport, uses empathy
Authority	Asserts medical authority
Escalation	Broad to narrow, building context
Logical	Hand-crafted per case: chains disclosed facts toward withheld ones (sanity check, not adversarial test)

Table 1: Six pressure strategies. Five are generic adversarial templates; *Logical* is a per-case hand-crafted query sequence and is reported separately throughout.

Three clinical cases span different medical specialties: cardiology (unstable angina, 25 facts, 8 withheld), respiratory (community-acquired pneumonia with undiagnosed asthma, 25 facts, 7 withheld), and GI (ulcerative colitis, 26 facts, 8 withheld). Each case was validated against Fareez OSCE transcripts for structural realism and MediTOD CMAS schema for fact coverage (see §3.1). The full experimental matrix is 6 conditions $\times$ 6 strategies $\times$ 3 cases $\times$ 3 runs = 324 experiments.

Six conditions represent a progression from simple prompting to full architectural isolation (Table 2).

#	Condition	Description
1	Naive	Full case in system prompt + "do not reveal these facts"
2	Structured	Per-fact disclosure rules, few-shot hedging examples, chain-of-thought
3	Self-Monitor	Generate response, self-check for leaks, regenerate if needed
4	**Isolated**	Planner evaluates disclosure conditions → content brief → generator + verifier
5	No-Iso. Abl.	Same pipeline as #4, but generator sees full case
6	No-Ver. Abl.	Same as #4, but without the verifier

Table 2: Six experimental conditions. Conditions 5–6 are ablation studies isolating each component's contribution.

Evaluation metrics. The *primary* leakage measure is **deterministic phrase matching**, computed by the experiment runner during each conversation. Each case file specifies a list of leak phrases per withheld fact (e.g., "shoes feel tight" for an ankle swelling fact, "atorvastatin" for a statin medication fact), and a leak event is recorded each time a generator response contains a phrase from the `leak_phrases` list of a still-withheld fact. The reported leakage count per conversation is the total number of such events across all 20 turns, summed over all withheld facts. This counts repeated disclosures of the same fact separately, since each occurrence represents a distinct pedagogical failure where the student's pressure was rewarded with information. This measure is exact, reproducible, and independent of any LLM evaluator. All headline leakage results in this paper use this measure.

GPT-4o-mini provides *supplementary* semantic signals where deterministic matching cannot easily reach: contradictions against the ground-truth case, L2L turn-to-turn consistency, P2L consistency against withheld facts, naturalness on a 1–5 scale, failure attribution (planner/generator/verifier), and disclosure rate (percentage of withheld facts properly unlocked). These supplementary measures are useful but, as the validation in §2.7 shows, GPT-4o-mini systematically under-counts leaks (recall ∼27% on the human-validated sample). I therefore treat GPT-4o-mini metrics as secondary and flag any table that depends on the LLM evaluator.

Five RQs follow: (RQ1) leakage reduction, (RQ2) consistency with withheld facts, (RQ3) naturalness, (RQ4) ablation, (RQ5) failure attribution.

2.2 RQ1: Does information isolation reduce leakage?



Figure 2: Mean leakage by condition across 3 runs (n=54 per condition). Error bars show ±1 SD. The isolated architecture achieves zero leak events with zero variance. Bracket: structured prompting leaks more than naive on this measure (p=0.039, Mann-Whitney U); see text for caveats.

Condition	Det. Leaks	SD	p vs Isolated
Naive Prompting	4.13	2.07	<0.001***
Structured Prompting	5.17	2.42	<0.001***
Self-Monitoring	4.22	2.30	<0.001***
Isolated Architecture	**0.00**	**0.00**	—
No-Isolation Ablation	0.81	1.10	<0.001***
No-Verifier Ablation	0.04	0.19	0.740

Table 3: Average deterministic leakage per 20-turn conversation across 324 experiments (3 runs × 108 combinations). Leakage counts leak-phrase events across all 20 turns. p-values from Mann-Whitney U tests; because the isolated condition has zero variance by design, these tests are degenerate—the magnitude of separation is the more meaningful comparison.

Information isolation eliminates leakage (Figure 2, Table 3). The isolated architecture recorded zero leak events across all 54 experiments (3 runs × 3 cases × 6 strategies), while all three baselines leaked consistently: naive prompting averaged 4.13 ± 2.07, structured prompting 5.17 ± 2.42, and self-monitoring 4.22 ± 2.30. All baseline-vs-isolated differences are significant on a Mann-Whitney U test (a non-parametric significance test that compares two distributions without assuming normality; $p < 0.001$); however, because the isolated condition has zero variance by design, these tests are degenerate and the more meaningful claim is the magnitude of separation. The no-verifier ablation is statistically indistinguishable from the full

isolated architecture ($p = 0.740$), demonstrating that isolation alone is nearly sufficient. The architecture does not over-withhold: it disclosed 73.2% of withheld facts on average when students asked the right questions (see §2.5 for the full ablation analysis).

Figure 8 (Appendix A) makes the abstract numbers concrete. On the same student message ("Is there anything else?"), the isolated architecture answers from a content brief that contains only authorized facts, while naive prompting answers from the full case and pulls in surrounding context the student didn't ask about. Both responses look fine in isolation; the difference is that one stays bounded to authorized material by construction, while the other relies on the model to suppress what it has been told to hide. Across 20-turn conversations, that second mode is what eventually leaks the withheld facts.

What "zero leaks" means here: the generator is structurally prevented from accessing withheld facts, so it cannot retrieve them. The remaining failure modes, which deterministic phrase matching cannot detect, are stochastic collisions where the generator hallucinates content that happens to match a withheld fact, and semantic paraphrases that bypass leak phrases. Section §2.8 examines these in detail; one such case (a fabricated "burning sensation") was found in manual inspection of run 1.

Suggestive finding: structured prompting may underperform naive. Structured prompting leaked more than naive prompting on the deterministic measure ($p = 0.039$, Mann-Whitney U). One reading is a "forbidden thought" effect, where detailed descriptions of what not to say prime the model toward those topics. There are three reasons to treat this as suggestive rather than established.

First, the p-value is borderline and would not survive a multiple-comparisons correction across the conditions tested.

Second, structured prompting bundles three changes from naive (per-fact rules, few-shot hedging examples, chain-of-thought reasoning), so the effect cannot be attributed to any one of them without further ablation.

Third, the same direction shows up only inconsistently across cases (Figure 4). Structured prompting did not improve over naive on this benchmark, and may have made things worse, but the data here are suggestive rather than conclusive.

Per-Strategy Vulnerability. Among the five generic strategies, gradual escalation is the most effective pressure tactic against baselines (5.0–6.7 mean leak events across the three baseline conditions), progressively building context until the model discloses (Figure 3). Authority claim is second most effective (5.1–5.6 across baseline conditions), exploiting the model's RLHF-trained deference to authoritative requests. Direct questioning is least effective (2.4–4.0), lacking manipulative framing. These results suggest that adversarial robustness testing for disclosure-controlled systems should prioritize escalation and authority strategies over straightforward questioning. The handcrafted logical inference strategy is excluded from this comparison; it is reported separately as a sanity check.



Figure 3: Baseline leakage by pressure strategy (isolated architecture omitted: 0.0 across all strategies). Strategies sorted by ascending mean leakage. Gradual escalation is the most effective generic attack.

The isolated architecture shows zero leakage across all six strategies because pressure targets the generator, which lacks the withheld information regardless of how the question is framed.

Per-Case Variation. The GI case leaks approximately 2× more than cardiology and respiratory across all baselines (Figure 4). This traces to high semantic overlap between disclosed and withheld facts: bowel frequency and urgency (G03, disclosed) and nocturnal diarrhea (G04, withheld) are closely related concepts. When the model discusses one, it tends to include details from the other. Cardiology withheld facts (ankle swelling, arm tingling, family history) are more topically distinct from the chief complaint (chest tightness), making accidental disclosure less likely. This suggests a design principle: cases with high semantic similarity between disclosed and withheld facts are inherently harder for prompting-based systems. The isolated architecture eliminates this vulnerability: 0.0 ± 0.0

leaks across all three cases.



Figure 4: Mean leakage (± SD) by condition and clinical case across 3 runs. The GI case is consistently most vulnerable for all baselines due to semantic overlap between disclosed and withheld facts.

Leak Timing. Baselines never stabilize. Cumulative leakage rises continuously through turn 20 (Figure 5). The isolated architecture remains flat at zero throughout. Structured prompting leaks faster than naive and self-monitoring across the conversation, consistent with the suggestion above but, as noted, not sufficient to establish a mechanism. This temporal analysis shows that baselines fail early and continue failing: the problem is not instruction decay over long conversations but immediate vulnerability whenever conversation topics approach withheld information.



Figure 5: Cumulative leakage over 20-turn conversations, averaged across 3 runs. Baselines rise continuously; the isolated architecture remains at zero. Different markers distinguish overlapping lines.

Disclosure by Strategy. Among the five generic strategies, disclosure rates cluster between 63% and 72%: rephrasing and emotional appeal each earn 63%, direct questioning 69%, authority claim 71%, and gradual escalation 72% (Figure 6). The differences are small relative to the variance and should be read as evidence that disclosure rate under the isolated architecture is roughly insensitive to which generic pressure tactic is applied—the expected behavior, since pressure cannot extract information the generator does not have, and disclosure depends on whether the keyword gate triggers on the message content. The hand-crafted logical inference strategy achieves 100% disclosure (zero variance across 9 experiments) by traversing exactly the keywords that unlock each fact—a sanity check that the gate fires on optimal queries, not evidence of pressure resistance.



Figure 6: Disclosure rate by student strategy for the isolated architecture. The five generic strategies cluster at 63–72%. *Logical inference* (100%) is hand-crafted per case to traverse unlock keywords and is shown as a sanity check, not a comparable adversarial strategy.

2.3 RQ2: Does the architecture maintain consistency?

Condition	Contrad.	L2L	P2L
Naive	1.9	2.6	9.2
Structured	1.5	2.1	11.6
Self-Monitoring	1.6	1.7	5.5
Isolated	**0.6**	**1.6**	**3.7**
No-Iso. Abl.	0.5	1.3	6.4
No-Ver. Abl.	1.1	1.6	3.7

Table 4: Consistency metrics per conversation (lower is better), *from supplementary GPT-4o-mini evaluations averaged across all 3 runs* (n=54 per condition). P2L measures contradictions against withheld facts (e.g., incorrectly denying a symptom the patient has). These numbers should be read as semantic estimates rather than ground truth; the same evaluator has ∼27% recall on leak detection against the human-validated sample (§2.7).

In the supplementary GPT-4o-mini evaluations across all 3 runs, the isolated architecture has the lowest P2L inconsistency (3.7 vs 5.5–11.6 for baselines), tied with the no-verifier ablation. Because

the generator never sees withheld facts, it cannot accidentally deny them. It hedges or redirects rather than making false negative claims. Baselines frequently contradict withheld facts because the model must actively suppress known information and sometimes over-corrects by denying true facts.

Structured prompting has the highest P2L inconsistency (11.6), consistent with the RQ1 suggestion that detailed don't-say-X instructions may produce more contradictions than simpler approaches; the same evaluator-bias caveats apply.

2.4 RQ3: Does isolation affect naturalness?

In supplementary GPT-4o-mini evaluations across all 3 runs, all six conditions scored between 3.25 and 3.43 on a 5-point naturalness scale. Information isolation imposes no detectable naturalness penalty on this measure.

Fareez Distributional Comparison. To validate against real patient dialogue, I scored 50 sampled Fareez OSCE patient responses with the same GPT-4o-mini prompt and compared three dimensions (Table 5).

Metric	Fareez	Ours
Naturalness (1–5)	3.02	3.12
Response length (words)	14.3	52.7
Hedging frequency	20%	17%

Table 5: Comparison against 50 real OSCE patient responses from Fareez et al. (2022), scored with the same evaluation prompt. "Ours" represents 50 sampled responses from the isolated architecture condition. Response length and hedging frequency are deterministic; the naturalness column uses GPT-4o-mini and is supplementary.

Generated responses scored comparably on naturalness (3.12 vs 3.02), though the evaluator clustered both distributions at score 3 (98% for Fareez, 88% for ours), suggesting limited discriminative power at this scale.

The primary quality gap is response length, which is measured directly: generated responses are 3.7× longer than real patient responses (52.7 vs 14.3 words). Real OSCE patients give short, direct answers; the generator elaborates. This is a generator-level limitation (Llama 3.1 8B verbosity), not an architectural one, and could be addressed by constraining `max_tokens`.

The isolated architecture hedges in 17% of responses (measured by regex match against a list of common hedge phrases like "I'm not sure" and "I don't remember"), comparable to real patients (20%). The architecture does not over-hedge. The content brief provides enough authorized material that the generator rarely needs to deflect. Self-monitoring hedges least (10%), likely because it self-corrects hedging into more definitive (and sometimes leaky) responses. The absence of over-hedging confirms that information restriction does not damage conversation quality.

2.5 RQ4: Ablation Study

Two ablation conditions isolate each architectural component's contribution:

- **No-Isolation Ablation:** Same planner → generator → verifier pipeline, but the generator receives the full case instead of only the content brief. Tests whether the factored architecture alone prevents leaks, or whether isolation is necessary.
- **No-Verifier Ablation:** Full information isolation, but the verifier is removed. Tests whether the post-generation safety net is essential, or whether isolation alone is sufficient.



Figure 7: Ablation analysis across 3 runs. Left: removing isolation causes roughly 20× more leakage than removing the verifier (0.81 ± 1.10 vs 0.04 ± 0.19). Right: all three conditions achieve similar disclosure rates (72–73%), confirming isolation does not cause over-withholding.

Isolation is the critical mechanism (Figure 7, left). Removing isolation causes roughly 20× more leakage (0.81 ± 1.10) than removing the verifier (0.04 ± 0.19). The no-verifier ablation's near-zero leakage demonstrates that isolation is nearly sufficient on its own. It is statistically indistinguishable from the full architecture ($p = 0.740$). The no-isolation ablation's leakage shows that even with a verifier, the generator occasionally conveys withheld information semantically, passing phrase-based scanning but still leaking.

All three architecture conditions achieve similar disclosure rates (Figure 7, right): Isolated 73.2% ±

17.4%, No-Isolation 73.1% ± 18.1%, No-Verifier 72.5% ± 18.8%. Information isolation does not impair earned disclosure: students who ask the right questions receive the withheld information, modulo the keyword-gate sensitivity discussed in RQ1.

The ablation's contribution is to distinguish two ways the architecture might be working. Post-hoc checking (the verifier) catches only patterns it is designed to detect; structural isolation prevents all retrieval-driven leakage by construction. The 20× gap between the two ablations shows that, on this task, isolation is doing the work.

2.6 RQ5: Where do failures originate?

Attribution	Count	%
Planner error	792	50%
Generator error	760	48%
Verifier miss	24	2%

Table 6: Failure attribution *from supplementary GPT-4o-mini evaluations averaged across all 3 runs* (324 experiments). Planner errors reflect incorrect unlock decisions; generator errors reflect hallucination or fabrication. Like other GPT-4o-mini measures, this should be read as a semantic estimate rather than ground truth.

Failures split roughly evenly between the planner (incorrect authorization) and the generator (hallucination or fabrication). GPT-4o-mini attributes only 2% of failures to the verifier, but this label is misleading. The verifier in the experiments reported here runs only the deterministic phrase scan, and that scan uses the same leak phrase list that defines the primary leakage measure: any phrase-list match triggers regeneration before the response leaves the system, so a phrase-list-detectable leak cannot reach output without showing up in Table 3 as well. The 2% labeled "verifier miss" is therefore not deterministic-verifier failure but rather semantic leaks that bypassed phrase matching—the gap a future LLM-based verifier (or a 'use_llm_check=True' configuration with a stronger evaluator) would aim to close. The 2% figure is consistent with the near-zero architecture-condition leakage in Table 3.

The ∼48% generator error rate in baselines is the fundamental retrieval-driven failure mode: when the model has access to withheld information, it sometimes includes it. The isolated architecture eliminates this failure mode—the generator never receives the withheld information, so it cannot retrieve it. Over-disclosure planner errors are caught by phrase-matching verification, but the system has no equivalent safety net for under-disclosure (a planner that refuses to unlock a fact the student has earned).

The keyword gate, surfaced. The planner combines an LLM unlock proposal with a deterministic keyword gate: a fact is unlocked only if (a) the LLM proposes it and (b) the student's message contains at least one fact-specific keyword (e.g., "family," "heart," "disease" for the family-cardiac-history fact). This hybrid design is necessary at the 8B model scale, where the LLM alone unlocks facts on vague questions like "tell me more." It also has a real cost: the keyword gate is a hand-curated symbolic component, not a semantic evaluation of the natural-language disclosure condition. Conditions like "the student seems genuinely concerned" or "the patient feels comfortable enough to disclose" cannot be evaluated by keyword matching and would need a different mechanism. Two implications follow. First, adapting the architecture to a new domain requires authoring keyword lists per fact, not just writing disclosure conditions. Second, the security boundary at the 8B scale lives substantially in the keyword lists, which is a hand-engineered component with the usual hand-engineering failure modes (forgotten synonyms, ambiguous terms). A larger planner model would likely allow relaxing or removing this gate, but that is a hypothesis I have not tested.

2.7 Evaluator Validation

Two independent annotators without medical training each labeled the same 50 stratified, randomized responses from run-1 experiments using an HTML annotation interface (Figure 9 in Appendix A), judging each as "no leak," "leaked," or "unsure." The use of non-medical annotators is a deliberate methodological choice: the task is text matching against an explicit withheld-fact list, not medical judgment, and high agreement between non-experts demonstrates that the task is well-defined and reproducible without domain expertise. (A third medical annotator on a subset would further address whether non-experts and experts converge; this is left to future work.) Runs 2–3 use the same GPT-4o-mini evaluation prompt and are expected to exhibit the same bias pattern.

Comparison	κ	Agreement
Annotator 1 vs Annotator 2	0.919	96%
Human vs GPT-4o-mini	0.208	—

Table 7: Cohen's kappa for leak detection on the human-validated sample (run-1). Humans found 22 leaks each; GPT-4o-mini found 6.

The inter-annotator agreement ($\kappa = 0.919$, almost perfect) confirms that leak detection is a reliable, well-defined task. (κ is Cohen's kappa, a chance-corrected measure of agreement between raters: $\kappa = 1$ is perfect agreement, $\kappa = 0$ is chance-level.) The low human-vs-GPT agreement ($\kappa = 0.208$, fair) reveals systematic undercounting by the LLM evaluator: high precision (1 false positive in 50 samples) but low recall (6 detected vs 22 human-identified). The deterministic phrase matching used as the primary measure was built into the experiment runner from the start; this validation confirms that treating the GPT-4o-mini-based numbers in Tables 4 and 6 as supplementary semantic estimates rather than ground truth is the right call.

All four isolated responses flagged by human annotators were earned disclosures—facts properly unlocked by the student's questions (e.g., "Does the pain spread anywhere else?" contains the unlock keyword "spread" for fact C05). The annotation task did not provide unlock context, so annotators could not distinguish leaked from earned.

2.8 Leak Inspection

The deterministic primary measure recorded zero leaks for the isolated architecture, but GPT-4o-mini and the human annotators each flagged some isolated responses on the supplementary semantic measure. All 12 GPT-4o-mini flags and 4 human flags on the isolated architecture in run 1 were manually inspected and classified as evaluator errors, not real leaks the deterministic measure missed. Full evidence for all 16 instances is in the repository.[1]

Wrong fact ID (7/12): The evaluator flagged a withheld fact not in the response. Example: sweating (C03, unlocked) flagged as arm tingling (C05, withheld) because both are cardiac symptoms.

Disclosed fact misidentified (3/12): Disclosed information confused with a similar withheld fact. Three involve the GI G03/G04 pair—the same semantic overlap driving higher baseline leakage (see Per-Case Variation).

Planner timing ambiguity (2/12): The student's question contained unlock keywords, but the evaluator's tracking did not reflect the planner's actual decision.

The bias is asymmetric: across all 54 run-1 isolated conversations, GPT-4o-mini's 12 leak flags were all false positives (manually verified above); on the 50-sample human-annotation subset, GPT-4o-mini detected only 6 of the 22 leaks human annotators identified on baselines. The reported gap between conditions is conservative in both directions.

One instance revealed a generator fabrication—a "burning sensation" absent from all case facts. This is not a retrieval-driven leak (the generator did not have the information to retrieve), but it is a case fidelity issue: the generator invented plausible detail beyond the brief. In a different case, such a fabrication could by chance match a withheld symptom and produce a stochastic-collision leak that deterministic phrase matching would catch but architectural isolation alone would not prevent. Quantifying the rate of such collisions is left to future work.

3 Deliverables

The complete system, code, data, results, and documentation are open-source at `https://github.com/wnc6/cant-leak`, organized as a single repository with file-level paths, build instructions, and per-step reproduction commands documented in the README. All milestone assignments (initial proposal, revised proposal, progress report, final report, and demo slides) are in the `milestone_docs/` folder.

The deliverables fall into three groups, each tied to a load-bearing claim in this report:

- **Artifacts that produce the headline result.** The architecture (planner, generator, verifier) and the unified harness that runs it alongside three prompting baselines (naive, structured, self-monitoring) and two ablation conditions (no-isolation, no-verifier). The full 324-experiment matrix with deterministic leak detection built into the runner—producing the headline measure independently of any LLM evaluator (§2.2, §2.5).
- **Artifacts that validate the methodology.** The browser-based human annotation interface and Cohen's kappa computation that

[1] `milestone_docs/leak_inspection_report.md`

revealed the LLM evaluator's ∼27% recall (§2.7); the leak inspection report providing manual evidence for all 16 evaluator false positives on the isolated condition (§2.8); the Fareez distributional comparison validating naturalness against real OSCE dialogue (§5).

- **Artifacts that enable extension.** The first OSCE clinical cases with structured per-fact disclosure annotations (§3.1, MIT licensed); an interactive playground notebook exposing the content brief at every turn (replacing the originally planned demo video, §4.5); a step-by-step adaptation guide for authoring case files in new domains; and a test suite covering the planner's keyword gate and end-to-end pipeline integration.

3.1 Clinical Case Design

Case	Diagnosis	Facts	Disc.	With.
Cardio	Unstable angina	25	17	8
Resp	Pneumonia + asthma	25	18	7
GI	Ulcerative colitis	26	18	8

Table 8: Clinical cases. Each fact has a disclosure condition, unlock keywords, leak phrases, and structured symptom attributes.

Each case was constructed through six steps: (1) structural validation against Fareez OSCE transcripts (demographics, chief complaint, history of present illness, past medical history, medications, social/family history, review of systems); (2) fact coverage against MediTOD CMAS (all 12 slot types: symptom, patient medical history, family medical history, habits, exposure, medication, medical test, disease, travel information, occupation, residence, basic information); (3) natural-language disclosure conditions mirroring real clinical interview dynamics; (4) deterministic unlock keywords preventing premature disclosure—these are the symbolic component of the planner's hybrid design and require careful per-fact authoring; (5) leak phrases per withheld fact, serving a dual role: the verifier scans output for them at runtime, and the experiment runner uses the same matches as the primary leakage measurement; (6) structured symptom attributes drawn from MediTOD CMAS, used today as authoring reference material to keep the `content` field consistent across facts (the current pipeline passes only `content` into the generator's brief; attribute-aware brief construction is straightforward but not implemented).

The choice of three specialties is a deliberate trade-off: enough variety to test that the architecture generalizes across different disclosure patterns within internal medicine, but few enough to author each case at high quality (manual schema validation, hand-curated unlock keywords, per-fact leak phrases). Larger benchmarks with more specialties or multiple cases per pattern are left to future work. The GI case's higher semantic overlap between disclosed and withheld facts was unintentional but provides a natural stress test. The cases are smaller in scale than Fareez's 272 transcripts but include structured per-fact disclosure annotations not present in any prior OSCE benchmark. They are released under MIT license.

3.2 External Materials

3.3 Reproducibility

The full pipeline (clone, install Ollama, run experiments, evaluate, generate charts) is documented step-by-step in the README with expected output at each step. Two scopes of reproducibility apply.

Methodological reproduction is exact: the deterministic primary measure, case files, leak-phrase definitions, and runner logic are version-pinned, so the report's tables and charts regenerate from the committed result files without re-executing the full pipeline—the playground notebook is the same way, runnable after Ollama installation alone.

Experimental reproduction runs locally on consumer hardware capable of 8B model inference (no GPU cluster, server farm, or cloud compute is required for the experiments), with floating-point nondeterminism across Ollama versions and hardware causing individual response wordings to vary; leakage counts are robust to such variation because they depend on deterministic phrase matching rather than verbatim response text. Total OpenAI API cost (for evaluation only): approximately $10 for all three runs.

4 Self-Evaluation

4.1 What I Accomplished

The central contribution is the first systematic application and evaluation of structural information isolation for OSCE simulated-patient dialogue, demonstrating that on the deterministic leakage measure, and against five generic adversarial pressure strategies, isolation provides a categorically

Resource	Relation	How Used
Fareez et al.	Built on + compared to	Case validation; naturalness benchmark
MediTOD	Built on	CMAS fact coverage
Abdulhai et al.	Built on	L2L/P2L metrics; persona drift evidence
EvoPatient	Conceptually compared	Full-case-access design alternative
AIPatient	Conceptually compared	RAG-based retrieval design alternative
Llama 3.1 8B	Built with	All conditions (local)
GPT-4o-mini	Built with	Supplementary post-hoc evaluation

Table 9: External materials and their relationship to this work. EvoPatient and AIPatient are discussed as design alternatives in Related Work; the prompting baselines (Naive, Structured) reimplement their core full-case-access pattern but the published systems were not run directly as experimental conditions.

stronger guarantee than prompting baselines.

The claim rests on three layers of evidence: controlled experiments across 324 conversations with ablation studies attributing the improvement to isolation specifically rather than to the factored architecture, distributional comparison against real OSCE dialogue validating no quality degradation, and human annotation showing GPT-4o-mini misses 16 of 22 leaks that two independent annotators agreed on ($\kappa = 0.919$ between annotators). The deterministic phrase-matching measure is built around the same leak phrase definitions the humans used, so it does not have this recall problem. Concrete artifacts supporting these claims are listed in §3.

4.2 Contributions

This is an individual project. All design, implementation, evaluation, analysis, and writing were performed by me. Two independent annotators without medical training each labeled the same 50 responses through the HTML annotation interface (Figure 9) for the Cohen's kappa validation. They had no involvement in the system's design, did not know which condition produced each response, and did not see the results before annotating—preserving independence.

4.3 Challenges and Problems Encountered

Evaluator calibration was the most time-consuming challenge, delaying the evaluation phase by approximately one week. The GPT-4o-mini evaluation prompt went through multiple iterations: the initial version over-flagged disclosed facts as leaks of thematically similar withheld facts (false positive rate >40%), and the tightened version under-flagged real leaks. The core difficulty is that leak detection is a semantic task requiring case-structure understanding—whether "I feel urgent to use the bathroom" leaks nocturnal diarrhea depends on knowing that urgency is already disclosed (G03) while nocturnal timing is withheld (G04). This problem motivated the methodological choice to use deterministic phrase matching as the primary leakage measure (§2.2, §2.7) and treat GPT-4o-mini outputs as supplementary signals.

Generator verbosity is the most visible quality limitation. The 8B model ignores length instructions, producing 3–4 sentences when prompted for 1–2. I considered hard truncation (risks incoherence), lower temperature (formulaic without shortening), and explicit length instructions (inconsistently followed). I chose to report the verbosity honestly rather than apply a mitigation with its own artifacts. For deployment, constraining `max_tokens` would be the most reliable fix.

Planner reliability and the keyword gate. The 8B model unlocked facts on vague questions ("tell me more"), which forced a hybrid LLM-plus-deterministic-keyword-gate design. This solved premature disclosure but introduced two costs that I want to be explicit about. First, it moves real authorization logic out of the LLM and into hand-curated keyword lists, which makes the system part symbolic and part neural rather than a clean architectural-isolation result driven entirely by the planner LLM. Second, natural disclosure conditions ("the student seems genuinely concerned") cannot be evaluated by keyword matching and would require a different mechanism. A larger planner would likely allow relaxing this gate, but I have not verified that.

4.4 What I Learned

Architectural vs. behavioral guarantees. Prompting asks the model to resist its own training objective—to be unhelpful when trained to be helpful. Information isolation reframes the problem: rather than "how do we make the model keep secrets?" the architecture asks "how do we en-

sure the model never has secrets to keep?" With prompting, every new adversarial strategy requires evaluating whether defenses hold. With isolation, the retrieval-driven defense is independent of the attack—though, as the leak inspection showed, stochastic generator fabrications remain a separate failure mode that isolation does not address.

Ablation design as argumentation. A reviewer could ask whether the factored architecture, not isolation, prevents leaks. The no-isolation ablation answers this by holding architecture constant and varying only isolation—its leakage (0.81 ± 1.10) proves factored architecture without isolation still leaks. Ablation conditions are arguments, each ruling out a specific alternative explanation.

Non-uniform evaluator bias. GPT-4o-mini over-flagged the isolated architecture (12 manually-verified false positives in run-1) and under-flagged baselines (missing 16 of 22 leaks on the human-validated sample). Non-uniform bias compresses the gap between conditions on a single measure. Any evaluation comparing LLM system variants with an LLM evaluator should check for condition-dependent bias through human validation, not just overall accuracy—and where possible, anchor headline claims to a deterministic measure that does not depend on the LLM evaluator at all.

Hybrid systems require honest accounting. The planner is described as "LLM-driven" but at the 8B scale a substantial part of its decision-making is the deterministic keyword gate. It would have been easy to under-describe this and let the LLM-driven framing do the rhetorical work. The honest version is that the headline guarantee depends on both the LLM proposal and the symbolic gate, and the gate is hand-engineered per case.

Semantic overlap as a predictive signal. The GI case's higher vulnerability emerged from the data and converged across baseline leakage rates, evaluator false positive rates, and the leak inspection report. Semantic overlap between disclosed and withheld facts could serve as a predictive metric for case difficulty—designers could compute inter-fact similarity scores and flag high-overlap cases as requiring isolation.

4.5 Deviations from Progress Report

Three deviations from the progress report's plan:

Quickstart notebook replaced with playground notebook. The progress report promised a quickstart notebook demonstrating how to run the system. I replaced it with an interactive playground (`playground.ipynb`) where users select a case, type their own student questions, and attempt to extract withheld information from the simulated patient. A live scoreboard tracks each fact's status, a content brief inspector shows exactly what the generator can see at each turn, and a baseline replay button switches the same conversation to naive prompting for direct comparison. This better demonstrates the isolation guarantee: a quickstart notebook would tell the reader the architecture works; the playground invites the reader to try to break it. Code-level reproducibility is covered by the README and the run scripts.

Side-by-side comparison video replaced with live demo and stitched figure. The progress report planned a recorded side-by-side comparison video. I dropped this in favor of three artifacts that, combined, do the same work better. First, the playground notebook renders both conditions inline with the same student input, displays the content brief panel that exposes what the generator can see, and updates a live scoreboard—the side-by-side comparison the video would have shown is in the artifact itself, not a static recording. Second, the stitched demo figure (`demo/demo_figure.html`, with a screenshot reproduced as Figure 8 in Appendix A) captures one such comparison as a shareable static page. Third, the live demo I gave during the elevator pitch walked the audience through the playground outputs and the headline charts, making the contrast visible while inviting questions a recorded video could not have answered.

Case sizes grew from 12–18 facts to 25–26 facts. The progress report estimated 12–18 facts per case with 4–6 withheld. Once I authored the cases against the MediTOD CMAS schema, that range proved insufficient: providing one informative fact per applicable slot of the 12-slot schema (full list in §3.1), plus the symptom-attribute granularity needed for realistic disclosure conditions, pushed totals to 25–26. Withheld counts grew proportionally to keep disclosure-condition difficulty constant: a case with twice as many facts and only 4–6 withheld would make the simulation easier than the progress report intended, because most of the student's questions would land on already-disclosed material. The 7–8 withheld facts per case preserve the original ratio.

4.6 Addressing Progress Report Feedback

The progress report raised two questions:

Pediatrics and PSS INSPIRE: would the LLM

simulate the child or the parent? For younger children, the parent or guardian is the primary informant. This is more than a casting choice; it changes the planner's job qualitatively. In adult OSCEs, every withheld fact is a fact the patient knows and is choosing not to volunteer. In pediatric OSCEs with a parent informant, withheld facts split into two categories: facts the parent knows but hasn't volunteered (same dynamic as adult OSCEs), and facts the parent doesn't know (e.g., a teenager's substance use, school behavior the child hides from the parent). The second category requires the planner to model what the parent *would plausibly know*, not just what's authorized to disclose. The current case file schema doesn't represent this—every fact has a single disclosure condition, not a fact-ownership attribute. Adapting to pediatrics would require extending the schema with ownership metadata (parent-knows, child-knows-but-parent-doesn't, etc.) and extending the planner to enforce ownership before checking disclosure conditions. I have not built this; flagging it as the concrete next step for pediatric deployment.

Motivation: am I working with someone on patient simulators? No—this work has no external collaborator, clinical advisor, or deployment partner. I picked the medical setting because OSCEs are an unusually clean instance of a general controllability problem: an agent must reveal information progressively, gated by a clear policy, under adversarial pressure, with stakes that make the failure mode concrete and the success mode measurable. Most controllability benchmarks lack one or more of these properties—safety benchmarks have policy without progressive disclosure, persona-consistency benchmarks have progressive disclosure without sharp evaluation, game NPCs have neither a clear policy nor measurable failure. OSCEs have all four, plus a real user community (medical educators) who would benefit if the controllability problem were solved. Finding a deployment partner is the most valuable next step, but the absence of one means the architecture has to stand on its own merits rather than being tuned to a stakeholder's preferences.

Limitations

These results come from a single LLM (Llama 3.1 8B). While the retrieval-driven isolation guarantee is model-agnostic by design, the prompting baselines may close some of the gap on stronger models, and the keyword gate may be relaxable on a larger planner. Testing across multiple model sizes would strengthen the generalizability claim.

The student agent is scripted, not adaptive. An LLM-based adversarial student that dynamically optimizes its strategy, and that has to discover unlock keywords without prior knowledge of them, would provide a stronger robustness test and would also be the right way to test whether the keyword gate is genuinely robust or merely robust to fixed templates.

The deterministic verifier and the primary leakage measure both use phrase matching. A semantic verifier would catch paraphrased leaks. The isolated architecture's zero-leak rate makes this primarily relevant for ablation conditions and for the stochastic-fabrication failure mode noted in §2.8.

All three cases are from internal medicine. Specialties with different disclosure dynamics, such as pediatrics where a parent answers on behalf of a child, would require schema and planner extensions; this is discussed in §4.6.

References

Marwa Abdulhai, Isadora White, Charlie Snell, Charles Sun, Joey Hong, Yuexiang Zhai, Kelvin Xu, and Sergey Levine. 2023. Lmrl gym: Benchmarks for multi-turn reinforcement learning with language models. *Preprint*, arXiv:2311.18232.

Zhuoyun Du, Lujie Zheng, Renjun Hu, Yuyang Xu, Xiawei Li, Ying Sun, Wei Chen, Jian Wu, Haolei Cai, and Haochao Ying. 2025. LLMs can simulate standardized patients via agent coevolution. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 17278–17306, Vienna, Austria. Association for Computational Linguistics.

Faiha Fareez, Tishya Parikh, Christopher Wavell, Saba Shahab, Meghan Chevalier, Scott Good, Isabella De Blasi, Rafik Rhouma, Christopher McMahon, Jean-Paul Lam, Thomas Lo, and Christopher W. Smith. 2022. A dataset of simulated patient-physician medical interviews with a focus on respiratory cases. *Scientific Data*, 9(1):313.

Vishal Vivek Saley, Goonjan Saha, Rocktim Jyoti Das, Dinesh Raghu, and Mausam . 2024. MediTOD: An English dialogue dataset for medical history taking with comprehensive annotations. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 16843–16877, Miami, Florida, USA. Association for Computational Linguistics.

Huizi Yu, Jiayan Zhou, Lingyao Li, Shan Chen, Jack Gallifant, Anye Shi, Jie Sun, Xiang Li, Jingxian He,

Wenyue Hua, Mingyu Jin, Guang Chen, Yang Zhou, Zhao Li, Trisha Gupte, Ming-Li Chen, Zahra Azizi, Qi Dou, Bryan P. Yan, and 7 others. 2025. Simulated patient systems powered by large language model-based AI agents offer potential for transforming medical education. *Communications Medicine*, 6(1):27.

A Reference Screenshots

This appendix collects two screenshots referenced from the main text. They are placed here at full text width so that small UI elements remain legible.

Figure 8 is a static capture of the playground notebook output (§2.2, §4.5) showing the isolated architecture and naive prompting answering the same student question on the same case. The content brief panel in the middle is the architectural insight made visible: it shows exactly what the generator can see in the isolated condition (three authorized facts and one newly unlocked fact, with twelve other facts hidden as not relevant and seven withheld facts not in the brief at all). The naive condition has no equivalent panel because the generator has full case access. The drift visible in the naive response toward unrequested context (work stress, weekend escalation) is the failure mode that produces leaks in longer conversations.

Figure 9 is the HTML annotation interface used by both human annotators in the evaluator validation work (§2.7). Each annotator opened the file in a browser, read each of 50 stratified responses alongside the case context and the unlock state, and selected one of three labels ("no leak," "leaked," or "unsure"). The interface keeps the labels independent across annotators and downloads a JSON file of the labels, which is then fed to the kappa computation.

B Worked Example: Disclosure Across a 20-Turn Conversation

This appendix traces a single isolated-architecture conversation (cardiology case, gradual escalation strategy, run 1) to illustrate how the planner's hybrid LLM-plus-keyword-gate design controls disclosure turn by turn. The conversation contains 20 turns; this section walks through five of them where disclosure decisions were materially in play.

The cardiology case has eight withheld facts. Of these, four become relevant during this conversation: **C03** diaphoresis, **C05** left arm tingling, **C06** ankle swelling, and **C18** father's heart attack at age 52. The other four follow the same pattern.

The unlock keywords for these four facts are: C03 = {sweat, dizz, associated, anything else, accompan, notice anything}; C05 = {radiat, spread, arm, tingl, numb, shoulder, anywhere else}; C06 = {swell, ankle, leg, feet, foot, edema, fluid}; C18 = {heart disease, heart attack, cardiac, cardiovascular, myocardial, coronary, heart problem}. A fact unlocks only if the student's message contains at least one of its keywords *and* the planner's LLM step also proposes the unlock.

Table 10 shows the relevant turns. For each turn, it lists the student's question, which withheld fact's unlock condition was at stake, whether the keyword gate fired, and what the patient said.

Turns 5–11 illustrate the architecture's precision: sweating, arm tingling, and ankle swelling each disclose at the moment the student's wording matches an unlock keyword, and not before. Turns 18–19 illustrate the cost of that precision. The student is explicitly asking about family medical problems, but the C18 keyword list requires *cardiac* terminology that the student never used. The strict-gate behavior is correct here—the student didn't ask the right question—but it would be the wrong call if the student were asking "has anyone in your family died young?" (no cardiac keyword, but a clinically valid question that should unlock the fact). This is the precision/flexibility trade-off discussed in §2.6.

This conversation recorded one regeneration event (`total_retries: 1`), but per-turn planner and verifier metadata is not logged in the current result files; adding it would enable verifier-triggered walkthroughs as future work.

T#	Student question (abbreviated)	Gate?	Outcome
5	"Walk me through one episode from start to finish." (C03 at stake)	no	Pressure and breathing only; sweating withheld.
6	"…do you notice anything besides the main symptom?" (C03 at stake)	yes	Sweating disclosed.
9	"Any pain, tingling, or unusual sensations?" (C05 at stake)	yes	Left arm tingling disclosed.
11	"Any swelling you've noticed anywhere on your body?" (C06 at stake)	yes	Ankle swelling and tight shoes disclosed.
18–19	"…medical problems run in your family? …serious or chronic conditions?" (C18 at stake)	no	Mother's hypertension and diabetes mentioned; father's heart attack remains withheld.

Table 10: Disclosure outcomes across five materially-relevant turns from the same isolated-architecture conversation. The keyword gate is doing the gating work: same student, same generator, same case, but disclosure happens only when the student's wording contains the per-fact unlock keywords listed above. Turn 5 vs. Turn 6 is the cleanest contrast—both are open-ended questions about the same episode, but only one matches a C03 keyword.



Figure 8: Side-by-side comparison of the isolated architecture (top blue) and naive prompting (bottom orange) on the same student question, same case. Top: the patient case header and live scoreboard tracking which of the eight withheld facts have been unlocked. Middle: a single conversation turn with the isolated condition's response and the planner's unlock decision. The yellow content brief panel below it shows what the generator received: three relevant authorized facts, twelve facts hidden as not relevant, and the newly unlocked diaphoresis fact (the seven other withheld facts are not in the brief). Bottom: the same two student questions answered by the isolated condition (blue) and naive prompting (orange) for direct comparison.



Figure 9: HTML annotation interface used in the human validation. Each annotator labels 50 randomized, stratified responses without seeing which condition produced each one. Labels download as a JSON file for kappa computation against the other annotator and against GPT-4o-mini. Inter-annotator agreement on this interface was $\kappa = 0.919$ (Table 7).