

An Extended Behavioral Type System for Memory-Leak Freedom

August 9, 2016

1 Abstract

In the previous work, we proposed a behavioral type system for a programming language with dynamic memory allocation and deallocation. The behavioral type system, which uses sequential processes as types where each action is related to an allocation and a deallocation, can estimate an upper bound of memory consumption of a program. However, the previous type system did not deal with path-sensitivity, which results in an imprecise abstraction even for a simple program. In order to address this problem, we propose an extension of the previous type system with dependent types. The dependent type carries more information for a program such that it can handle path-sensitivity and estimate an upper bound of memory cell consumption more precisely. We prove the soundness of the extended type system and propose a type inference algorithm of this type system. We also implemented the algorithm. Our experiment shows that the extended type system is very useful to deal with a practical path-sensitive program by checking whether the if-guard-part is a null pointer or not.

2 Introduction

Manual memory mangagement primitives (e.g. `malloc` and `free` in C language) are a very flexible way to manage computer memory cells. We can write a program which dynamically allocates a memory cell during running and deallocates a memory cell when it is no longer used. However, manual memory management primitives often cause hard-to-find problems, for example, double frees (`free` a deallocated memory cell), memory leaks (forget to deallocate memory cells) and illegal accesses to a dangling pointer. Therefore, many static verification methods have been proposed to guarantee safe memory deallocation. They prove *partial* memory-leak freedom: if a program terminates, all the memory cells are safe deallocated. As we know that nonterminating programs are very common in real-world programmings such as Web servers and operating systems. To guarantee *total* memory-leak freedom, if a program does not consume unbounded number of memory cells during execution, is a very crucial issue.

Example 2.1. Figure 1 describes partial and total memory-leak freedom. Both h and h' are partially memory-leak free because they do not terminate. The function h is totally memory-leak

| | | | |
|---|---|--|---|
| 1 | $h() =$ | | $h'() =$ |
| 2 | let $x = \mathbf{malloc}()$ in | | let $x = \mathbf{malloc}()$ in |
| 3 | let $y = \mathbf{malloc}()$ in | | let $y = \mathbf{malloc}()$ in |
| 4 | free (x); free (y); $h()$ | | $h'()$; free (x); free (y) |

Figure 1: Memory leaks in nonterminating programs.

free since it consumes at most two cells¹. However, the function h' , when it is invoked, consumes unbounded number of memory cells; hence h' is not totally memory-leak free.

In order to prove *total* memory deallocation, we proposed a behavioral type system in previous study[1]. It can abstract the behavior of a program by using sequential process whose actions represent manual memory management primitives. For example, the abstract behavioral type of function h in Figure 1 is $\mu\alpha.\mathbf{malloc}; \mathbf{malloc}; \mathbf{free}; \mathbf{free}; \alpha$, which represents function h allocates two memory cells, deallocates them, and then recursively call itself again; the behavioral type of function h' is abstracted as $\mu\alpha.\mathbf{malloc}; \mathbf{malloc}; \alpha; \mathbf{free}; \mathbf{free}$, which represents h' allocates two memory cells, call itself again, and then deallocates those two cells. From these two examples you may notice that our behavior type only consider the the number and order of manual memory management primitives and recursively calls. That way we can easily estimate the upper bound of memory cells a program consumed.

Although our previous behavioral type system can abstract the behavior of a program and estimate the upper bound of memory consumption, verification on abstracted behavioral types are failed in some cases. For example, the extracted behavioral type of function foo in Figure 2 is $\mu\alpha.\mathbf{malloc}; \mathbf{malloc}; \mathbf{malloc} + \mathbf{0}; \mathbf{free} + \mathbf{0}; \mathbf{free}; \mathbf{free}; \alpha$, which expresses that function foo allocates two memory cells, a choice command between allocating one memory cell and skipping, a choice command between deallocating one cell and skipping, deallocates two cells, and then call itself again. Due to the choice behavioral type, the above type may be seen as $\mu\alpha.\mathbf{malloc}; \mathbf{malloc}; \mathbf{malloc}; \mathbf{0}; \mathbf{free}; \mathbf{free}; \alpha$, which expresses function foo consumes three memory cells but deallocates two memory cells, and then iterates this behavior again. This behavior means function foo consumes unbounded number of memory cells, although the original program is *total* memory-leak freedom.

```

1      foo() =
2          let y = malloc() in
3          let x = malloc() in
4          ifnull (*y) then skip else let x1 = malloc() in *x ← x1;
5          ifnull (*y) then skip else free(*x);
6          free(x) ; free(y) ; foo()

```

Figure 2: a nonterminating program with conditionals

Example 2.2. Figure 2 describes that function foo is a total memory-leak freedom program, because it consumes at most three memory cells during execution. This function has two conditionals: if $*y$ is not a null pointer, it will allocates one cell at first conditional and deallocates that cell at second conditional, otherwise skips.

¹We assume that every memory cell allocated by **malloc** is fixed size to simplify our type system introduced in Section 4. Extension with variable-length cells is one of our future work.

My current idea is to extend previous behavioral type system with dependent types¹. The dependent types takes more precise information than traditional types, for example, the type $(*x)(\mathbf{malloc}, \mathbf{0})$ is a dependent type, because it depends on the value $(*x)$. See the function *foo* again, the current behavioral type of it is $\mu\alpha.\mathbf{malloc}; \mathbf{malloc}; (*x)(\mathbf{malloc}, \mathbf{0}); (*x)(\mathbf{free}, \mathbf{0}); \mathbf{free}; \mathbf{free}; \alpha$. Therefore, the part $(*x)(\mathbf{malloc}, \mathbf{0}); (*x)(\mathbf{free}, \mathbf{0})$ can be seen as $\mathbf{malloc}; \mathbf{free}$ or $\mathbf{0}; \mathbf{0}$ if $(*x)$ does not change between these two choices, which expresses total memory-leak freedom.

The reminder of this paper is structured as follows. Section 3 describes an imperative language with allocation and deallocation primitives and its operational semantics. Section 4 introduces the extended behavioral type system with dependent types. Section 5 describes the type reconstruction procedure; Section 6 shows some experiments and give a discussion; Section 7 describes the related works; Section 8 concludes this paper.

3 Language \mathcal{L}

In this section we define an imperative language \mathcal{L} with memory allocation and deallocation primitives, and for simplification we only use pointers as values.

The syntax of the language \mathcal{L} is as follows.

| | | |
|------------------------------|-------|--|
| x, y, z, \dots (variables) | \in | Var |
| s (statements) | $::=$ | $\mathbf{skip} \mid s_1; s_2 \mid *x \leftarrow y \mid \mathbf{free}(x)$ $\mid \mathbf{let } x = \mathbf{malloc}() \mathbf{ in } s \mid \mathbf{let } x = \mathbf{null} \mathbf{ in } s$ $\mid \mathbf{let } x = y \mathbf{ in } s \mid \mathbf{let } x = *y \mathbf{ in } s$ $\mid \mathbf{ifnull } (*x) \mathbf{ then } s_1 \mathbf{ else } s_2 \mid f(\vec{x})$ $\mid \mathbf{const}(*x)s \mid \mathbf{endconst}(*x)$ |
| d (proc. defs.) | $::=$ | $\{f \mapsto (x_1, \dots, x_n)s\}$ |
| D (definitions) | $::=$ | $\langle d_1 \cup \dots \cup d_n \rangle$ |
| P (programs) | $::=$ | $\langle D, s \rangle$ |
| E (context) | $::=$ | $E; s \mid []$ |

Notation \vec{x} is for a finite sequence $\{x_1, \dots, x_n\}$, where we assume that each element is distinct; $[\vec{x}/\vec{x}]s$ is for a term obtained by replacing each free occurrence of \vec{x} in s with variables \vec{x} ; the $\mathbf{Dom}(f)$ is a mapping from function name f to its domain; for a map f , the $f\{x \mapsto v\}$ and $f \setminus x$ are defined as follows:

$$\begin{aligned}
f\{x \mapsto v\}(w) &= \begin{cases} v & \text{if } x = w \\ f(w) & \text{otherwise.} \end{cases} \\
(f \setminus x)(w) &= \begin{cases} \text{undefined} & \text{if } x = w \\ f(w) & \text{otherwise.} \end{cases}
\end{aligned}$$

and $\mathit{filter_C}(C, *x)$ is defined by a pseudocode as follows:

$$\begin{aligned}
\mathit{filter_C}(C, *x) &= \text{let } C' = C - \mathbf{const}(*x) \text{ in} \\
&\quad \text{if } \mathbf{const}(*x) \in C' \text{ then return } C' \\
&\quad \text{else return } C' \setminus \{\mathbf{null}(*x), \neg\mathbf{null}(*x)\}
\end{aligned}$$

The **Var** is a countably infinite set of *variables* and each variable is a pointer. The statement **skip** means "does nothing". The statement $s_1; s_2$ is a sequential execution of s_1 and s_2 . The statement $*x \leftarrow y$ updates the content of cell which is pointed to by x with the value y . The statement **free**(x) deallocates a memory cell which is pointed to by pointer x . The statement **let** $x = e$ **in** s evaluates the expression e , binds x to the result, and executes s . The expression **malloc**() allocates a new memory cell. The expression **null** evaluates to the null pointer. The expression $*y$ means dereferencing a memory cell pointed to by y . The statement **ifnull** ($*x$) **then** s_1 **else** s_2 executes s_1 if $*x$ is **null** and executes s_2 otherwise. The statement $f(\vec{x})$ expresses a procedure f with arguments \vec{x} . The statement **const**($*x$) s means ($*x$) is a constant in statement s ; the statement **endconst**($*x$) means from this point ($*x$) maybe not constant.

The d represents a procedure definition which maps a procedure name f to its procedure body $(\vec{x})s$; The D represents a set of procedure definitions $\langle d_1 \cup \dots d_n \rangle$, and each definition is distinct; The pair $\langle D, s \rangle$ represents a program, where D is a set of definitions and s is a main statement; the E represents evaluation context.

3.1 Operational semantics

In this section we introduce operational semantics of language \mathcal{L} . We assume there is a countable infinite set \mathcal{H} of *heap addresses* ranged over by l .

We use a configuration $\langle H, R, s, n, C \rangle$ to express a run-time state. Each elements in the configuration is as follows.

- H , a *heap*, is a finite mapping from \mathcal{H} to $\mathcal{H} \cup \{\mathbf{null}\}$;
- R , an *environment*, is a finite mapping from **Var** to $\mathcal{H} \cup \{\mathbf{null}\}$;
- s is the statement that is being executed;
- n is a natural number that represents the number of memory cells available for allocation.
- C is a set of actions, which contains **const**($*x$), **null**($*x$) and $\neg \mathbf{null}(*x)$.

The operational semantics of the language \mathcal{L} is given by a labeled transition relation $\langle H, R, s, n, C \rangle \xrightarrow{\rho}_D \langle H', R', s', n', C' \rangle$. The label ρ is as follows.

$$\rho \text{ (label)} ::= \mathbf{malloc}(x') \mid \mathbf{free} \mid \mathbf{null}(*x) \mid \neg \mathbf{null}(*x) \mid \tau$$

The ρ , an *action*, is **malloc**, **free**, or τ . The action **malloc** expresses an allocation of a memory cell; **free** expresses a deallocation of a memory cell; τ expresses the other actions. We often omit τ in $\xrightarrow{\tau}_D$. We use a metavariable σ for a finite sequence of actions $\rho_1 \dots \rho_n$. We write $\xrightarrow{\rho_1 \dots \rho_n}_D$ for $\xrightarrow{\rho_1}_D \xrightarrow{\rho_2}_D \dots \xrightarrow{\rho_n}_D$. We write $\xRightarrow{\rho}_D$ for $\xrightarrow{*}_D \xrightarrow{\rho}_D \xrightarrow{*}_D$. We write $\xRightarrow{\rho_1 \dots \rho_n}_D$ for $\xRightarrow{\rho_1}_D \dots \xRightarrow{\rho_n}_D$.

Figure 3 depicts the relation $\xrightarrow{\rho}_D$. Several important rules are listed as follows.

- SEM-CONSTSKIP: That a memory cell pointed to by x is no longer a constant is expressed by doing nothing.
- SEM-CONSTSEQ: That a memory cell pointed to by x should be a constant in a statement s is expressed by adding a statement **endconst**($*x$) at the end of statement s .

- SEM-FREE: Deallocation of a memory cell pointed to by x is expressed by deleting the entry for $R(x)$ from the heap. This action increments the number of available cells (i.e., n) by one (i.e., $n + 1$).
- SEM-MALLOC and SEM-OUTOFMEM: Allocation of a memory cell is expressed by adding a fresh entry to the heap. This action is allowed only if the number of available cells is positive; if the number is zero, then the configuration leads to an error state **OutOfMemory**.
- SEM-ASSIGNEXN, SEM-FREEEXN, SEM-DEREFEXN and SEM-FREEEXN : These rules express an illegal access to memory. If such action is performed, then the configuration leads to exceptional state **MemEx**. This state **MemEx** is not seen as an erroneous state in the current paper, hence a well-typed program may lead to these states. The command **free**(x) , if x is a null pointer, leads to **MemEx** in the current semantics, although it is equivalent to **skip** in the C language.
- SEM-CONSTEXN: expresses that if a constant $*x$ is changed in s it will raise **ConstEx** exception.

Our goal is to guarantee *total* memory-leak freedom and reject memory leaks. By our language \mathcal{L} , they are formally defined as follows:

Definition 1 (total memory-leak freedom). *A program $\langle D, s \rangle$ is totally memory-leak free if there is a natural number n such that it does not require more than n cells.*

Definition 2 (Memory leak). *A configuration $\langle H, R, s, n, C \rangle$ goes overflow if there is σ such that $\langle H, R, s, n, C \rangle \xRightarrow{\sigma} \text{OutOfMemory}$. A program $\langle D, s \rangle$ consumes at least n cells if $\langle \emptyset, \emptyset, s, n, \emptyset \rangle$ goes overflow.*

4 Type system

4.1 Types

The syntax of the types is as follows.

| | | |
|--------------------------------------|-------|--|
| P (behavioral types) | $::=$ | $\mathbf{0} \mid P_1; P_2 \mid \mathbf{free} \mid \alpha \mid \mu\alpha.P$ $\mid \mathbf{let } x = y \mathbf{ in } P \mid \mathbf{let } x = \mathbf{malloc} \mathbf{ in } P$ $\mid \mathbf{let } x = \mathbf{null} \mathbf{ in } P \mid \mathbf{let } x = *y \mathbf{ in } P$ $\mid (*x)(P_1, P_2) \mid \mathbf{const}(*x)P \mid \mathbf{endconst}(*x)$ |
| Γ (variable type environment) | $::=$ | $\{x_1, x_2, \dots, x_n\}$ |
| Ψ (dependent function type) | $::=$ | $(\vec{x})P$ |
| Θ (function type environment) | $::=$ | $\{f_1 : \Psi_1, \dots, f_n : \Psi_n\}$ |
| k (constant values) | $::=$ | $\mathbf{null}(*x) \mid \neg \mathbf{null}(*x) \mid \mathbf{const}(*x)$ |
| F (constant value environment) | $::=$ | $\{k_1, \dots, k_n\}$ |

Behavioral types ranged over by P express the abstraction of behaviors of a program. The type $\mathbf{0}$ represents the do-nothing behavior; the type $P_1; P_2$ represents the sequential execution of P_1 and P_2 ; The type **malloc** represents an allocation of a memory cell exactly once; the type **free** represents a deallocation; the type $\mu\alpha.P$ represents the behavior of α defined by the recursive

$$\begin{array}{c}
\frac{C' = \text{filter_}C(C, *x)}{\langle H, R, \text{endconst}(*x), n, C \rangle \rightarrow_D \langle H, R, \text{skip}, n, C' \rangle} \quad (\text{SEM-CONSTSKIP}) \\
\langle H, R, \text{const}(*x)s, n, C \rangle \rightarrow_D \langle H, R, s; \text{endconst}(*x), n, C \cup \{\text{const}(*x)\} \rangle \quad (\text{SEM-CONSTSEQ}) \\
\langle H, R, \text{skip}; s, n, C \rangle \rightarrow_D \langle H, R, s, n, C \rangle \quad (\text{SEM-SKIP}) \\
\frac{\langle H, R, s_1, n, C \rangle \xrightarrow{\rho}_D \langle H', R', s'_1, n', C' \rangle}{\langle H, R, s_1; s_2, n, C \rangle \xrightarrow{\rho}_D \langle H', R', s'_1; s_2, n', C' \rangle} \quad (\text{SEM-SEQ}) \\
\frac{x' \notin \text{Dom}(R)}{\langle H, R, \text{let } x = \text{null in } s, n, C \rangle \rightarrow_D \langle H, R \{x' \mapsto \text{null}\}, [x'/x]s, n, C \rangle} \quad (\text{SEM-LETNULL}) \\
\frac{x' \notin \text{Dom}(R)}{\langle H, R, \text{let } x = y \text{ in } s, n, C \rangle \rightarrow_D \langle H, R \{x' \mapsto R(y)\}, [x'/x]s, n, C \rangle} \quad (\text{SEM-LETEQ}) \\
\frac{H(R(x)) = \text{null}, \text{const}(*x) \notin C}{\langle H, R, \text{ifnull}(*x) \text{ then } s_1 \text{ else } s_2, n, C \rangle \xrightarrow{\text{null}(*x)}_D \langle H, R, s_1, n, C \rangle} \quad (\text{SEM-IFNULLT}) \\
\frac{H(R(x)) \neq \text{null}, \text{const}(*x) \notin C}{\langle H, R, \text{ifnull}(*x) \text{ then } s_1 \text{ else } s_2, n, C \rangle \xrightarrow{\neg \text{null}(*x)}_D \langle H, R, s_2, n, C \rangle} \quad (\text{SEM-IFNULLF}) \\
\frac{H(R(x)) = \text{null}, \text{const}(*x) \in C}{\langle H, R, \text{ifnull}(*x) \text{ then } s_1 \text{ else } s_2, n, C \rangle \xrightarrow{\text{null}(*x)}_D \langle H, R, s_1, n, C \cup \{\text{null}(*x)\} \rangle} \quad (\text{SEM-IFCONSTNULLT}) \\
\frac{H(R(x)) \neq \text{null}, \text{const}(*x) \in C}{\langle H, R, \text{ifnull}(*x) \text{ then } s_1 \text{ else } s_2, n, C \rangle \xrightarrow{\neg \text{null}(*x)}_D \langle H, R, s_2, n, C \cup \{\neg \text{null}(*x)\} \rangle} \quad (\text{SEM-IFCONSTNULLF}) \\
\frac{\text{const}(*x) \notin C}{\langle H \{R(x) \mapsto v\}, R, *x \leftarrow y, n, C \rangle \rightarrow_D \langle H \{R(x) \mapsto R(y)\}, R, \text{skip}, n, C \rangle} \quad (\text{SEM-ASSIGN}) \\
\frac{x' \notin \text{Dom}(R) \quad R(y) \in \text{Dom}(H)}{\langle H, R, \text{let } x = *y \text{ in } s, n, C \rangle \rightarrow_D \langle H, R \{x' \mapsto H(R(y))\}, [x'/x]s, n, C \rangle} \quad (\text{SEM-LETDEREF}) \\
\frac{R(x) \neq \text{null} \text{ and } R(x) \in \text{Dom}(H)}{\langle H \{R(x) \mapsto v\}, R, \text{free}(x), n, C \rangle \xrightarrow{\text{free}}_D \langle H \setminus R(x), R, \text{skip}, n+1, C \rangle} \quad (\text{SEM-FREE}) \\
\frac{l \notin \text{Dom}(H) \quad n > 0}{\langle H, R, \text{let } x = \text{malloc}() \text{ in } s, n, C \rangle \xrightarrow{\text{malloc}(x')}_D \langle H \{l \mapsto v\}, R \{x' \mapsto l\}, [x'/x]s, n-1, C \rangle} \quad (\text{SEM-MALLOC}) \\
\frac{D(f) = (\vec{y})s}{\langle H, R, f(\vec{x}), n, C \rangle \rightarrow_D \langle H, R, [\vec{x}/\vec{y}]s, n, C \rangle} \quad (\text{SEM-CALL}) \quad \frac{R(x) = \text{null} \text{ or } R(x) \notin \text{Dom}(H)}{\langle H, R, \text{free}(x), n, C \rangle \xrightarrow{\text{free}}_D \text{MemEx}} \quad (\text{SEM-FREEEXN}) \\
\frac{R(x) = \text{null} \text{ or } R(x) \notin \text{Dom}(H)}{\langle H, R, *x \leftarrow y, n, C \rangle \rightarrow_D \text{MemEx}} \quad (\text{SEM-ASSIGNEXN}) \quad \frac{R(y) = \text{null} \text{ or } R(y) \notin \text{Dom}(H)}{\langle H, R, \text{let } x = *y \text{ in } s, n, C \rangle \rightarrow_D \text{MemEx}} \quad (\text{SEM-DEREFEXN}) \\
\frac{\forall z. \text{const}(*z) \in C \text{ and } R(x) = R(z)}{\langle H \{R(x) \mapsto v\}, R, *x \leftarrow y, n, C \rangle \rightarrow_D \text{ConstEx}} \quad (\text{SEM-ASSIGNCONSTEXN}) \\
\langle H, R, \text{let } x = \text{malloc}() \text{ in } s, 0, C \rangle \xrightarrow{\text{malloc}(x')}_D \text{OutOfMemory} \quad (\text{SEM-OUTOFMEM})
\end{array}$$

Figure 3: Operational semantics of \mathcal{L} .

equation $\alpha = P$; the type $(*x)(P_1, P_2)$ represents that P_1 or P_2 is obtained dependent on $*x$; the type $P_1 + P_2$ represents the choice between P_1 and P_2 ; the α is a type variable; the type **const** $(*x)P$ represents that $*x$ is a constant in behavioral type P ; the type **endconst** $(*x)$ represents $*x$ no longer be a constant from this point.

A type environments for variables ranged over by Γ is a set of variables. Since our interest is the behavior of a program, not the types of values, a variable type environment does not carry information on the types of variables.

Dependent function types ranged over by Ψ represents the behavior of a function; \vec{x} is the formal arguments of the function.

Function types ranged over by Θ is a mapping from function names to dependent function types.

k represents constant values, where **null** $(*x)$ represents $(*x)$ is a null pointer; \neg **null** $(*x)$ represents $(*x)$ is not a null pointer; **const** $(*x)$ represents $(*x)$ is a constant.

Constant value environment ranged over by F is a set of constant variables.

Figure 4 depicts semantics of behavioral types with dependent types, and they are given by the labeled transition system. The relation $\langle P, F \rangle \xrightarrow{\rho} \langle P', F' \rangle$ means that P can make an action ρ , and P turns into P' after it makes action ρ ; F and F' record constant value environment before and after action ρ respectively.

Notation $filter_T(F, *x)$ is defined by a pseudocode as follows:

$$\begin{aligned} filter_T(F, *x) &= \text{let } F' = F - \mathbf{const}(*x) \text{ in} \\ &\quad \text{if } \mathbf{const}(*x) \notin F' \text{ then return } (F' \setminus \{\mathbf{null}(*x), \neg\mathbf{null}(*x)\}) \\ &\quad \text{else return } F' \end{aligned}$$

4.2 Typing rules

The type judgment for statements is of the form $\Theta; \Gamma \vdash s : P$, which represents that under the function type environment Θ and the variable type environment Γ , the abstracted behavioral type of statement s is P .

Before showing typing rules for statements in Figure 5, we need explain several important definitions. The first one is $OK_n(P, F)$, a predicate, where P represents the behavior of a program which consumes at most n memory cells.

Definition 3 ($\#_\rho(\sigma)$). $\#_\rho(\sigma)$ is the number of ρ in the sequence σ .

Definition 4. $OK_n(P, F)$ holds if, (1) $\forall P'$ and σ . if $\langle P, F \rangle \xrightarrow{\sigma} \langle P', F' \rangle$, then $\#_m(\sigma) - \#_f(\sigma) \leq n$ and (2) $OK(F)$

Definition 5. $OK(F)$ holds if F does not contain both **null** $(*x)$ and \neg **null** $(*x)$.

Definition 6 (Subtyping). $F \vdash P_1 \leq P_2$ is the largest relation such that, for any P'_1, F' and ρ , if $\langle P_1, F \rangle \xrightarrow{\rho} \langle P'_1, F' \rangle$, then there exists P'_2 such that $\langle P_2, F \rangle \xRightarrow{\rho} \langle P'_2, F' \rangle$ and $F' \vdash P'_1 \leq P'_2$. We write $P_1 \leq P_2$ if $F \vdash P_1 \leq P_2$ for any F .

$$\begin{array}{c}
\langle \mathbf{0}; P, F \rangle \rightarrow \langle P, F \rangle \quad (\text{TR-SKIP}) \\
\langle \mathbf{free}, F \rangle \xrightarrow{\mathbf{free}} \langle \mathbf{0}, F \rangle \quad (\text{TR-FREE}) \quad \langle \mu\alpha.P, F \rangle \rightarrow \langle [\mu\alpha.P/\alpha]P, F \rangle \quad (\text{TR-REC}) \\
\langle P_1 + P_2, F \rangle \rightarrow \langle P_1, F \rangle \quad (\text{TR-CHOICE L}) \quad \langle P_1 + P_2, F \rangle \rightarrow \langle P_2, F \rangle \quad (\text{TR-CHOICE R}) \\
\frac{\langle P_1, F \rangle \xrightarrow{\rho} \langle P'_1, F' \rangle}{\langle P_1; P_2, F \rangle \xrightarrow{\rho} \langle P'_1; P_2, F' \rangle} \quad (\text{TR-SEQ}) \\
\langle \mathbf{let } x = \mathbf{malloc} \mathbf{ in } P, F \rangle \xrightarrow{\mathbf{malloc}(x')} \langle [x'/x]P, F \rangle \quad (\text{TR-LETMALLOC}) \\
\langle \mathbf{let } x = y \mathbf{ in } P, F \rangle \rightarrow \langle [x'/x]P, F \rangle \quad (\text{TR-LETXY}) \\
\langle \mathbf{let } x = *y \mathbf{ in } P, F \rangle \rightarrow \langle [x'/x]P, F \rangle \quad (\text{TR-LETX*Y}) \\
\langle \mathbf{let } x = \mathbf{null} \mathbf{ in } P, F \rangle \rightarrow \langle [x'/x]P, F \rangle \quad (\text{TR-LETX}) \\
\langle \mathbf{const}(*x)P, F \rangle \rightarrow \langle P; \mathbf{endconst}(*x), F \cup \{\mathbf{const}(*x)\} \rangle \quad (\text{TR-CONST}) \\
\frac{F' = \mathit{filter_T}(F, *x)}{\langle \mathbf{endconst}(*x), F \rangle \rightarrow \langle \mathbf{0}, F' \rangle} \quad (\text{TR-ENDCONST}) \\
\frac{\mathbf{const}(*x) \notin F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\mathbf{null}(*x)} \langle P_1, F \rangle} \quad (\text{TR-NOTCONST1}) \quad \frac{\mathbf{const}(*x) \notin F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\neg \mathbf{null}(*x)} \langle P_2, F \rangle} \quad (\text{TR-NOTCONST2}) \\
\frac{\mathbf{null}(*x) \in F \quad \mathbf{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \rightarrow \langle P_1, F \rangle} \quad (\text{TR-NULLIN}) \quad \frac{\neg \mathbf{null}(*x) \in F \quad \mathbf{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \rightarrow \langle P_2, F \rangle} \quad (\text{TR-NNULLIN}) \\
\frac{\mathbf{null}(*x), \neg \mathbf{null}(*x) \notin F \quad \mathbf{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\mathbf{null}(*x)} \langle P_1, F \cup \mathbf{null}(*x) \rangle} \quad (\text{TR-NNULLNOTIN1}) \\
\frac{\mathbf{null}(*x), \neg \mathbf{null}(*x) \notin F \quad \mathbf{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\neg \mathbf{null}(*x)} \langle P_2, F \cup \neg \mathbf{null}(*x) \rangle} \quad (\text{TR-NNULLNOTIN2})
\end{array}$$

Figure 4: semantics of behavioral types with dependent types.

$$\begin{array}{c}
\Theta; \Gamma \vdash \mathbf{skip} : \mathbf{0} \quad (\text{T-SKIP}) \qquad \frac{\Theta; \Gamma \vdash s_1 : P_1 \quad \Theta; \Gamma \vdash s_2 : P_2}{\Theta; \Gamma \vdash s_1; s_2 : P_1; P_2} \quad (\text{T-SEQ}) \\
\Theta; \Gamma, x, y \vdash *x \leftarrow y : \mathbf{0} \quad (\text{T-ASSIGN}) \qquad \Theta; \Gamma, x \vdash \mathbf{free}(x) : \mathbf{free} \quad (\text{T-FREE}) \\
\frac{\Theta; \Gamma, x \vdash s : P}{\Theta; \Gamma \vdash \mathbf{let } x = \mathbf{malloc}() \mathbf{ in } s : \mathbf{let } x = \mathbf{malloc} \mathbf{ in } P} \quad (\text{T-MALLOC}) \qquad \frac{\Theta; \Gamma, x, y \vdash s : P}{\Theta; \Gamma, y \vdash \mathbf{let } x = y \mathbf{ in } s : \mathbf{let } x = y \mathbf{ in } P} \quad (\text{T-LETEQ}) \\
\frac{\Theta; \Gamma, x, y \vdash s : P}{\Theta; \Gamma, y \vdash \mathbf{let } x = *y \mathbf{ in } s : \mathbf{let } x = *y \mathbf{ in } P} \quad (\text{T-LETDEREF}) \qquad \frac{\Theta; \Gamma, x \vdash s : P}{\Theta; \Gamma \vdash \mathbf{let } x = \mathbf{null} \mathbf{ in } s : \mathbf{let } x = \mathbf{null} \mathbf{ in } P} \quad (\text{T-LETNULL}) \\
\Theta; \Gamma, x \vdash \mathbf{endconst}(*x) : \mathbf{endconst}(*x) \quad (\text{T-ENDCONST}) \\
\frac{\Theta; \Gamma, x \vdash s : P}{\Theta; \Gamma, x \vdash \mathbf{const}(*x)s : \mathbf{const}(*x)P} \quad (\text{T-CONST}) \\
\frac{\Theta; \Gamma, x \vdash s_1 : P_1 \quad \Theta; \Gamma, x \vdash s_2 : P_2}{\Theta; \Gamma, x \vdash \mathbf{ifnull}(*x) \mathbf{ then } s_1 \mathbf{ else } s_2 : (*x)(P_1, P_2)} \quad (\text{T-IFNULL}) \\
\Theta, f : (\vec{y})P; \Gamma, \vec{x} \vdash f(\vec{x}) : P[\vec{x}/\vec{y}] \quad (\text{T-CALL}) \\
\frac{\Theta; \Gamma \vdash s : P_1 \quad P_1 \leq P_2}{\Theta; \Gamma \vdash s : P_2} \quad (\text{T-SUB}) \\
\frac{\Theta(f) = (\vec{x})P \quad \mathbf{Dom}(D) = \mathbf{Dom}(\Theta) \quad \Theta; x_1, \dots, x_n \vdash s : P \text{ for each } f \mapsto (x_1, \dots, x_n)s \in D}{\vdash D : \Theta} \quad (\text{T-DEF}) \\
\frac{\vdash D : \Theta \quad \Theta; \emptyset \vdash s : P \quad OK_n(P, F)}{\vdash \langle D, s \rangle : n} \quad (\text{T-PROGRAM})
\end{array}$$

Figure 5: typing rules

4.3 Type soundness

Theorem 4.1. *If $\vdash \langle D, s \rangle : n$ for some n , then $\langle D, s \rangle$ is totally memory-leak free.*

The proof is based on the following lemmas: preservation and lack of immediate overflow.

Definition 7. *we write $\Theta; \Gamma \vdash \langle H, R, s, n, C \rangle : \langle P, F \rangle$, if $\Theta; \Gamma \vdash s : P$ and $OK_n(P, F)$ with $C \approx F$.*

Lemma 4.2 (Preservation). *suppose that $\Theta; \Gamma \vdash \langle H, R, s, n, C \rangle : \langle P, F \rangle$. If $\langle H, R, s, n, C \rangle \xrightarrow{\rho} \langle H', R', s', n', C' \rangle$ then $\exists P', F'$ s.t. (1) $\Theta; \Gamma \vdash \langle H', R', s', n', C' \rangle : \langle P', F' \rangle$ and (2) $\langle P, F \rangle \xRightarrow{\rho} \langle P', F' \rangle$.*

Lemma 4.3 (Lack of immediate overflow). *If $\Theta; \Gamma \vdash \langle H, R, s, n, C \rangle : \langle P, F \rangle$, then $\langle H, R, s, n, C \rangle \not\xrightarrow{\text{malloc}} \text{OutOfMemory}$.*

5 Type Reconstruction

[to do]

6 Experiments

[to do]

7 Related Works

[to do]

8 Conclusion

9 Proof of Lemmas

Lemma 9.1. *If $\langle P, F \rangle \xrightarrow{\rho} \langle P', F' \rangle$ and $OK(F)$, then $OK(F')$*

Proof. By induction on $\langle P, F \rangle \xrightarrow{\rho} \langle P', F' \rangle$.

- Case $P = \mathbf{0}$; P' and $\langle \mathbf{0}; P', F \rangle \rightarrow \langle P', F \rangle$

We need to prove $OK(F')$. From assumption, we have that $OK(F)$ holds, and in this case F' is the same as F . Therefore, $OK(F')$ holds.

- Case $P = \text{let } x = \text{malloc in } P'$ and $\langle \text{let } x = \text{malloc in } P', F \rangle \xrightarrow{\text{malloc}(x')} \langle [x'/x]P', F \rangle$

Similar to above.

- Case $P = \text{let } x = y \text{ in } P'$ and $\langle \text{let } x = y \text{ in } P', F \rangle \rightarrow \langle [x'/x]P', F \rangle$

Similar to above.

- Case $P = \text{let } x = *y \text{ in } P'$ and $\langle \text{let } x = *y \text{ in } P', F \rangle \rightarrow \langle [x'/x]P', F \rangle$
Similiar to above.
- Case $P = \text{let } x = \text{null in } P'$ and $\langle \text{let } x = \text{null in } P', F \rangle \rightarrow \langle [x'/x]P', F \rangle$
Similiar to above.
- Case $P = \text{free}$ and $\langle \text{free}, F \rangle \xrightarrow{\text{free}} \langle \mathbf{0}, F \rangle$
Similiar to above.
- Case $P = (*x)(P_1, P_2)$ and $\frac{\text{const}(*x) \notin F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\text{null}(*x)} \langle P_1, F \rangle}$
We need to prove $OK(F)$. From the assumption, $OK(F)$ holds.
- Case $P = (*x)(P_1, P_2)$ and $\frac{\text{const}(*x) \notin F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\neg \text{null}(*x)} \langle P_2, F \rangle}$
We need to prove $OK(F)$. From the assumption, $OK(F)$ holds.
- Case $P = (*x)(P_1, P_2)$ and $\frac{\text{null}(*x) \in F \quad \text{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \rightarrow \langle P_1, F \rangle}$
We need to prove $OK(F)$. From the assumption, $OK(F)$ holds.
- Case $P = (*x)(P_1, P_2)$ and $\frac{\neg \text{null}(*x) \in F \quad \text{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \rightarrow \langle P_2, F \rangle}$
We need to prove $OK(F)$. From the assumption, it holds.
- Case $P = (*x)(P_1, P_2)$ and $\frac{\text{null}(*x), \neg \text{null}(*x) \notin F \quad \text{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\text{null}(*x)} \langle P_1, F \cup \text{null}(*x) \rangle}$
We need to prove $OK(F \cup \text{null}(*x))$. From the assumption, we have $OK(F)$ and $\neg \text{null}(*x) \notin F$. Therefore $OK(F \cup \text{null}(*x))$ holds.
- Case $P = (*x)(P_1, P_2)$ and $\frac{\text{null}(*x), \neg \text{null}(*x) \notin F \quad \text{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\neg \text{null}(*x)} \langle P_2, F \cup \neg \text{null}(*x) \rangle}$
We need to prove $OK(F \cup \neg \text{null}(*x))$. From the assumption, we have $OK(F)$ and $\text{null}(*x) \notin F$. Therefore $OK(F \cup \neg \text{null}(*x))$ holds.
- Case $P = \text{const}(*x)P'$ and $\langle \text{const}(*x)P', F \rangle \rightarrow \langle P'; \text{endconst}(*x), F \cup \{\text{const}(*x)\} \rangle$
We need to prove $OK(F \cup \{\text{const}(*x)\})$. From the assumption, we have $OK(F)$ holds. Also, $F \cup \{\text{const}(*x)\}$ does not contain both $\text{null}(*x)$ and $\neg \text{null}(*x)$. Therefore, $OK(F \cup \{\text{const}(*x)\})$ holds.
- Case $P = \text{endconst}(*x)$ and $\frac{F' = \text{filter}.T(F, *x)}{\langle \text{endconst}(*x), F \rangle \rightarrow \langle \mathbf{0}, F' \rangle}$
we need to prove $OK(F')$. Form assumption, we have $OK(F)$ which means F does not contain both $\text{null}(*x)$ and $\neg \text{null}(*x)$. By the definition of *filter* function, we have $F' = F \setminus \{\text{null}(*x), \neg \text{null}(*x)\}$ or $F - \text{const}(*x)$, which means F' does not contain both $\text{null}(*x)$ and $\neg \text{null}(*x)$. Therefore, $OK(F')$ holds.
- Case $P = \mu\alpha.P'$ and $\langle \mu\alpha.P', F \rangle \rightarrow \langle [\mu\alpha.P']P', F \rangle$
We need to prove $OK(F)$. From the assumption, we have that $OK(F)$ holds.

- Case $P = P_1; P_2$ and $\frac{\langle P_1, F \rangle \xrightarrow{\rho} \langle P'_1, F' \rangle}{\langle P_1; P_2, F \rangle \xrightarrow{\rho} \langle P'_1; P_2, F' \rangle}$

We need to prove $OK(F')$. By IH, we have $\langle P_1, F \rangle \xrightarrow{\rho} \langle P'_1, F' \rangle$ and $OK(F)$ holds, then $OK(F')$ holds.

□

Lemma 9.2. *If $OK_n(P, F)$ and $\langle P, F \rangle \xrightarrow{\rho} \langle P', F' \rangle$, then*

- $OK_{n-1}(P', F')$ if $\rho = \mathbf{malloc}$,
- $OK_{n+1}(P', F')$ if $\rho = \mathbf{free}$,
- $OK_n(P', F')$ if $\rho = \text{Otherwise}$

Proof. By induction on $\langle P, F \rangle \xrightarrow{\rho} \langle P', F' \rangle$.

- Case $P = \mathbf{0}; P'$ and $\langle \mathbf{0}; P', F \rangle \rightarrow \langle P', F \rangle$

We need to prove $OK_n(P', F)$. Assume that $OK_n(P', F)$ does not hold. Then, we have (1) $\exists \sigma$ and Q s.t. $\langle P', F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, $\sharp_m(\sigma) - \sharp_f(\sigma) > n$ or (2) $OK(F)$ does not hold.

From the definition of that $OK(\mathbf{0}; P', F)$ holds, we have (1) if $\langle \mathbf{0}; P', F \rangle \rightarrow \langle P', F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, then $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n$ and (2) $OK(F)$, which are in contradiction to the assumption. Therefore, $OK_n(P', F)$ holds.

- Case $P = \mathbf{let } x = \mathbf{malloc} \mathbf{ in } P'$ and $\langle \mathbf{let } x = \mathbf{malloc} \mathbf{ in } P', F \rangle \xrightarrow{\mathbf{malloc}(x')} \langle [x'/x]P', F \rangle$

we need to prove $OK_{n-1}([x'/x]P', F)$. Assume that $OK_{n-1}([x'/x]P', F)$ does not hold. Then we have (1) $\exists \sigma$ and Q s.t. $\langle [x'/x]P', F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$ and $\sharp_m \sigma - \sharp_f \sigma > n$ or (2) $OK(F)$ does not hold.

From the definition of $OK_n(P, F)$, we have (1) $\langle \mathbf{let } x = \mathbf{malloc} \mathbf{ in } P', F \rangle \xrightarrow{\mathbf{malloc}(x')} \langle [x'/x]P', F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$ and $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n - 1$ and (2) $OK(F)$ holds. Therefore, we get the contradiction, and the $OK_{n-1}([x'/x]P', F)$ holds.

- Case $P = \mathbf{let } x = y \mathbf{ in } P'$ and $\langle \mathbf{let } x = y \mathbf{ in } P', F \rangle \rightarrow \langle [x'/x]P', F \rangle$

Similar to the above.

- Case $P = \mathbf{let } x = *y \mathbf{ in } P'$ and $\langle \mathbf{let } x = *y \mathbf{ in } P', F \rangle \rightarrow \langle [x'/x]P', F \rangle$

Similar to the above.

- Case $P = \mathbf{let } x = \mathbf{null} \mathbf{ in } P'$ and $\langle \mathbf{let } x = \mathbf{null} \mathbf{ in } P', F \rangle \rightarrow \langle [x'/x]P', F \rangle$

Similar to the above.

- Case $P = \mathbf{free}$ and $\langle \mathbf{free}, F \rangle \xrightarrow{\mathbf{free}} \langle \mathbf{0}, F \rangle$

We need to prove $OK_{n+1}(\mathbf{0}, F)$, which means we need to prove (1) $\forall \sigma$ and Q if $\langle \mathbf{0}, F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, then $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n$ and (2) $OK(F)$ holds. There is no Q and σ s.t. $\langle \mathbf{0}, F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, so (1) holds. $OK(F)$ holds from Lemma 9.1. Therefore, $OK(\mathbf{0}, F)$ holds.

- Case $P = \mathbf{endconst}(*x)$ and $\frac{F' = \mathit{filter_T}(F, *x)}{\langle \mathbf{endconst}(*x), F' \rangle \rightarrow \langle \mathbf{0}, F' \rangle}$

We need to prove $OK_n(\mathbf{0}, F')$, which means we need to prove (1) $\forall \sigma$ and Q if $\langle \mathbf{0}, F' \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, then $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n$ and (2) $OK(F')$ holds. There is no Q and σ s.t. $\langle \mathbf{0}, F' \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, so (1) holds. From the assumption $OK_n(P, F)$, we have $OK(F)$, which means F does not contain both $\mathbf{null}(*x)$ and $\neg \mathbf{null}(*x)$. By the definition of function $\mathit{filter_T}$, we have $F' = F \setminus \{\mathbf{null}(*x), \neg \mathbf{null}(*x)\}$ or $F - \mathbf{const}(*x)$. Therefore $OK(F')$ holds. So $OK_n(\mathbf{0}, F')$ holds.

- Case $P = (*x)(P_1, P_2)$ and $\frac{\mathbf{const}(*x) \notin F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\mathbf{null}(*x)} \langle P_1, F \rangle}$

We need to prove $OK_n(P_1, F)$. Assume that $OK_n(P_1, F)$ does not hold. Then, we have (1) $\exists \sigma$ and Q s.t. $\langle P_1, F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$ and $\sharp_m(\sigma) - \sharp_f(\sigma) > n$ or (2) $OK(F)$ does not hold.

From the definition of that $OK_n((*x)(P_1, P_2), F)$ holds, we have (1) if $\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\mathbf{null}(*x)} \langle P_1, F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$ then $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n$ and (2) $OK(F)$ holds, which are in contradiction to the assumption. Therefore, $OK_n(P_1, F)$ holds.

- Case $P = (*x)(P_1, P_2)$ and $\frac{\mathbf{const}(*x) \notin F}{\langle (*x)(P_1, P_2), F \rangle \rightarrow \langle P_2, F \rangle}$

We need to prove $OK_n(P_2, F)$. Assume that $OK_n(P_2, F)$ does not hold. Then, we have (1) $\exists \sigma$ and Q s.t. $\langle P_2, F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$ and $\sharp_m(\sigma) - \sharp_f(\sigma) > n$ or (2) $OK(F)$ does not hold.

From the definition of that $OK_n((*x)(P_1, P_2), F)$ holds, we have (1) if $\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\neg \mathbf{null}(*x)} \langle P_2, F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, then $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n$ and (2) $OK(F)$ holds, which are in contradiction to the assumption. Therefore, $OK_n(P_2, F)$ holds.

- Case $P = (*x)(P_1, P_2)$ and $\frac{\mathbf{null}(*x) \in F \quad \mathbf{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \rightarrow \langle P_1, F \rangle}$

We need to prove $OK_n(P_1, F)$. Assume that $OK_n(P_1, F)$ does not hold. Then, we have (1) $\exists \sigma$ and Q s.t. $\langle P_1, F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$ and $\sharp_m(\sigma) - \sharp_f(\sigma) > n$ or (2) $OK(F)$ does not hold.

From the definition of that $OK_n((*x)(P_1, P_2), F)$ holds, we have (1) if $\langle (*x)(P_1, P_2), F \rangle \rightarrow \langle P_1, F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, then $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n$ and (2) $OK(F)$ holds, which are in contradiction to the assumption. Therefore, $OK_n(P_1, F)$ holds.

- Case $P = (*x)(P_1, P_2)$ and $\frac{\neg \mathbf{null}(*x) \in F \quad \mathbf{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \rightarrow \langle P_2, F \rangle}$

We need to prove $OK_n(P_2, F)$. Assume that $OK_n(P_2, F)$ does not hold. Then we have (1) $\exists \sigma$ and Q s.t. $\langle P_2, F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$ and $\sharp_m(\sigma) - \sharp_f(\sigma) > n$ or (2) $OK(F)$ does not hold.

From the definition of that $OK_n((*x)(P_1, P_2), F)$ holds, we have (1) if $\langle (*x)(P_1, P_2), F \rangle \rightarrow \langle P_2, F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, then $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n$ and (2) $OK(F)$ holds, which are in contradiction to the assumption. Therefore, $OK_n(P_2, F)$ holds.

- Case $P = (*x)(P_1, P_2)$ and $\frac{\mathbf{null}(*x), \neg \mathbf{null}(*x) \notin F \quad \mathbf{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\mathbf{null}(*x)} \langle P_1, F \cup \{\mathbf{null}(*x)\} \rangle}$

We need to prove $OK_n(P_1, F \cup \{\mathbf{null}(*x)\})$. Assume that $OK_n(P_1, F \cup \{\mathbf{null}(*x)\})$ does not hold. Then we have (1) $\exists \sigma$ and Q s.t. $\langle P_1, F \cup \{\mathbf{null}(*x)\} \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$ and $\sharp_m(\sigma) - \sharp_f(\sigma) > n$ or (2) $OK(F \cup \{\mathbf{null}(*x)\})$ does not hold.

From the definition of that $OK_n((*)x)(P_1, P_2), F$ holds, we have (1) if $\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\text{null}(*x)} \langle P_1, F \cup \{\text{null}(*x)\} \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, then $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n$ and (2) $OK(F)$ holds. By $OK(F)$ and $\text{null}(*x), \neg\text{null}(*x) \notin F$, we have $OK(F \cup \{\text{null}(*x)\})$ holds. Therefore, we get the contradiction and $OK_n(P_1, F \cup \{\text{null}(*x)\})$ holds.

- Case $P = (*x)(P_1, P_2)$ and $\frac{\text{null}(*x), \neg\text{null}(*x) \notin F \quad \text{const}(*x) \in F}{\langle (*x)(P_1, P_2), F \rangle \xrightarrow{\neg\text{null}(*x)} \langle P_2, F \cup \{\neg\text{null}(*x)\} \rangle}$

Similar to the above.

- Case $P = \text{const}(*x)P'$ and $\langle \text{const}(*x)P', F \rangle \rightarrow \langle P'; \text{endconst}(*x), F \cup \text{const}(*x) \rangle$
We need to prove $OK_n(P'; \text{endconst}(*x), F \cup \text{const}(*x))$. Assume that $OK_n(P'; \text{endconst}(*x), F \cup \text{const}(*x))$ does not hold. Then, we have (1) $\exists \sigma$ and Q s.t. $\langle P'; \text{endconst}(*x), F \cup \text{const}(*x) \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$ and $\sharp_m(\sigma) - \sharp_f(\sigma) > n$ or (2) $OK(F \cup \text{const}(*x))$ does not hold.

From the definition of that $OK_n(\text{const}(*x)P', F)$ holds, we have (1) if $\langle \text{const}(*x)P', F \rangle \rightarrow \langle P'; \text{endconst}(*x), F \cup \text{const}(*x) \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, then $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n$ and (2) $OK(F)$ holds, which are in contradiction to the assumption. Therefore, $OK_n(P_1, F)$ holds.

- Case $P = \mu\alpha.P'$ and $\langle \mu\alpha.P', F \rangle \rightarrow \langle [\mu\alpha.P'/\alpha]P', F \rangle$

We need to prove $OK_n([\mu\alpha.P'/\alpha]P', F)$. Assume that $OK_n([\mu\alpha.P'/\alpha]P', F)$ does not hold. Then, we have (1) $\exists \sigma$ and Q s.t. $\langle [\mu\alpha.P'/\alpha]P', F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$ and $\sharp_m(\sigma) - \sharp_f(\sigma) > n$ or (2) $OK(F)$ does not hold.

From the definition of that $OK_n(\mu\alpha.P', F)$ holds, we have (1) if $\langle \mu\alpha.P', F \rangle \rightarrow \langle [\mu\alpha.P'/\alpha]P', F \rangle \xrightarrow{\sigma} \langle Q, F' \rangle$, then $\sharp_m(\sigma) - \sharp_f(\sigma) \leq n$, which is a contradiction; and (2) $OK(F)$ holds. From the Lemma 9.1, $OK(F \cup \neg\text{null}(*x))$ holds. Therefore, $OK([\mu\alpha.P'/\alpha]P', F)$ holds.

- Case $P = P_1; P_2$ and $\frac{\langle P_1, F \rangle \xRightarrow{\rho} \langle P'_1, F' \rangle}{\langle P_1; P_2, F \rangle \xRightarrow{\rho} \langle P'_1; P_2, F' \rangle}$

We need to prove $OK_{n'}(P'_1; P_2, F)$, where n' is determined by

$$n' = \begin{cases} n + 1 & \rho = \text{free} \\ n - 1 & \rho = \text{malloc} \\ n & \text{Otherwise.} \end{cases}$$

Assume that $OK_{n'}(P'_1; P_2, F)$ does not hold. Then, we have (1) $\exists \sigma, Q$ and F'' s.t. $\langle P'_1; P_2, F \rangle \xrightarrow{\sigma} \langle Q, F'' \rangle$ and $\sharp_m(\sigma) - \sharp_f(\sigma) > n'$ or (2) $OK(F')$ does not hold.

From the definition of that $OK_n(P_1; P_2, F)$ holds, we have (1) if $\langle P_1; P_2, F \rangle \xRightarrow{\rho} \langle P'_1; P_2, F' \rangle \xrightarrow{\sigma} \langle Q, F'' \rangle$, then $\sharp_m(\rho\sigma) - \sharp_f(\rho\sigma) \leq n$ and (2) $OK(F)$ holds.

From (1), we get $n' + \sharp_m(\rho) - \sharp_f(\rho) < \sharp_m(\rho) + \sharp_m(\sigma) - \sharp_f(\rho) - \sharp_f(\sigma) \leq n$. For any ρ , the $n' + \sharp_m(\rho) - \sharp_f(\rho) = n$, therefore we get a contradiction. By IH, we have $OK(F')$ holds, which is a contradiction. Therefore, $OK_{n'}(P_1; P_2, F)$ holds.

□

Proof of Lemma 4.2: By induction on the derivation of $\langle H, R, s, n, C \rangle \xrightarrow{\rho} \langle H', R', s', n', C' \rangle$.

- Case: $\langle H, R, \mathbf{const}(*x)s, n, C \rangle \rightarrow \langle H, R, s; \mathbf{endconst}(*x), n, C \cup \{\mathbf{const}(*x)\} \rangle$

From the assumption $\Theta; \Gamma \vdash \langle H, R, \mathbf{const}(*x)s, n, C \rangle : \langle P, F \rangle$, we have $\Theta; \Gamma \vdash \mathbf{const}(*x)s : P$ and $OK_n(P, F)$. From the inversion of typing rules, we get $\Theta; \Gamma \vdash s : P''$ and $\mathbf{const}(*x)P'' \leq P$ for some P'' . By subtyping, we have $P''; \mathbf{endconst}(*x) \leq Q$ and $\langle P, F \rangle \Rightarrow \langle Q, F \cup \{\mathbf{const}(*x)\} \rangle$ for some Q .

we need to find P' and F' s.t. $\Theta; \Gamma \vdash s; \mathbf{endconst}(*x) : P'$, $OK_n(P', F')$ and $\langle P, F \rangle \Rightarrow \langle P', F' \rangle$. Taking Q as P' and $F \cup \{\mathbf{const}(*x)\}$ as F' . Therefore $\langle P, F \rangle \rightarrow \langle P', F' \rangle$ holds, and $OK_n(P', F')$ holds from Lemma 9.2. From $\Theta; \Gamma \vdash s; \mathbf{endconst}(*x) : P''; \mathbf{endconst}(*x)$, $P''; \mathbf{endconst}(*x) \leq Q$ and T-SUB, $\Theta; \Gamma \vdash s; \mathbf{endconst}(*x) : P'$ holds.

- Case: $\langle H, R, \mathbf{endconst}(*x), n, C \rangle \rightarrow \langle H, R, \mathbf{skip}, n, C' \rangle$ where $C' = \mathit{filter_C}(C, *x)$

From the assumption $\Theta; \Gamma \vdash \langle H, R, \mathbf{endconst}(*x), n, C \rangle : \langle P, F \rangle$, we have $\Theta; \Gamma \vdash \mathbf{endconst}(*x) : P$ and $OK_n(P, F)$. From the inversion of typing rules, we get $\Theta; \Gamma \vdash \mathbf{endconst}(*x) : \mathbf{endconst}(*x)$ and $\mathbf{endconst}(*x) \leq P$. By subtyping and function $\mathit{filter_T}(F, *x)$, we get $0 \leq Q$ and $\langle P, F \rangle \rightarrow \langle Q, F' \rangle$ for some Q .

we need to find P' and F' s.t. $\Theta; \Gamma \vdash \mathbf{skip} : P'$, $OK_n(P', F')$ and $\langle P, F \rangle \Rightarrow \langle P', F' \rangle$. Taking Q as P' and F' as F' therefore $F' \approx C'$ from functions $\mathit{filter_T}(F, *x)$ and $\mathit{filter_C}(C, *x)$; $\langle P, F \rangle \rightarrow \langle P', F' \rangle$ and $OK_n(P', F')$ hold. From T-SKIP, T-SUB and $0 \leq Q$, then $\Theta; \Gamma \vdash \mathbf{skip} : P'$ holds.

- Case: $\langle H, R, \mathbf{free}(x), n, C \rangle \xrightarrow{\mathbf{free}} \langle H', R, \mathbf{skip}, n+1, C' \rangle$

From the assumption $\Theta; \Gamma \vdash \langle H, R, \mathbf{free}(x), n, C \rangle : \langle P, F \rangle$, we have $OK_n(P, F)$ and $\Theta; \Gamma \vdash \mathbf{free}(x) : P$. From inversion of the typing rules, we have $\Theta; \Gamma \vdash \mathbf{free}(x) : \mathbf{free}$ and $\mathbf{free} \leq P$. By the subtyping, we have $\langle P, F \rangle \xrightarrow{\mathbf{free}} \langle Q, F \rangle$ and $0 \leq Q$ for some Q .

We need to find P' and F' such that $\langle P, F \rangle \xrightarrow{\mathbf{free}} \langle P', F' \rangle$, $\Theta; \Gamma \vdash \mathbf{skip} : P'$, and $OK_{n+1}(P', F')$. Take Q as P' and F as F' . Then, $\langle P, F \rangle \xrightarrow{\mathbf{free}} \langle P', F' \rangle$ holds, and $OK_{n+1}(P', F')$ holds from Lemma 9.2. We also have $\Theta; \Gamma \vdash \mathbf{skip} : P'$ from T-SKIP, $0 \leq Q$ and T-SUB.

- Case: $\langle H, R, \mathbf{let } x = \mathbf{malloc}() \mathbf{ in } s, n, C \rangle \xrightarrow{\mathbf{malloc}(x')} \langle H', R', [x'/x]s, n-1, C' \rangle$

From the assumption $\Theta; \Gamma \vdash \langle H, R, \mathbf{let } x = \mathbf{malloc}() \mathbf{ in } s, n, C \rangle : \langle P, F \rangle$, we have $\Theta; \Gamma \vdash \mathbf{let } x = \mathbf{malloc}() \mathbf{ in } s : P$ and $OK_n(P, F)$. By the inversion of typing rules, we have $\Theta; \Gamma, x \vdash s : P''$ and $\mathbf{let } x = \mathbf{malloc} \mathbf{ in } P'' \leq P$ for some P'' . By subtyping, we get $\langle P, F \rangle \xrightarrow{\mathbf{malloc}(x')} \langle Q, F \rangle$ and $[x'/x]P'' \leq Q$ for some Q .

We need to find P' and F' such that $\Theta; \Gamma, x' \vdash [x'/x]s : P'$ and $\langle P, F \rangle \xrightarrow{\mathbf{malloc}(x')} \langle P', F' \rangle$ and $OK_{n-1}(P', F')$. Take Q as P' and F as F' . Then $\langle P, F \rangle \xrightarrow{\mathbf{malloc}(x')} \langle P', F' \rangle$ holds, and $OK_{n-1}(P', F')$ holds by Lemma 9.2. From $\Theta; \Gamma, x \vdash s : P''$ and $\mathbf{let } x = \mathbf{malloc} \mathbf{ in } P'' \leq P$, we have $\Theta; \Gamma, x'' \vdash [x''/x]s : [x''/x]P''$ and $\mathbf{let } x'' = \mathbf{malloc} \mathbf{ in } [x''/x]P'' \leq P$, and then by the definition of subtyping we have $[x''/x]P'' \leq Q'$ for some Q' . Therefore, we get $\Theta; \Gamma, x'' \vdash [x''/x]s : Q'$. Take x'' as x' and Q' as P' , then $\Theta; \Gamma, x' \vdash [x'/x]s : P'$ holds.

- Case: $\langle H, R, \mathbf{skip}; s, n, C \rangle \rightarrow \langle H, R, s, n, C \rangle$

From the assumption $\Theta; \Gamma \vdash \langle H, R, \mathbf{skip}; s, n, C \rangle : \langle P, F \rangle$, we have $\Theta; \Gamma \vdash \mathbf{skip}; s : P$ and $OK_n(P, F)$. From the inversion of the typing rules, we get $\Theta; \Gamma \vdash s : P''$ and $0; P'' \leq P$. From the definition of subtyping, we have $\langle P, F \rangle \Longrightarrow \langle Q, F \rangle$ and $P'' \leq Q$ for some Q .

We need to find P' and F' such that $\Theta; \Gamma \vdash s : P'$ and $\langle P, F \rangle \rightarrow \langle P', F' \rangle$ and $OK_n(P', F')$. Take Q as P' and F as F' . Then $\langle P, F \rangle \Longrightarrow \langle P', F' \rangle$ and $OK_n(P', F')$ hold. We also have $\Theta; \Gamma \vdash s : P'$ from T-SUB, $\Gamma \vdash s : P''$ and $P'' \leq Q$.

- Case: $\langle H, R, *x \leftarrow y, n, C \rangle \rightarrow \langle H', R, \mathbf{skip}, n, C \rangle$

From the assumption $\Theta; \Gamma \vdash \langle H, R, *x \leftarrow y, n, C \rangle : \langle P, F \rangle$, we have $\Theta; \Gamma \vdash *x \leftarrow y : P$ and $OK_n(P, F)$. From the inversion of typing rules, we have $0 \leq P$.

We need to find P' such that $\Theta; \Gamma \vdash \mathbf{skip} : P'$, $\langle P, F \rangle \Longrightarrow \langle P', F' \rangle$ and $OK_n(P', F')$. Take P as P' and F as F' . Then, $\langle P, F \rangle \Longrightarrow \langle P', F' \rangle$ and $OK_n(P', F')$ hold. We also have $\Theta; \Gamma \vdash \mathbf{skip} : P'$ from T-SKIP, $0 \leq P$ and T-SUB.

- Case: $\langle H, R, \mathbf{let } x = y \mathbf{ in } s, n, C \rangle \rightarrow \langle H, R', [x'/x]s, n, C \rangle$

From the assumption $\Theta; \Gamma \vdash \langle H, R, \mathbf{let } x = y \mathbf{ in } s, n, C \rangle : \langle P, F \rangle$, we have $\Theta; \Gamma, y \vdash \mathbf{let } x = y \mathbf{ in } s : P$ and $OK_n(P, F)$. From the inversion of typing rules, we have $\Theta; \Gamma, x, y \vdash s : P''$ and $\mathbf{let } x = y \mathbf{ in } P'' \leq P$ for some P'' . By subtyping, we have $\langle P, F \rangle \rightarrow \langle Q, F \rangle$ and $[x'/x]P'' \leq Q$ for some Q .

We need to find P' and F' such that $\Theta; \Gamma, x', y \vdash [x'/x]s : P'$, $\langle P, F \rangle \rightarrow \langle P', F' \rangle$ and $OK_n(P', F')$. Take Q as P' and F as F' . Then $\langle P, F \rangle \Longrightarrow \langle P', F' \rangle$ and $OK_n(P', F')$ hold. From $\Theta; \Gamma, x, y \vdash s : P''$ and $\mathbf{let } x = y \mathbf{ in } P'' \leq P$, we have $\Theta; \Gamma, x'', y \vdash [x''/x]s : [x''/x]P''$ and $\mathbf{let } x'' = y \mathbf{ in } [x''/x]P'' \leq P$, and then by subtyping we have $[x''/x]P'' \leq Q'$ for some Q' . Therefore, we have $\Theta; \Gamma, x'', y \vdash [x''/x]s : Q'$. Take x'' as x' and Q' as P' , then $\Theta; \Gamma, x', y \vdash [x'/x]s : P'$ holds.

- Case: $\langle H, R, \mathbf{let } x = \mathbf{null in } s, n \rangle \rightarrow \langle H, R', [x'/x]s, n \rangle$

Similar to the above.

- Case: $\langle H, R, \mathbf{let } x = *y \mathbf{ in } s, n \rangle \rightarrow \langle H, R', [x'/x]s, n \rangle$

Similar to the above.

- Case: $\langle H, R, \mathbf{ifnull } (*x) \mathbf{ then } s_1 \mathbf{ else } s_2, n, C \rangle \xrightarrow{\mathbf{null}(*x)} \langle H, R, s_1, n, C \rangle$ if $H(R(x)) = \mathbf{null}$ and $\mathbf{const}(*x) \notin C$

From assumption $\Theta; \Gamma \vdash \langle H, R, \mathbf{ifnull } (*x) \mathbf{ then } s_1 \mathbf{ else } s_2, n, C \rangle : \langle P, F \rangle$, we have $\Theta; \Gamma \vdash \mathbf{ifnull } (*x) \mathbf{ then } s_1 \mathbf{ else } s_2 : P$ and $OK_n(P, F)$. From the inversion of typing rules, we have $\Theta; \Gamma \vdash s_1 : P_1$, $\Theta; \Gamma \vdash s_2 : P_2$ and $(*) (P_1, P_2) \leq P$. By subtyping and $\mathbf{const}(*x) \notin C$, which means $\mathbf{const}(*x) \notin F$, we get $\langle P, F \rangle \xrightarrow{\mathbf{null}(*x)} \langle Q, F \rangle$ and $P_1 \leq Q$ for some Q .

We need to find P' and F' such that $\Theta; \Gamma \vdash s_1 : P'$, $\langle P, F \rangle \xrightarrow{\mathbf{null}(*x)} \langle P', F' \rangle$ and $OK_n(P', F')$. Take Q as P' and F as F' . Then $\langle P, F \rangle \xrightarrow{\mathbf{null}(*x)} \langle P', F' \rangle$ and $OK_n(P', F')$ hold. We also have $\Theta; \Gamma \vdash s_1 : P'$ from T-SUB, $\Theta; \Gamma \vdash s_1 : P_1$ and $P_1 \leq Q$.

- Case: $\langle H, R, \mathbf{ifnull } (*x) \mathbf{ then } s_1 \mathbf{ else } s_2, n, C \rangle \xrightarrow{\neg \mathbf{null}(*x)} \langle H, R, s_1, n, C \rangle$ if $H(R(x)) \neq \mathbf{null}$ and $\mathbf{const}(*x) \notin C$

Similar to the above.

- Case: $\langle H, R, \text{ifnull}(*x) \text{ then } s_1 \text{ else } s_2, n, C \rangle \xrightarrow{\text{null}(*x)} \langle H, R, s_1, n, C' \rangle$ if $H(R(x)) = \text{null}$, $\text{const}(*x) \in C$ and $C' = C \cup \{\text{null}(*x)\}$

From assumption $\Theta; \Gamma \vdash \langle H, R, \text{ifnull}(*x) \text{ then } s_1 \text{ else } s_2, n, C \rangle : \langle P, F \rangle$, we have $\Theta; \Gamma \vdash \text{ifnull}(*x) \text{ then } s_1 \text{ else } s_2 : P$ and $OK_n(P, F)$. From the inversion of typing rules, we have $\Theta; \Gamma \vdash s_1 : P_1$, $\Theta; \Gamma \vdash s_2 : P_2$ and $(*x)(P_1, P_2) \leq P$. By subtyping and $\text{const}(*x) \in C$, we get $\langle P, F \rangle \xrightarrow{\text{null}(*x)} \langle Q, F \cup \{\text{null}(*x)\} \rangle$ and $P_1 \leq Q$ for some Q .

We need to find P' and F' such that $\Theta; \Gamma \vdash s_1 : P'$, $\langle P, F \rangle \xrightarrow{\text{null}(*x)} \langle P', F' \rangle$ and $OK_n(P', F')$. Take Q as P' and $F \cup \{\text{null}(*x)\}$ as F' . Then $C' \approx F'$, $\langle P, F \rangle \xrightarrow{\text{null}(*x)} \langle P', F' \rangle$ and $OK_n(P', F')$ hold. We also have $\Theta; \Gamma \vdash s_1 : P'$ from T-SUB, $\Theta; \Gamma \vdash s_1 : P_1$ and $P_1 \leq Q$.

- Case: $\langle H, R, \text{ifnull}(*x) \text{ then } s_1 \text{ else } s_2, n, C \rangle \xrightarrow{\neg \text{null}(*x)} \langle H, R, s_2, n, C' \rangle$ if $H(R(x)) \neq \text{null}$, $\text{const}(*x) \in C$ and $C' = C \cup \{\neg \text{null}(*x)\}$

Similar to the above proof.

- Case: $\langle H, R, s_1; s_2, n, C \rangle \rightarrow \langle H', R', s'_1; s_2, n', C' \rangle$

From the assumption $\Theta; \Gamma \vdash \langle H, R, s_1; s_2, n, C \rangle : \langle P, F \rangle$, we have $\Theta; \Gamma \vdash s_1; s_2 : P$ and $OK_n(P, F)$ with $C \approx F$. By inversion of typing rules, we have $\Theta; \Gamma \vdash s_1 : P_1$, $\Theta; \Gamma \vdash s_2 : P_2$ and $P_1; P_2 \leq P$ for some P_1 and P_2 .

By IH on $\langle H, R, s_1, n, C \rangle$ with derivation $\langle H, R, s_1, n, C \rangle \xrightarrow{\rho} \langle H', R', s'_1, n', C' \rangle$, we have $\exists P'_1, F'_1$ s.t. $\Theta; \Gamma \vdash \langle H', R', s'_1, n', C' \rangle : \langle P'_1, F'_1 \rangle$ and $\langle P_1, F \rangle \xrightarrow{\rho} \langle P'_1, F'_1 \rangle$.

By subtyping we have $\langle P, F \rangle \xrightarrow{\rho} \langle Q, F'_1 \rangle$ and $P'_1; P_2 \leq Q$ for some Q .

We need to find P' and F' s.t. $\langle P, F \rangle \xrightarrow{\rho} \langle P', F' \rangle$, $OK_n(P', F')$ and $\Theta; \Gamma \vdash s'_1; s_2 : P'$. Take Q as P' and F'_1 as F' , $\langle P, F \rangle \xrightarrow{\rho} \langle P', F' \rangle$ and $OK_n(P', F')$ hold. By T-Sub, $\Theta; \Gamma \vdash s'_1; s_2 : P'_1; P_2$ and $P'_1; P_2 \leq Q$, we have $\Theta; \Gamma \vdash s'_1; s_2 : P'$ holds.

□

We write $\langle H, R, s, n, C \rangle \xrightarrow{\rho}$ if there is a transition $\xrightarrow{\rho}$ from $\langle H, R, s, n, C \rangle$.

Lemma 9.3. *If $\Theta; \Gamma \vdash \langle H, R, s, n, C \rangle : \langle P, F \rangle$ and $\langle H, R, s, n, C \rangle \xrightarrow{\rho}$ and $\rho \in \{\text{malloc}(x'), \text{free}, \text{null}(*x), \neg \text{null}(*x)\}$, then there exists P' and F' such that $\langle P, F \rangle \xrightarrow{\rho} \langle P', F' \rangle$.*

Proof. Induction on the derivation of $\Theta; \Gamma \vdash \langle H, R, s, n, C \rangle : \langle P, F \rangle$. □

Proof of Lemma 4.3:

By contradiction. Assume $\langle H, R, s, n, C \rangle \xrightarrow{\rho} \text{OutOfMemory}$. Then, n is 0 and $\rho = \text{malloc}(x')$ from SEM-OUTOFMEM. From the assumption we have $\Theta; \Gamma \vdash s : P$ and $OK_0(P, F)$. From Lemma 9.3, there exists P' and F' such that $\langle P, F \rangle \xrightarrow{\text{malloc}(x')} \langle P', F' \rangle$. However, this contradicts $OK_0(P, F)$. □

Proof of Theorem 4.1:

We have $\Theta; \emptyset \vdash s : P, \vdash D : \Theta$ and $OK_n(P, F)$.

Suppose that there exists σ such that $\langle \emptyset, \emptyset, s, n, C \rangle \xrightarrow{\sigma} \langle H', R', s', n', C' \rangle \xrightarrow{\rho} \text{OutOfMemory}$. Then, $n' = 0$ and $\rho = \text{malloc}(x')$. From Lemma 4.2, there exists P' and F' such that $\Theta; \Gamma' \vdash s' : P'$,

$\langle P, F \rangle \xRightarrow{\sigma} \langle P', F' \rangle$, and $OK_0(P', F')$; hence $\langle H', R', s', 0 \rangle \xrightarrow{\text{malloc}(x')} \cdot$. However, this contradicts Lemma 4.3. \square

10 Syntax Directed Typing Rules

$$\begin{array}{c}
\frac{C = \emptyset}{\Theta; \Gamma; C \vdash \text{skip} : \mathbf{0}} \quad (\text{ST-Skip}) \\
\\
\frac{\Theta; \Gamma; C_1 \vdash s_1 : P_1 \quad \Theta; \Gamma; C_2 \vdash s_2 : P_2 \quad C = C_1 \cup C_2 \cup \{P_1; P_2 \leq P\}}{\Theta; \Gamma; C \vdash s_1; s_2 : P} \quad (\text{ST-Seq}) \\
\\
\frac{\Theta; \Gamma; C_1 \vdash y \quad \Theta; \Gamma; C_2 \vdash x : C = C_1 \cup C_2}{\Theta; \Gamma; C \vdash *x \leftarrow y : \mathbf{0}} \quad (\text{ST-Assign}) \\
\\
\frac{\Theta; \Gamma; C_1 \vdash x \quad C = C_1}{\Gamma; C \vdash \text{free}(x) : \text{free}} \quad (\text{ST-Free}) \\
\\
\frac{\Theta; \Gamma, x; C_1 \vdash s : P_1 \quad C = C_1 \cup \{P_1 \leq P\}}{\Theta; \Gamma; C \vdash \text{let } x = \text{malloc}() \text{ in } s : \text{malloc}; P} \quad (\text{ST-Malloc}) \\
\\
\frac{\Theta; \Gamma; C_1 \vdash y \quad \Theta; \Gamma, x; C_2 \vdash s : P_1 \quad C = C_1 \cup C_2 \cup \{P_1 \leq P\}}{\Theta; \Gamma; C \vdash \text{let } x = y \text{ in } s : P} \quad (\text{ST-LetEq}) \\
\\
\frac{\Theta; \Gamma; C_1 \vdash y \quad \Theta; \Gamma, x; C_2 \vdash s : P_1 \quad C = C_1 \cup C_2 \cup \{P_1 \leq P\}}{\Theta; \Gamma; C \vdash \text{let } x = *y \text{ in } s : P} \quad (\text{ST-LetDref}) \\
\\
\frac{\Theta; \Gamma; C_1 \vdash x \quad \Theta; \Gamma; C_2 \vdash s_1 : P_1 \quad \Theta; \Gamma; C_3 \vdash s_2 : P_2 \quad C = C_1 \cup C_2 \cup C_3 \cup \{(*x)(P_1, P_2) \leq P\}}{\Theta; \Gamma; C \vdash \text{ifnull}(*x) \text{ then } s_1 \text{ else } s_2 : P} \quad (\text{ST-IfNull}) \\
\\
\frac{\Theta(f) = P_1 \quad C = P_1 \leq P}{\Gamma, \vec{x} : \vec{\tau} \vdash f(\vec{x}) : P} \quad (\text{ST-Call}) \\
\\
\frac{\Theta \vdash D : \Theta \quad \Theta; \emptyset; C_1 \vdash s : P \quad C = C_1 \cup \{OK_n(P)\}}{C \vdash (D, s)} \quad (\text{ST-Program}) \\
\\
\frac{\Theta; \Gamma; C_1 \vdash x \quad C = C_1}{\Theta; \Gamma; C \vdash \text{endconst}(*x) : \text{endconst}(*x)} \quad (\text{ST-ENDCONST}) \\
\\
\frac{\Theta; \Gamma; C_1 \vdash x \quad \Theta; \Gamma; C_2 \vdash s : P_1 \quad C = C_1 \cup C_2 \cup \{P_1 \leq P\}}{\Theta; \Gamma; C \vdash \text{const}(*x)s : \text{const}(*x)P} \quad (\text{ST-CONST})
\end{array}$$

11 Type Inference

$$\begin{aligned}
PT_{\Theta}(f) &= \\
&\quad \text{let } \alpha = \Theta(f) \\
&\quad \text{in } (C = \{\alpha \leq \beta\}, \beta) \\
PT_{\Theta}(\text{skip}) &= (\emptyset, 0) \\
PT_{\Theta}(s_1; s_2) &= \\
&\quad \text{let } (C_1, P_1) = PT_{\Theta}(s_1) \\
&\quad \quad (C_2, P_2) = PT_{\Theta}(s_2) \\
&\quad \text{in } (C_1 \cup C_2 \cup \{P_1; P_2 \leq \beta\}, \beta) \\
PT_{\Theta}(*x \leftarrow y) &= \\
&\quad \text{let } (C_1, \emptyset) = PT_v(*x) \\
&\quad \quad (C_2, \emptyset) = PT_v(y) \\
&\quad \text{in } (C_1 \cup C_2, 0) \\
PT_{\Theta}(\text{free}(x)) &= \\
&\quad \text{let } (C_1, \emptyset) = PT_v(x) \\
&\quad \text{in } (C_1, \text{free}) \\
PT_{\Theta}(\text{endconst}(*x)) &= \\
&\quad \text{let } (C_1, \emptyset) = PT_v(*x) \\
&\quad \text{in } (C_1, \text{endconst}(*x)) \\
PT_{\Theta}(\text{const}(*x)s) &= \\
&\quad \text{let } (C_1, \emptyset) = PT_v(*x) \\
&\quad \text{let } (C_2, P_1) = PT_{\Theta}(s) \\
&\quad \text{in } (C_1 \cup C_2 \cup P_1 \leq \beta, \text{const}(*x)\beta) \\
PT_{\Theta}(\text{let } x = \text{malloc}() \text{ in } s) &= \\
&\quad \text{let } (C_1, P_1) = PT_v(s) \\
&\quad \text{in } (C_1 \cup \{P_1 \leq \beta\}, \text{malloc}; \beta) \\
PT_{\Theta}(\text{let } x = y \text{ in } s) &= \\
&\quad \text{let } (C_1, \emptyset) = PT_v(y) \\
&\quad \quad (C_2, P_1) = PT_{\Theta}(s) \\
&\quad \text{in } (C_1 \cup C_2 \cup \{P_1 \leq \beta\}, \beta) \\
PT_{\Theta}(\text{let } x = *y \text{ in } s) &= \\
&\quad \text{let } (C_1, \emptyset) = PT_v(y) \\
&\quad \quad (C_2, P_1) = PT_{\Theta}(s) \\
&\quad \text{in } (C_1 \cup C_2 \cup \{P_1 \leq \beta\}, \beta) \\
PT_{\Theta}(\text{ifnull}(*x) \text{ then } s_1 \text{ else } s_2) &= \\
&\quad \text{let } (C_1, P_1) = PT_{\Theta}(s_1) \\
&\quad \quad (C_2, P_2) = PT_{\Theta}(s_2) \\
&\quad \quad (C_3, \emptyset) = PT_v(*x) \\
&\quad \text{in } (C_1 \cup C_2 \cup C_3 \cup \{(*x)(P_1, P_2) \leq \beta\}, \beta) \\
PT(\langle D, s \rangle) &= \\
&\quad \text{let } \Theta = \{f_1 : \alpha_1, \dots, f_n : \alpha_n\} \\
&\quad \quad \text{where } \{f_1, \dots, f_n\} = \text{dom}(D) \text{ and } \alpha_1, \dots, \alpha_n \text{ are fresh} \\
&\quad \text{in let } (C_i, P_i) = PT_{\Theta}(D(f_i)) \text{ for each } i \\
&\quad \text{in let } C'_i = \{\alpha_i \leq P_i\} \text{ for each } i \\
&\quad \text{in let } (C, P) = PT_{\Theta}(s) \\
&\quad \text{in } (C_i \cup C'_i) \cup C \cup \{OK(P)\}, P)
\end{aligned}$$

Figure 6: Type Inference Algorithm