Table 14.5.1 Pharmacodynamic Parameters (Pharmacodynamic Set)

<*Parameter*>

Visit		Arm I (Nab-paclitaxel and gemcitabine) (N=xx)	Arm II (VCN-01 with Nab-paclitaxel and gemcitabine) (N=xx)	p-value
Screening	n	xx	xx	
	Mean	xx	xx	
	STD	xx	xx	
	Median	xx	xx	
	Minimum	xx	xx	
	Maximum	xx	xx	
Baseline	n	xx	xx	
	Mean	xx	xx	
	STD	xx	xx	
	Median	xx	xx	
	Minimum	xx	xx	
	Maximum	xx	xx	
<*Visit*>	n	xx	xx	
	Mean	xx	xx	
	…			
Change from Baseline to <*Visit*>	n	xx	xx	
	Mean	xx	xx	
	…			
<*Test*>				x.xxxx
…				

Source: Listing 16.2.6
Path\Filename

Programming Note: Above layout should be used for parameters where both arms as assessed. Please indicate test used in the first column as appropriate.

<*Parameter*>

Visit		Arm I (Nab-paclitaxel and gemcitabine) (N=xx)	Arm II (VCN-01 with Nab-paclitaxel and gemcitabine) (N=xx)	p-value
Screening	n	NA	xx	
	Mean		xx	
	STD		xx	
	Median		xx	
	Minimum		xx	
	Maximum		xx	
Baseline	n	NA	xx	
	Mean		xx	
	STD		xx	
	Median		xx	
	Minimum		xx	
	Maximum		xx	
<*Visit*>	n	NA	xx	
	Mean		xx	
	…			
<*Test*>				x.xxxx
Change from Baseline to <*Visit*>	n	NA	xx	
	Mean		xx	
	…			
…				

NA = Not applicable.

Source: Listing 16.2.13
Path\Filename

Programming Note: Above layout should be used for parameters only applicable for Arm II. Please indicate test used in the first column as appropriate. These two layouts should be combined in one output, starting each parameter on a new page.