Design Deque

Design your implementation of the circular double-ended queue (deque).

Implement the MyCircularDeque class:

- MyCircularDeque(int k) Initializes the deque with a maximum size of k.
- boolean insertFront() Adds an item at the front of Deque. Returns true if the operation is successful, or false otherwise.
- boolean insertLast() Adds an item at the rear of Deque. Returns true if the operation is successful, or false otherwise.
- boolean deleteFront() Deletes an item from the front of Deque. Returns true if the operation is successful, or false otherwise.
- boolean deleteLast() Deletes an item from the rear of Deque. Returns true if the operation is successful, or false otherwise.
- int getFront() Returns the front item from the Deque. Returns -1 if the deque is empty.
- int getRear() Returns the last item from Deque. Returns -1 if the deque is empty.
- boolean isEmpty() Returns true if the deque is empty, or false otherwise.
- boolean isFull() Returns true if the deque is full, or false otherwise.

Example 1:

Input

```
["MyCircularDeque", "insertLast", "insertLast", "insertFront", "insertFront", "getRear", "isFull", "deleteLast", "insertFront", "getFront"]
```

```
[[3], [1], [2], [3], [4], [], [], [], [4], []]
```

Output

```
[null, true, true, true, false, 2, true, true, true, 4]
```

Explanation

```
MyCircularDeque myCircularDeque = new MyCircularDeque(3);
myCircularDeque.insertLast(1); // return True
myCircularDeque.insertLast(2); // return True
myCircularDeque.insertFront(3); // return True
```

```
myCircularDeque.insertFront(4); // return False, the queue is full.
myCircularDeque.getRear(); // return 2
myCircularDeque.isFull(); // return True
myCircularDeque.deleteLast(); // return True
myCircularDeque.insertFront(4); // return True
myCircularDeque.getFront(); // return 4
```

Constraints:

- 1 <= k <= 1000
- 0 <= value <= 1000
- At most 2000 calls will be made to insertFront, insertLast, deleteFront, deleteLast, getFront, getRear, isEmpty, isFull.