

Cloning a Project With Submodules

Learn to clone a project with submodules with the help of a “recursive” flag.

We'll cover the following



- The git clone --recursive flag

Submodules have a special status within Git repositories. Since they are both included within a repository and at the same time reference as a remote repository, a simple clone will *not* check out the included submodule. Let's show that:

```
1 cd ../../
2 git clone bob_repo bob_repo_cloned
3 cd bob_repo_cloned
4 ls -1
5 cd alicelib
6 ls
7 cd ..
```

Terminal 1



Terminal



Click to Connect...



`alicelib`'s content is not there. Confusingly, `git submodule status` gives you a little clue of what's going on here.

```
8  git submodule status
```

The dash (or minus sign) at the front indicates the submodule is not checked out. Only by running a `git submodule init` and a `git submodule update` can you retrieve the appropriate submodule repository:

```
9  git submodule init
10 git submodule update
11 git submodule status
```

The submodule status has no dash, and a commit ID has been added to the output (`969b840 ...`).

The `git clone --recursive` flag

Fortunately, there is an easier way. You can clone the repository with a `--recursive` flag to automatically init and update any submodules (and submodules of those submodules ad infinitum) within the cloned repository:

```
12 cd ..
13 git clone --recursive bob_repo bob_repo_cloned_recursive
```

In case you're wondering if you clone a repository with `--recursive` and there are no submodules, then Git does not complain.

Terminal 1






Terminal




 **Back**


Git Tracks the Submodule's State




Next 

What Are Pull Requests?

 Mark as Completed

 Report an Issue

 Ask a Question
(https://discuss.educative.io/tag/cloning-a-project-with-submodules__git-submodules__learn-git-the-hard-way)